

ORACLE LIGHTING

UNIVERSAL LED ILLUMINATED LETTERS

THIS IS A UNIVERSAL PRODUCT AND PROFESSIONAL INSTALLATION IS HIGHLY RECOMMENDED

INSTALLATION: FIRST REMOVE THE GRILL

Step #1) Remove Grill Cover Air Shield (Push Pins)

Step #2) Remove (4) 10mm bolts on the top of grill.

Step #3) Pull Grill to Release Remaining Clips.



REMOVING THE FACTORY LETTERS:

With the grill now removed you can drill out the plastic rivets holding in the factory letters. Using a 1/4" drill bit drill out the (2) melted plastic rivets on the BACK side of each letter. The original letters will simply drop out once the plastic is removed.

INSTALLING THE LED LETTERS:

Optional: Use Tape Primer ORACLE Part #2082-504 to treat the surface. Drill holes for cables to pass through. Attach the individual letters and group all the red and black wires together.



WIRING GUIDE:

Ground the black cables to the fender ground post or battery post. Connect red wires to desired power source. For example: Parking Lights, Aux Switch, or ignition switched fuse in the fuse box by using an "add-a-circuit"



ORACLE
LIGHTING

www.oraclelights.com

© 2020 ORACLE LIGHTING

4401 Division St.
Metairie, LA 70002
P: 1(800)407-5776
F: 1(800)407-2631