

OWNER'S MANUAL AIR CONDITIONER

Please read this manual carefully before operating your set and retain it for future reference. 804109817

OREAD THIS MANUAL

hedrogys will their energy why list feature. Then but in an II make all you will be close and I make all you will not explain any part of a subject of the supplementary of the s You'll the many provinces to common gration you the discrete of the common gration you be discreted. The other than the common of the common o Transfer deading Tips for a post may be used to call for all the state of the state

A PRECAUTION

Contact assemble being.
 The air conditional as not standard for use by you so in the row or whole without supervisor.

house of littles about the properties of the remain that they do not play with the six conditioner. Type after each read to prehared in months in with the Salard Decare Gode by norther and authorized personnel only

Safety Precautions

To prevent injury to the user or other people and property decrape, the belowing instructions

must be followed.

It is considered to the long state of considering It cause have no demage. The sedicusness. is described by the following indicatories.

AWARNING The synthetindenday the posses thy of death or senses injury.

ACAUTION This syntal indicates the possibility of injury or contage to properties only.

■ Wearings of symbols tasic in this restail are so shown below:

Be sure not to do. Be sure to follow the instruction.

AWARNING

outlet.

Installation -Don't use a power conf. a

plug, or a local socket which is damaged Otherwick is many column a firm or ward was of old

De set disapperable or

needly products.

Operation –


the fire stocks to

power cord longth. - barillouse electric modes: No Otherwise, Throughouse a fire dovict ad germanic t





Allower plug into a grounded



Do not modify at extent the



Do not place heavy object on the power card and lake core so that the cord should not be present.





Do not share the outer with other appliances.

Take the power plan soil if increasing, holding the head of the plug and do not leach it with well bonds. • I will cause shot to shoot only — • Offenvise, it may become if we have in head generators — — of a solding product.

⊗*



The second second second





Use a park doth to clean. Bo not use appropriate from strong detergent. a with source for any of must never place as a suit.

8





× 35 If water orders the product ham of the the power arists of the main body of appliance. Contact sonites conion after taking the power-plagicum from the accide.




usage and div/gen depletion.

HAN DOGGE ENGINEER TWO COLDS

Unplug the unit if stronge sounds, odors, or smoke come train it.


















0


The I cause electric shock or first contribution series






Nover leach the metal parts









For inner cleaning, contact a Service Center.

On not use harsh detergent that causes corrector or damage on the unit. Harsh detergent may also cause to lune of product, tire, or electric efforts.

ACAUTION)

Inetallation

horsel the product on the exhaust and noise. Follow brutalisation brutalistic exactly. are not a med directly at the neighbors.



Otherwich (comby days) albertion provider





One a half uloth to clean. Do not use wax, thinner or a arrong delargest.

■ Operation


Do not use this appliance for special purposes such as cooling pale, foods, precision residency, or objects of all g is an air conditioned not a

⊗

Bo not sieg on the indocreasidoor anit and do dol and enything on th

If may cruise on injury first upli-drouping of the unit or falling down.

trajentes



























De not insert the hands or birs through the air inlet or outlet during operation.

Otherwise, ill may cause personal injury.

Before Operation

Preparing for Operation

- Occuert en instellation acedial at for inscallation.
- Flug in the power plus properly.
- Lise a dedicated circuit.
- Do not use an extension conf-
- Do not stertamp operation by proggreg/unplugging the power cont.
- B. If the controlling is diamaginal, replace it with only an authorized replacement

Usage

- 1. Deing exposed to direct airflow for an extended period of time could be razardous to your health.
- No correlation between fan usage and oxygen depletion.
- De not use this air conditioner for non-specified special purposes (e.g. preserving precision devices food pale practs, and articlipads). Such usage could damage the issue.

Cleaning and Maintenance


- 1. Do not touch the metal parts of the unit when removing the fifter, injuries can oppur when handling sharp motal bages.
- 2. Do not use water to clean inside the air conditioner. Exposure to water can
- destroy the insulation leading to possible electric shock. When destroy the militiation make sum that the power shot breaks mere times. off. The far relates at a very high speed during operation. There is a possibility of injury if the unit's power is adolest by triggered on while. deaning inner parts of the unit.

Service

For repair and mantenence, contact a Service Center.

Introduction


Symbols Used in this Manual



NOTICE This symbol indicates special notes.

WARNING


areas a rechallage be installed in accomplice with the Maria fall Elponio Dodu.



The images shown here are for illustrative purposes only and may be subject to change

Electrical Safety

Electrical Data



Power bushing a studies barred interrupted with American model from to provide a formation of the play state. The studies smalled the resident on a certificial to delive the powering of TEST bushing dispersion of the test powering of the TEST has not deep configuration of the air conditioner and conditioner.

NOTICE

Use Wall Micaglable	Poor Supply
Ster and Select Service growth a recipional costs Selected Selecte	Jul 20 July de ja de les de 20 July de la les de

▲ WARNING

USE OF EATENSION CORDS RISK OF FIRE court cause serious injury or death CO NOT use an extension cost with the window

EO NOT use surge promoters or multi-culture screptors with this wint to air conditioner.

A WARNING Never push the test button during operation Otherwise this plug can damaged,

Do not remove modely, or remeree Tra gug I this device tries, the cause should

the connected before further use. A CAUTION

The conductors made the personnel account of the conductor by disekts, which maniprise

leakage current.
These shields are not grounded.
Periodically execute the continuous demage. On not use this product in ins-

event the at leide became exposess. Asset allege hazard. The unit control be user-early bed, UK NATH report the terr per-recovery sealed portion. All warrant extant performance with be woded. This writts not intended to be used as an ONEST switch.

A CAUTION PLEASE MEAD CAREFULLY:

FOR THE USER'S PLASONAL SAFETY, THIS APPLIANCE WHET BE PROPERLY ORGANIZED The power are introduced as a support with a few artists proceedings by Utahaham with a market have the introducing with some collisions and as the proceeding with a control of the support of the collisions and the hand of the collisions are the hand of the collisions are the collisions.

оо мол оит ол лекоме тле тляго (опозмо) глама етом тле гожен изок: 4. от использяний на долимов мии, се соверхнествя послежений к

consistences reconsistency of the property of the action of which is not of the property of the action of the acti


Attending the copper groups before as so the war received from some took and groups the applications of the protection of the protection of the protection of the solution of the copy and the copy and the things of the forest which go is a solution of the forest which go is a solution of the forest which go is a solution of the copy of the c

Decorractive sourceed from the adaptar using one with married a CR server. For which, growing browning one right brown CO NOT USE the application with a process stopping ag.

SITUATIONS WHEN THE CHALLANCE MILL HE DISCONNECTED OFTEN.

The compact of the play is the state one impaging response and the army can end to in-creased one again the ground bratish. The wall response is to a first replace by a financial grounding underly case.

Installation



ACTIVITIES

Have the following constituting stapeted available and statistical


- Ad ustable Philips hose _____ Gsprewertyer "Roller Soksors or Shorter FRA 12 * Loyel ********** · thi-likely -* Pencil

Window Requirements

NOTICE


> suge in particular best action in what it is any or result. This and in decipies to have align in standard docate long entius, websitation opening is the from 29 or 41." The tip entire testion who be best into topic to the fits to other a class results appoint of 8.0 cm the terror of the appearant in the class shock.

The conditional teacher feed due to a site could be local and of the could be local and 10°C.




Preparation Of Chassis

complete some which bean the capital at both some are the sace. Need the power for belong at



 Slide the land from the challes by or boing the base pair. handle or tiple ing to word white brooks the cabbet.



bether we becked it to the undervice of the Advantable frame guides into the bolism of the

7 (a) the window rout results the people length had all the backing and about the Footh PF.





Supported frame current frameworks against

Figure Resemble at the unit eth IC Type A.



Cabinet Installation

1. Open the sundrive Mark a line on the owner of SC PRESENTATION OF used yearshine oil are seen a new support are converged to see legans and the seen ref

Cabinet Installation

- 2. Are thine sill one set of the window at using Be screen (Igua II). Carefuly stare the cabinet in the Alactor Scot a kluby. No collar more anticipation bent. abb the content on mother window spoil.
- It do not be seen (Type Open the Section at about Jip appert precise to Perceiping to de from the for first stack hale after the skill hydronies are unter copy of the wirelay all higher the carriage set are the lock out Bo suit the course; dema subversi.
- 4 Politic soften winder sock down being the top real territor until they need.

A CAUTION

Dated displayed in the polarical and the entire designed to powers with expension early 142 of NOW HINLIP DAY

NOTICE

- Consignatificates above and access soughly may the monopolical letter of reliable modested. Adopt the oriented of the Kindow e and by visibing the screens (By the First rough). The colorist independent about
- 2. The cut will displace the half-flow of a very alight the country toward the classics.
- 2 PM such times patient falls present whether such the topics no barural i made
- 4 Abot such tions curtain the windows of by using service Pyre-Cu.
- 5 Sharing and address and a


A CAUTION

м энций, разрож, тетрия этом, с fremoved from set, lettus cabinet violes.

- Clarific framework (Hot with rown horizon)
 In the proper length and instant between the pper window such one for lower weepens and
- Alland dia Westerlanding presentation in serve. (Type C)
- Control Installing the front prins, but out the work control ferror located stown the safe control crops, as shown.



Guide the lever covers by through the price but




Window installation of coordinates of non-completed, the ELECTRICAL DATA for allerthing power confile electrical outlet.




The image shown here is for illustrative s only and may be subject to change.

Operating Instructions

The review senset and ecopol panel will took like one of the following pictures



The image shown here is for illustrative purposes only and may be subject to change. The actual descriptions of control panel and their locations may vary depending on the model.



The remote control vary depend of model The buttons on remote control may have a

POWER.

Operation starts when this button is pressed and stops when you. press the button again.

OPERATION MODE SELECTOR.

Pash the MCOC hatter to refere between Charge Sever / Cool/ Fan / Hast.

Energy Elever - The lan stops when the compressor expecteding Approximately every 8 minutes the fan will turn on and check the room air. temperature Floodling is needed.

Cool - Compressor runs and cools the morn Use the $\Lambda_{\mathcal{F}}V$ and hAN pullkness: set the desired temperature and arould on fan speed.

F89 - Lan droubnes an but compressur does not not. Use the nets button to set the desired (an appear.)

hisat - Heater t, his and heats the room.

(>) ON/OFF TIMER

Getay GW - when the sir conditioner is still, if can be set to suppress cally from on from 1 to 24 hours at its previous mode and fan settings.

Date: O(r) - when the or conditionar x or, if can be well to entimatically turn off from 1 to 24 hours.

(FAN SPEED SELECTOR.)

Use to sell the fan speed to Low (F1), High (F2).

■TEMPERATURE CONTROL

The ther moster, man icre retent temperature to maintain the desired immperature. The thermoster can be set between $60^{\circ}F \cdot 60^{\circ}F \cap 70^{\circ} \cdot 30^{\circ}C$.

ENAUTO SWING

Screen pain

Sed to

Doct of

Scientific for

Indian inch

NE LINE TO PER

2000

This batterness rectamescurity control the an flow direction,

Count' for LLD will plat up to saids you that your fiber needs to be a served. After despite the fiber, press Texto $A \in \mathcal{C}$ together to turn of Colon Fiber light it. The need must be done from anti-control penel not remain control.

[4] Remocon Signal Receiver

A slight heet order may come from the unit when the switching to HEAT aborded conling season is over. This orior, its seed by time dust particles on the heater, will clospass quickly.

NOTICE

They have no contributed a sum the Architen (See Municipality) for those of later (less suited. They I TD (light) will the nations when \$50 hours of complian

AUTO ATSTART

During operation in history of process, power, the one runs as provided acting approxima-

The unit obtains to Scorpy Saver mode each time the unit is awained on except rectarbility offer as electival power carbigo and the reade. **A CAUTION**

The remote controller will not function property if strong light strikes the senser of the air conditioner or if there are obstacles between the remote controller and the air conditionar.

Inserting the Remote (Batteries Not Supplied)

Pich as the dwar or the cedibline render combined search with 2. Buy stone on to binds and losed one see. ASA 1.75 betwy. 3. Buy both. U. a. soc.


NOTICE

Epinoticse rocks graphe battery. Make sore that the pattery is new. Dungston sites he extended (Carton-director sacturgueste (Pedra Accordan) Despera


In property prevents with tigh reasons the softeness from the regions of the attention to the attention and going to be used for an additional cannot be these steep the source common toway from one or a property of the region and to page 19. To maintain optimal operation of the remon postor, the memor sense about not be exposed to company and

Vandilation

The vertiles on lever mist be in the CLOSE position in order is maintenable the twen cooling conditions. When intenable is accessary in the storm, set the vertiles of lever to the CPPIN position. "to damper is opered and room an kildrawn out



Air Direction



Their vactor of an ear to controlled wherever you words and artist by the top compliance and the terms of the terms.

HONIZONTAL AIR-DIRECTION CONTROL to control had stored infraction of air flow, store the DN nos don nie air swing switch and the air flow will be swept fortennially by the automatic air swing. System

if you want to stop the air flow from moving, switch of the alrewing switch at the desired position of the

VERTICAL AIR-DIRECTION CONTROL The vertical at the color is acquisited by moving the rorizontal curve:

Additional Features

This air conditioner is equipped with a

elinger fan.

The tan has an outer ring that most inthe water that collects in the base pan-Hilf gets deep. That condensate is then picked up by the farrand expelled through the concenser making the air conditioner more efficient.





A CAUTION: Be careful when inserting the drain pipe. Push away from the sharp fin area to avoid slipping injuring yourself.

Maintenance and Service

Air Filter

Check the air titler at least twice a month to see it cleaning is necessary. Irapped periotes in the filter can hold up and block the airlise, reducing cooling capacity and causing an accumulation of frost on the evaporator. To clean the air filter,





- Lift the idlet on temperat
- 2. Remove the air filter from the front grille by pulling the air filter up slightly. Wash the filter using lukewarm water below 46°O (104 °F).
- 4. Gently shake the excess water from the filter and replace.

Cleaning The Air Conditioner

he more got a and one; got a may be Wiped with a cloth dampened in a milddesergent solution. the cabinet may be washed with mid-

mswedul bra tragatab ro gade water, then polished with liquid way for Appliances.

To ensure continued peak efficiency,

the condenser colle to liske of unit) should be checked periodically and deaned it slogged with sout or dist from the almosphere.

Common Problems and Solutions

Before Calling for Service

flyou have problems with your air conditioner, read the rollowing information and try to solve the problem iff you cannot find a solution, turn of the air conditioner and Contact a service ranta.

Air conditioner does not operate

I. Ensure that the air conditioner is plugged into an outer of the proper witage and emperage

Check the fuse or circuit breaker.

Check whether the voltage is unusually high or low. Air does not feel cold enough on the cooling setting.

Ensure that the temperature settings are correct.

- 2. Check to see if the air titler is clogged with dust, if so, clean the filter.
- Ensure that the air flow from the cutside is not obstructed and that there is a. dearance of over 20" between the back of the air conditioner and the wall or lence pehind it
 - Close all doors and windows and chack for any source of heat in the room.

Water drip from the rear of the unit

You see water dripping from the rear of the unit. Water may be collected in the peak pain in highly found conditions or on painty days. This water exections and origs from the rear of the unb.

Normal Sound High pliched Chatter Sound of Rushing Air Today's high efficiency comme risky have a high pich ad chatter can be the cast ing eye of Cathering of the coll, you may have the sound of the date. In the significant by the last. Pinging or Seasting Coptets of water filting condenses during name combe to the came ggwerg-not Gurglattias. Vibration -Sugling or hear of notice may be translated, in the product of a that may introduce it increments because of poor reality and recommendation or increment installation transiduct, congruent page of the state of t

Troubleshooting.

The eir conditioner may be operating abnormally when:

Problem	Possible Causes	What To Do
As conditioner took rot. As conditioner took rot. As conditioner took rot rot. 15 Tallets 13	the an constitute is analygies.	Make sure the un conductor of play is pushed completely into the culter.
	The fuse is allow delical breaker by stopped	Check the house to select threater box and replace the fase of poer, the tyricher.
	Ремя ш ше	If power faster occurs, to I the mode consol to Ch. When power is recipred, was 3 minutes to the air combinations in prevent stocking of the compressor eventual.
	The current interruption covice is pipped	Press he MESSI button located on his cower or o prog. The NESSI button with not stay empaged, discontinue use of the sit conditions and course a custified and course a custified son on writingly.
	Artista Simprised	White some from are no curtains. Since, of furnished blocking the front of the air conditions.
	The temp control may not be secondary	DICCOCLINETT CHESTIN DECRESSES (1911)
	The air filter in dirty.	O can be filter at these every 2 sheeks. See the care and Maintenance section.
	the room may have been hot.	When the Africand light is transped on with need to allow time for the room to cool down.
	Cod sin Flascabling	Check to open humade flooring stars and boil an returns.
	Cooling on have cedup.	See Air Conductive Treasure Up below
Ar or others housing up	The spoking politically lead over	toe may block the kindox and obstruct the an- cand torse from properly eaching the room. Set the mode control of High Famor High Gool
Water diese outside	(fol. famed weather	Trik kinomali
West thos moons	The virtual displayers not uited to the outside	For proper water disposed imake some than as concilioner startes a girtly from the cause front to the root.
Alter or hade to been peri	Moissure removed from ein and discussions, used 220	has a round to a short period in areas with 100 harmonly normal to a larger period in very harmid sessio.
Air conditions	Citry sin firer - tilt recordest.	Country Hist.
oms on and of abidy	Dura de temperatura Dispersoly (40)	Set FAM speed to a feature adding to dring uit- tion, ghidholog their store frequently
Volse when unit is country	Air movement wound.	I say normal, if the book softly love. EAR softing
	Window vibration - poor in the barion.	Refr: to installation that, place or there with stall in.
Remote Sanding	Remote control not located within range.	Place written control within 20 line 5 1 201 in citization to be front of the unit.
Dearthading	Recipie control signal costnicted	Ramena obstances
Report too	Set recipants in our low.	house or unperior.

Byourse 101: In the display please call a service certis:



804109817

