### USE AND CARE GUIDE

PORTABLE AIR CONDITIONER



Please read this manual carefully before operating your unit and retain for future reference.

#### Safety Information

Taperowith by the first part of efficiency property claimings, the find a characteristic manner in part to be because Decrease appearing due to growing of instructions may as we have at decage. The level of decide shows by the fall owing indistribute



CAUTION: This symbol indicates a legarifour alloador which if necessities, cook hout in miner or moderate in any



This last lastes is not take at left use by personal fact utiling obligates with reduced physical, persons or mental copybilities or layer if there into the control of the price of the control of the control of the second of the control of the contro



- To not appears your oir conditions in a hardifusers with as a bollecome in terroling or
- Se such the sit concritane that been success, and controlly interface according to the industrial instructions in the mean at 5 km this. But had not according to both the second of the mean at 5 km this.
- High linear analysing paperly. There are to say construct to describe the transport to tight window
- Board eithig sees on the globe of an investigation agree seeds typy seeds during an invited by the transfer forms.
- Riveys en or of robes per releasible to held par releignery were released real.
- Books Repaid from action or severa mindigenous processing from 8. From particular pay or methor and contracted
- the like contribution for the description of the traces having from other collections.
- Exact sports or viry the unit by insofting or put must five propriets of step.
- De ante aporato vella vent transco en monory los del conferior colle transcy canno, cleri de siscoli.
- Examplifies with the mine less contact with any electric parts it may come follow or electric shock.
- So not use the account if \$1 is been or consignal, thency being the and electric aboots.
- Do not use or keep the power condicions to healing applications, it may cause the and electric stool
- Expectations are day content occur als for installation that are not recommended to this exercise.
- To set disease table or seed years, it was come followed electric roads.
- To net demage or use or alternate source cost. If may cause the and electric stack. If his power cost is demaged, it as at the replaced. Contacts are visit contacts and in a similar contact and in the similar contacts are similar to a similar contact.
- Egan Sincial for analytic prison is modificable help heart.
- En artispen the artisticing operation, it may cause electric above
- Lo act assists power card sear fluorestes gas or conducables, such as gase ha, because, it must see the approximate gas or conducables, such as seen as a second se
- Discrete cuttiden danger det se constineir et analet. Virgues rejerçorsy sex-Assist the report or electric classe. By set about represent one or a vaccinor plug. Discreteness, any congestion the power cost
- Space that it conditions is group by great facility ment and easility receive, proposition and operated, the proposition is compared with a flavor group, promiting this proposition is approximate to the contract.
- (ii) You do not then to seld to not the oping type and also if exception if the cell compact year maintained at the people per other or exceptible pulled by a first of a pulled to except a could be proper interpated. Describe compacts in a certain of the proper interpated.
- See on the freedom control for the late for the model on their change the principles for the fact that the control of the cont located on the side of the cubinst and be shat the pills.
- Wentle in Works to record the of local the reduperty of forms. It was constitute.
- Wen the artifector depring solid of last tented the signal resides
- De not deutenit schappover beer an 8, has come fiel electric shock or liquip
- Do you place exhibites around all in late or the lite of his partial, it may cause failure or accident.
- Other with a mit domenty. So not use stong evangents that periods wepon to ment as it may dering the product.
- (i) Use prutier when expecting and learning. Sharp edges coald cause stary.
- in. On not despite air parditioner with water.
- Water may amende out and degrade the fleaturing smith could read to electric shape.
- ... De notigues par or noisse plant where in will be apposed to direct it move. This pay of lighter the pat or harm the plant I lold the plug by the head of the power plug when taking it out. Otherwise, it may cause electric shock and changes
- Ensure that the limitalistics is properly secured to prevent the product from potentially falling.
- . Do not place heavy objects on the power cord and ensure that the cord is not compressed. Otherwise, there is danger of the or electric
- . If water is splitted on the emit, furnioff the unit and switch off the choult breaker, beliefs supply by taking the power-plug set and contact a
- Do not use man gas views or other gas burning application, as at flow may affect gas memberation.
- District and for any concepts other from contract combat.
- Da soi ave litte de conflit our le presente probbe divines, font, pels plants, and at réjects. It may cause defendantion.
- 5. Turn of the main power switch if the soil is not to be used for an extended time.
- Always Insert the filters securely. Clean filter once even two weeks. Scentiles without filters may cause follows. Do not tirisk water strained from the circonditioner.

CAUTION: Not of Bod complete solution. Propried for 8:292:0 on to only in



to an externation for source, there is a risk of line. CAUTION This symbol shows that the operation resocial should be read carefully.



# CAUTION This symbol shows that information is swellable such as the operating manual or installation manual

WARNING: This sential shows that this appliance used a flammable raffigers at If the refrigerant is leaked and exposed

#### WARRIED for many ROY of partial sale.

- So not the to accelerate the delicaterosists of the effects of despine that are not recommended by the manufacturer.
- The confidence that he consists a committee is continued by operating patient occurs. For example, oper forms or or operating gas applicant, as a significant content in continue or operating state of the continued of the contin sons without ignition sources.
- So not playce or bern,
- is were that the minigeness may not contain an other
- Sero warnitalino aprology, chamilit necessorine.
- Bit the strip in the employee by a Viscous wall helped survives, justice contact a consecution
- Her with integral a lists. A least with a an earliest on those before the instructions or entity to hands, install, than the new review the At confidence to write decays or house. To set dispose it is seen through the decay. Get and qualified a group to seeper disposal
- To specify and devices that generalizes advicable shall be about the air specifiers to world receiving by till on the flammable of tigorian receiving the most account to present account of present accounts of Arrango to securing.

#### Pre-Installation


#### TOOLS REQUIRED (TOOLS NOT INCLUDED)



# News or plan

#### HARDWARE INCLUDED





J#I	00	Form Soal B (Non-achorive)
	EE	Security Brasket and Screws
	H*	Window Slider A
	06	Window Slider B
	144	Foam Seal As/Adhesive)
		Drain Mase
	, II	Balt
	96	Remote Control (only for remote control modella)

00

Description

Unit Adaptor


Extraget Hosa

Window Slider Advator

Accessory type and quantity may vary depending on the model

#### PACKAGE CONTENTS

Post	Description	THE REST OF
A	Central Flavol	C 13
В	Remote Signal Receptor	
0	Horizontal Louwer Control	
D	Vertical Lauver Control	1.3
Е	Panel	
£	Caster	
G	Handle (both sides)	
Н	Altreliter	1
1	Upper Air Intake	
J	Drain Outlet	
К	Air Outlet	
L.	Lower Vir Intake	
и	Diction Tow Orain Outled	94 J 5-387 J 48



#### DESIGN NOTICE


In order to ensure the optimal performance of our products, the design operations of the unit and remote control are subject to change

### AMBIENT TEMPERATURE RANGE FOR OPERATION

MODE	Temperature Range	
Cost	17-3570 (63-559)	
Dry	15-38°C (58-68°F)	

#### EXHAUST HOSE INSTALLATION

The editual trace and eductor models included or removad in accordance with the page mode. For COOL, or ALTO mode exhaust income and to have the fact that for FAS, or FAS in otherwise or between strips marked.



The images shown in this manual are for illustrative purposes only and may be subject to change.

#### Your installation loss for should weet the following requirements:

- Make sales that you liketed you must be an even to the orbit to be notice and elevation.
- The unit must be installed means grounded plug, and the Collection Tray Drain shaund on the back of the units must be accessible.
- The protoclastic behavior of the control of the con manda basal layer 19.7 In. (30 cm) sweet from obstrates.
- DONOT cover the intakes, Cuttets or Remote Signs (Receptor of the unit, as this could cause damage to the unit.

#### ENERGY RATING INFORMATION

The accept rating contrainer of amorpha for this contribution and description using an one-development dust without n store a dier adapter par atown in the haral atom pretter of this manual s. At the name time, the unit must be operate on the COOL MCCC. and RIGHEAM SPERMS remote controller.

#### HOW TO STAY COOL WITH A NEW PORTABLE AIR CONDITIONER/FOR THE MODELS THAT COMPLY WITH THE REQUIREMENTS OF DEPARTMENT OF ENERGY IN US)

Springer of a new toking top procedure to the table An Conditionary, you may reduct that the conting reporting trains on portains and conditionary per scriping and sprintforms, in we than that of popular produced prior to XIVT. This is the first observe in the rest process are, not to the portrate an acrest areas storractical.

#### WHAT SHOULD I LOOK FOR FIRST WHEN PURCHASING A PORTABLE AIR CONDITIONER?

The right of conditioner has be your on a soon efficiently. An understood on it worth and temporately will be one thails in a large will not remove enough fundably leading the direction come. To Sed the proper of conditional determine the proper control of the more year.

Verific and by multiplying the room long it by the width from the repullations it is not an actually in 15 (Brites Thermal Unit) make, which indicates the minural of heat B can remove from a room. A higher number means more confine power for a larger years. The turn you are companing only review medic to compare motion motion may concern a town a mixton security, but any capable to come, less an a to "descript" hyper perhabits are conditioned will as placed in a very planty, make being, or in a motion with high codings. After you had been the right proling palacity myon many yourself lank at other findules.

#### WHY IS THE COOLING CAPACITY LOWER ON NEWER MODELS THAN ON OLDER UNITS?

Federal resultations require want learnings to sense and ingregative abset on a specific test projection, which was attended just this you. Note through date before DHY was latter until a different procedure and cooling expectly be assemblifferently than it area your model. So, while the PHIs may be have the service in property of the six conditionary than an absolute


#### WHAT IS SACC ?

SACC is the representative value of Endouranty Adjusted Cooking Councily, in HTUH as determinated in associative with the Engographe In all to ago \$00) has provide a state 10 Code of Found Regulation \$200, 400, acquaint, appear of Code applicable according plane.

#### Installation

- Prepare the Exhaust Hose assembly
- Proce the spherot large EEE for extended extracts social into the window's dorinated to (CC) for wall or was adiators and unit adiagram (AV). Clamp submarile sily by election white of the arbotout.





Install the Exhaust hose assembly to


### 3 Preparing the Adjustable Window Slider

- Charse the window sliders according the size of your window. Sometimes, it meets to be cut short to insert the window size, please take extra care to suffit properly.
- Use helps to better the window clickers \$45 and \$65 area they are a dischart in the proper length



### 4 Install Adhesive Foam Seal


Dat the activates Form Seed A (MM) stripe to the present lengths, and about them to the window such and frame as shown.





### 5 Install Window Slider

Insert the window siliter (FF and GS) assembly into the window opening






### 6 Cut Foam to Length


On the non-otherive From Seal B (300) only to match the wildth jor height) of the wildow. Insert the seal between the glass and the window flame to prevent air and insceto from getting into the rooms






### Install Security Bracket (optional)

Install the security bracket (BB with 2 carews as shown.





### 8 Install Window Slider Adaptor

ment the window silking adoptor (CQ) into the holes of the window slider (EQ).





HOTE: To see, in proper facility, 30 NOT secretarily to brief the resp. Note, one if all time is no straight accurable of our sets of losses in the secretarily proper facilities and the control of the second of losses in the second of the s








### Operation

MOTES to deline to previous for operation of proportions of the contribution of the co

#### Using the Control Panel



#### MODE MODE by Lon.

Salests the appropriate operating mode. Each time ecolorest the furtion, a mode is selected in a sequence that poet. from COOL, DRY, and RAN. The mode indicator light flaminates under the different mode setting.



Up (a) and Down Cirbertons Used to adjust (increasing/decreasing) temperature settings in ±10 / 2°F (or ±1°F) increments in a range of ±17°C / 62°F to SIFC/88TH to: 88Th).



EAH operation

IEE dooby

- Press the "MODE" button until the "DRY" indicator fight somes on
- The flux speed or the temperature cannot be rejurted. The flux motor spectrus at LOW speed.

NOTE: Seep windows and down classed for the best dail unicitying effect.

Press the "MODE" button until the "ENV" indicator light comes on.

#### ... Press the 1995 SWEO" factor on the sensite control to show after the speed. The temperature can not be ody-sted Do not put the duct to window.

Shows the set temperature while oit stor, being a so much. Will be 1991 and FWI moder, it shows the more

#### to exercise. Stave Every coding:

- HO-FEREN WYG.

El-Roan temperatura conservarios

 Elevant with the service before one. E)-Continuer temperature version ever (in some metable). RE-Gradey poech communication error.

 DG-Refrig great to strage detection multi-rector (on some model s). Energy protection state: 71-Bottom key to full--Connect the countries and drain the collected vector away.



indicator light

Either Times— or Windows Indicator light

Timer indicator lightenly sat by remote controlle



Power budge Topic coint south

0

NOTE: The actual descriptions of control panel and their locations may vary depending on the model.




### 2 Constant Fan operation(On some models)

 If Cost ad or Bey mere, press the MRF further for the second storm conduct the consecut Drafamation. When the further is seried. cute as start to lief will don and do tiving do not be an accompaste to conin. When this tempor is small of the constant tembrah or great, strately in great, strately in a constant tembrah or great, strately in great, strately in a constant or constant.

### 3 I SENSE feature

 This feature can be activated from the remote points DAD. The remote control serves are a remote terminated law by for the process temperature control of the booker. To activate the ISDRE feature, paint the remote control beyonds the anit and press the ISDRE. In attent. The removal content will prese this of great parties also conditioned with the ASPASE to these in present again. If the whit days have receive the Life Related control and it micross interval, the and with wint the LISBASE mode.



### 4 Auto-Restart

- $\alpha$  . If the unit turns of land accretely due to the sover out, it will restort with the provious function setting automatisally when the sover CONTROL
- AWIT 2 MINUTES DEFORE RESUMING OPERATION.
- After the certified stapped, if cannot be restarted in the first 3 minutes. This is to greated the an I. Speaker will automatically start.

### 5 Water Drainage

 During bother is type modes, conservation than public from both of the part inspection, the recommendate (AST conservation of the Prince Conservation). For the models without the incommendate, participate the photo inspects the Prince the open and of the home placing over the district in your basement from






When the same level of the action copy maples is greden connections, the unit large, Ellines, the cigital display area chose. For At this time to an continuous gifteton initial ten process with most abbrevious between the function of continue to question (bits in normal). Decidity move that and to a drain incoder, remove the bottom drain plug and led the various or Relocated the soften doing a property to involve and the TPT synical diagnosts. If the converges is not for service.





MOTE disease to in relatified community purposes that against a vigories of.




#### Using the Remote Control

Madel	RESHBOOKSERH-M
Flated Voltage	3.09 (Dry balteries 902/1/100x3)
Signal Receiving Buryo	Sim
Environment.	2519-14019 (6/C-8070)

NOTE: The remote control vary depend of model: The buttons on the remote control may have a different name or location than the remote control shows in this manual.

Solding you begin using your new directed force, make sure to familiarize yourself with the remote continut. The following are to of instructions for the remote control that it. For instructions on how to operate your air conditions, rater to the flow to the Dasic Parcitons. saction of this manual.



### Using Cool Mode



: Press the MODE button to select 000L mode.



: Pysis MA fuller to select the fan spect: AUT0, DOV or




### SETTING TEMPERATURE


The operating temperature manyer for units is 62-38 % (17-30°C). You can increase on decrease the self-temperature ( % (17-3) increments.

### 2 Using Auto Mode

- In AUTO mode, the unit will automatically select the COOL.

  FAM, or HEXT operation based on the set less perstans.
- Proce the MSDE butter to school ABTS.
- ni. Sat your desired temperature using the TCMP. William TBVP A totals
- Press the 05/00FF button to grant the unit.





## 3 Using Fan Mode

- Press the MODE batton to select FAN mode.
- Press MAN faulton to select the ran appeal AUTO, LDW, or
- Press the ON/SEF button to court the unit.

MOTTE: No. confront temperature in PAI second for a second year second research LCB secrets will set display.



Due the time to set the emporated time after which the protection administration between the content.

Press TEMP up or down button for multiple times to set the desired time to have prothe and.

Fless TEMP as on power buttor for multiple times to get the desired time to turn off the unit.

iii What withing the TMCD CF or TMCD CFC the throught concept p30 minutes income with year around a partial that increase in Their temperature partial product of the partial parti

The images shown in this manual are for illustrative purposes only and may be subject to change.

Power TIMER (IN button to initiate the DM time exquences:

Frest TIMER OFF buttoms initiate the OFF time sequence.

in Carpal editectoration by carting to sinverse \$10s.

Epilit rando to unit and wai; floor the TIMER OFF will be advisable.

Point remote to unit and wait lose, the TMER DM vill be applieded.

Using the Timer

TIMER OF orting

TIMER OFF SETTING

## 4 Using Dry Mode

- Press the MDGC button to pelect ORY.
- a Set your desired temperature using the TEM™ ▼ or TRIF A birtin.
- Premithe ONOFF button to start the unit.



10 Using the Sleep Function

5 Using the Time (continued)

6 Using I SENSE

When the I SCIST function is activated, the remate clopies is the actual temperature of its reciden. The remate control

will sand this signal to the sinconditioner in 2 into te-

Press the LBS Chipley better to term entered form of the

Conserve.

intervals and press that SEASE button again.

I SENS:

8 Using the LED Display

Keep in mind that the time particle years of for both functions refer to have after the current time.

However the control of 20 PM, to do the control of Service Store at the 20 PM and control of 600 PM.

- The SEEP function is used to decrease energy as exhali-you deep provider timed the constraints as eatings to stoy contorates. This is etian convery to activate. with the remark control.
- The place function is not available in first or thy share. Possonsta for a DWRFTS MARCAL in your details.



Using the °C/°F button

9 Using the Short Cut setting

a. Coud to realize the construction they are require previous

Pasinthe butter when remain control on sort. If a system

will communically revert such to the previous estimate and alog operating more, patting temperature, but speed level and class for a reliff policyted. If patting more

their Executive. The system will communicate involve. the purport countries settings including countries mode exhibit tempositive, but speak involved along feature (II 200-000)

0.0734

Proto this aution to atomatic the temperature display believe in the 'T-B-T'.

TOTE !

# 11 Inserting and Replacing Batteries

- Pottre balticles in the region control terbris as-Side the book cover from the remote central downward, expeding the between compartment.
- resort the patients, paying attention to match up the (a) and () and () and () it is built not not also as yet to be read the tackly minution to
- Side the bettery cover texts into place.



- To extrate oid and may be to fee, or because an office and Concluse ballates in the perole control floor, their playes along the day on the street mention are the.
- NOTE: So not dispose of Setudios as essented as noticed security for in large times to a proportion could be design.

### Too for extra remark control.

- The complex composition of the world within 8 million of the
- O many other materials and circums inlight can intraders with the infrared skiller rose yet.

# MOTIO: The device could comple with the book halfond

- : In Conselle, hashes to every letter \$28,000-500,5460-3506. in 65% tolerable as the office with part 65 of the 75% fields. On the original to the first belowing the contribution
- flexion reason of costs for material reasons, sec This pay to as it accept any interference received. relating least enter Richardy many welcomes.

Against an electric rection as means that statistics.
This equipment presents are a means that statistics are the equipment of presents are a medical controller to the entire of the en Merfenhabe will set oppor in a persoular laste, safer, if this grigorent, dem coper hore fall in ter fenome lo sectore retente ection, which can be obtained to forming french against of land on the later is press, would be two present the

- deflavage by set of poer of the tollowing magazine. Secret in death the enverge decision was the consider whose the extended activities.
- Consider the region of the extends of a principal format from that to which the receive its connected. Date. This for over an experience ratio? A before safety
- Distripts or prodifications not approved by the party responsible for might assemble mean contraditions; in
- considerate oculoment. buildings to death that of trobonery 57/34 y 5/6/27 (beginning lateral later

FCC Compliance Centerment (products subject to Part 85) This divides complied with Part. 5 of the PCC Bules. Consulter to subject to whence before the for receiver.

The two buildings of the manufactual flow because the set of the set of the manufactual flow and the set of the manufactual flow buildings of the set of t


#### Maintenance

#### SAFETY PRECAUTIONS

- Wwwys unplug the unit before cleaning or sarviding
- 00 NOT use flammable liquids or chamicals to clear the unit.
- FO NOT wash the unit under running water. Doing so causes electical danger.
- DO NOT operate the machine if the power supply was during cleaning. A clamaged power cord must be replaced.

### Care and Cleaning

#### AIR FILTER CLEANING



### Maleranae te Toe.

- Ho suicito elemine air filter overy 2 was is fair out adapartements.
- The water call technicary should be drained to mediately after Fill over occurs, and before decays to preventions d.
- Intraced and switch many, you will have a conscioutly expected the griff or proved stocked units with the disclosure of face.



#### UNIT CLEANING

Discribe and using a diams, looked cloth and mild delergent. By the and with a phylinish so clots.

#### STORE THE UNIT WHEN NOT IN USE

- Only the mill becale reduction thay according to the extractionary the following social.
- But the appliance of TAV inposition 12 hours is a warre, your to dy it and greward middle
- Tark of the applicacy and protogrit.
- Bow the set life specially a distinuisacions is dispersional scalar. Harsfull the stort sky litter to see storing.
- Beginner the harteries from the remove capabil.



MOTE/for the manufactor of the place of the set of the contract and the set of the set of the contract of the

#### Troubleshooting

Problem	Possible Grusco	Bolados
	P1 Protection Code	<ul> <li>The Water Callestian Day is fall. Turn off the unit, drain the water from the Water Callestian Fray and restart the unit.</li> </ul>
Unit class not turn on when possing ON-DIT button	In COSL made reconstances to lower than the set temperature.	□ Recel the temperature
	ES ES TEM and	<ul> <li>Contact a service center or a similar qualified person for service.</li> </ul>
	The sinfiller is blacked with dust or asimal to in	a. Turn of the unit and clean the litter according to instructions
	Extract hase is not connected or is Mechanic	<ul> <li>Term of the anit, discensed the haso, shock for bleckage are resourced for have</li> </ul>
	The unit is low correlagement.	<ul> <li>Call a service technique to respect the unit and top of refrigurers.</li> </ul>
Historiae anticod well	Temperature setting is less high	c. Decrease the antitemperature
	The windows and doors in the room are spen	Make cure all windows and deore are closed
	The community leadings	c. Double-check the cooling area.
	There are head accuracy inside the record	c. Farneys the heat courses if possible
	The ground is not level	<ul> <li>Place the unit on a flat, level curiace</li> </ul>
The unit is notes and worston the much	The pir filter is blocked with destroy unlend help	u formal tip unit and down the litter vocaming as increasions
The unit makes a garging exact	This council is counted by the flow of rathigenest inside the unit.	o Tribicosmil

PRINTED IN MEXICO

Elbrd: J.M / SHNMDL: VAP09R1AWT B SC: 09-12-2025 / OBPN: 16120300A28600 814100507