



REEL YAKS

Assembly Instructions

Radar

10ft Radar Modular Propeller Drive Pedal Fishing Kayak
430lbs Capacity | 2 Piece



Our Commitment

Congratulations on buying your Reel Yaks pedal kayak! We want you to love your kayak as much as we do. If you have any questions on your Reel Yaks kayak assembly, then please email us at hello@reelyaks.com or call us on 855 202 5035. Note we also have assembly videos on our website at WWW.REELYAKS.COM and on YouTube. If you run into any other issues, no matter how small, let us know and we'll take care of you.

Don't forget to fill out the **warranty form** on our website at www.reelyaks.com/pages/warranty-registration

If you are looking for any accessories to go with your Reel Yaks kayak such as a trolling mount, bimini, etc. then please visit us at WWW.REELYAKS.COM

Kayak Maintenance: We recommend a fresh water wash of all parts after every use and to spray any moving parts, screws and cables with WD40 once a month as a preventative measure.

Radar 10ft Propeller Pedal Drive Kayak Assembly Booklet

Congratulations on buying your Reel Yaks pedal kayak!! Note we also have assembly videos on our website at Reelyaks.com and on YouTube. If you have any questions on your Reel Yaks kayak assembly, then please email us at info@reelyaks.com or call us on 855 202 5035.

There are **six key** pieces of assembly to be done:

- 2 x Kayak halves
- Pedal drive
- Rudder
- Stadium seat
- Paddle
- Fishing rod holder

First step is to unpack your kayak which should come in two boxes and the kayak parts will have an outer sheet of bubble wrap, and some parts will be in cardboard boxes (e.g.: pedal drive). Please ensure to dispose of these materials safely in particular the plastic.



Each package will have:

- 1 x kayak (in two sections)
- 1 x rudder
- 1 x rudder security (cotter) pin
- 1 x paddle (in two sections)
- 1 x propeller pedal drive unit
- 1 x pedals (2)
- 1 x stadium chair
- 1 x fishing rod holder

The larger items will be secured in the main cockpit area: pedal drive unit, pedal drive pedals, paddle and stadium chair. Others like the fishing rod holder will be inside the cockpit hatch.


Kayak Assembly

For the kayak assembly ensure you have the two halves facing each other.

Step 1) Flip the kayak over so it's bottom up and bring the two halves together

Step 2) Close the three underside latches

Step 3) Flip the kayak over so its facing up the right way and close the top two latches




The latches should be set correctly for your kayak, but if you find you're having to force it then stop. Adjust the nut (orange arrow) to get a firm lock closure, but not without forcing it. If it's too loose then adjust the nut accordingly to get a good firm fit. Forcing the latch closed for an overly tight fit can damage the screws unnecessarily (blue arrow) on the adjoining catch.



Propeller Drive Assembly


For the propeller drive assembly there are a number of pieces that need to be assembled. First step is to find the two screws with black tops. These secure the pedals to the drive. The screws thread for each screw run counter/opposite to each other. Pick up the drive and check each screw to find which side they each fit to, be careful not to force the screws and strip the threads. The screws can **only fit into one side**.




Once you know which side they fit in then select a pedal these will have a label L for left and R for right. Choose R for right pedal, and with the pin for the propeller shaft pointing towards you secure the right pedal to the right side. Do the same for the left, making sure the left pedal is at the top when the right pedal is at the bottom so they are the complete opposite sides from each other (**Orange arrows**).



Next, we are going to secure the propeller to the drive. Find the propeller shaft pin and push it into the propeller drive (**Orange arrow**), there are two marks on the pin to help you center the shaft (**Blue arrows**).



Once this is in place, put the propeller onto the drive. You will need to gently rotate the propeller until it drops into place and locks over the shaft pin. To test you have this right, move the pedals and the propeller should now start to spin. Open the little plastic bag with the screw and lock washer. Place the lock washer onto the screw and screw this into place to secure the propeller to the drive.



REEL YAKS

Now grab the 4 long screws with nuts on the end. Take each of the 4 nuts off and push them into the 2 plastic curved arms with the blue side up. You'll see that on one side they have a hexagonal shape where the nuts sits. Push the nuts into there with your thumb and then use a hammer to gently secure them in place.




Then secure the arms to the drive shaft with the curve pointing down towards the propeller (Blue arrows) by screwing in the 4 screws into the nuts through the drive shaft.

Dependent on the kayak model – some bigger kayaks (+10ft) provide more space to provide an additional locking brackets (Green arrows) that are pushed onto either side of the shaft. If you fit these and then the drive doesn't fit into the recess well then don't be concerned, these can be removed and you can use the drive without them.



The drive is then locked into place. Make sure that the propeller is pointing to the seating area. Ensure the front and back knobs (Red arrows) are screwed all the way up before inserting the drive. The drop the drive in and twist locking handles on the left and right (Green arrows). Next gently and evenly twist the front and back knobs (Red arrows) until they are firm and prevent the drive from rocking forward and back. Be careful not to overtighten these!



Once this is complete and the drive is secure, there should be no side to side or forward and back motion in the drive. You'll now add the splash guards around the drive. Gently push these into place until they are flush with the deck.




Rudder Assembly


In some case the rudder handle may be in the front compartment. Use the supplied screw to secure it (**orange arrow**). Ensure when you've completed securing the handle that you have left it in the neutral position, with the handle parallel to the centre line of the kayak (**blue arrow**).



Next, ensure your rudder is untangled and the lines run free when taking it out of the cargo area. Put the pin of the rudder through the rear hole in the kayak. Check that the raising and lowering of the rudder operates smoothly. Next put in the rudder security pin (**orange arrow**) through the hole at the bottom of the rudder pin.




Next unwind the butterfly nuts and put them through the plastic holes on either side of the rudder and righten the butterfly nuts again.



Next grab hold of the rudder steering handle on the left side of the kayak near where the seat would be located. Pull the rudder handle all the way left and then all the way right, to ensure the rudder is tracking correctly, adjust the butterfly nuts as needed. Leave the rudder steering in the approximate centre spot. The steering wires should have a little bit of slack for ease of turning and to ensure minimal wear and tear where they enter the kayak.


In most cases the rudders lowering and raising cable is attached for transport (**Green Arrow**). However, in some cases it may not be and you'll need to thread the rudder rope through the center line of the rudder and attach it.

- 1) Thread it through the main hole at the start of the rudder (**Yellow Arrow**)
- 2) over the top of the wheel, but under the cross bar
- 3) down through the gap (**Purple Arrow**) and
- 4) then thread it through the hole (**blue arrow**) and tie a knot.



RY REEL YAKS

Test your rudder by pulling on the rudder raising/lower cable on the right side of the cockpit. 1) rudder is deployed and down in the water 2) rudder is pulled up and locked in position




Stadium Chair Assembly

For the stadium chair assembly you'll need the 2 X long screws, black seat brackets and allen wrench. In each seat rail you will have two slider receivers in which to you can secure your seat. Move one to the back of the kayak for each rail and screw in the black bracket in each.



Sit the back bar of the seat on top of the brackets, but don't pop them in yet. Screw the front of the seat into the two front slider receivers.



And then push the back bar down into the back seat brackets to secure that.



Lastly connect and secure the two side straps which hold the back of the seat upwards. Secure this in a slightly off of 90 degree upright position, this can be further adjusted once you're on the water. Also remember to take your allen wrench on your first couple of outings in case you want to further adjust your seat location.

Paddle Assembly

The paddle assembly is super simple, just depress the button and pop it into the desired hold (3 locations to choose from) to get the preferred orientation of your blades. Then use the paddle stretch cord to secure it. Remember not to leave it attached like that when the kayak is travelling on your car or truck.



Fishing Rod Holder Assembly


The rod holder assembly requires the: rod holder, the rod holder bracket (3 pieces), 2 x screws and the allen wrench.



Combine the three black round pieces together with the bottom, middle and top as indicated above.

Decide which rail in the cockpit you want to secure it to and move the slider receivers apart the approximate width of the screw holds and insert the screws.

Next insert the fishing rod holder into the now secure base by 'opening' the base as indicated below (**orange arrow**). Next close the slider to lock the fishing rod holder in place (**green arrow**).



You're now ready to hit the water!!

And don't forget to fill out the warranty form on our site.

And a reminder if you have any questions or concerns in respect of your Reel Yaks kayak then please email us at info@reelyaks.com or call us on 855 202 5035.

If you are looking for any accessories to go with your Reel Yaks kayak such as a trolling mount, bimini, etc. then please visit us at REELYAKS.COM

Kayak Accessories

If you are looking for any accessories to go with your Reel Yaks kayak or spare parts then please visit us at REELYAKS.COM

Kayak Trolley Dolly		Pedal Drive Cover	
Kayak Uv waterproof Cover		Kayak Motor Mount Bar	
Kayak Stabilizer Pontoons		Spare Pedal Drive Fins	
6 pack Accessory Rail Slider Mounts		Kayak Anchor Trolley Kit	

RY REEL YAKS

Kayak Uv shade Bimini		Kayak Sail Kite	
Pedal drive & bar mounted tolling motors Wide range 24lbs - 86lbs thrust		360 Fishing Rod Holder	

Also checkout our **Reel Yaks Kayak Fishing shirts** with **SPF50 Protection**
And many many more....

