

User Manual Jump Starter





GE PRO



SUPERSAFE® is a safety protection technology by GOOLOO®

Thank you for choosing GOOLOO jump starter. To ensure a good user experience, personal safety, and property security, please read all of the instructions carefully before using this product, please keep this manual for easy reference.




While reading through the manual, you can begin to charge up your GE PRO with your mobile phone charger and the type-c cable attached.

AWarning

This unit is for vehicle (equipment) with 12V batteries. It may be dangerous if it is used with other types of batteries. Read and understand the safety information before using the jump starter. Failure to follow the safety information may cause damage to the jump starter, and may also result in electric shock, explosions, fire, property damage, and personal injury.

Parts and Functional Description







Product Highlights

[POWERFUL START PERFORMANCE] GOOLOO GE PRO jump starter 6250A peak current can instantly start any 12V vehicle (ALL gas or 12L diesel engine). And the car starter battery capacity is up to 88.8Wh and has a service life of more than 1000+ recharge cycles.

IADVANCED START-UP SOLUTION The upgraded Intelligent chip & integrated design of the jump starter battery pack and jumper cable make the instantaneous starting current of the GE PRO battery booster pack increase by 80%, and the starting success rate is 50% higher than other traditional battery jump starter!

[ERGONOMIC DESIGN] GE PRO car jump starter is manufactured by a professional design team based on ergonomics combined with a large amount of experimental data. The grip design assists you to hold the GE PRO battery starter more firmly, and the integrated appearance makes the product easier to store.

[COMPREHENSIVE & INTELLIGENT PROTECTION]

The unique design of the GE PRO car battery booster makes it easy and fast to start your car in extreme environments (-4°F to 140°F), with built-in 10 safety protection technologies.

IMORE THAN A JUMP STARTER 400 lumens LED light provides you with three modes (Normal, Strobe, SOS) under different conditions, and jump box supports 48 hours of high-brightness lighting. Moreover, designed with USB outputs, the USB port can fully charge your cellphones, tablets, and other mobile

devices at the fastest speed possible.

Operation Instructions

Battery Indicator:

Press the power switch to check the battery power:


Indicator	Unlit	1 Solid	2 Solid	3 Solid	4 Solid
Battery Power	0%	25%	50%	75%	100%

The indicator will blink one by one during the period of charging. Different numbers of solid indicators show different battery power. All indicators will be turned off automatically when the charging process has finished.

How to Charge the GE PRO

This unit can be charged with the Type-C cable and your phone wall charger.

(Only via the QC3.0 wall charger or QC3.0 car charger can achieve the 18W max input function, QC3.0 wall charger and car charger can be purchased separately.)



How to Start a 12V Vehicle

(Make sure the battery power ≥ 2 bars) Note: Do not press the "BOOST" button before connecting the vehicle battery correctly.



1. Connect Vehicle Battery



2. Green LED illuminates(solid)



3. Start Vehicle Engine

Check the LED indicator in the front of this product and follow the instructions as below:

LED Indicator	Operation
Green LED (solid)	The connection is correct, you can start the vehicle directly.
Red LED+Beeping	Reverse connection, please correct the polarity of battery clamps.
Green LED (blinks) with beeping	The vehicle battery voltage is too low. Try to press the "BOOST" button for 2-3 seconds. When the green LED illuminates steadily, start the vehicle within 30 seconds.
NO Light, NO Beeping	The vehicle battery may be damaged. First, make sure the connection is correct. Press the "BOOST" button for 2-3 seconds. When the green LED illuminates steadily, and then start the vehicle within 30 seconds.
Green+Red LED (blinks)	If you start the vehicle non-stop more than 4 times within 10 minutes, the jump starter will enter safe mode. Stop starting your vehicle, safe mode will disappear after 10 mins.

If any problem persists, stop using the jump starter and contact our service team directly at **Karen@gooloo.com**, we will do our best to solve the problem within 24 hours.

How to Charge Your Phone or Tablet

- Plug the charging cable into the USB-A port and your devices.
- 2. After pressing the power switch, the unit can identify your device and charge it automatically. The battery indicators will light up when charging.



How To Turn On/Off The LED Flashlight

Long press the power switch 3 seconds to start the LED light. There are 3 modes of LED light appear in order (Normal, Strobe, SOS, Off) if you press slightly.

How to Turn Off This Unit

This unit will be turned off automatically in 30s when it's not used (no load).

Package Content

#	Part Name	Quantity
1	Host with battery clamps	1
2	Carrying Bag	1
3	USB-A to USB-C Cable	1
4	User Manual	1

Technical Specification

Capacity	88.8Wh
Starting Current	800A
Peak Current	6250A
USB-C In	5V/2A, 9V/2A
USB Out	5V/2.4A
Operating Temp	-20℃~60℃/-4 F ~140 F
Life time	> 1000 Cycles
Full Charge Time	6-8 hours (QC3.0 charger)

Toxic and Harmful Substances

Composition and amount of toxic or harmful substance in this product

Pb Ha Cd Cr(Vi) PBB PBDE

 Pb
 Hg
 Cd
 Cr(Vi)
 PBB
 PBDE

 0
 0
 0
 0
 0
 0

0: Indicate that the content of harmful substances in all homogeneous materials is all lower than the prescribed limit of MCV (the standard 2002/95/EC/RoHs)

FAQ

Q1: What is the operating temperature of this unit and how to store it?

A: This unit uses a lithium-polymer battery, and its operating temp is -20-60°C/ -4-140°F. If the ambient temperature is higher than 60°C/140°F, the internal construction of the polymer lithium-ion cells will be damaged, and it may swell and become unsafe. So don't store the device in a vehicle which is parked in hot weather for long periods of time.

Q2: How to start a vehicle with this unit?

A: Please refer to the instructions about " How to Start a 12V Vehicle."

Q3: Why do Green and Red light blink alternately?

A: The jump starter has an Over-start Protection function. If you start the vehicle continuously for more than 4 times within 10 minutes, the jump starter will turn into Over-start Protection (the green and red lights will blink alternately). Meanwhile, there will be no output of battery clamps. You can disconnect the jumper cable plug from the jumper starter, and then the Over-start Protection will be removed.

Q4: How do you know if this unit is connected to the vehicle correctly?

A: The battery clamps are connected to the vehicle battery. When the indicator shines a steady green light, it means it's connected correctly. If the red light is on and solid, and there is beeping, it means it's a reverse connection.

Q5: What should I do if this unit can't start a vehicle?

A: Recharge this unit fully, and try to press the "BOOST" button. Wait until the GREEN LIGHT is on and solid, then start the vehicle within 30s. If it still doesn't work, please contact us at karen@gooloo.com and kindly attach your order ID.

Q6: What should I do if this unit can't be charged? **A:** Charge it with a USB-C cable and wall charger to activate it. If it still doesn't work, please contact us at karen@gooloo.com and kindly attach your order ID.

Q7: What should I do if this unit can't charge other devices?

A: Try to use another charging cable to charge it again. If it can charge with another one, the charging cable attached is defective; Contact us we will provide you a new one. If it still doesn't work, please contact us at karen@gooloo.com and kindly attach your order ID for assistance.

Q8: How to turn off this unit?

A: The unit will be turned off automatically in 30 seconds when it has no load.

Q9: Can this unit charge other devices while it is being charged?

A: Yes.

Q10: Can this unit charge other devices while starting a vehicle?

A: No.

Q11: How often does this unit need to recharge? **A:** It would be best to be recharged every 3 months.

Q12: Why it shuts off in 30s when charging for other devices?

A: This product may not be able to charge for the devices that need weak current like iphone 6 series, headphone, smart watch, etc. Because this unit has a minimum load current (200mA). it will be automatically off after 30s if the load current is less than 200mA.



- 1. Read this instruction manual carefully before using this unit
- Use caution while using this unit. Injury to self, or damage to the unit or the vehicle battery if precautions are not followed.
- 3. Do Not allow to use by persons who do not have proper knowledge or ability to operate the device without supervision.
- 4. Do Not use as a toy. Keep the unit away from children to avoid accident.
- 5.This unit is for 12V vehicles only, it may not be suitable for other vehicles. It is forbidden to use for other machines such as aircraft, boats, etc.
- 6. Do Not use this unit if any cable, clamp, or cord is damaged or if the unit is overheated or swelled or leaking fluid.
- Do Not use in place of a vehicle battery or as a vehicle battery charger.
- Do Not use the unit to start a vehicle while charging the internal battery.
- 9. Only use the jumper cable attached and use the correct and qualified charger to charge this unit.
- 10. Do Not let this unit over-discharge (do not let the battery run to empty), please charge it regularly; it would be best to recharge it every 3 months.

- 11. Make sure the blue plug of the jumper cable is plugged fully into the jumper socket; otherwise, the blue plug could melt.
- 12. Make sure the battery terminal are clean before starting, and make sure the battery clamps are well connected. If the battery terminals on the vehicle are dirty or corroded, the output power of the unit will be lessened.
- 13. Do Not start the vehicle continuously more than 4 times within 10minutes, if the vehicle can't be started at one time, please wait at least 30seconds to restart it.
- 14. Do Not connect the two clamps together.
- 15. Do Not connect the jump starter's clamps to the battery reversely while pressing the "BOOST" button to avoid accident.
- 16. Only use this unit to start the vehicle when the battery indicator is more than 2 bars.
- 17. Do Not keep the unit connected to the vehicle battery after successfully starting the engine. Remove the product from the vehicle battery after starting the engine. If not, it could lead to damage.
- 18. Do Not recharge this product immediately after using it to start the vehicle, please cool it down for 30 minutes before charging.
- 19. Do Not allow the product to become wet and Do Not immerse in water.
- 20. Do Not operate the product in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust.

- 21. Do Not modify or disassemble the unit. Only a repair technician may repair this unit.
- 22. Do Not expose product to extreme heat or fire.
- 23. Do Not drop or crush the unit. If the unit has received a sharp blow or is damaged in any other way, a qualified battery technician should check it.
- 24. Do Not store in locations where the temperature may exceed 60° C/ 140° F.
- 25. Charge only at ambient temperature between -10~45°C/14~113°F.
- 26. Under extreme conditions, the battery may leak. If a liquid is leaking from the unit, Do Not handle with bare hands. In case of skin contact wash with soap and water immediately. If the liquid contacts to eyes, rinse eyes with cold running water for at least 10 minutes and get medical treatment immediately.
- 27. The unit contains the lithium-based batteries. At end of the product life, or if the unit is leaking liquid, dispose the unit according to local regulation.

Your Warranty Includes

- 18 Months Online After- Sales Service
 Within 18 months, we will provide timely and effective
 online after- sales service after your purchase.
- 30 Days Money Back Guarantee
 Within the first 30 days after your purchase, you can apply return for it when you have any issue.

30 Days to 18 Months

We will replace the defective unit due to manufacturing issues with a new one within 18 months

Disclaimer

- **A.** The warranty is valid upon presentation of the original receipt (Order ID) by the original purchaser with the product need to be repaired or replaced.
- **B.** The warranty does not cover damage or product failure resulting from normal wear and tear, physical abuse, improper installation, misuse, modification or repairs by unauthorized third parties.
- **C.** We are not liable for any incidental or consequential damage that arises from incorrect use or misuse of this product.
- **D.** All warranty claims are limited to repair or replacement of the defective product and at the sole discretion of GOOLOO.



Attention



Do Not Submerge In Water



Do Not Disassemble



Do Not Drop



Avoid Extreme Temperatures



Do Not Place Near or Into Fire



Overcharge/Discharge Fuse Protection Against-reverse Protection



Plug

Customer Service



18 Months Limited Warranty Service



Lifetime Technical Service



Feel Free to Contact Us karen@gooloo.com



For FAQ and More Information www.gooloo.com



1-888-886-1805 Mon.-Fri. PST 9:00a.m.-5:00p.m.



Thank You for Choosing



Manufacturer	Shenzhen Carku Technology Co.,Ltd	
Address	No.103, block A, Qixing Creative factory, GaoFeng	
	community, Dalang street, LongHua, Shenzhen,	
	Guangdong, China	
Importer	shen zhen shi lan de wo ke ji you xian gong si	
Address	Guangdong, Shenzhen, Longgang, 2nd Floor,	
	Building 12, Shenao Cultural Industry Park,	
	Dafapu Community, Bantian Street	
Tel	+442921680945	
UK Representative Name and contact	UK REP Office 101 32 Threadneedle Street, London, United Kingdom, ECZR 8AY OST_UK_20220608000011 contact@evatost.com We simply act as UK representative for cross-border sellers, and are not manufacturers in the product. Therefore, we are not responsible for any after-sellers schwicks related to the product. In case of any groduct quality or infringement issues, the manufacturer/importer/seller shall be soldly bled responsible.	