



# **Uni Wall Mount**

## BWP420 LED NW 220V 20W WB PSU 7012

Uni Wall Mount, 2700 lm, 20 W, 740 neutral white, Safety class I

Public areas all seek for the most reliable and professional lighting solutions, e.g., parking areas, entrances, outdoor terrace, and wall in garden. Thanks to the adjustable mounting angle, the fixture can be installed in accordance with per requirement, delivering the optimized lighting to surroundings. The modern sleek design makes the fixture suitable to be installed either in renovation or new installation scenarios. The Philips Uni Wall Mount help you achieve superb reliability and more. Same as other product range in Philips, the product is designed under a variety of Philips quality standard with a good price/quality ratio. Therefore, Philips Uni Wall Mount offers an affordable, energy — efficient and stable choice in wall Mounting family.

#### **Product data**

| General Information                |                   |
|------------------------------------|-------------------|
| Driver included                    | Yes               |
| Light source engine type           | LED               |
| CE mark                            | CE mark           |
| Warranty period                    | 3 years           |
|                                    |                   |
| Light Technical                    |                   |
| Luminous Flux                      | 2,700 lm          |
| Correlated Color Temperature (Nom) | 4000 K            |
| Luminous Efficacy (rated) (Nom)    | 125 lm/W          |
| Color rendering index (CRI)        | 70                |
| Light source color                 | 740 neutral white |
| Optical cover type                 | Flat glass        |
|                                    |                   |

| Operating and Electrical  |                        |
|---------------------------|------------------------|
| Input Voltage             | 220 to 240 V           |
| Line Frequency            | 50 or 60 Hz            |
| Power Consumption         | 20 W                   |
| Power Factor (Fraction)   | 0.95                   |
| Connection                | Connection unit 3-pole |
| Cable                     | Cable without plug     |
|                           |                        |
| Temperature               |                        |
| Ambient temperature range | -40 to +50 °C          |
|                           |                        |
| Controls and Dimming      |                        |
| Dimmable                  | No                     |
| Control interface         | -                      |
|                           |                        |


Datasheet, 2024, March 8 data subject to change

# **Uni Wall Mount**

| Mechanical and Housing              |  |  |
|-------------------------------------|--|--|
| Housing Material                    | Aluminum die-cast                            |  |
| Optical cover material              | Tempered glass                               |  |
| Housing Color                       | Gray   |  |
| Overall length                      | 168 mm                                       |  |
| Overall width                       | 113 mm                                       |  |
| Overall height                      | 197 mm                                       |  |
| Dimensions (Height x Width x Depth) | 197 x 113 x 168 mm                           |  |
|                                     |  |  |
| Approval and Application            |  |  |
| Ingress protection code             | IP65 [Dust penetration-protected, jet-proof] |  |
| Mech. impact protection code        | IK08 [5 J vandal-protected]                  |  |
| Protection class IEC                | Safety class I                               |  |
|                                     |  |  |
| Initial Performance (IEC Compliant) |  |  |
| Luminous flux tolerance             | +/-10%                                       |  |

| Power consumption tolerance     | +/-10%                             |
|---------------------------------|------------------------------------|
|                                 |                                    |
| Product Data                    |                                    |
| Order product name              | BWP420 LED NW 220V 20W WB PSU 7012 |
| Full product name               | BWP420 LED NW 220V 20W WB PSU 7012 |
| Full product code               | 692382861096899                    |
| Order code                      | 911401698008                       |
| Material Nr. (12NC)             | 911401698008                       |
| Numerator - Quantity Per Pack   | 1                                  |
| EAN/UPC - Product/Case          | 6923828610968                      |
| Numerator - Packs per outer box | 4                                  |
| EAN/UPC - Case                  | 6923828611231                      |
|                                 |                                    |

## Dimensional drawing





© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.