

# **GIGABYTE™**

## **G4L3-ZD1-LAX3**

## **G4L3-ZD1-LAX5**

HPC/AI Server

AMD EPYC™ 9005/9004

4U DP NVIDIA HGX™ H200 8-GPU DLC (LAX3)

4U DP NVIDIA HGX™ B200 8-GPU DLC (LAX5)

## **User Manual**

Rev.1.0

## **Copyright**

© 2025 Giga Computing Technology CO., LTD. All rights reserved.

The trademarks mentioned in this manual are legally registered to their respective owners.

## **Disclaimer**

Information in this manual is protected by copyright laws and is the property of Giga Computing. Changes to the specifications and features in this manual may be made by Giga Computing without prior notice. No part of this manual may be reproduced, copied, translated, transmitted, or published in any form or by any means without Giga Computing's prior written permission.

## **Documentation Classifications**

In order to assist in the use of this product, Giga Computing provides the following types of documentation:

- User Manual: detailed information & steps about the installation, configuration and use of this product (e.g. motherboard, server barebones), covering hardware and BIOS.
- User Guide: detailed information about the installation & use of an add-on hardware or software component (e.g. BMC firmware, rail-kit) compatible with this product.
- Quick Installation Guide: a short guide with visual diagrams that you can reference easily for installation purposes of this product (e.g. motherboard, server barebones).

Please see the support section of the online product page to check the current availability of these documents.

## **For More Information**

For related product specifications, the latest firmware and software, and other information please visit our website at <http://www.gigabyte.com/Enterprise>

For GIGABYTE distributors and resellers, additional sales & marketing materials are available from our reseller portal: <http://reseller.b2b.gigabyte.com>

For further technical assistance, please contact your GIGABYTE representative or visit <https://esupport.gigabyte.com/> to create a new support ticket

For any general sales or marketing enquiries, you may also message GIGABYTE server directly by email: [server.grp@gigabyte.com](mailto:server.grp@gigabyte.com)

# Conventions

The following conventions are used in this user's guide:

|                                                                                   |                                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
|  | <b>NOTE!</b><br>Pieces of additional information related to the current topic.                      |
|  | <b>CAUTION!</b><br>Precautionary measures to avoid possible hardware or software problems.          |
|  | <b>WARNING!</b><br>Alerts to any damage that might result from doing or not doing specific actions. |

## Server Warnings and Cautions

Before installing a server, be sure that you understand the following warnings and cautions.



### **WARNING!**

**To reduce the risk of electric shock or damage to the equipment:**

- Do not disable the power cord grounding plug. The grounding plug is an important safety feature.
- Plug the power cord into a grounded (earthed) electrical outlet that is easily accessible at all times.
- Unplug the power cord from the power supply to disconnect power to the equipment.



- Shock Hazard! Disconnect all power supply cords before servicing.
- Do not route the power cord where it can be walked on or pinched by items placed against it. Pay particular attention to the plug, electrical outlet, and the point where the cord extends from the server.
- Do not route the power cord where it can be walked on or pinched by items placed against it. Pay particular attention to the plug, electrical outlet, and the point where the cord extends from the server.



### **WARNING!**

**To reduce the risk of personal injury from hot surfaces, allow the drives and the internal system components to cool before touching them.**



**This server is equipped with high speed fans. Keep away from hazardous moving fan blades during servicing.**



**This equipment is intended to be used in Restrict Access Location. The access can only be gained by Skilled person. Only authorized by well trained professional person can access the restrict access location.**

•



**This equipment is not intended for use by children.**



**CAUTION!**

- Do not operate the server for long periods with the access panel open or removed. Operating the server in this manner results in improper airflow and improper cooling that can lead to thermal damage.
- Danger of explosion if battery is incorrectly replaced.
- Replace only with the same or equivalent type recommended by the manufacturer.
- Dispose of used batteries according to the manufacturer's instructions.

**CAUTION!**

Risk of explosion if battery is replaced incorrectly or with an incorrect type. Replace the battery only with the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instructions.

**Warning Stability hazard**

The slide-rail may tip over causing serious personal injury

- Before extending the rack to its installation position, read the installation instructions.
- Do not put any load on the slide-rail mounted equipment in the installation position.
- Do not leave the slide-rail mounted equipment in the installation position.



## Electrostatic Discharge (ESD)

### CAUTION!

ESD CAN DAMAGE DRIVES, BOARDS, AND OTHER PARTS. WE RECOMMEND THAT YOU PERFORM ALL PROCEDURES AT AN ESD WORKSTATION. IF ONE IS NOT AVAILABLE, PROVIDE SOME ESD PROTECTION BY WEARING AN ANTI-STATIC WRIST STRAP ATTACHED TO CHASSIS GROUND -- ANY UNPAINTED METAL SURFACE -- ON YOUR SERVER WHEN HANDLING PARTS.

Always handle boards carefully, they can be extremely sensitive to ESD. Hold boards only by their edges without touching any components or connectors. After removing a board from its protective ESD bag or from the system, place the board component side up on a grounded, static free surface. Use a conductive foam pad if available but not the ESD bag. Do not slide the board over any surface.

**System power on/off:** To service components within the server, please ensure the power has been disconnected.

e.g. Remove the node from the server chassis (to disconnect power) or disconnect the power from the server chassis.

Make sure the system is removed from the rack before opening the chassis, adding, or removing any non hot-plug components.

**Hazardous conditions, devices and cables:** Hazardous electrical conditions may be present on power, telephone, and communication cables. Turn off the system chassis and disconnect the cables attached to the system before servicing the chassis. Otherwise, personal injury or equipment damage can result.

**Electrostatic discharge (ESD) and ESD protection:** ESD can damage drives, boards, and other parts. We recommend that you perform all procedures in this chapter only at an ESD workstation. If one is not available, provide some ESD protection by wearing an antistatic wrist strap attached to chassis ground (any unpainted metal surface on the server) when handling parts.

**ESD and handling boards:** Always handle boards carefully. They can be extremely sensitive to electrostatic discharge (ESD). Hold boards only by their edges. After removing a board from its protective wrapper or from the system, place the board component side up on a grounded, static free surface. Use a conductive foam pad if available but not the board wrapper. Do not slide board over any surface.

**Installing or removing jumpers:** A jumper is a small plastic encased conductor that slips over two jumper pins. Some jumpers have a small tab on top that can be gripped with fingertips or with a pair of fine needle nosed pliers. If the jumpers do not have such a tab, take care when using needle nosed pliers to remove or install a jumper; grip the narrow sides of the jumper with the pliers, never the wide sides. Gripping the wide sides can damage the contacts inside the jumper, causing intermittent problems with the function controlled by that jumper. Take care to grip with, but not squeeze, the pliers or other tool used to remove a jumper, or the pins on the board may bend or break.

# Table of Contents

|                                                          |    |
|----------------------------------------------------------|----|
| Chapter 1 Hardware Installation .....                    | 11 |
| 1-1 Installation Precautions .....                       | 11 |
| 1-2 Product Specifications .....                         | 12 |
| 1-3 System Block Diagram .....                           | 15 |
| 1-4 PCIe Block Diagram .....                             | 16 |
| Chapter 2 System Appearance .....                        | 17 |
| 2-1 Front View .....                                     | 17 |
| 2-2 Rear View .....                                      | 18 |
| 2-3 System Components .....                              | 19 |
| 2-4 Front Panel LEDs and Buttons .....                   | 20 |
| 2-5 RoT LEDs .....                                       | 21 |
| 2-6 Front System LAN LEDs .....                          | 23 |
| 2-7 Rear System LAN LED .....                            | 23 |
| 2-8 Power Supply Unit LED .....                          | 24 |
| 2-9 Hard Disk Drive LEDs .....                           | 25 |
| Chapter 3 System Hardware Installation .....             | 26 |
| 3-1 Removing and Installing the Hard Disk Drive .....    | 27 |
| 3-2 Removing and Installing the GPU Tray .....           | 28 |
| 3-3 Removing and Installing the Motherboard Tray .....   | 29 |
| 3-4 Liquid Cooling Assembly Information .....            | 30 |
| 3-4-1 Liquid Cooling Specifications .....                | 32 |
| 3-5 Installing the CPU and the Coolant Pipe Module ..... | 34 |
| 3-6 Removing and Installing Memory .....                 | 36 |
| 3-6-1 Eight Channel Memory Configuration .....           | 36 |
| 3-6-2 Removing and Installing a Memory Module .....      | 37 |
| 3-6-3 Processor and Memory Module Matrix Table .....     | 37 |
| 3-6-4 Memory Population Table .....                      | 38 |
| 3-7 Removing and Installing the PCIe Card .....          | 39 |
| 3-8 Removing and Installing the Power Supply .....       | 42 |
| 3-9 Installing the M.2 Device and Heat Sink .....        | 43 |
| 3-9-1 M.2 device with Heatsink .....                     | 43 |
| 3-10 Removing and Installing the Top Cover .....         | 44 |
| 3-11 Installing the System into the Cabinet .....        | 45 |
| 3-12 Cable Connection .....                              | 46 |

|                                                              |     |
|--------------------------------------------------------------|-----|
| Chapter 4 Motherboard Components .....                       | 50  |
| 4-1 Motherboard Components .....                             | 50  |
| 4-2 Jumper Settings .....                                    | 52  |
| 4-3 Backplane Board Storage Connector .....                  | 53  |
| 4-2-1 CBPG641 (Front System Storage Board) .....             | 53  |
| Chapter 5 BIOS Setup .....                                   | 54  |
| 5-1 The Main Menu .....                                      | 56  |
| 5-2 Advanced Menu .....                                      | 59  |
| 5-2-1 KMIP Server Configuration .....                        | 60  |
| 5-2-2 KMS Policy Configuration .....                         | 61  |
| 5-2-3 CPU Configuration .....                                | 62  |
| 5-2-4 NVMe Configuration .....                               | 63  |
| 5-2-5 SATA Configuration .....                               | 64  |
| 5-2-6 USB Configuration .....                                | 65  |
| 5-2-7 PCI Subsystem Settings .....                           | 67  |
| 5-2-8 AST2600 Super IO Configuration .....                   | 69  |
| 5-2-9 Serial Port Console Redirection .....                  | 71  |
| 5-2-10 Network Stack Configuration .....                     | 75  |
| 5-2-11 Post Report Configuration .....                       | 76  |
| 5-2-12 Trusted Computing .....                               | 77  |
| 5-2-13 PSP Firmware Versions .....                           | 78  |
| 5-2-14 S5 RTC Wake Settings .....                            | 79  |
| 5-2-15 Graphic Output Configuration .....                    | 80  |
| 5-2-16 AMD Mem Configuration Status .....                    | 81  |
| 5-2-17 Tls Auth Configuration .....                          | 82  |
| 5-2-18 RAM Disk Configuration .....                          | 83  |
| 5-2-19 iSCSI Configuration .....                             | 84  |
| 5-2-20 Intel(R) Ethernet Controller X710 for 10GBASE-T ..... | 85  |
| 5-2-21 VLAN Configuration .....                              | 87  |
| 5-2-22 MAC IPv4 Network Configuration .....                  | 88  |
| 5-2-23 MAC IPv6 Network Configuration .....                  | 89  |
| 5-3 AMD CBS Menu .....                                       | 90  |
| 5-3-1 CPU Common Options .....                               | 91  |
| 5-3-2 DF Common Options .....                                | 97  |
| 5-3-3 UMC Common Options .....                               | 105 |
| 5-3-4 NBIO Common Options .....                              | 125 |
| 5-3-5 FCH Common Options .....                               | 137 |
| 5-3-6 SOC Miscellaneous Control .....                        | 145 |
| 5-3-7 CXL Common Options .....                               | 147 |
| 5-4 AMD PBS Menu .....                                       | 149 |

|       |                                      |     |
|-------|--------------------------------------|-----|
| 5-4-1 | RAS .....                            | 150 |
| 5-5   | Chipset Setup Menu.....              | 152 |
| 5-5-1 | North Bridge .....                   | 153 |
| 5-6   | Server Management Menu.....          | 154 |
| 5-6-1 | System Event Log .....               | 156 |
| 5-6-2 | View FRU Information .....           | 157 |
| 5-6-3 | BMC VLAN Configuration.....          | 158 |
| 5-6-4 | BMC Network Configuration .....      | 159 |
| 5-6-5 | IPv6 BMC Network Configuration ..... | 160 |
| 5-7   | Security Menu .....                  | 161 |
| 5-7-1 | Secure Boot .....                    | 162 |
| 5-8   | Boot Menu.....                       | 164 |
| 5-9   | Save & Exit Menu.....                | 166 |
| 5-10  | BIOS Recovery .....                  | 167 |

# Chapter 1 Hardware Installation

## 1-1 Installation Precautions

The motherboard/system contain numerous delicate electronic circuits and components which can become damaged as a result of electrostatic discharge (ESD). Prior to installation, carefully read the service guide and follow these procedures:

- Prior to installation, do not remove or break motherboard S/N (Serial Number) sticker or warranty sticker provided by your dealer. These stickers are required for warranty validation.
- Always remove the AC power by unplugging the power cord from the power outlet before installing or removing the motherboard or other hardware components.
- When connecting hardware components to the internal connectors on the motherboard, make sure they are connected tightly and securely.
- When handling the motherboard, avoid touching any metal leads or connectors.
- It is best to wear an electrostatic discharge (ESD) wrist strap when handling electronic components such as a motherboard, CPU or memory. If you do not have an ESD wrist strap, keep your hands dry and first touch a metal object to eliminate static electricity.
- Prior to installing the motherboard, please have it on top of an antistatic pad or within an electrostatic shielding container.
- Before unplugging the power supply cable from the motherboard, make sure the power supply has been turned off.
- Before turning on the power, make sure the power supply voltage has been set according to the local voltage standard.
- Before using the product, please verify that all cables and power connectors of your hardware components are connected.
- To prevent damage to the motherboard, do not allow screws to come in contact with the motherboard circuit or its components.
- Make sure there are no leftover screws or metal components placed on the motherboard or within the computer casing.
- Do not place the computer system on an uneven surface.
- Do not place the computer system in a high-temperature environment.
- Turning on the computer power during the installation process can lead to damage to system components as well as physical harm to the user.
- If you are uncertain about any installation steps or have a problem related to the use of the product, please consult a certified computer technician.

## 1-2 Product Specifications



### NOTE:

We reserve the right to make any changes to the product specifications and product-related information without prior notice.

|                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  System Dimension | <ul style="list-style-type: none"><li>◆ 2U</li><li>◆ 438 (W) x 87.5 (H) x 815(D) mm</li></ul>                                                                                                                                                                                                                                                                                                                                                        |
|  CPU              | <ul style="list-style-type: none"><li>◆ AMD EPYC™ 9005 Series Processors</li><li>◆ AMD EPYC™ 9004 Series Processors</li></ul> <p>Dual processor, cTDP up to 500W <sup>[1]</sup></p> <p>[1] The ambient temperature is limited to 30°C when NVIDIA BlueField®-3 DPUs are installed.</p> <p>[Note] If only 1 CPU is installed, some PCIe or memory functions might be unavailable.</p>                                                                 |
|  Socket           | <ul style="list-style-type: none"><li>◆ 2 x LGA 6096</li><li>◆ Socket SP5</li></ul>                                                                                                                                                                                                                                                                                                                                                                  |
|  Chipset          | <ul style="list-style-type: none"><li>◆ System on Chip</li></ul>                                                                                                                                                                                                                                                                                                                                                                                     |
|  Memory           | <ul style="list-style-type: none"><li>◆ 24 x DIMM slots</li><li>◆ DDR5 memory supported</li><li>◆ 12-Channel memory per processor</li></ul> <p><b>AMD EPYC™ 9005:</b></p> <ul style="list-style-type: none"><li>◆ RDIMM: Up to 6400 MT/s</li></ul> <p><b>AMD EPYC™ 9004:</b></p> <ul style="list-style-type: none"><li>◆ RDIMM: Up to 4800 MT/s</li></ul>                                                                                            |
|  LAN             | <p><b>Front (I/O board - CFPG540):</b></p> <p>2 x 10Gb/s LAN (1 x Intel® X710-AT2)</p> <ul style="list-style-type: none"><li>◆ Support NCSI function</li><li>◆ 1 x 10/100/1000 management LAN</li></ul> <p><b>Rear (MLAN board - CDB66):</b></p> <ul style="list-style-type: none"><li>◆ 1 x 10/100/1000 Mbps Management LAN</li></ul> <p>[Note] When both MLAN ports are connected with cables, the front MLAN port will be set as the default.</p> |
|  Video          | <ul style="list-style-type: none"><li>◆ Integrated in ASPEED® AST2600</li><li>◆ 1 x VGA port</li></ul>                                                                                                                                                                                                                                                                                                                                               |



|                                                                                     |                  |                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------------------------------------------------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Storage          | <p><b>Front hot-swap:</b></p> <ul style="list-style-type: none"> <li>◆ 8 x 2.5" Gen5 NVMe</li> <li>◆ (NVMe from PEX89104)</li> </ul> <p><b>Internal M.2:</b></p> <ul style="list-style-type: none"> <li>◆ 1 x M.2 (2280/22110), PCIe Gen3 x4, from CPU_1</li> <li>◆ 1 x M.2 (2280/22110), PCIe Gen3 x1, from CPU_0</li> </ul>                                                                                 |
|    | Modular GPU      | <p><b>G4L3-ZD1-LAX3</b></p> <ul style="list-style-type: none"> <li>◆ Liquid-cooled NVIDIA HGX™ H200 with 8 x SXM GPUs</li> </ul> <p><b>G4L3-ZD1-LAX5</b></p> <ul style="list-style-type: none"> <li>◆ Liquid-cooled NVIDIA HGX™ B200 with 8 x SXM GPUs</li> </ul>                                                                                                                                             |
|    | Expansion Slot   | <p><b>PCIe Bridge Board - CBG76:</b></p> <ul style="list-style-type: none"> <li>◆ P8 x FHHL x16 (Gen5 x16), from PEX89104</li> </ul> <p><b>PCIe Bridge Board - CPBG045 x 2:</b></p> <ul style="list-style-type: none"> <li>◆ 4 x FHHL x16 (Gen5 x16), from PEX89048</li> </ul>                                                                                                                                |
|    | Front I/O        | <p><b>I/O board - CFPG540:</b></p> <ul style="list-style-type: none"> <li>◆ 2 x USB 3.2 Gen1 ports (Type-A)</li> <li>◆ 1 x VGA port</li> <li>◆ 2 x RJ45 ports</li> <li>◆ 1 x MLAN port (default)</li> <li>◆ 1 x Power button with LED</li> <li>◆ 1 x ID button with LED</li> <li>◆ 1 x NMI button</li> <li>◆ 1 x Reset button</li> <li>◆ 1 x Storage activity LED</li> <li>◆ 1 x System status LED</li> </ul> |
|   | Rear I/O         | <p><b>MLAN board - CDB66:</b></p> <ul style="list-style-type: none"> <li>◆ 1 x MLAN port</li> </ul>                                                                                                                                                                                                                                                                                                           |
|  | Backplane Board  | <p>Speed and bandwidth:</p> <ul style="list-style-type: none"> <li>◆ PCIe Gen5 x4</li> </ul>                                                                                                                                                                                                                                                                                                                  |
|  | Security Modules | <ul style="list-style-type: none"> <li>◆ 1 x TPM header with SPI interface</li> <li>◆ <b>Optional</b> TPM2.0 kit: CTM010</li> </ul>                                                                                                                                                                                                                                                                           |



## Power Supply

- ◆ 4+4 3000W 80 PLUS Titanium redundant power supplies <sup>[1]</sup>

[1] The system power supply requires C19 power cord.

### [Note]

- ◆ Please refer to GIGABYTE Website for detail power supply specification.
- ◆ GIGABYTE offers PSUs with various efficiency ratings and power outputs. Full redundancy may depend on your server configuration, and alternative PSU options may be needed. Please contact our sales representatives for the best power solution.



## System Management

- ◆ ASPEED® AST2600 Baseboard Management Controller
- ◆ GIGABYTE Management Console web interface
- ◆ Dashboard
- ◆ HTML5 KVM
- ◆ Sensor Monitor (Voltage, RPM, Temperature, CPU Status ...etc.)
- ◆ Sensor Reading History Data
- ◆ FRU Information
- ◆ SEL Log in Linear Storage / Circular Storage Policy
- ◆ Hardware Inventory
- ◆ Fan Profile
- ◆ System Firewall
- ◆ Power Consumption
- ◆ Power Control
- ◆ Advanced power capping
- ◆ LDAP / AD / RADIUS Support
- ◆ Backup & Restore Configuration
- ◆ Remote BIOS/BMC/CPLD Update
- ◆ Event Log Filter
- ◆ User Management
- ◆ Media Redirection Settings
- ◆ PAM Order Settings
- ◆ SSL Settings
- ◆ SMTP Settings



## Operating Properties


- ◆ Operating temperature: 10°C to 35°C
- ◆ Operating humidity: 8%-80% (non-condensing)
- ◆ Non-operating temperature: -40°C to 60°C
- ◆ Non-operating humidity: 20%-95% (non-condensing)

### NOTE!

- ◆ **To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 40°C.**




# 1-4 PCIe Block Diagram




## Chapter 2 System Appearance

### 2-1 Front View

G4L3-ZD1-LAX3



G4L3-ZD1-LAX5




| No.                                                                                                                                                                                                                     | Description                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| 1.                                                                                                                                                                                                                      | USB 3.2 Gen1 Port x 2        |
| 2.                                                                                                                                                                                                                      | Management LAN Port          |
| 3.                                                                                                                                                                                                                      | VGA Port                     |
| 4.                                                                                                                                                                                                                      | Front Panel LEDs and Buttons |
| 5.                                                                                                                                                                                                                      | Data LAN Port x 2            |
| 6.                                                                                                                                                                                                                      | Motherboard Tray             |
| 7.                                                                                                                                                                                                                      | GPU Tray                     |
| 8.                                                                                                                                                                                                                      | Coolant Pipe slot            |
| <div style="display: flex; justify-content: space-between; align-items: center;"> <span><span style="color: blue;">●</span> Coolant Supply</span> <span><span style="color: red;">●</span> Coolant Return</span> </div> |                              |



- Refer to section **2-4 Front Panel LEDs and Buttons** for a detailed description of the function of the LEDs.
- Only one Management LAN (front side or rear) can be used at a time.
- The actual product may vary based on the cooling module configurations.

## 2-2 Rear View




| No. | Description         |
|-----|---------------------|
| 1.  | PCIe Card Cage x 2  |
| 2.  | PCIe Slot x 8       |
| 3.  | Management LAN Port |




- Refer to section **2-6 Front System LAN LEDs** for a detailed description of the function of the LEDs.
- Only one Management LAN (front side or rear) can be used at a time.

## 2-3 System Components



## 2-4 Front Panel LEDs and Buttons




| No. | Name                                 | Color           | Status   | Description                                                                                                                                   |
|-----|--------------------------------------|-----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 1.  | ID Button with LED <sup>(Note)</sup> | Blue            | On       | System identification is active.                                                                                                              |
|     |                                      | N/A             | Off      | System identification is disabled.                                                                                                            |
| 2.  | Power button with LED                | Green           | On       | Indicates the system is powered on.                                                                                                           |
|     |                                      | N/A             | Off      | System is not powered on or in ACPI S5 state (power off)                                                                                      |
| 3.  | NMI button                           | --              | --       | Press this button for the server to generate a NMI to the processor. If multiple-bit ECC errors occur, the server will effectively be halted. |
| 4.  | Reset Button                         | --              | --       | Press this button to reset the system.                                                                                                        |
| 5.  | System Status LED <sup>(Note)</sup>  | Green           | Solid On | System is operating normally.                                                                                                                 |
|     |                                      | Amber           | Solid On | Critical condition, may indicate:<br>System fan failure<br>System temperature                                                                 |
|     |                                      |                 | Blink    | Non-critical condition, may indicate:<br>Redundant power module failure<br>Temperature and voltage issue<br>Chassis intrusion                 |
|     |                                      | N/A             | Off      | System is not ready, may indicate:<br>POST error<br>NMI error<br>Processor or terminator missing                                              |
| 6.  | HDD Status LED                       | Green           | On       | Indicates locating the HDD.                                                                                                                   |
|     |                                      |                 | Blink    | Indicates accessing the HDD.                                                                                                                  |
|     |                                      | Amber           | On       | Indicates HDD error.                                                                                                                          |
|     |                                      | Green/<br>Amber | Blink    | Indicates HDD rebuilding.                                                                                                                     |
|     |                                      | N/A             | Off      | Indicates no HDD access or no HDD error.                                                                                                      |

(Note) If your server features RoT function, please see the following section for detail LED behavior.



## 2-5 RoT LEDs




| LED on Front panel <sup>(Note5)</sup>                                         |                                   |                                    |
|-------------------------------------------------------------------------------|-----------------------------------|------------------------------------|
|                                                                               | ID LED                            | Status LED                         |
| <b>EC Firmware (FW) Authentication fail or not exit</b>                       |                                   |                                    |
| EC FW is broken or not exit <sup>(Note1)</sup>                                | OFF                               | OFF                                |
| <b>Authenticating/Recovering BMC/BIOS Images</b>                              |                                   |                                    |
| Authenticating Images                                                         | OFF                               | OFF                                |
| Recovering BMC Active Flash                                                   | Blinks Blue<br>4 times per second | Blinks Green<br>4 times per second |
| Recovering BIOS Active Flash                                                  | Blinks Blue<br>4 times per second | Blinks Green<br>4 times per second |
| <b>Authentication (AUTH) Pass</b>                                             |                                   |                                    |
| Recovering BIOS Active Flash                                                  | OFF                               | OFF                                |
| BMC : AUTH pass after doing recovery<br>BIOS : AUTH pass after doing recovery | OFF                               | OFF                                |
| BMC : AUTH pass after doing recovery<br>BIOS : AUTH pass                      | OFF                               | OFF                                |
| BMC : AUTH pass<br>BIOS : AUTH pass after doing recovery                      | OFF                               | OFF                                |

| <b>Active Flash Authentication (AUTH) Fail</b>                  |                                       |                                       |
|-----------------------------------------------------------------|---------------------------------------|---------------------------------------|
| <b>BMC : AUTH Fail</b> <sup>(Note2)</sup>                       | Blinks Blue                           | Blinks Green                          |
|                                                                 | 1 time per second                     | 1 time per second                     |
| <b>BIOS : AUTH fail</b> <sup>(Note2)</sup>                      | Blinks Blue                           | Blinks Amber                          |
|                                                                 | 1 time per second                     | 1 time per second                     |
| <b>BMC : AUTH fail after doing recovery</b> <sup>(Note3)</sup>  | Blinks Blue                           | Blinks Green                          |
|                                                                 | 2 times per second<br>[ON OFF OFF]    | 2 times per second<br>[ON OFF OFF]    |
| <b>BIOS : AUTH fail after doing recovery</b> <sup>(Note3)</sup> | Blinks Blue                           | Blinks Amber                          |
|                                                                 | 2 times per second<br>[ON OFF OFF]    | 2 times per second<br>[ON OFF OFF]    |
| <b>Backup Flash Authentication Fail</b> <sup>(Note4)</sup>      |                                       |                                       |
| <b>BMC : AUTH fail</b>                                          | Blinks Blue                           | Blinks Green                          |
|                                                                 | 2 times per second<br>[ON OFF ON OFF] | 2 times per second<br>[ON OFF ON OFF] |
| <b>BIOS : AUTH fail</b>                                         | Blinks Blue                           | Blinks Amber                          |
|                                                                 | 2 times per second<br>[ON OFF ON OFF] | 2 times per second<br>[ON OFF ON OFF] |

#### NOTE!


1. EC FW is broken or not exited result in Microchip CEC1702 cannot load EC FW for authentication.
2. CEC1702's bootloader load EC FW from BMC Flash1 when AC on. It must authenticate this FW firstly before run the FW. If the authenticate fail or not get the FW successfully, CEC1702 is not allowed to execute this FW and ECSTS\_LED1 on the MB is OFF state.
3. if active flash is still authentication failed after recovery sequence, Microchip CEC1702 stop the process and showing LED behavior.
4. If backup flash authentication is failed cause by configuration table, public key or protected area is broken. Microchip CEC1702 stop the process and showing LED behavior.
5. Front panel LED is controlled by BMC or Microchip CEC1702. Once Microchip CEC1702 is working(Auth or recovery), the front panel LED is controlled by Microchip CEC1702 and vice versa.

## 2-6 Front System LAN LEDs



| No. | Name                      | Color  | Status | Description                                     |
|-----|---------------------------|--------|--------|-------------------------------------------------|
| 1.  | 1GbE Speed LED            | Yellow | On     | 1 Gbps data rate                                |
|     |                           | Green  | On     | 100 Mbps data rate                              |
|     |                           | N/A    | Off    | 10 Mbps data rate                               |
| 2.  | 1GbE Link / Activity LED  | Green  | On     | Link between system and network or no access    |
|     |                           |        | Blink  | Data transmission or reception is occurring.    |
|     |                           | N/A    | Off    | No data transmission or reception is occurring. |
| 3   | 10GbE Speed LED           | Yellow | On     | 10 Gbps data rate                               |
|     |                           | Green  | On     | 1 Gbps data rate                                |
|     |                           | N/A    | Off    | 100 Mbps data rate                              |
| 4.  | 10GbE Link / Activity LED | Green  | On     | Link between system and network or no access    |
|     |                           |        | Blink  | Data transmission or reception is occurring.    |
|     |                           | N/A    | Off    | No data transmission or reception is occurring. |

## 2-7 Rear System LAN LED




| No. | Name                     | Color  | Status | Description                                     |
|-----|--------------------------|--------|--------|-------------------------------------------------|
| 1.  | 1GbE Speed LED           | Yellow | On     | 1 Gbps data rate                                |
|     |                          | Green  | On     | 100 Mbps data rate                              |
|     |                          | N/A    | Off    | 10 Mbps data rate                               |
| 2.  | 1GbE Link / Activity LED | Green  | On     | Link between system and network or no access    |
|     |                          |        | Blink  | Data transmission or reception is occurring.    |
|     |                          | N/A    | Off    | No data transmission or reception is occurring. |

## 2-8 Power Supply Unit LED




### NOTE!

The power supply may be vary based on the system configuration.



| State              | Description                                                                                                               |
|--------------------|---------------------------------------------------------------------------------------------------------------------------|
| OFF                | No AC power to all power supplies                                                                                         |
| 1Hz Green Blinking | AC present / only standby on / Cold redundant mode                                                                        |
| 2Hz Green Blinking | Power supply firmware updating mode                                                                                       |
| Amber              | AC cord unplugged or AC power lost; with a second power supply in parallel still with AC input power                      |
|                    | Power supply critical event causing shut down: failure, OCP, OVP, fan failure and UVP                                     |
| 1Hz Amber Blinking | Power supply warning events where the power supply continues to operate: high temp, high power, high current and slow fan |

## 2-9 Hard Disk Drive LEDs



| RAID SKU                                              |                                      | LED #1 | Locate | HDD Fault | Rebuilding        | HDD Access | HDD Present (No Access) |
|-------------------------------------------------------|--------------------------------------|--------|--------|-----------|-------------------|------------|-------------------------|
| No RAID configuration (via HBA)                       | Disk LED (LED on Back Panel)         | Green  | ON(*1) | OFF       |                   | BLINK (*2) | OFF                     |
|                                                       |                                      | Amber  | OFF    | OFF       |                   | OFF        | OFF                     |
|                                                       | Removed HDD Slot (LED on Back Panel) | Green  | ON(*1) | OFF       |                   | --         | --                      |
|                                                       |                                      | Amber  | OFF    | OFF       |                   | --         | --                      |
| RAID configuration (via HW RAID Card or SW RAID Card) | Disk LED                             | Green  | ON     | OFF       |                   | BLINK (*2) | OFF                     |
|                                                       |                                      | Amber  | OFF    | ON        | (Low Speed: 2 Hz) | OFF        | OFF                     |
|                                                       | Removed HDD Slot                     | Green  | ON(*1) | OFF       | (*3)              | --         | --                      |
|                                                       |                                      | Amber  | OFF    | ON        | (*3)              | --         | --                      |

| LED #2 | HDD Present | No HDD |
|--------|-------------|--------|
| Green  | ON          | OFF    |

### NOTE:

\*1: Depends on HBA/Utility Spec.

\*2: Blink cycle depends on HDD's activity signal.

\*3: If HDD is pulled out during rebuilding, the disk status of this HDD is regarded as faulty.

## Chapter 3 System Hardware Installation



### Pre-installation Instructions

Computer components and electronic circuit boards can be damaged by discharges of static electricity. Working on computers that are still connected to a power supply can be extremely dangerous. Follow the simple guidelines below to avoid damage to your computer or injury to yourself.

- Always disconnect the computer from the power outlet whenever you are working inside the computer case.
- If possible, wear a grounded wrist strap when you are working inside the computer case. Alternatively, discharge any static electricity by touching the bare metal system of the computer case, or the bare metal body of any other grounded appliance.
- Hold electronic circuit boards by the edges only. Do not touch the components on the board unless it is necessary to do so. Do not flex or stress the circuit board.
- Leave all components inside the static-proof packaging until you are ready to use the component for the installation.

## 3-1 Removing and Installing the Hard Disk Drive




Read the following guidelines before you begin to install the hard disk drive:

- Take note of the HDD tray orientation before sliding it out.
- The tray will not fit back into the bay if it is inserted incorrectly.
- Make sure that the hard disk drive is connected to the connector on the backplane.

Follow these instructions to install a 2.5" hard disk drive:

1. Press the release button.
2. Extend the locking lever.
3. Pull the locking lever in the direction indicated to remove the HDD tray.
4. Align the hard disk drive with the positioning stud on the HDD tray.
5. Slide the hard disk drive into the HDD tray.
6. Reinsert the HDD tray into the slot and close the locking lever.



## 3-2 Removing and Installing the GPU Tray




Before you remove or install the GPU Tray:

- Make sure the system is not turned on or connected to AC power

Follow these instructions to remove/install the GPU tray

1. Loosen the top thumbnail screw securing the handles on both sides of the system.
2. Pull the grip handles on both sides of the system slide the tray to the front of the system at the same time to pull out the tray.
3. Slide the white latch on both sides of the tray rail and carefully remove the GPU tray.
4. To reinstall the GPU tray, align it with the rails on both sides and push the blue latches on each side of the tray rail backward to slide it into the system. Then, reverse steps 1-2 to secure the GPU tray in position.

**NOTE!** Push the handle back only after the GPU tray is fully inserted into the system.





### 3-3 Removing and Installing the Motherboard Tray





Before you remove or install the Motherboard Tray:

- Make sure the system is not turned on or connected to AC power

Follow these instructions to remove/install the motherboard tray


1. Loosen the top thumbnail screw securing the handles on both sides of the system.
2. Pull the grip handles on both sides of the system slide the tray to the front of the system at the same time to pull out the tray.
3. Slide the white latch on both sides of the tray rail and carefully remove the motherboard tray.
4. To reinstall the motherboard tray, align it with the rails on both sides and push the blue latches on each side of the tray rail backward to slide it into the system. Then, reverse steps 1-2 to secure the motherboard tray in position.

**NOTE!** Push the handle back only after the motherboard tray is fully inserted into the system.




### 3-4 Liquid Cooling Assembly Information

The liquid cooling assembly is designed to capture heat from the processors and GPUs in the node and cool the components. The coolant flow for the assembly is produced by the eight quick disconnects at the rear of the server chassis.




The flow of the CPU coolant is shown below:



| Flow Order | Component          |
|------------|--------------------|
| First      | Coolant into CPU   |
| Second     | CPU coolant return |

The flow of the GPU baseboard coolant is shown below:



| Flow Order | Component                       |
|------------|---------------------------------|
| First      | Coolant into GPU and NVSwitch   |
| Second     | GPU and NVSwitch coolant return |

### 3-4-1 Liquid Cooling Specifications

The cold plate assembly in the liquid cooling assembly mounts directly on top of the processors.

The retention mechanism for installation on top of the processors is integrated into the cold plate. The liquid coolant contained within the tubes, is a mixture of demineralized water and propylene glycol with the following beneficial features: Anti-Freeze, Anti-Corrosion and Anti Bacterial. The following table lists the features and specifications of the liquid cooling assembly.

| System Configuration with NVIDIA H200 GPU |                                                                                 |
|-------------------------------------------|---------------------------------------------------------------------------------|
| Specification                             | Value                                                                           |
| Cold plate material                       | Copper                                                                          |
| Thermal Interface Material                | SHIN ETSU X23-7921 (CPU)<br>Honeywell (PCM) (GPU)<br>Honeywell (PCM) (NVSWITCH) |
| Operating liquid temperature              | Minimum: 5°C<br>Maximum: 70°C                                                   |
| Operating Air temperature                 | 40°C                                                                            |
| Coolant Flow Rate                         | 1.45 LPM (CPU)<br>4.0 LPM Typical (GPU)<br>0.95 LPM Typical (NVSwitch)          |
| Operating Humidity                        | 5 - 90%                                                                         |
| Storage Temperature                       | -40°C to 70°C                                                                   |
| Storage Humidity                          | 5 - 90%                                                                         |
| Dimensions                                |                                                                                 |
| CPU                                       | 1140 mm * 308 mm * 30 mm                                                        |
| GPU                                       | 996 mm * 164 mm * 60 mm                                                         |
| NVSwitch                                  | 666 mm * 338 mm * 60 mm                                                         |
| Weight                                    |                                                                                 |
| CPU                                       | ~ 1.6 KG                                                                        |
| GPU                                       | ~ 6.4 KG                                                                        |
| NVSwitch                                  | ~ 2.8 KG                                                                        |

**NOTE:**

To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 40°C.

| System Configuration with NVIDIA B200 GPU |                                                                                                                         |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Specification                             | Value                                                                                                                   |
| Cold plate material                       | Copper                                                                                                                  |
| Thermal Interface Material                | SHIN ETSU X23-8079-2 (CPU)<br>Honeywell (PCM) (GPU)<br>Honeywell (PCM) (NVSWITCH)                                       |
| Operating liquid temperature              | Minimum: 5°C<br>Maximum: 70°C                                                                                           |
| Operating Air temperature                 | 40°C                                                                                                                    |
| Coolant Flow Rate                         | 1.3 LPM (CPU)<br>2.4 LPM Typical (GPU/Front)<br>2.1 LPM Typical (GPU/Rear)<br>1.0 LPM Typical<br>(NVSwitch and Retimer) |
| Operating Humidity                        | 5 - 90%                                                                                                                 |
| Storage Temperature                       | -40°C to 70°C                                                                                                           |
| Storage Humidity                          | 5 - 90%                                                                                                                 |
| Dimensions                                |                                                                                                                         |
| CPU                                       | 1140 mm * 308 mm * 30 mm                                                                                                |
| GPU                                       | 996 mm * 164 mm * 60 mm                                                                                                 |
| NVSwitch                                  | 666 mm * 338 mm * 60 mm                                                                                                 |
| Weight                                    |                                                                                                                         |
| CPU                                       | ~ 1.6 KG                                                                                                                |
| GPU                                       | ~ 6.4 KG                                                                                                                |
| NVSwitch                                  | ~ 2.8 KG                                                                                                                |

**NOTE:**

To ensure system stability and prevent condensation, when the relative humidity exceeds 50%, the coolant inlet temperature must be higher than the dry-bulb temperature and it should not exceed 40°C.

## 3-5 Installing the CPU and the Coolant Pipe Module



Read the following guidelines before you begin to install the CPU:

- Make sure that the motherboard supports the CPU.
- Always turn off the computer and unplug the power cord from the power outlet before installing the CPU to prevent hardware damage.
- Unplug all cables from the power outlets.
- Disconnect all telecommunication cables from their ports.
- Place the system unit on a flat and stable surface.
- Open the system according to the instructions.



### **WARNING!**


Failure to properly turn off the server before you start installing components may cause serious damage. Do not attempt the procedures described in the following sections unless you are a qualified service technician.



### **Follow these instructions to install the CPU:**

1. Loosen the three captive screws securing the CPU cover.
2. Flip open the CPU cover.
3. Remove the CPU carrier from the CPU frame using the handle on the CPU carrier.
4. Using the handle on the CPU carrier insert the new CPU carrier with CPU installed into the CPU frame.

NOTE: Ensure the CPU is installed in the CPU carrier in the correct orientation, with the triangle on the CPU aligned to the top left corner of the CPU carrier.


5. Flip the CPU frame with CPU installed into place in the CPU socket.
6. Flip the CPU cover into place over the CPU socket.
7. Tighten the CPU cover screw to secure the CPU cover in place. Repeat steps 1-7 for the second CPU.





- Lock the CPU by using a Torx T20 screwdriver to tighten screw.
- The screw tightening torque:  $13.5 \pm 0.5$  kgf-cm.

8



- Please refer to the Coldplate Label for the screw tightening torque value.
- To ensure the system operates properly, make sure the coldplate is seated on the processor firmly.

## 3-6 Removing and Installing Memory




Read the following guidelines before you begin to install the memory:

- Make sure that the motherboard supports the memory. It is recommended that memory of the same capacity, brand, speed, and chips be used.
- Always turn off the computer and unplug the power cord from the power outlet before installing the memory to prevent hardware damage.
- Memory modules have a foolproof design. A memory module can be installed in only one direction. If you are unable to insert the memory, switch the direction.

### 3-6-1 Eight Channel Memory Configuration

This motherboard provides 24 DDR5 memory sockets and supports Twelve Channel Technology. After the memory is installed, the BIOS will automatically detect the specifications and capacity of the memory.






### 3-6-2 Removing and Installing a Memory Module



Before installing a memory module, make sure to turn off the computer and unplug the power cord from the power outlet to prevent damage to the memory module. Be sure to install DDR5 DIMMs on to this motherboard.

Follow these instructions to install a DIMM module:

1. Insert the DIMM memory module vertically into the DIMM slot and push it down.
2. Close the plastic clip at both edges of the DIMM slots to lock the DIMM module.
3. Reverse the installation steps when you want to remove the DIMM module.



### 3-6-3 Processor and Memory Module Matrix Table

| Memory Q'ty<br>for each CPU | CPU0 |    |    |    |    |    |    |    |    |    |    |    | CPU1 |    |    |    |    |    |    |    |    |    |    |    |
|-----------------------------|------|----|----|----|----|----|----|----|----|----|----|----|------|----|----|----|----|----|----|----|----|----|----|----|
|                             | F0   | E0 | D0 | C0 | B0 | A0 | G0 | H0 | I0 | J0 | K0 | L0 | R0   | Q0 | P0 | O0 | N0 | M0 | S0 | T0 | U0 | V0 | W0 | X0 |
| 1 DIMM                      |      |    |    |    |    | v  |    |    |    |    |    |    |      |    |    |    |    | v  |    |    |    |    |    |    |
| 2 DIMM                      |      |    |    |    |    | v  | v  |    |    |    |    |    |      |    |    |    |    | v  | v  |    |    |    |    |    |
| 4 DIMM                      |      |    |    | v  |    | v  | v  |    | v  |    |    |    |      |    |    | v  |    | v  | v  |    | v  |    |    |    |
| 6 DIMM                      |      |    |    | v  | v  | v  | v  | v  | v  |    |    |    |      |    |    | v  | v  | v  | v  | v  | v  |    |    |    |
| 8 DIMM                      |      | v  |    | v  | v  | v  | v  | v  | v  |    | v  |    |      | v  |    | v  | v  | v  | v  | v  | v  |    | v  |    |
| 10 DIMM                     |      | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  |    |      | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  |
| 12 DIMM                     | v    | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  | v    | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  | v  |

### 3-6-4 Memory Population Table

EPYC Memory Speed based on DIMM Population (One DIMM per Channel)

| DIMM Type | DIMM Population | EPYC 9004<br>DDR5 Frequency (MT/s) |
|-----------|-----------------|------------------------------------|
|           | DIMM 0          |                                    |
| RDIMM     | 1R (1 Rank)     | 4800                               |
|           | 2R (2 Ranks)    | 4800                               |
| 3DS RDIMM | 2S2R (4 Ranks)  | 4800                               |
|           | 2S4R (8 Ranks)  | 4800                               |
|           | 2S8R (16 ranks) | 4800                               |

| DIMM Type                 | DIMM Population | EEPC 9005<br>DDR5 Frequency MT/s |                         |                         |
|---------------------------|-----------------|----------------------------------|-------------------------|-------------------------|
|                           |                 | 6400 MT/s<br>Grade DIMM          | 5600 MT/s<br>Grade DIMM | 4800 MT/s<br>Grade DIMM |
| RDIMM                     | 1R (1 rank)     | 6400 <sup>1</sup>                | 5600                    | 4800                    |
|                           | 2R (2 ranks)    | 6400 <sup>1</sup>                | 5600                    | 4800                    |
| 3DS RDIMM*                | 2R xH           | 6400 <sup>1</sup>                | 5600                    | 4800                    |
| MRDIMM (1:1) <sup>2</sup> | 4R (4 ranks)    | 6400                             |                         |                         |

|                             |                         |                 |
|-----------------------------|-------------------------|-----------------|
| *For 3DS RDIMM <sup>2</sup> | When x = 2              | DIMM Ranks = 4  |
|                             | When x =4               | DIMM Ranks = 8  |
|                             | When x = 8 <sup>3</sup> | DIMM Ranks = 16 |

**Note:**

- When only one DIMM is used, it must be populated in memory slot DIMM1.
1. 6400 MT/s supported with specific DIMMs listed in product page QVL.
  2. MRDIMM will be evaluated as a post-PR feature, pending ecosystem readiness.
  3. 3DS RDIMM at 2 Rank (8H DRAM Pkgs) will be a post-PR feature, pending ecosystem readiness.

## 3-7 Removing and Installing the PCIe Card



- Voltages can be present within the server whenever an AC power source is connected. This voltage is present even when the main power switch is in the off position. Ensure that the system is powered off and all power sources have been disconnected from the server prior to installing a PCIe card.
- Failure to observe these warnings could result in personal injury or damage to equipment.



- The PCIe riser assembly does not include a riser card or any cabling as standard. To install a PCIe card, a riser card must be installed.

Follow these instructions to install a PCIe card:




### Left PCIe Card Cage

1. Press the release latch.
2. Simultaneously pulling up the tray handle for the PCIe card cage.
3. Pull the cage out of the system.
4. Orient the PCIe card with the riser guide slot and push in the direction of the arrow until the PCIe card sits in the PCIe card connector.

**NOTE:** Some riser brackets allow for single or multiple PCIe cards.

Repeat steps 3-4 as necessary.

5. Secure the PCIe card with the screw.
6. Repeat steps 1-2 to install the PCIe card cage into the system.



Follow these instructions to install a PCIe card:


### **Right PCIe Card Cage**

1. Press the release latch.
2. Simultaneously pulling up the tray handle for the PCIe card cage.
3. Pull the cage out of the system.
4. Remove the screw securing the Management module tray.
5. Remove the Management module tray from the PCIe cage.
6. Orient the PCIe card with the riser guide slot and push in the direction of the arrow until the PCIe card sits in the PCIe card connector.

**NOTE:** Some riser brackets allow for single or multiple PCIe cards.

Repeat steps 4-5 as necessary.

7. Secure the PCIe card with the screw.
8. Repeat steps 1-3 to install the PCIe card cage into the system.



Follow these instructions to install a PCIe card:


### **Middle PCIe Card Cage**

1. Press the release latches.
2. Simultaneously pulling up the tray handle for the PCIe card cage and pull the cage out of the system.
3. Remove the fan duct.
4. Remove the screw securing the Management module tray.
5. Remove the Management module tray from the PCIe cage.
6. Orient the PCIe card with the riser guide slot and push in the direction of the arrow until the PCIe card sits in the PCIe card connector.

**NOTE:** Some riser brackets allow for single or multiple PCIe cards.

Repeat steps 4-5 as necessary.



7. Secure the PCIe card with the screw.
8. Repeat steps 1-3 to install the PCIe card cage into the system.



## 3-8 Removing and Installing the Power Supply

Follow these instructions to replace the power supply:

1. Flip up and then grasp the power supply handle.
2. Press the retaining clip on the right side of the power supply unit in the direction indicated.
3. Pull out the power supply unit using the handle.
4. Insert the replacement power supply unit firmly into the chassis. Connect the AC power cord to the replacement power supply.
5. Repeat steps 1-4 for replacement of the second power supply.



## 3-9 Installing the M.2 Device and Heat Sink




### CAUTION

The position of the stand-off screw will depend on the size of the M.2 device. The stand-off screw is pre-installed for 22110 cards as standard. Refer to the size of the M.2 device and change the position of the stand-off screw accordingly.

### Follow these instructions to install the M.2 device:

1. Insert the M.2 SSD module into the slot.
2. Secure it with the screw, tightening as necessary to fasten the M.2 SSD module in place.



### 3-9-1 M.2 device with Heatsink



### WARNING:


Please ensure a heatsink is attached to any M.2 device installed into the system. Installing an M.2 device without any heatsink may result in the system overheating or system performance being throttled.



- Please Go to for specific M.2 Slot location.
- To install/remove the M.2 module and Heatsink use a No. 1 Phillips-head screwdriver with a screw torque of  $1.5 \pm 0.2 \text{ kgf}\cdot\text{cm}$

### Follow these instructions to install the M.2 device and heat sink:

1. Insert the M.2 device into the M.2 connector.
2. Press down on the M.2 device.
3. Install the thermal pad of the M.2 device to the M.2 device.
4. Press down on the thermal pad.
5. Secure the M.2 device and its thermal pad to the motherboard with a single screw.
6. Reverse steps 1-2 to remove the M.2 device.



## 3-10 Removing and Installing the Top Cover




Before you remove the top cover:

Make sure the system is not turned on or connected to AC power.

**Follow these instructions to remove the top cover:**

1. Remove the screw securing the top cover.
2. Unlock the plastic handle.
3. Pull the grip handle.
4. Slide the cover to the rear of the system and then remove the cover in the direction indicated by the arrow.
5. To reinstall the chassis cover reverse steps 1-3.





### 3-11 Installing the System into the Cabinet




Read the following guidelines before you begin to install the system into the cabinet:


- Make sure the system is not turned on or connected to AC power.
- A Lift Table is required. Place the system unit on Lift Table. **Recommended load capacity for the lift table: 200 kilograms.**
- Four Person lift required. Firmly hold the bottom of the system when required to lift and carry the system.
- Failure to observe these warnings could result in personal injury or damage to the equipment.

**Follow these instructions to install the system into the cabinet:**


1. Pull out and release the thumbnail screw securing the chassis handle in place.
2. Remove the four handles on each side of the system.
3. Carefully slide the system into the cabinet.




### 3-12 Cable Connection




|   |                             |                            |
|---|-----------------------------|----------------------------|
| A | Front USB 3.0 Cable         | Motherboard: F_USB3        |
|   |                             | Front IO Board: F_USB3_CON |
| B | Front IO Board Signal Cable | Motherboard: FP_IO         |
|   |                             | Front IO Board: FP_IO      |
| C | Front IO VGA Cable          | Motherboard: VGA_CON       |
|   |                             | Front IO Board: F_VGA1_CON |
| D | Front IO Board LAN Cable    | Motherboard: FP_LAN        |
|   |                             | Front IO Board: FP_MLAN    |
| E | Front IO Board Power Cable  | Motherboard: FP_PWR        |
|   |                             | Front IO Board: P12V_2     |



|   |                                          |                                                  |
|---|------------------------------------------|--------------------------------------------------|
| A | Rear LAN to Motherboard<br>Signal Cable  | Rear LAN Board: U2_PE1                           |
|   |                                          | Motherboard:<br>A1: U2_P0_G3A1<br>A2: U2_P0_G3B1 |
| B | Rear LAN to Motherboard<br>Signal Cable  | Rear LAN Board: U2_PE1                           |
|   |                                          | Motherboard:<br>B1: U2_P1_G1A1<br>B2: U2_P1_G1B1 |
| C | Rear LAN to Front IO LAN<br>Signal Cable | Rear LAN Board: REAR_MLAN                        |
|   |                                          | Front IO Board: CN_LAN_F                         |




|   |                                  |                                 |
|---|----------------------------------|---------------------------------|
| A | HDD Backplane Board Signal Cable | Motherboard: BP_1               |
|   |                                  | Front HDD Board: BP_1           |
| B | HDD Backplane Board Signal Cable | Left Front HDD Board: BP_SERIES |
|   |                                  | Right Front HDD Board: BP_1     |
| C | HDD Backplane Board Power Cable  | Motherboard: BPB_PWR1           |
|   |                                  | Left Front HDD Board: BP_PWR    |
| D | HDD Backplane Board Power Cable  | Motherboard: BPB_PWR            |
|   |                                  | Right Front HDD Board: BP_PWR   |



|   |                   |                          |   |                   |                          |
|---|-------------------|--------------------------|---|-------------------|--------------------------|
| A | NVMe 0-1<br>Cable | Motherboard:<br>U2_PEX0  | C | NVMe 4-5<br>Cable | Motherboard:<br>U2_PEX2  |
|   |                   | Front HDD Board:<br>U2_0 |   |                   | Front HDD Board:<br>U2_0 |
| B | NVMe 2-3<br>Cable | Motherboard:<br>U2_PEX1  | D | NVMe 6-7<br>Cable | Motherboard:<br>U2_PEX3  |
|   |                   | Front HDD Board:<br>U2_1 |   |                   | Front HDD Board:<br>U2_1 |

# Chapter 4 Motherboard Components



## 4-1 Motherboard Components



| Item | Description                                    |
|------|------------------------------------------------|
| 1    | 2 x 4 Pin Front Panel Power Connector (FP_PWR) |
| 2    | 2 x 3 Backplane Power Connector (BPB_PWR)      |
| 3    | FAN_11/FAN_12 Connector                        |
| 4    | FAN_9/FAN_10 Connector                         |
| 5    | FAN_7/FAN_8 Connector                          |
| 6    | FAN_5/FAN_6 Connector                          |
| 7    | FAN_3/FAN_4 Connector                          |
| 8    | FAN_1/FAN_2 Connector                          |
| 9    | CPU1 FAN Connector                             |
| 10   | CPU0 FAN Connector                             |
| 11   | M.2 Slot (PCIe Gen3 x1, Support NGFF-22110)    |
| 12   | HDD Backplane Board Connector                  |

| Item | Description                                            |
|------|--------------------------------------------------------|
| 13   | 2 x 3 Backplane Power Connector (BPB_PWR1)             |
| 14   | MCIO Connector (U2_P1_G1A1/PCIe Gen5)                  |
| 15   | MCIO Connector (U2_P1_G1B1/PCIe Gen5)                  |
| 16   | MCIO Connector (U2_P0_G3B1/PCIe Gen5)                  |
| 17   | MCIO Connector (U2_P0_G3A1/PCIe Gen5)                  |
| 18   | Battery Cable Connector                                |
| 19   | MCIO Connector (U2_8/for Power Board Side Band Signal) |
| 20   | VGA/Serial Port Connector                              |
| 21   | Front USB 3.2 Gen1 Connector                           |
| 22   | MCIO Connector (U2_11/for MLAN)                        |
| 23   | BMC Firmware Readiness LED                             |
| 24   | TPM Module Connector                                   |
| 25   | IPMB Connector                                         |
| 26   | MCIO Connector (U2_PEX0/PCIe Gen5)                     |
| 27   | MCIO Connector (U2_PEX1/PCIe Gen5)                     |
| 28   | MCIO Connector (U2_PEX2/PCIe Gen5)                     |
| 29   | MCIO Connector (U2_PEX3/PCIe Gen5)                     |
| 30   | M.2 Slot (PCIe Gen3 x4, Support NGFF-22110)            |
| 31   | Motherboard Power Connector (MB_PWR4/MB_PWR4)          |
| 32   | PCIe Signal Connector (EX_SXMJ7-10)                    |
| 33   | Guide Pin Connector (GP2)                              |
| 34   | PCIe Signal Connector (EX_SLT5_6/EX_SLT6_7/EX_SLT8)    |
| 35   | PCIe Bridge Board Power Connector (PCIE_PWR1)          |
| 36   | PCIe Signal Connector (EX_SLT1_3/EX_SLT2_3_EX_SLT4)    |
| 37   | Guide Pin Connector (GP1)                              |
| 38   | PCIe Signal Connector (EX_SXMJ3-6)                     |
| 39   | Power Distribution Board Connector (PDB_IO)            |
| 40   | Motherboard Power Connector (MB_PWR1/MB_PWR2)          |

## 4-2 Jumper Settings




| SW_PLD |           | ON                        | OFF              |
|--------|-----------|---------------------------|------------------|
| 1      | HSMB_SEL  | BMC Control               | PCH [Default]    |
| 2      |           | Reserved function         |                  |
| 3      | BIOS_PWD  | Clear supervisor password | Normal [Default] |
| 4      | BIOS_RCVR | BIOS recovery mode        | Normal [Default] |

| J2 |             | ON                  | OFF              |
|----|-------------|---------------------|------------------|
| 1  | FORCE_PWRON | Force power on mode | Normal [Default] |
| 2  |             | Reserved function   |                  |
| 3  |             | Reserved function   |                  |
| 4  |             | Reserved function   |                  |



# 4-3 Backplane Board Storage Connector

## 4-2-1 CBPG641 (Front System Storage Board)



| Item | Description                 |
|------|-----------------------------|
| 1    | MCIO 8i (SFF-TA1016/U2_1)   |
| 2    | MCIO 8i (SFF-TA1016/U2_0)   |
| 3    | MCIO 4i (SFF-TA1016/SL_CN1) |

## Chapter 5 BIOS Setup

BIOS (Basic Input and Output System) records hardware parameters of the system in the EFI on the motherboard. Its major functions include conducting the Power-On Self-Test (POST) during system startup, saving system parameters, loading the operating system etc. The BIOS includes a BIOS Setup program that allows the user to modify basic system configuration settings or to activate certain system features. When the power is turned off, the battery on the motherboard supplies the necessary power to the CMOS to keep the configuration values in the CMOS.

To access the BIOS Setup program, press the <DEL> key during the POST when the power is turned on.



- BIOS flashing is potentially risky, if you do not encounter any problems when using the current BIOS version, it is recommended that you don't flash the BIOS. To flash the BIOS, do it with caution. Inadequate BIOS flashing may result in system malfunction.
- It is recommended that you not alter the default settings (unless you need to) to prevent system instability or other unexpected results. Inadequately altering the settings may result in system's failure to boot. If this occurs, try to clear the CMOS values and reset the board to default values. (Refer to the **Exit** section in this chapter or introductions of the battery/clearing CMOS jumper in Chapter 4 for how to clear the CMOS values.)

### BIOS Setup Program Function Keys

|          |                                                                          |
|----------|--------------------------------------------------------------------------|
| <<-><->> | Move the selection bar to select the screen                              |
| <↑><↓>   | Move the selection bar to select an item                                 |
| <+>      | Increase the numeric value or make changes                               |
| <->      | Decrease the numeric value or make changes                               |
| <Enter>  | Execute command or enter the submenu                                     |
| <Esc>    | Main Menu: Exit the BIOS Setup program<br>Submenus: Exit current submenu |
| <F1>     | Show descriptions of general help                                        |
| <F3>     | Restore the previous BIOS settings for the current submenus              |
| <F9>     | Load the Optimized BIOS default settings for the current submenus        |
| <F10>    | Save all the changes and exit the BIOS Setup program                     |

■ **Main**

This setup page includes all the items of the standard compatible BIOS.

■ **Advanced**

This setup page includes all the items of AMI BIOS special enhanced features.

(ex: Auto detect fan and temperature status, automatically configure hard disk parameters.)

■ **AMD CBS**

This setup page includes the common items for configuration of AMD motherboard-related information.

■ **AMD PBS Option**

This setup page includes the common items for configuration of AMD CPM RAS related settings.

■ **Chipset**

This setup page includes all the submenu options for configuring the functions of the North Bridge.

■ **Server Management**

Server additional features enabled/disabled setup menus.

■ **Security**

Change, set, or disable supervisor and user password. Configuration supervisor password allows you to restrict access to the system and BIOS Setup.

A supervisor password allows you to make changes in BIOS Setup.

A user password only allows you to view the BIOS settings but not to make changes.

■ **Boot**

This setup page provides items for configuration of the boot sequence.

■ **Save & Exit**

Save all the changes made in the BIOS Setup program to the CMOS and exit BIOS Setup. (Pressing <F10> can also carry out this task.)

Abandon all changes and the previous settings remain in effect. Pressing <Y> to the confirmation message will exit BIOS Setup. (Pressing <Esc> can also carry out this task.)

# 5-1 The Main Menu

Once you enter the BIOS Setup program, the Main Menu (as shown below) appears on the screen. Use arrow keys to move among the items and press <Enter> to accept or enter other sub-menu.

## Main Menu Help

The on-screen description of a highlighted setup option is displayed on the bottom line of the Main Menu.

## Submenu Help

While in a submenu, press <F1> to display a help screen (General Help) of function keys available for the menu. Press <Esc> to exit the help screen. Help for each item is in the Item Help block on the right side of the submenu.



- When the system is not stable as usual, select the **Restore Defaults** item to set your system to its defaults.
- The BIOS Setup menus described in this chapter are for reference only and may differ by BIOS version.





(Note1) Functions available on selected models.

(Note2) This section will display capacity and frequency information of the memory that the customer has installed.



| Parameter                               | Description                                                   |
|-----------------------------------------|---------------------------------------------------------------|
| Onboard LAN Information                 |                                                               |
| LAN1/LAN2 MAC Address <sup>(Note)</sup> | Displays LAN MAC address information.                         |
| System Date                             | Sets the date following the weekday-month-day-year format.    |
| System Time                             | Sets the system time following the hour-minute-second format. |

---

(Note) The number of LAN ports listed will depend on the motherboard / system model.

## 5-2 Advanced Menu


The Advanced Menu displays submenu options for configuring the function of various hardware components. Select a submenu item, then press <Enter> to access the related submenu screen.







### 5-2-2 KMS Policy Configuration




| Parameter                   | Description                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------|
| KMS Option                  | Options available: KMS with KMIP, Disabled.<br>Default setting is <b>KMS with KMIP</b> . |
| KMS KMIP Server Retry Count | Define KMS KMIP Server Retry Count.                                                      |

5-2-3 CPU Configuration




| Parameter           | Description                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------------------|
| SVM Mode            | Enable/Disable the CPU Virtualization.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> . |
| CPU 0/1 Information | Press [Enter] to view the memory information related to CPU 0/1.                                                    |

### 5-2-4 NVMe Configuration




| Parameter          | Description                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| NVMe Configuration | Displays the NVMe devices connected to the system.                                                                                      |
| NVMe LED Control   | Enable/Disable NVMe LED Control.<br>Options available: System Default, Disabled, Enabled.<br>Default setting is <b>System Default</b> . |

### 5-2-5 SATA Configuration



| Parameter          | Description                     |
|--------------------|---------------------------------|
| SATA Configuration | No onboard SATA in this system. |

### 5-2-6 USB Configuration




| Parameter                                         | Description                                                                                                                                                                                                                                                                       |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USB Configuration                                 |                                                                                                                                                                                                                                                                                   |
| USB Module Version                                | Displays the USB module version information.                                                                                                                                                                                                                                      |
| USB Controllers                                   | Displays the supported USB controllers.                                                                                                                                                                                                                                           |
| USB Devices:                                      | Displays the USB devices connected to the system.                                                                                                                                                                                                                                 |
| Legacy USB Support                                | Enable/Disable the Legacy USB support function. AUTO option disables legacy support if no USB devices are connected. DISABLE option will keep USB devices available only for EFI applications.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Enabled</b> . |
| XHCI Hand-off                                     | Enable/Disable the XHCI Hand-off support.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .                                                                                                                                                            |
| USB Mass Storage Driver Support <sup>(Note)</sup> | Enable/Disable the USB Mass Storage Driver Support.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                                                                                                  |
| USB hardware delays and time-outs                 |                                                                                                                                                                                                                                                                                   |
| USB transfer time-out                             | Selects the time-out value for USB Control/Bulk/Interrupt transfers.<br>Options available: 1 sec, 5 sec, 10 sec, 20 sec.<br>Default setting is <b>20 sec</b> .                                                                                                                    |

(Note) This item is present only if you attach USB devices.

| Parameter             | Description                                                                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device reset time-out | Selects the time-out value during a USB mass storage device reset.<br>Options available: 10 sec, 20 sec, 30 sec, 40 sec.<br>Default setting is <b>20 sec</b> .                                                                                                                   |
| Device power-up delay | Maximum time the device will take before it properly reports itself to the Host Controller. "Auto" uses default value: for a Root port it is 100 ms, for a Hub port the delay is taken from Hub descriptor.<br>Options available: Auto, Manual. Default setting is <b>Auto</b> . |
| Mass Storage Devices  | Displays the mass storage devices available on the system.                                                                                                                                                                                                                       |

### 5-2-7 PCI Subsystem Settings



| Parameter                                       | Description                                                                                                                                                                                 |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PCI Bus Driver Version                          | Displays the PCI Bus Driver version information.                                                                                                                                            |
| U2_P0_P0/1/2/3/G3                               | Change PCIe lanes.                                                                                                                                                                          |
| U2_P1_P0/1/2/3/G1 Lanes <sup>(Note1)</sup>      | Options available: Disabled, Auto, x8, x16, x4x4, x8x8, x8x4x4, x4x4x8, x4x4x4x4. Default setting is <b>Auto</b> .                                                                          |
| U2_P0_P0/1/2/3/G3                               | When enabled, this setting will initialize the device expansion ROM for the related devices.                                                                                                |
| U2_P1_P0/1/2/3/G1 I/O ROM <sup>(Note1)</sup>    | Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                                                                   |
| U2_P0_P0/1/2/3/G3                               | Configure PCIe slot max link speed.                                                                                                                                                         |
| U2_P1_P0/1/2/3/G1 Link Speed <sup>(Note1)</sup> | Options available: Auto, Gen5, Gen4, Gen3, Gen2, Gen1. Default setting is <b>Auto</b> .                                                                                                     |
| Onboard LAN Controller <sup>(Note2)</sup>       | Enable/Disable the onboard LAN devices.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                        |
| Onboard LAN# I/O ROM <sup>(Note2)</sup>         | Enable/Disable the onboard LAN devices, and initializes device expansion ROM.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                  |
| PCI Devices Common Settings                     |                                                                                                                                                                                             |
| SR-IOV Support                                  | If the system has SR-IOV capable PCIe devices, this item Enable/Disable Single Root IO Virtualization Support.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> . |

(Note1) This section is dependent on the available MCIO connector.

(Note2) This section is dependent on the available LAN controller.



### 5-2-8 AST2600 Super IO Configuration



| Parameter                      | Description                                        |
|--------------------------------|----------------------------------------------------|
| AST2600 Super IO Configuration |                                                    |
| Super IO Chip                  | Displays the super IO chip information             |
| Serial Port 1 Configuration    | Press [Enter] for configuration of advanced items. |


5-2-8-1 Serial Port 1 Configuration



| Parameter                     | Description                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serial Port 1 Configuration   |                                                                                                                                                                                                                                                                                                                                                |
| Serial Port <sup>(Note)</sup> | Enable/Disable the Serial Port (COM). When set to Enabled allows you to configure the Serial port 1 settings. When set to Disabled, displays no configuration for the serial port.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                                |
| Devices Settings              | Displays the Serial Port 1 device settings.                                                                                                                                                                                                                                                                                                    |
| Change Settings               | Select an optimal settings for Super IO Device.<br>Options available for Serial Port 1:<br>Auto<br>IO=3F8h; IRQ=4;<br>IO=3F8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;<br>IO=2F8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;<br>IO=3E8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;<br>IO=2E8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12;<br>Default setting is <b>Auto</b> . |

(Note) Advanced items prompt when this item is defined.

### 5-2-9 Serial Port Console Redirection



| Parameter                                                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COM1/Serial Over LAN Console Redirection <sup>(Note)</sup> | <p>Select whether to enable console redirection for specified device. Console redirection enables the users to manage the system from a remote location.</p> <p>Options available: Enabled, Disabled. Default setting is <b>Disabled</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| COM1/Serial Over LAN Console Redirection Settings          | <p>Press [Enter] to configure advanced items.</p> <p><b>Please note that this item is configurable when COM1/Serial Over LAN Console Redirection is set to Enabled.</b></p> <ul style="list-style-type: none"> <li>◆ Terminal Type <ul style="list-style-type: none"> <li>– Selects a terminal type to be used for console redirection.</li> <li>– Options available: VT100, VT100Plus, ANSI, VT-UTF8. Default setting is <b>VT100Plus</b>.</li> </ul> </li> <li>◆ Bits per second <ul style="list-style-type: none"> <li>– Selects the transfer rate for console redirection.</li> <li>– Options available: 9600, 19200, 38400, 57600, 115200. Default setting is <b>115200</b>.</li> </ul> </li> <li>◆ Data Bits <ul style="list-style-type: none"> <li>– Selects the number of data bits used for console redirection.</li> <li>– Options available: 7, 8. Default setting is <b>8</b>.</li> </ul> </li> </ul> |

(Note) Advanced items prompt when this item is defined.

| Parameter                                                           | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COM1/Serial Over LAN<br>Console Redirection Settings<br>(continued) | <ul style="list-style-type: none"> <li>◆ Parity <ul style="list-style-type: none"> <li>– A parity bit can be sent with the data bits to detect some transmission errors.</li> <li>– Even: parity bit is 0 if the num of 1's in the data bits is even.</li> <li>– Odd: parity bit is 0 if num of 1's in the data bits is odd.</li> <li>– Mark: parity bit is always 1. Space: Parity bit is always 0.</li> <li>– Mark and Space Parity do not allow for error detection.</li> <li>– Options available: None, Even, Odd, Mark, Space. Default setting is <b>None</b>.</li> </ul> </li> <li>◆ Stop Bits <ul style="list-style-type: none"> <li>– Stop bits indicate the end of a serial data packet. (A start bit indicates the beginning). The standard setting is 1 stop bit. Communication with slow devices may require more than 1 stop bit.</li> <li>– Options available: 1, 2. Default setting is <b>1</b>.</li> </ul> </li> <li>◆ Flow Control <ul style="list-style-type: none"> <li>– Flow control can prevent data loss from buffer overflow. When sending data, if the receiving buffers are full, a 'stop' signal can be sent to stop the data flow. Once the buffers are empty, a 'start' signal can be sent to re-start the flow. Hardware flow control uses two wires to send start/stop signals.</li> <li>– Options available: None, Hardware RTS/CTS. Default setting is <b>None</b>.</li> </ul> </li> <li>◆ VT-UTF8 Combo Key Support <ul style="list-style-type: none"> <li>– Enable/Disable the VT-UTF8 Combo Key Support.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Enabled</b>.</li> </ul> </li> <li>◆ Recorder Mode <ul style="list-style-type: none"> <li>– When this mode enabled, only texts will be send. This is to capture Terminal data.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Disabled</b>.</li> </ul> </li> <li>◆ Resolution 100x31 <ul style="list-style-type: none"> <li>– Enable/Disable extended terminal resolution.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Enabled</b>.</li> </ul> </li> <li>◆ Putty KeyPad <ul style="list-style-type: none"> <li>– Selects Function Key and KeyPad on Putty.</li> <li>– Options available: VT100, LINUX, XTERMR6, SC0, ESCN, VT400. Default setting is <b>VT100</b>.</li> </ul> </li> </ul> |

| Parameter                                                                                                                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Legacy Console Redirection                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Legacy Console Redirection Settings                                                                                        | <p>Press [Enter] to configure advanced items.</p> <ul style="list-style-type: none"> <li>◆ Redirection COM Port <ul style="list-style-type: none"> <li>– Selects a COM port for Legacy serial redirection.</li> <li>– Default setting is <b>COM1/SOL</b>.</li> </ul> </li> <li>◆ Resolution <ul style="list-style-type: none"> <li>– Selects the number of rows and columns used in Console Redirection for legacy OS support.</li> <li>– Options available: 80x24, 80x25. Default setting is <b>80x24</b>.</li> </ul> </li> <li>◆ Redirect After POST <ul style="list-style-type: none"> <li>– When Bootloader is selected, then Legacy Console Redirection is disabled before booting to legacy OS. When Always Enable is selected, then Legacy Console Redirection is enabled for legacy OS.</li> <li>– Options available: Always Enable, BootLoader. Default setting is <b>Always Enable</b>.</li> </ul> </li> </ul>                                                                |
| Serial Port for Out-of-Band Management / Windows Emergency Management Services (EMS) Console Redirection <sup>(Note)</sup> | <p>EMS console redirection allows the user to configure Console Redirection Settings to support Out-of-Band Serial Port management.</p> <p>Options available: Disabled, Enabled. Default setting is <b>Disabled</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Serial Port for Out-of-Band EMS Console Redirection Settings                                                               | <p>Press [Enter] to configure advanced items.</p> <p><b>Please note that this item is configurable when Serial Port for Out-of-Band Management EMS Console Redirection is set to Enabled.</b></p> <ul style="list-style-type: none"> <li>◆ Out-of-Band Mgmt Port <ul style="list-style-type: none"> <li>– Microsoft Windows Emergency Management Service (EMS) allows for remote management of a Windows Server OS through a serial port.</li> <li>– Default setting is <b>COM1/SOL</b>.</li> </ul> </li> <li>◆ Terminal Type <ul style="list-style-type: none"> <li>– Selects a terminal type to be used for console redirection.</li> <li>– Options available: VT100, VT100Plus, ANSI, VT-UTF8. Default setting is <b>ANSI</b>.</li> </ul> </li> <li>◆ Bits per second <ul style="list-style-type: none"> <li>– Selects the transfer rate for console redirection.</li> <li>– Options available: 9600, 19200, 57600, 115200. Default setting is <b>115200</b>.</li> </ul> </li> </ul> |

(Note) Advanced items prompt when this item is defined.

| Parameter                                                                     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serial Port for Out-of-Band<br>EMS Console Redirection<br>Settings(continued) | <ul style="list-style-type: none"> <li>◆ Flow Control <ul style="list-style-type: none"> <li>– Flow control can prevent data loss from buffer overflow. When sending data, if the receiving buffers are full, a 'stop' signal can be sent to stop the data flow. Once the buffers are empty, a 'start' signal can be sent to re-start the flow. Hardware flow control uses two wires to send start/stop signals.</li> <li>– Options available: None, Hardware RTS/CTS, Software Xon/Xoff. Default setting is <b>None</b>.</li> </ul> </li> </ul> |

## 5-2-10 Network Stack Configuration



| Parameter                            | Description                                                                                                                          |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Network Stack                        | Enable/Disable the UEFI network stack.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .                  |
| Ipv4 PXE Support <sup>(Note)</sup>   | Enable/Disable the Ipv4 PXE feature.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .                    |
| Ipv4 HTTP Support <sup>(Note)</sup>  | Enable/Disable the Ipv4 HTTP feature.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                  |
| Ipv6 PXE Support <sup>(Note)</sup>   | Enable/Disable the Ipv6 PXE feature.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .                    |
| Ipv6 HTTP Support <sup>(Note)</sup>  | Enable/Disable the Ipv6 HTTP feature.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                  |
| PXE boot wait time <sup>(Note)</sup> | Wait time in seconds to press ESC key to abort the PXE boot.<br>Press the <+> / <-> keys to increase or decrease the desired values. |
| Media detect count <sup>(Note)</sup> | Number of times the presence of media will be checked.<br>Press the <+> / <-> keys to increase or decrease the desired values.       |

(Note) This item appears when **Network Stack** is set to **Enabled**.

### 5-2-11 Post Report Configuration



| Parameter                 | Description                                                                                                                 |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Post Report Configuration |                                                                                                                             |
| Error Message Report      |                                                                                                                             |
| Post Error Message        | Enable/Disable the POST Error Message support.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> . |
| Halt On                   | Options available: No Error, All Error. Default setting is <b>No Error</b> .                                                |




5-2-12 Trusted Computing



| Parameter               | Description                                                                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration           |                                                                                                                                                                                                                                       |
| Security Device Support | <p>Enable/Disable BIOS support for security device. OS will not show security device. TCG EFI protocol and INT1A interface will not be available.</p> <p>Options available: Disabled, Enabled. Default setting is <b>Enabled</b>.</p> |
| SPI TPM Support         | <p>Select Enable to activate TPM support feature.</p> <p>Options available: Disabled, Enabled. Default setting is <b>Enabled</b>.</p>                                                                                                 |

### 5-2-13 PSP Firmware Versions

The PSP Firmware Versions page displays the basic PSP firmware version information. Items on this window are non-configurable.




5-2-14 S5 RTC Wake Settings



| Parameter           | Description                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Wake System from S5 | Enable/Disable system wake on alarm event.<br>Options available: Disabled, Fixed Time, Dynamic Time. When Fixed Time is selected, system will wake on the hr::min::sec specified. Default setting is <b>Disabled</b> . |

## 5-2-15 Graphic Output Configuration




| Parameter          | Description                                                                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output Device Type | Selects output device type.<br>Options available: First loaded Device, Onboard Device, External Device, Specific Device. Default setting is <b>Onboard Device</b> . |

5-2-16 AMD Mem Configuration Status



| Parameter | Description                                                               |
|-----------|---------------------------------------------------------------------------|
| CPU 0/1   | Press [Enter] to view the memory configuration status related to CPU 0/1. |


5-2-17 Tls Auth Configuration



| Parameter                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Server CA Configuration   | <p>Press [Enter] for configuration of advanced items.</p> <ul style="list-style-type: none"><li>◆ Enroll Cert<ul style="list-style-type: none"><li>– Press [Enter] to enroll a certificate<ul style="list-style-type: none"><li>• Enroll Cert Using File</li><li>• Cert GUID</li></ul></li></ul></li></ul> <p>Input digit character in 1111111-2222-3333-4444-1234567890ab format.</p> <ul style="list-style-type: none"><li>– Commit Changes and Exit</li><li>– Discard Changes and Exit</li></ul> |
| Client Cert Configuration | <p>Press [Enter] for configuration of advanced items.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                           |



## 5-2-19 iSCSI Configuration



| Parameter            | Description                                                                               |
|----------------------|-------------------------------------------------------------------------------------------|
| iSCSI Initiator Name | Press [Enter] and name iSCSI Initiator. Only IQN format is accepted. Range: from 4 to 223 |
| Add an Attempt       | Press [Enter] to configure advanced items.                                                |
| Delete Attempts      | Press [Enter] to configure advanced items.                                                |
| Change Attempt Order | Press [Enter] to configure advanced items.                                                |




5-2-20 Intel(R) Ethernet Controller X710 for 10GBASE-T




| Parameter                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Firmware Image Properties | Press [Enter] to view device firmware version information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| NIC Configuration         | <p>Press [Enter] to configure advanced items.</p> <ul style="list-style-type: none"> <li>◆ Link Speed <ul style="list-style-type: none"> <li>– Default setting is <b>Auto Negotiated</b>.</li> </ul> </li> <li>◆ Wake On LAN <ul style="list-style-type: none"> <li>– Enables power on of the system via LAN. Note that configuring Wake on LAN in the operating system does not change the value of this setting, but does override the behavior of Wake on LAN in OS controlled power states.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Enabled</b>.</li> </ul> </li> <li>◆ LLDP Agent <ul style="list-style-type: none"> <li>– Enable/Disable firmware's LLDP Agent.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Enabled</b></li> </ul> </li> </ul> |
| Blink LEDs                | Identifies the physical network port by blinking the associated LED. Press the numeric keys to adjust desired values (up to 15 seconds).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| UEFI Driver               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Adapter PBA               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Device Name               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Chip Type                 | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| PCI Device ID             | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| PCI Address               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Link Status               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| MAC Address               | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Virtual MAC Address       | Displays the technical specifications for the Network Interface Controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## 5-2-21 VLAN Configuration



| Parameter                | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enter Configuration Menu | <p>Press [Enter] to configure advanced items.</p> <ul style="list-style-type: none"> <li>◆ Create new VLAN</li> <li>◆ VLAN ID               <ul style="list-style-type: none"> <li>– Sets VLAN ID for a new VLAN or an existing VLAN.</li> <li>– Press the &lt;+&gt; / &lt;-&gt; keys to increase or decrease the desired values.</li> <li>– The valid range is from 0 to 4094.</li> </ul> </li> <li>◆ Priority               <ul style="list-style-type: none"> <li>– Sets 802.1Q Priority for a new VLAN or an existing VLAN.</li> <li>– Press the &lt;+&gt; / &lt;-&gt; keys to increase or decrease the desired values.</li> <li>– The valid range is from 0 to 7.</li> </ul> </li> <li>◆ Add VLAN               <ul style="list-style-type: none"> <li>– Press [Enter] to create a new VLAN or update an existing VLAN.</li> </ul> </li> <li>◆ Configured VLAN List</li> <li>◆ Remove VLAN               <ul style="list-style-type: none"> <li>– Press [Enter] to remove an existing VLAN.</li> </ul> </li> </ul> |

5-2-22 MAC IPv4 Network Configuration





| Parameter                           | Description                                                                                                                                        |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Configured                          | Indicates whether network address is configured successfully or not.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> . |
| Enable DHCP <sup>(Note)</sup>       | Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                                                                         |
| Local IP Address <sup>(Note)</sup>  | Press [Enter] to configure local IP address.                                                                                                       |
| Local NetMask <sup>(Note)</sup>     | Press [Enter] to configure local NetMask.                                                                                                          |
| Local Gateway <sup>(Note)</sup>     | Press [Enter] to configure local Gateway                                                                                                           |
| Local DNS Servers <sup>(Note)</sup> | Press [Enter] to configure local DNS servers                                                                                                       |
| Save Changes and Exit               | Press [Enter] to save all configurations.                                                                                                          |

(Note) This item appears when **Configured** is set to **Enabled**.





### 5-3-1 CPU Common Options



| Parameter                     | Description                                                                                                                                                                                                                     |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU Common Options            |                                                                                                                                                                                                                                 |
| Performance                   | Press [Enter] for configuration of advanced items.                                                                                                                                                                              |
| REP-MOV/STOS Streaming        | Allow REP-MOV/STOS to use non-caching streaming stores for large sizes.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                            |
| Prefetcher settings           | Press [Enter] for configuration of advanced items.                                                                                                                                                                              |
| Core Watchdog                 | Press [Enter] for configuration of advanced items.                                                                                                                                                                              |
| RedirectForReturnDis          | From a workaround for GCC/C000005 issue for XV Core on CZ A0,<br>setting MSRC001_1029 Decode Configuration (DE_CFG) bit 14<br>[DecfgNoRdrctForReturns] to 1.<br>Options available: Auto, 1, 0. Default setting is <b>Auto</b> . |
| Platform First Error Handling | Enable/Disable PFEH, cloak individual banks, and mask deferred error<br>interrupts from each bank.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b> .                                              |
| Core Performance Boost        | Enable/Disable the Core Performance Boost function.<br>Options available: Disabled, Auto. Default setting is <b>Auto</b> .                                                                                                      |
| Global C-state Control        | Controls the IO based C-state generation and DF C-states.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                       |
| Power Supply Idle Control     | Configures the Power Supply Idle Control.<br>Options available: Low Current Idle, Typical Current Idle, Auto.<br>Default setting is <b>Auto</b> .                                                                               |
| Streaming Stores Control      | Enable/Disable the Streaming Stores functionality.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                              |
| Local APIC Mode               | Sets the Local APIC Mode.<br>Options available: xAPIC, x2APIC, Auto.<br>Default setting is <b>Auto</b> .                                                                                                                        |
| ACPI_CST C1 Declaration       | Determines whether or not to declare the C1 state to the OS..<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                   |
| ACPI CST C2 Latency           | Enter in microseconds (decimal value).                                                                                                                                                                                          |
| MCA error thresh enable       | Enable MCA error thresholding.<br>Options available: False, True, Auto. Default setting is <b>True</b> .                                                                                                                        |
| MCA error thresh count        | Effective error threshold count = 0xFFFF(4095) - <this value> (e.g. the<br>default value of 0xFF5(4085) results in a threshold of 0xA (10)).                                                                                    |
| MCA FruText                   | Enable MCA FruText.<br>Options available: False, True. Default setting is <b>True</b> .                                                                                                                                         |
| SMU and PSP Debug Mode        | When this option is enabled, specific uncorrected errors detected by the<br>PSP FW or SMU FW will hand and not reset the system.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                |
| PPIN Opt-in                   | Enable/Disable the PPIN feature.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                |
| SMEE                          | Controls the Secure Memory Encryption Enable (SMEE) function.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                     |
| Action on BIST Failure        | Action to take when a CCD BIST failure is detected.<br>Options available: Do nothing, Down-CCD, Auto. Default setting is <b>Auto</b> .                                                                                          |



| Parameter                       | Description                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enhanced REP MOVSB/STOSB (ERSM) | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| Log Transparent Errors          | Enable/Disable the log Transparent errors function.<br>Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b> .                                                               |
| AVX512                          | Enable/Disable AVX512.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                            |
| ERMSB Caching Behavior          | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| CPU Speculative Store Modes     | Select the CPU speculative store modes.<br>Options available: Balanced, More Speculative, Less Speculative, Auto.<br>Default setting is <b>Auto</b> .                                             |
| Fast Short REP MOVSB (FSRM)     | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| PauseCntSel_1_0                 | Options available: Auto, 16 cycles, 32 cycles, 64 cycles, 128 cycles.<br>Default setting is <b>Auto</b> .                                                                                         |
| Prefetch/Request Throttle       | Enables XI logic which calculates average latency, updates throttle level, and sends throttle level messages to L2.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> . |
| Scan Dump Debug Enable          | Options available: Disable, Enable. Default setting is <b>Disable</b> .                                                                                                                           |
| MCAX 64 bank support            | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| Adaptive Allocation (AA)        | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| Latency Under Load (LUL)        | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| Core Trace Dump Enable          | Options available: Disable, Enable. Default setting is <b>Disable</b> .                                                                                                                           |
| FP512                           | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                      |
| AMD_ERMSB Reporting             | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                                                                                                        |

5-3-1-1 Performance



| Parameter                          | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Performance                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OC Mode <sup>(Note)</sup>          | Options available: Normal Operation, Customized. Default setting is <b>Normal Operation</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Custom Core Pstates                | Allows you to accept or decline enabling Custom Core Pstates. When accepted, you can disable or customize core pstates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| CCD/Core/Thread Enablement         | Allows you to accept or decline enabling CCDs, processor cores and threads. When accepted, you can control the number of CCDs to be used, and the number of cores to be used. <ul style="list-style-type: none"><li>• CCD Control<ul style="list-style-type: none"><li>– Options available: Auto, 2 CCDs, 4 CCDs, 6 CCDs, 8 CCDs, 10 CCDs. Default setting is <b>Auto</b>.</li></ul></li><li>• Core Control<ul style="list-style-type: none"><li>– Options available: Auto, ONE(1+0), TWO(2+0), THREE(3+0) FOUR(4+0), FIVE(5+0), SIX(6+0), SEVEN(7+0).</li><li>– Default setting is <b>Auto</b>.</li></ul></li></ul> |
| SMT Control                        | Can be used to disable symmetric multithreading. To re-enable SMT, a POWER CYCLE is needed after select the 'Enable' option. Select 'Auto' base on BIOS PCD. (PcdAmdSmtMode) default setting.<br>Options available: Disable, Enable, Auto. Default setting is <b>Enable</b> .                                                                                                                                                                                                                                                                                                                                        |
| Enable Requested CPU min frequency | Options available: Disable, Enable. Default setting is <b>Disable</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |


(Note) Advanced items are configurable when this item is defined.

### 5-3-1-2 Prefetcher Settings



| Parameter               | Description                                                                                                                                                                                                                                                         |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Prefetcher settings     |                                                                                                                                                                                                                                                                     |
| L1 Stream HW Prefetcher | Enable/Disable L1 Stream HW Prefetcher.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                                                               |
| L1 Stride Prefetcher    | Use memory access history of individual instructions to fetch additional lines when each access is a constant distance from the previous.<br>Enable/Disable L1 Stride Prefetcher.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .     |
| L1 Region Prefetcher    | Use memory access history to fetch additional lines when the data access for a given instruction tends to be followed by other data accesses.<br>Enable/Disable L1 Region Prefetcher.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> . |
| L2 Stream HW Prefetcher | Enable/Disable L2 Stream HW Prefetcher.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                                                               |
| L2 Up/Down Prefetcher   | Use memory access history to determine whether to fetch the next or previous line for all memory accesses.<br>Enable/Disable L2 Up/Down Prefetcher.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                   |
| L1 Burst Prefetch Mode  | Enable/Disable L1 Burst Prefetch Mode.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                                                                |

### 5-3-1-3 Core Watchdog



| Parameter                                    | Description                                                                                                                                                                                                                |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Core Watchdog                                |                                                                                                                                                                                                                            |
| Core Watchdog Timer Enable <sup>(Note)</sup> | Enable/Disable CPU Watchdog Timer.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .<br>Select the CPU Watchdog Timer interval.                                                              |
| Core Watchdog Timer Interval                 | Options available: 2.681s, 1.340s, 669.41ms, 334.05ms, 166.37ms, 82.53ms, 40.61ms, 20.970ms, 10.484ms, 5.241ms, 2.620ms, 1.309ms, 654.08us, 326.4us, 162.56us, 80.64us, 39.68us, Auto.<br>Default setting is <b>Auto</b> . |

(Note) Advanced items prompt when this item is defined.

### 5-3-2 DF Common Options



| Parameter                                        | Description                                                                                                                                                                           |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DF Common Options                                |                                                                                                                                                                                       |
| Memory Addressing                                | Press [Enter] for configuration of advanced items.                                                                                                                                    |
| ACPI                                             | Press [Enter] for configuration of advanced items.                                                                                                                                    |
| Link                                             | Press [Enter] for configuration of advanced items.                                                                                                                                    |
| SDCI                                             | Press [Enter] for configuration of advanced items.                                                                                                                                    |
| Probe Filter                                     | Press [Enter] for configuration of advanced items.                                                                                                                                    |
| DF Watchdog Timer Interval                       | Configures the Data Fabric watchdog timer interval.<br>Options available: Auto, 41ms, 166ms, 334ms, 669ms, 1.34 seconds, 2.68 seconds, 5.36 seconds. Default setting is <b>Auto</b> . |
| Disable DF to external IP sync flood propagation | Enable/Disable SyncFlood to UMC & downstream slaves.<br>Options available: Sync flood disabled, Sync flood enabled, Auto.<br>Default setting is <b>Auto</b> .                         |
| Sync flood propagation to DF Components          | Enable/Disable DF Sync Flood propagation.<br>Options available: Sync flood disabled, Sync flood enabled, Auto.<br>Default setting is <b>Auto</b> .                                    |
| Freeze DF module queues on error                 | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                          |
| CC6 memory region encryption                     | Controls whether or not the CC6 save/restor memory is encrypted.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                      |
| CCD B/W Balance Throttle Level                   | Options available: Auto, Level 0, Level 1, Level 2, Level 3, Level 4. Default setting is <b>Auto</b> .                                                                                |

| Parameter                         | Description                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------|
| Number of PCI Segments            | Options available: Auto, 1 Segment, 2 Segments, 4 Segment.<br>Default setting is <b>Auto</b> . |
| CCM Throttler                     | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                   |
| Clean Victim FTI Cmd<br>Balancing | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                   |
| CXL Strongly Ordered writes       | Options available: Disabled, One at a time. Default setting is <b>Disabled</b> .               |

### 5-3-2-1 Memory Addressing



| Parameter                          | Description                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Memory Addressing                  |                                                                                                                                                                                                                                                                                                                                                          |
| NUMA nodes per socket              | <p>Specifies the number of desired NUMA nodes per socket.</p> <p>Options available: NPS0, NPS1, NPS2, NPS4, Auto. Default setting is <b>Auto</b>.</p> <p><b>NOTE!</b></p> <ul style="list-style-type: none"><li>• <b>Available options may vary by system configuration.</b></li><li>• <b>Only dual processor configuration supports NPS0.</b></li></ul> |
| Memory interleaving                | <p>Enable/Disable the Memory interleaving feature.</p> <p>Options available: Disabled, Auto, Enabled. Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                |
| Mixed interleaving mode            | <p>Allows for interleaving UMC and CXL together.</p> <p>Options available: Disabled, Auto, Enabled. Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                  |
| Region Size                        | <p>Options available: 1 K Region Size, 2K Region Size, Auto.</p> <p>Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                                                  |
| CXL Memory interleaving            | <p>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                                                                       |
| CXL Sublink interleaving           | <p>Options available: Enable, Disable, Auto. Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                                                                         |
| DRAM map inversion                 | <p>Enable/Disable the DRAM map inversion function.</p> <p>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b>.</p>                                                                                                                                                                                                                |
| Location of private memory regions | <p>Controls whether or not the private memory regions (PSP, SMU and CC6) are at the top of DRAM or distributed.</p> <p>Options available: Distributed, Consolidated, Auto. Default setting is <b>Auto</b>.</p>                                                                                                                                           |

5-3-2-2 ACPI



| Parameter                          | Description                                                                                                                                        |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| ACPI                               |                                                                                                                                                    |
| ACPI SRAT L3 Cache As NUMA Domain  | Enable/Disable report each L3 cache as a NUMA Domain to the OS.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .    |
| ACPI SLIT Distance Control         | Determines how the SLIT distances are declared.<br>Options available: Manual, Auto. Default setting is <b>Auto</b> .                               |
| ACPI SLIT remote relative distance | Sets the remote socket distance for 2P systems as near (2.8) or far (3.2).<br>Options available: Near, Far, Auto. Default setting is <b>Auto</b> . |



### 5-3-2-3 Link



| Parameter               | Description                                                                                                                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GMI encryption control  | Enable/Disable GMI link encryption.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                              |
| xGMI encryption control | Enable/Disable xGMI link encryption.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                             |
| xGMI Link Configuration | Configures the number of xGMI2 links used on a multi-socket system.<br>Options available: Auto, 3 xGMI Links, 4 xGMI Links, 2 xGMI Links + 2 PCI Links. Default setting is <b>3 xGMI Links</b> . |
| 4-link xGMI max speed   | Specifies the max speed of 4-link xGMI.<br>Options available: 20Gbps, 25Gbps, 32Gbps, Auto. Default setting is <b>Auto</b> .                                                                     |
| 3-link xGMI max speed   | Specifies the max speed of 3-link xGMI.<br>Options available: 20Gbps, 25Gbps, 32Gbps, Auto. Default setting is <b>Auto</b> .                                                                     |
| xGMI CRC Scale          | Configures leaky bucket scale for xGMI and WAFL CRC errors. Every scale milliseconds an error will leak from the CRC counter. Default setting is <b>7</b> .                                      |
| xGMI CRC Threshold      | Configures leaky bucket threshold for xGMI and WAFL CRC errors. If link CRC counter exceeds this threshold, an error will be logged. Default setting is <b>25</b> .                              |
| xGMI Preset Control     | Enable/Disable xGMI Preset control.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Enabled</b> .                                                                           |
| xGMI Global Preset List | Press [Enter] to configure the xGMI Preset list.                                                                                                                                                 |
| xGMI Initial Preset     | Press [Enter] to configure the xGMI Initial Preset CPU0/1 link.                                                                                                                                  |
| xGMI TXEQ Search Mask   | Press [Enter] to configure the xGMI TXEQ Search Mask CPU0/1 link.                                                                                                                                |

| Parameter               | Description                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| xGMI AC/DC Coupled Link | Press [Enter] to configure the xGMI AC/DC Coupled link.<br>♦ xGMI AC/DC Coupled Link Control <sup>(Note)</sup><br>– Options available: Manual, Auto. Default setting is <b>Auto</b> . |
| xGMI Channel Type       | Press [Enter] to configure the xGMI Channel Type.<br>♦ xGMI Channel Type Control <sup>(Note)</sup><br>– Options available: Manual, Auto. Default setting is <b>Auto</b> .             |

(Note) Advanced items prompt when this item is defined.

5-3-2-4 SDCI



| Parameter              | Description                                                                  |
|------------------------|------------------------------------------------------------------------------|
| SDCI <sup>(Note)</sup> | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| DisRmSteer             | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |

(Note) Advanced items prompt when this item is defined.

### 5-3-2-5 Probe Filter



| Parameter                             | Description                                                                                                                                                          |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Organization                          | Specifies whether multiple memory/CXL channels will share probe filter storage.<br>Options available: Auto, Dedicated, Shared. Default setting is <b>Dedicated</b> . |
| Periodic Directory Rinse (PDR) Tuning | Controls PDR settings that may impact performance by workload and/or processor.<br>Options available: Periodic, Blended, Auto. Default setting is <b>Auto</b> .      |
| Tracking Granularity                  | Options available: Finer-Grain, Coarser-Grain, Auto. Default setting is <b>Auto</b> .                                                                                |

5-3-3 UMC Common Options



| Parameter                    | Description                                        |
|------------------------------|----------------------------------------------------|
| UMC Common Options           |                                                    |
| DDR Addressing Options       | Press [Enter] for configuration of advanced items. |
| DDR Controller Configuration | Press [Enter] for configuration of advanced items. |
| DDR MBIST Options            | Press [Enter] for configuration of advanced items. |
| DDR RAS                      | Press [Enter] for configuration of advanced items. |
| DDR Bus Configuration        | Press [Enter] for configuration of advanced items. |
| Enforce POR                  | Press [Enter] for configuration of advanced items. |
| DDR Training Options         | Press [Enter] for configuration of advanced items. |
| DDR Security                 | Press [Enter] for configuration of advanced items. |
| DDR PMIC Configuration       | Press [Enter] for configuration of advanced items. |
| DDR Thermal Throttling       | Press [Enter] for configuration of advanced items. |

### 5-3-3-1 DDR Addressing Options



| Parameter               | Description                                                                                                                               |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| DDR Addressing Options  |                                                                                                                                           |
| Chipselect Interleaving | Interleaves memory blocks across the DRAM chip selects for node 0.<br>Options available: Disabled, Auto. Default setting is <b>Auto</b> . |
| Address Hash Bank       | Enable or disable bank addressing hashing.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                |
| Address Hash CS         | Enable or disable CS addressing hashing.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| Address Hash RM         | Enable or disable RM addressing hashing for 3DS DIMMs.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .    |
| Address Hash Subchannel | Enable or disable sub-channel addressing hashing.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .         |
| BankSwapMode            | Options available: Auto, Disabled, Swap CPU. Default setting is <b>Auto</b> .                                                             |

5-3-3-2 DDR Controller Configuration



| Parameter                    | Description                                                                  |
|------------------------------|------------------------------------------------------------------------------|
| DDR Controller Configuration |                                                                              |
| DDR Power Options            | Press [Enter] for configuration of advanced items.                           |
| Memory Channel Disable       | Press [Enter] for configuration of advanced items.                           |
| Refresh Management (RFM)     | Press [Enter] for configuration of advanced items.                           |
| Memory Context Restore       | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| DRAM Survives Warm Reset     | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .   |


### 5-3-3-2-1 DDR Power Options



| Parameter                             | Description                                                                                                            |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| DDR Power Options                     |                                                                                                                        |
| Power Down Enable                     | Enable or disable DDR power down mode.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| Sub Urgent Refresh Lower Bound        | Specifies the stored refresh limit required to enter sub-urgent refresh mode.                                          |
| Urgent Refresh Limit                  | Specifies the stored refresh limit required to enter urgent refresh mode.                                              |
| DRAM Refresh Rate                     | DRAM refresh rate: 1.95us or 3.9us.<br>Options available: 3.9 usec, 1.95 usec. Default setting is <b>3.9 usec</b> .    |
| Self-Refresh Exit Staggering          | Options available: Disabled, n=1~9. Default setting is <b>n=9</b> .                                                    |
| DRAM 2X Refresh Temperature Threshold | Options available: 85°-90°, 90°-95°, 95-100°, >100°. Default setting is <b>85°-90°</b> .                               |



5-3-3-2-2 Memory Channel Disable



| Parameter                               | Description                                                                |
|-----------------------------------------|----------------------------------------------------------------------------|
| Memory Channel Disable                  |                                                                            |
| Memory Channel Disable Float Power Good | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> . |
| Memory Channel Disable Bitmask          |                                                                            |
| CPU0/1 Channel_#                        | Press [Enter] to enable/disable specific memory channel.                   |



### 5-3-3-3 DDR MBIST Options



| Parameter                                          | Description                                                                                                                                                                                                                                                                    |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DDR MBIST Options                                  |                                                                                                                                                                                                                                                                                |
| MBIST Enable                                       | Enable/Disable the Memory MBIST function.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                                                      |
| MBIST Test Mode <sup>(Note1)</sup>                 | Selects MBIST Test Mode.<br><b>Interface Mode</b> : Tests Single and Multiple CS transactions and Basic Connectivity.<br><b>Data Eye Mode</b> : Measures Voltage vs. Timing.<br>Options available: Auto, Both, Interface Mode, Data Eye Mode. Default setting is <b>Auto</b> . |
| MBIST Aggressors <sup>(Note1)</sup>                | Enable/Disable MBIST Aggressor test.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                                                                                                                                                           |
| DDR Healing BIST                                   | Options available: Disabled, PMU Mem BIST, Self-Healing Mem BIST, PMU and Self-Healing Mem BIST. Default setting is <b>Disabled</b> .                                                                                                                                          |
| DDR Healing BIST Execution Mode <sup>(Note2)</sup> | Options available: One Time, Every boot.<br>Default setting is <b>One Time</b> .                                                                                                                                                                                               |
| DDR Healing BIST Repair Type <sup>(Note2)</sup>    | For DRAM errors found in the BIOS memory BIST select the repair type.<br>Options available: Soft Repair, Hard Repair, No Repairs -Test only. Default setting is <b>Soft Repair</b> .                                                                                           |

(Note1) This item can be configured when **MBIST Enable** is set to **Enabled**.

(Note2) This item can be configured when **DDR Healing BIST** is defined.

| Parameter | Description                                |
|-----------|--------------------------------------------|
| Data Eye  | Press [Enter] to configure advanced items. |


5-3-3-3-1 Data Eye



| Parameter                                  | Description                                                                                                                                                |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Data Eye                                   |                                                                                                                                                            |
| Pattern Select                             | Options available: PRBS, SSO, Both. Default setting is <b>PRBS</b> .                                                                                       |
| Pattern Length                             | Determines the pattern length. The possible options are N=3....12.                                                                                         |
| Aggressor Channel                          | This item helps read the aggressors channels.<br>Options available: One Sub-Channel, Half Channels, All Channels. Default setting is <b>All Channels</b> . |
| Aggressor Static Lane Control              | Enable/Disable the Aggressor Static Lane Control function.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                   |
| Aggressor Static Lane Select Upper 32 bits | This item is configurable when <b>Aggressor Static Lane Control</b> is set to <b>Enabled</b> .                                                             |
| Aggressor Static Lane Select Lower 32 bits | This item is configurable when <b>Aggressor Static Lane Control</b> is set to <b>Enabled</b> .                                                             |
| Aggressor Static Lane Select ECC           | This item is configurable when <b>Aggressor Static Lane Control</b> is set to <b>Enabled</b> .                                                             |
| Aggressor Static Lane Value                | This item is configurable when <b>Aggressor Static Lane Control</b> is set to <b>Enabled</b> .                                                             |
| Target Static Lane Control                 | Enable/Disable the Target Static Lane Control function.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                      |

| Parameter                               | Description                                                                                                                           |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Target Static Lane Select Upper 32 bits | This item is configurable when <b>Target Static Lane Control</b> is set to <b>Enabled</b> .                                           |
| Target Static Lane Select Lower 32 bits | This item is configurable when <b>Target Static Lane Control</b> is set to <b>Enabled</b> .                                           |
| Target Static Lane Select ECC           | This item is configurable when <b>Target Static Lane Control</b> is set to <b>Enabled</b> .                                           |
| Target Static Lane Value                | This item is configurable when <b>Target Static Lane Control</b> is set to <b>Enabled</b> .                                           |
| Read Voltage Sweep Step Size            | Configures the step size for read Data Eye voltage sweep.<br>Options available: 1, 2, 4. Default setting is 1.                        |
| Read Timing Sweep Step Size             | Configures the step size for read Data Eye timing sweep.<br>Options available: 1, 2, 4. Default setting is 1.                         |
| Write Voltage Sweep Step Size           | Configures the step size for write Data Eye voltage sweep.<br>Options available: 1, 2, 4. Default setting is 1.                       |
| Write Timing Sweep Step Size            | Configures the step size for write Data Eye timing sweep.<br>Options available: 1, 2, 4. Default setting is 1.                        |
| Silent Execution                        | Execute MBIST Data Eye silently without ABL log output.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> . |

### 5-3-3-4 DDR RAS



| Parameter                                 | Description                                                                                                                                                                                                                                                                         |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DDR RAS                                   |                                                                                                                                                                                                                                                                                     |
| Data Poisoning                            | Enable/Disable the Data Poisoning function.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                                                                                                                                                         |
| DRAM Boot Time Post Package Repair        | Enable/Disable the DRAM Boot Time Post Package Repair function.<br>Options available: Enable, Disable. Default setting is <b>Disable</b> .                                                                                                                                          |
| DRAM Runtime Post Package Repair          | Enable/Disable the DRAM Runtime Post Package Repair function.<br>Options available: Enable, Disable. Default setting is <b>Disable</b> .                                                                                                                                            |
| DRAM Post Package Repair Config Initiator | Options available: In-Band, Out of Band. Default setting is <b>In-Band</b> .                                                                                                                                                                                                        |
| RCD Parity                                | Enable/Disable the RCD Parity function.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Enabled</b> .                                                                                                                                                          |
| Write CRC                                 | Options available: Auto, Enabled, Disabled. Default setting is <b>Disabled</b> .                                                                                                                                                                                                    |
| Read CRC                                  | Options available: Auto, Enabled, Disabled. Default setting is <b>Disabled</b> .                                                                                                                                                                                                    |
| Memory Error Injection                    | Options available: False, True, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                                                              |
| EcsStatus Interrupt                       | Options available: False, True. Default setting is <b>False</b> .                                                                                                                                                                                                                   |
| ECC Configuration                         | Press [Enter] to configure advanced items. <ul style="list-style-type: none"><li>◆ DRAM ECC Symbol Size<ul style="list-style-type: none"><li>– Configures the DRAM ECC Symbol Size.</li><li>– Options available: Auto, x4, x16. Default setting is <b>Auto</b>.</li></ul></li></ul> |

| Parameter                        | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ECC Configuration<br>(continued) | <ul style="list-style-type: none"> <li>♦ DRAM ECC Enable <ul style="list-style-type: none"> <li>– Enable/Disable DRAM ECC. When set to Auto, it will set ECC to enable.</li> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ DRAM UECC Retry <ul style="list-style-type: none"> <li>– Enable/Disable DRAM UECC Retry.</li> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Disabled</b>.</li> </ul> </li> <li>♦ Max DRAM UECC Error Replay<sup>(Note)</sup> <ul style="list-style-type: none"> <li>– Default setting is <b>8</b>.</li> </ul> </li> <li>♦ Memory Clear <ul style="list-style-type: none"> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ Address XOR after ECC <ul style="list-style-type: none"> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ CypherText Hiding Enable <ul style="list-style-type: none"> <li>– Options available: Disable, Enable. Default setting is <b>Disable</b>.</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                       |
|                                  | Press [Enter] to configure advanced items.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                  | <ul style="list-style-type: none"> <li>♦ DRAM ECS Mode <ul style="list-style-type: none"> <li>– Options available: Auto, AutoECS, ManualECS, DisableECS. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ DRAM Redirect Scrubber Enable <ul style="list-style-type: none"> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ DRAM Scrub Redirection Limit <ul style="list-style-type: none"> <li>– Options available: Auto, 8 Scrubs, 4 Scrubs, 2 Scrubs, 1 Scrub. Default setting is <b>Auto</b>.</li> </ul> </li> <li>♦ DRAM Scrub Time <ul style="list-style-type: none"> <li>– Options available: Disabled, 1 hour, 4 hours, 6 hours, 8 hours, 12 hours, 16 hours, 24 hours, 48 hours. Default setting is <b>24 Hours</b>.</li> </ul> </li> <li>♦ ECS Config <ul style="list-style-type: none"> <li>– DRAM Error Threshold Count <ul style="list-style-type: none"> <li>» Options available: Auto, ETC_4, ETC_16, ETC_64, ETC_256, ETC_1024, ETC_4096. Default setting is <b>Auto</b>.</li> </ul> </li> <li>– DRAM ECS Count Mode <ul style="list-style-type: none"> <li>» Options available: Auto, Row Count Mode, Code Word Count Mode. Default setting is <b>Auto</b>.</li> </ul> </li> <li>– DRAM AutoEcs during Self Refresh <ul style="list-style-type: none"> <li>» Options available: Auto, AutoEcs Disabled, AutoEcs Enabled. Default setting is <b>Auto</b>.</li> </ul> </li> </ul> </li> </ul> |
| DRAM Scrubbers                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

(Note) This item available when **DRAM UECC Retry** is set to **Enabled**.



| Parameter                                     | Description                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DRAM Scrubbers<br>(continued)                 | <ul style="list-style-type: none"> <li>– DRAM ECS WriteBack Suppression               <ul style="list-style-type: none"> <li>» Options available: Auto, Enable, Disable. Default setting is <b>Auto</b>.</li> </ul> </li> <li>– DRAM X4 WriteBack Suppression               <ul style="list-style-type: none"> <li>» Options available: Auto, Enable, Disable. Default setting is <b>Auto</b>.</li> </ul> </li> </ul> |
| DRAM Corrected Error Counter Enable           | Configure DRAM Corrected Error Counter function.<br>Options available: Disable, NoLeakMode, LeakMode. Default setting is <b>LeakMode</b> .                                                                                                                                                                                                                                                                            |
| DRAM Corrected Error Counter Interrupt Enable | Enable SMI when DRAM corrected Error Counter count exceeds the threshold value.<br>Options available: False, True. Default setting is <b>True</b> .                                                                                                                                                                                                                                                                   |
| DRAM Corrected Counter Leak Rate              | Program Rate value for DRAM Corrected Error Counter function.<br>Default setting is <b>7</b> .                                                                                                                                                                                                                                                                                                                        |
| DRAM Corrected Error Counter Start Count      | Program starting value for DRAM Corrected Error Counter function.<br>Default setting is <b>FFF5</b> .                                                                                                                                                                                                                                                                                                                 |

5-3-3-5 DDR Bus Configuration



| Parameter                    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DDR Bus Configuration        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| P-State 0 Dram ODT Impedance | <p>Press [Enter] to configure advanced items.</p> <ul style="list-style-type: none"><li>• RTT_NOM_WR P-State 0<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_NOM_RD P-State 0<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_WR P-State 0<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_PARK P-State 0<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• DQS_RTT PARK P-State 0<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li></ul> |
| P-State 1 Dram ODT Impedance | <p>Press [Enter] to configure advanced items.</p> <ul style="list-style-type: none"><li>• RTT_NOM_WR P-State 1<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_NOM_RD P-State 1<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_WR P-State 1<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• RTT_PARK P-State 1<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li><li>• DQS_RTT PARK P-State 1<ul style="list-style-type: none"><li>– Default setting is <b>Auto</b>.</li></ul></li></ul> |

| Parameter                         | Description                                                                                                                                                                                                                                                                                                    |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Processor ODT Pull Up impedance   | Select the ODT impedance for all DBYTE IOs.<br>Options available: Auto, High Impedance, 480 ohm, 240 ohm, 160 ohm, 120 ohm, 96 ohm, 80 ohm, 68.6 ohm, 60 ohm, 53.3 ohm, 48 ohm, 43.6 ohm, 40 ohm, 36.9 ohm, 34.3 ohm, 32 ohm, 30 ohm, 28.2 ohm, 26.7 ohm, 25.3 ohm. Default setting is <b>Auto</b> .           |
| Processor ODT Pull Down impedance | Select the ODT pull down impedance for all DBYTE IOs.<br>Options available: Auto, High Impedance, 480 ohm, 240 ohm, 160 ohm, 120 ohm, 96 ohm, 80 ohm, 68.6 ohm, 60 ohm, 53.3 ohm, 48 ohm, 43.6 ohm, 40 ohm, 36.9 ohm, 34.3 ohm, 32 ohm, 30 ohm, 28.2 ohm, 26.7 ohm, 25.3 ohm. Default setting is <b>Auto</b> . |
| Dram DQ drive strengths           | Select the Dram Pull-up and Pull-Down Output Driver Impedance for all DQ and DMI IOs.<br>Options available: Auto, 48 ohm, 40 ohm, 34 ohm, Default setting is <b>Auto</b> .                                                                                                                                     |

5-3-3-6 Enforce POR



| Parameter                                       | Description                                                                                                                                                                     |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enforce POR                                     | Decline/Accept to configure the advanced items.                                                                                                                                 |
| Accept                                          |                                                                                                                                                                                 |
| Active Memory Timing Settings <sup>(Note)</sup> | Active memory Timing Settings.<br>Options available: Auto, Enabled. Default setting is <b>Auto</b> .                                                                            |
| Memory Target Speed                             | Specifies the memory target speed in MT/s.<br>Options available: Auto, DDR3600, DDR4000, DDR4400, DDR4800, DDR5200, DDR5600, DDR6000, DDR6400. Default setting is <b>Auto</b> . |
| SPD Timing                                      | Press [Enter] to configure advanced items.                                                                                                                                      |
| Non-SPD Timing                                  | Press [Enter] to configure advanced items.                                                                                                                                      |

(Note) Advanced items prompt when this item is defined.

5-3-3-7 DDR Training Options



| Parameter                              | Description                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DDR Training Options                   |                                                                                                                                                                                                                                                                                                                                                                                        |
| DRAM PDA Enumerate ID Programming Mode | Specify PDA enumeration mode.<br>Options available: Auto, Toggling PDA enumeration mode, Legacy PDA enumeration mode. Default setting is <b>Auto</b> .                                                                                                                                                                                                                                 |
| Periodic Phase Training                | Press [Enter] to configure advanced items. <ul style="list-style-type: none"><li>Periodic Training Mode<ul style="list-style-type: none"><li>Options available: Disabled, Legacy. Default setting is <b>Legacy</b>.</li></ul></li><li>Periodic Interval Mode<ul style="list-style-type: none"><li>Options available: Auto, Manual. Default setting is <b>Auto</b>.</li></ul></li></ul> |
| Write Training Burst Length            | Options available: 4x, 8x. Default setting is <b>4x</b> .                                                                                                                                                                                                                                                                                                                              |

5-3-3-8 DDR Security



| Parameter     | Description                                                                                                     |
|---------------|-----------------------------------------------------------------------------------------------------------------|
| Security      |                                                                                                                 |
| TSME          | Enable/Disable Transparent SME.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> . |
| AES           | Options available: AES-128, AES-256. Default setting is <b>AES-256</b> .                                        |
| Data Scramble | Enable/Disable Data Scrambling.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .    |
| SME-MK        | Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                                      |

### 5-3-3-9 DDR PMIC Configuration



| Parameter              | Description                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| DDR PMIC Configuration |                                                                                                                     |
| PMIC Error Reporting   | Enables support for PMIC Error Reporting.<br>Options available: Auto, False, True. Default setting is <b>Auto</b> . |
| PMIC Operation Mode    | Options available: Secure Mode, Programmable Mode.<br>Default setting is <b>Programmable Mode</b> .                 |
| PMIC Fault Recovery    | Options available: Always, Never, Once. Default setting is <b>Always</b> .                                          |
| PMIC SWA/SWB VDD Core  | Default setting is <b>1100</b> .                                                                                    |
| PMIC SWC VDDIO         | Default setting is <b>1100</b> .                                                                                    |
| PMIC SWD VPP           | Default setting is <b>1800</b> .                                                                                    |
| PMIC Stagger Delay     | Default setting is <b>5</b> .                                                                                       |
| Max PMIC Power On      | Default setting is <b>FF</b> .                                                                                      |

### 5-3-3-10 DDR Thermal Throttling



| Parameter                       | Description                                                                       |
|---------------------------------|-----------------------------------------------------------------------------------|
| DDR Thermal Throttling          |                                                                                   |
| ODTS Thermal Throttle Control   | Default setting is <b>Enabled</b> .                                               |
| ODTS Thermal Throttle Threshold | Options available: Auto, > 85°C, > 90°C, > 95°C. Default setting is <b>Auto</b> . |
| TSOD Thermal Throttle Control   | Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .         |



### 5-3-4 NBIO Common Options



| Parameter                              | Description                                                                  |
|----------------------------------------|------------------------------------------------------------------------------|
| NBIO Common Options                    |                                                                              |
| SMU Common Options                     | Press [Enter] for configuration of advanced items.                           |
| NBIO RAS Common Options                | Press [Enter] for configuration of advanced items.                           |
| PCIE                                   | Press [Enter] for configuration of advanced items.                           |
| nBif Common Options                    | Press [Enter] for configuration of advanced items.                           |
| IOMMU/Security                         | Press [Enter] for configuration of advanced items.                           |
| Enable Port Bifurcation                | Press [Enter] for configuration of advanced items.                           |
| Link EQ Present Options                | Press [Enter] for configuration of advanced items.                           |
| PCIe loopback Mode                     | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| Enable 2SPC (Gen 4)                    | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .   |
| Enable 2SPC (Gen 5)                    | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .   |
| Safe recovery upon a BERExceeded Error | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .   |
| Periodic Calibration                   | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .   |

### 5-3-4-1 SMU Common Options



| Parameter                     | Description                                                                                                                                                                                                                             |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SMU Common Options            |                                                                                                                                                                                                                                         |
| Power Policy Quick Setting    | Options available: Standard, Best Performance, Energy Efficient. Default setting is <b>Standard</b> .                                                                                                                                   |
| TDP Control                   | Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                       |
| PPT Control                   | Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                       |
| Determinism Control           | Selects use the fused Determinism or set customized Determinism. Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                      |
| xGMI Link Width Control       | Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                       |
| APBDIS                        | Options available: 0, 1, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                         |
| Power Profile Selection       | Options available: High Performance Mode, Efficiency Mode, Maximum IO Performance Mode, Balanced Memory Performance Mode, Balanced Core Performance Mode, Balanced Core Memory Performance Mode, Auto. Default setting is <b>Auto</b> . |
| xGMI Pstate Control           | Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                       |
| BoostFmaxEn                   | Options available: Manual, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                       |
| DF PState Frequency Optimizer | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                                                                                                                                                            |

| Parameter                           | Description                                                                                                      |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------|
| DF Cstates                          | Options available: Disabled, Enabled, Auto. Default setting is <b>Disabled</b> .                                 |
| CPPC                                | Enable/Disable the CPPC feature.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| HSMP Support                        | Enable/Disable the HSMP support.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |
| SVI3 SVC Speed Control              | Options available: Auto, Manual. Default setting is <b>Auto</b> .                                                |
| 3D V-Cache                          | Options available: Auto, Disable, 1 stack. Default setting is <b>Auto</b> .                                      |
| L3 BIST                             | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                       |
| Diagnostic Mode                     | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                     |
| GMI Folding                         | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                     |
| Separate CPU power plane throttling | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                       |
| DfPstate Range Support              | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                       |

### 5-3-4-2 NBIO RAS Common Options



| Parameter                         | Description                                                                                                                                                                            |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NBIO RAS Common Options           |                                                                                                                                                                                        |
| NBIO RAS Control                  | Options available: Disabled, MCA, Auto. Default setting is <b>Auto</b> .                                                                                                               |
| NBIO SyncFlood Generation         | The value may be used to mask SyncFlood caused by NBIO RAS options.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b> .                                    |
| NBIO SyncFlood Reporting          | The value may be used to enable SyncFlood reporting to APML.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b> .                                           |
| PCIe Aer Reporting Mechanism      | Selects the method of reporting AER errors from PCI Express.<br>Options available: Firmware First, Firmware First but allow OS First, OS First, Auto. Default setting is <b>Auto</b> . |
| Edpc Control                      | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                           |
| ACS RAS Request Value             | Options available: Direct Request Access Enabled, Request Blocking Enabled, Request Redirect Enabled, Auto. Default setting is <b>Auto</b> .                                           |
| NBIO Poison Consumption           | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                                                                                                           |
| Sync Flood on PCIe Fatal Error    | Options available: Auto, True, False. Default setting is <b>Auto</b> .                                                                                                                 |
| NBIO RAS Numerical Common Options | Options available: Disable, Manual. Default setting is <b>Disable</b> .                                                                                                                |

### 5-3-4-3 PCIE



| Parameter                            | Description                                                                                                                                                                                                     |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PCIe                                 |                                                                                                                                                                                                                 |
| Data Object Exchange                 | Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b> .                                                                                                                                    |
| RTM Margining Support                | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                                                                                                                      |
| Multi Auto Speed Change On Last Rate | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                                                                                                                      |
| Multi Upstream Auto Speed Change     | Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b> .                                                                                                                                    |
| Allow Compliance                     | When enabled, allows the PCIe RP to enter Polling.Compliance state.<br>Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                                               |
| EQ Bypass To Highest Rate            | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                                                      |
| Data Link Feature Cap                | Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b> .                                                                                                                                    |
| SRIS                                 | Options available: Auto, Disable, Enable. Default setting is <b>Auto</b> .                                                                                                                                      |
| ACS Enable                           | Enable/Disable ACS.<br>Options available: Enable, Disabled, Auto. Default setting is <b>Auto</b> .                                                                                                              |
| PCIe Ten Bit Tag Support             | Enable/Disable PCIe ten bit tags for supported devices. (Auto=Disabled)<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                           |
| PCIe ARI Enumeration                 | ARI Forwarding Enable for each downstream port.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                   |
| PCIe ARI Support                     | Enable/Disable Alternative Routing-ID Interpretation.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                             |
| Presence Detect Select mode          | Controls the Presence Detect Select mode.<br>Options available: OR, AND, Auto. Default setting is <b>Auto</b> .                                                                                                 |
| Hot Plug Handling mode               | Controls the Hot Plug Handling mode.<br>Options available: OS First, Firmware First/EDR if OS supports, Firmware First but allow OS First, System Firmware Intermediary, Auto. Default setting is <b>Auto</b> . |
| Presence Detect State Settle Time    | Options available: True, False, Auto. Default setting is <b>Auto</b> .                                                                                                                                          |
| Hot Plug Port Settle Time            | Configure Hot Plug Port Settle Time.                                                                                                                                                                            |
| Hot Plug Support                     | Options available: Auto, Disabled. Default setting is <b>Auto</b> .                                                                                                                                             |
| Early Link Speed                     | Configures Early Link Speed.<br>Options available: Auto, Gen1, Gen2. Default setting is <b>Auto</b> .                                                                                                           |
| Enable AER Cap                       | Enable/Disable Advanced Error Reporting Capability.<br>Options available: Enable, Disabled, Auto. Default setting is <b>Auto</b> .                                                                              |

| Parameter                                | Description                                                                                            |
|------------------------------------------|--------------------------------------------------------------------------------------------------------|
| PCIe Link Speed Capability               | Options available: Maximum speed, Gen1, Gen2, Gen3, Gen4, Gen5, Auto. Default setting is <b>Auto</b> . |
| PCIe Target Link Speed                   | Options available: Maximum Speed, GEN1, GEN2, GEN3, GEN4, GEN5, Auto. Default setting is <b>Auto</b> . |
| ASPM Control                             | Options available: Disable, L1, Auto. Default setting is <b>Auto</b> .                                 |
| MCTP Enable                              | Options available: Enable, Disable, Auto. Default setting is <b>Disable</b> .                          |
| Non-PCIe Compliant Support               | Options available: Enable, Disable, Auto. Default setting is <b>Auto</b> .                             |
| Limit hotplug devices to PCIe boot speed | Options available: Enable, Disable, Auto. Default setting is <b>Auto</b> .                             |

### 5-3-4-4 nBif Common Options



| Parameter | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RCC_DEV0  | <ul style="list-style-type: none"><li>◆ ACS Rcc_Dev0<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ AER Rcc_Dev0<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ DllEnableStrap1<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ Phy16GTStrap1<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ MarginEnStrap1<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ SourceValStrap5<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ TranslationalBlockingStrap5<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ P2pReq ACS Control<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ P2pCompStrap5<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li><li>◆ UpstreamFwdStrap5<ul style="list-style-type: none"><li>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li></ul></li></ul> |



| Parameter               | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RCC_DEV0<br>(continued) | <ul style="list-style-type: none"> <li>◆ P2PEgressStrap5<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ DirectTranslatedStrap5<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ SsidEnStrap5<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ PriEnPageReq<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ PriResetPageReq<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ SourceVal ACS cntl<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ TranslationalBlocking ACS Control<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ P2pComp ACS Control<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ UpstreamFwd ACS Control<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ P2PEgress ACS Control<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ P2pReqStrap5<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ E2E_PREFIX<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ EXTENDED_FMT<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> <li>◆ AtomicRoutingStrap5<br/>– Options available: Auto, Disabled, Enabled. Default setting is <b>Auto</b>.</li> </ul> |


5-3-4-5 IOMMU/Security



| Parameter                      | Description                                                                                                                            |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| SEV-SNP Support                | Enable/Disable the SEV-SNP support.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                      |
| DRTM Memory Reservation        | Enable/Disable DRTM Memory reservation.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                |
| DRTM Virtual Device Support    | Enable/Disable DRTM ACPI virtual device.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .               |
| DMA Protection                 | Enable/Disable DMA remap support in IVRS IVinfo Field.<br>Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> . |
| IOMMU                          | Enable/Disable the IOMMU function.<br>Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                       |
| DMAR Support <sup>(Note)</sup> | Enable/Disable DMAR system protection during POST.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .     |

(Note) This item is configurable when **IOMMU** is set to **Enabled**.


5-3-4-6 Enable Port Bifurcation



| Parameter                            | Description                                                                |
|--------------------------------------|----------------------------------------------------------------------------|
| Enable Bifurcation <sup>(Note)</sup> | Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> . |
| Socket0 Slot Info Override           |                                                                            |
| Socket1 Slot Info Override           |                                                                            |


(Note) Advanced items prompt when this item is defined.

5-3-4-7 Link EQ Preset Options




| Parameter | Description                                                                                                                                                                                 |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GEN3/4/5  | <div>Press [Enter] to configure advanced items.</div> <div><div>◆ Preset Search Mask Configuration</div><div>– Options available: Custom, Auto. Default setting is <b>Auto</b>.</div></div> |

5-3-5 FCH Common Options



| Parameter                     | Description                                        |
|-------------------------------|----------------------------------------------------|
| FCH Common Options            |                                                    |
| I3C/I2C Configuration Options | Press [Enter] for configuration of advanced items. |
| SATA Configuration Options    | Press [Enter] for configuration of advanced items. |
| USB Configuration Options     | Press [Enter] for configuration of advanced items. |
| AC Power Loss Options         | Press [Enter] for configuration of advanced items. |
| Uart Configuration Options    | Press [Enter] for configuration of advanced items. |
| FCH RAS Options               | Press [Enter] for configuration of advanced items. |
| Miscellaneous Options         | Press [Enter] for configuration of advanced items. |

### 5-3-5-1 I3C/I2C Configuration Options



| Parameter                                | Description                                                                                                  |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| I3C/I2C Configuration Options            |                                                                                                              |
| I3C/I2C 0/1/2/3 Enable <sup>(Note)</sup> | Options available: Both Disabled, I3C Enabled, I2C Enabled, Auto. Default setting is <b>I3C Enabled</b> .    |
| I2C 4/5 Enable                           | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                 |
| Release SPD Host Control                 | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                   |
| PMFW Poll DDR5 Telemetry                 | Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                    |
| Ixc Telemetry Ports Fence Control        | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                   |
| I2C SDA Hold Override                    | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                 |
| APMR SB-TSI & RMI Mode                   | Options available: I3C, I2C. Default setting is <b>I3C</b> .                                                 |
| I3C Mode Speed                           | Options available: SDR2(6MHz), SDR0(12.5MHz), Auto. Default setting is <b>Auto</b> .                         |
| I3C Push Pull HCNT Value                 | SCL push-pull High count for I3C transfers targeted to I3C devices.                                          |
| I3C SDA Hold Value                       | Specifies I3C SDA Hold value.                                                                                |
| I3C SDA Hold Override                    | Override I3C SDA Hold value.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |

(Note) Advanced items prompt when this item is defined.

### 5-3-5-2 SATA Configuration Options



| Parameter                            | Description                                                                                                                                                                                                                  |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SATA Configuration Options           |                                                                                                                                                                                                                              |
| SATA Enable                          | Enable/Disable OnChip SATA controller.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                       |
| SATA RAS Support                     | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                                                 |
| SATA Staggered Spin-up               | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                                                 |
| SATA Disabled AHCI Prefetch Function | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                                                                                                                                 |
| SATA Controller options              | Press [Enter] for configuration of advanced items. <ul style="list-style-type: none"><li>◆ SATA Controller Enable</li><li>◆ SATA Controller eSATA</li><li>◆ SATA Controller DevSlp</li><li>◆ SATA Controller SGPIO</li></ul> |


### 5-3-5-3 USB Configuration Options



| Parameter                 | Description                                                                                                                                                                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USB Configuration Options |                                                                                                                                                                                                                                                                 |
| XHCI Controller0/1 enable | Enable/Disable USB controller.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b> .                                                                                                                                                  |
| MCM USB enable            | Press [Enter] for configuration of advanced items. <ul style="list-style-type: none"><li>◆ XHCI2/ XHCI3 enable (Socket1)<ul style="list-style-type: none"><li>– Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b>.</li></ul></li></ul> |



### 5-3-5-4 AC Power Loss Options



| Parameter                          | Description                                                                                                                                                  |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Power Loss Options              |                                                                                                                                                              |
| AC Loss Control                    | Selects the AC Loss Control Method.<br>Options available: Power Off, Power On, Last State.<br>Default setting is <b>Last State</b> .                         |
| Set FCH Power failed shadow in ABL | Enable/Disable set FCH power failed shadow by AC Loss control policy in ABL.<br>Options available: Enabled, Disabled, Auto. Default setting is <b>Auto</b> . |

5-3-5-5 Uart Configuration Options



| Parameter                  | Description                                                                  |
|----------------------------|------------------------------------------------------------------------------|
| Uart Configuration Options |                                                                              |
| Uart 0/1/2/3 Enable        | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> . |

5-3-5-6 FCH RAS Options



| Parameter              | Description                                                                                                                                             |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCH RAS Options        |                                                                                                                                                         |
| ALink RAS Support      | Enable/Disable the ALink RAS Support.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                   |
| Reset After Sync-Flood | Enables AB to forward downstream sync-flood message to system controller.<br>Options available: Enable, Disable, Auto. Default setting is <b>Auto</b> . |

### 5-3-5-7 Miscellaneous Options



| Parameter             | Description                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Miscellaneous Options |                                                                                                                                               |
| FCH Spread Spectrum   | Select whether or not Enable the Spread Spectrum Feature.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Disabled</b> . |
| Boot Timer Enable     | Enable/Disable Boot Timer.<br>Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                                    |

### 5-3-6 SOC Miscellaneous Control



| Parameter                                     | Description                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SOC Miscellaneous Control                     |                                                                                                                                                                                                                                       |
| ABL Console Out Control <sup>(Note)</sup>     | Enable/Disable the ConsoleOut function for ABL.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                         |
| ABL Console Out Serial Port <sup>(Note)</sup> | Options available: eSPI, SOC UART0, SOC UART1, Auto. Default setting is <b>Auto</b> .                                                                                                                                                 |
| ABL Console Out Serial Port IO                | Options available: 0x3F8, 0x2F8, 0x3E8, 0x2E8, Auto. Default setting is <b>Auto</b> .                                                                                                                                                 |
| ABL Serial port IO customized enabled         | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                                                                                                                                            |
| ABL Basic Console Out Control                 | Enable/Disable the Basic ConsoleOut function for ABL.<br>Options available: Disable, Enable, Auto. Default setting is <b>Auto</b> .                                                                                                   |
| ABL PMU message Control                       | To Control the total number of PMU debug messages.<br>Options available: Auto, Detailed debug message, Coarse debug message, Stage completion, Assertion messages, Firmware completion message only. Default setting is <b>Auto</b> . |
| ABL Memory Population message Control         | Options available: Warning message, Fatal error. Default setting is <b>Warning message</b> .                                                                                                                                          |

(Note) Advanced items are configurable when this item is defined.

| Parameter                    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PSP error injection support  | Options available: False, True. Default setting is <b>False</b> .                                                                                                                                                                                                                                                                                                                                                                                             |
| Firmware Anti-rollback (FAR) | <p>Press [Enter] for configuration of advanced items.</p> <ul style="list-style-type: none"> <li>◆ FAR enforcement state <ul style="list-style-type: none"> <li>– Default setting is <b>Enabled</b>.</li> </ul> </li> <li>◆ SPL value in the CPU Fuse</li> <li>◆ SPL value in the SPL table</li> <li>◆ FAR Switch <ul style="list-style-type: none"> <li>– Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b>.</li> </ul> </li> </ul> |
| SEC_I2C Voltage Mode         | Options available: Auto, 1.8V, 1.1V. Default setting is <b>Auto</b> .                                                                                                                                                                                                                                                                                                                                                                                         |

5-3-7 CXL Common Options



| Parameter                             | Description                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------|
| CXL Common Options                    |                                                                                               |
| CXL Control                           | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| CXL Physical Addressing               | Options available: Normalized address, System address, Auto. Default setting is <b>Auto</b> . |
| CXL Memory Attribute                  | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| CXL Encryption                        | Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                    |
| CXL DVSEC Lock                        | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| CXL HDM Decoder Lock on Commit        | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| Temp Gen5 Advertisement               | Options available: Disabled, Enabled, Auto. Default setting is <b>Auto</b> .                  |
| Sync Header Bypass                    | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |
| Sync Header Bypass Compatibility Mode | Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b> .                  |

| Parameter                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CXL RAS                   | <p>Press [Enter] for configuration of advanced items.</p> <ul style="list-style-type: none"> <li>◆ CXL Protocol Error Reporting <ul style="list-style-type: none"> <li>– Options available: Disabled, SameAsPcieAer, ForceAerFwFirstIfCxlPresent. Default setting is <b>SameAsPcieAer</b>.</li> </ul> </li> <li>◆ CXL Component Error Reporting <ul style="list-style-type: none"> <li>– Options available: Allow OS First, Force FW-First, Debug FW-First. Default setting is <b>Debug FW-First</b>.</li> </ul> </li> <li>◆ CXL Root Port Isolation <ul style="list-style-type: none"> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b>.</li> </ul> </li> <li>◆ CXL Root Port Isolation FW Notification. <ul style="list-style-type: none"> <li>– Options available: Auto, Enabled, Disabled. Default setting is <b>Auto</b></li> </ul> </li> </ul> |
| CXL Memory Online/Offline | <p>All 4 Plink sots support memory online/offline. Only slot4 of Amber supports hot plug CXL memory interleaving automatically disabled globally when this CBS is enabled.</p> <p>Options available: Enabled, Disabled. Default setting is <b>Disabled</b>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Override CXL Memory Size  | Options available: 32GB, 64GB, 128GB, Auto. Default setting is <b>Auto</b> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |




## 5-4 AMD PBS Menu

AMD PBS Option menu displays submenu options for configuring the function of AMD PBS. Select a submenu item, then press [Enter] to access the related submenu screen.



| Parameter               | Description                                                                                                                                                                                                                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AMD Variable Protection | Protect some AMD specific variables for CBS, PBS and AOD. If locked, some utilities like RU that modify variable at runtime do not work.<br>Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                                                                                  |
| RAS                     | Press [Enter] for configuration of advanced items.                                                                                                                                                                                                                                                                      |
| Range Encryption        | Press [Enter] for configuration of advanced items. <ul style="list-style-type: none"><li>◆ Range1/2/3/4/5/6/7<ul style="list-style-type: none"><li>– Configure the Range 1/2/3/4/5/6/7 Memory Base.</li><li>– Configure the Range 1/2/3/4/5/6/7 Memory Limit/Size.</li></ul></li><li>◆ Start Range Encryption</li></ul> |

### 5-4-1 RAS



| Parameter                        | Description                                                                                                                                     |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| RAS Periodic SMI Control         | Enable/Disable the Periodic SMI for polling [MCA Threshold] error.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> . |
| SMI Threshold                    | Configures the SMI Threshold value.                                                                                                             |
| SMI Scale                        | Configures the SMI Scale value.                                                                                                                 |
| SMI Scale Unit                   | Defines the unit of time scale.<br>Options available: millisecond, second, minute. Default setting is <b>millisecond</b> .                      |
| SMI Period                       | Configures the SMI Period.                                                                                                                      |
| GHES Notify Type                 | Selects the Notification type for deferred/ corrected errors.<br>Options available: Polled, SCI. Default setting is <b>Polled</b> .             |
| GHES UnCorr Notify Type          | Selects the Notification type for uncorrected errors.<br>Options available: Polled, NMI. Default setting is <b>NMI</b> .                        |
| PCIe GHES Notify Type            | Selects the Notification type for PCIe corrected errors.<br>Options available: Polled, SCI. Default setting is <b>Polled</b> .                  |
| PCIe UnCorr GHES Notify Type     | Selects the Notification type for PCIe uncorrected errors.<br>Options available: Polled, NMI. Default setting is <b>NMI</b> .                   |
| PCIe Root Port Corr Err Mask Reg | Initialize the PCIe AER Corrected Error Mask register of Root Port.                                                                             |

| Parameter                          | Description                                                                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PCIe Root Port UnCorr Err Mask Reg | Initialize the PCIe AER Uncorrected Error Mask register of Root Port.                                                                                                              |
| PCIe Root Port UnCorr Err Sev Reg  | Initialize the PCIe AER Uncorrected Error Severity register of Root Port.                                                                                                          |
| PCIe Device Corr Err Mask Reg      | Initialize the PCIe AER Corrected Error Mask register of PCIe device.                                                                                                              |
| PCIe Device UnCorr Err Mask Reg    | Initialize the PCIe AER Uncorrected Error Mask register of PCIe device.                                                                                                            |
| PCIe Device UnCorr Err Sev Reg     | Initialize the PCIe AER Uncorrected Error Severity register of PCIe device.                                                                                                        |
| CXL DP CIE Mask Enable             | Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                                                                                                          |
| DRAM Hard Post Package Repair      | This feature allows spare DRAM rows to replace malfunctioning rows via an in-field repair mechanism.<br>Options available: Disabled, Enabled. Default setting is <b>Disabled</b> . |
| HEST DMC Structure Support         | HEST DMC (Deferred Machine Check) Structure Support.<br>Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                                 |
| CXL Error Report Support           | Enable/Disable CXL Error Reporting.<br>Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                                                  |


## 5-5 Chipset Setup Menu

Chipset Setup menu displays submenu options for configuring the function of the North Bridge. Select a submenu item, then press <Enter> to access the related submenu screen.



| Parameter                | Description                                                                                                                    |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| PCIe Compliance Mode     | Options available: Off, On. Default setting is <b>Off</b> .                                                                    |
| Program All VR           | Enable/Disable program all VR on MB.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .              |
| Power Button 1s shutdown | Enable/Disable Press power button 1 sec shutdown.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> . |
| North Bridge             | Press [Enter] for configuration of advanced items.                                                                             |

5-5-1 North Bridge



| Parameter                                        | Description                                           |
|--------------------------------------------------|-------------------------------------------------------|
| North Bridge Configuration<br>Memory Information |                                                       |
| Total Memory                                     | Displays the total memory information.                |
| CPU 0/1 Information                              | Press [Enter] to view information related to CPU 0/1. |

## 5-6 Server Management Menu



| Parameter                              | Description                                                                                                                                    |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| FRB-2 Timer                            | Enable/Disable FRB-2 timer (POST timer).<br>Default setting is <b>Enabled</b> .                                                                |
| FRB-2 Timer timeout                    | Configures the FRB-2 Timer timeout.<br>Default setting is <b>20 minutes</b> .                                                                  |
| FRB-2 Timer Policy                     | Configures the FRB-2 Timer policy.<br>Options available: Do Nothing, Reset, Power Down, Power Cycle.<br>Default setting is <b>Do Nothing</b> . |
| OS Watchdog Timer                      | Enable/Disable OS Watchdog Timer function.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                       |
| OS Wtd Timer Timeout <sup>(Note)</sup> | Configures OS Watchdog Timer.<br>Options available: 5 minutes, 10 minutes, 15 minutes, 20 minutes.<br>Default setting is <b>10 minutes</b> .   |
| OS Wtd Timer Policy <sup>(Note)</sup>  | Configure OS Watchdog Timer Policy.<br>Options available: Do Nothing, Reset, Power Down, Power Cycle.<br>Default setting is <b>Reset</b> .     |
| Wait BMC Ready                         | Post wait BMC ready and reboot system.<br>Options available: Disabled, 2 minutes, 4 minutes, 6 minutes. Default setting is <b>2 minutes</b> .  |

(Note) This item is configurable when **OS Watchdog Timer** is set to **Enabled**.

| Parameter                      | Description                                |
|--------------------------------|--------------------------------------------|
| System Event Log               | Press [Enter] to configure advanced items. |
| View FRU Information           | Press [Enter] to view the FRU information. |
| BMC VLAN configuration         | Press [Enter] to configure advanced items. |
| BMC network configuration      | Press [Enter] to configure advanced items. |
| IPv6 BMC Network Configuration | Press [Enter] to configure advanced items. |

5-6-1 System Event Log




| Parameter                    | Description                                                                                                                                                                                  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enabling / Disabling Options |                                                                                                                                                                                              |
| SEL Components               | Change this item to enable or disable all features of System Event Logging during boot.<br>Options available: Disabled, Enabled. Default setting is <b>Enabled</b> .                         |
| Erasing Settings             |                                                                                                                                                                                              |
| Erase SEL                    | Choose options for erasing SEL.<br>Options available: No/Yes, On next reset/Yes, On every reset. Default setting is <b>No</b> .                                                              |
| When SEL is Full             | Choose options for reactions to a full SEL.<br>Options available: Do Nothing, Erase Immediately. Default setting is <b>Do Nothing</b> .                                                      |
| Custom EFI Logging Options   |                                                                                                                                                                                              |
| Log EFI Status Codes         | Enable/Disable the logging of EFI Status Codes (if not already converted to legacy).<br>Options available: Disabled, Both, Error code, Progress code. Default setting is <b>Error code</b> . |




### 5-6-2 View FRU Information

The FRU page is a simple display page for basic system ID information, as well as System product information. Items on this window are non-configurable.



(Note) The model name will vary depends on the product you purchased

### 5-6-3 BMC VLAN Configuration




| Parameter              | Description                                                                                                                                  |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| BMC VLAN Configuration |                                                                                                                                              |
| BMC VLAN ID            | Select to configure BMC VLAN ID. The valid range is from 0 to 4094. When set to 0, BMC VLAN ID will be disabled.                             |
| BMC VLAN Priority      | Select to configure BMC VLAN Priority. The valid range is from 0 to 7. When BMC VLAN ID is set to 0, BMC VLAN Priority will not be selected. |

## 5-6-4 BMC Network Configuration



| Parameter                         | Description                                                                                                                                                                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select NCSI and Dedicated LAN     | Options available: Do Nothing, Mode1 (Dedicated), Mode2 (NCSI), Mode3 (Failover). Default setting is <b>Mode3 (Failover)</b> .                                                                                                                                      |
| Lan Channel 1                     |                                                                                                                                                                                                                                                                     |
| Configuration Address source      | Selects to configure LAN channel parameters statically or dynamically (DHCP). Do nothing option will not modify any BMC network parameters during BIOS phase.<br>Options available: Unspecified, Static, DynamicBmcDhcp. Default setting is <b>DynamicBmcDhcp</b> . |
| Station IP address                | Displays IP Address information.                                                                                                                                                                                                                                    |
| Subnet mask                       | Displays Subnet Mask information.<br>Please note that the IP address must be in three digitals, for example, 192.168.000.001.                                                                                                                                       |
| Router IP address                 | Displays the Router IP Address information.                                                                                                                                                                                                                         |
| Station MAC address               | Displays the MAC Address information.                                                                                                                                                                                                                               |
| VLAN Support                      | Set BMC to enable/disable VLAN support.<br>Options available: Enabled, Disabled. Default setting is <b>Disabled</b> .                                                                                                                                               |
| Real-time get BMC network address | Press [Enter] will set LAN mode and Address source and then get IP, Subnet, Gateway and MAC address.                                                                                                                                                                |

5-6-5 IPv6 BMC Network Configuration



| Parameter                             | Description                                                                                                                                                                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPv6 BMC network configuration        |                                                                                                                                                                                                                                           |
| IPv6 BMC Lan Channel 1                |                                                                                                                                                                                                                                           |
| IPv6 BMC Lan Option                   | Enable/Disable IPv6 BMC LAN channel function. When this item is disabled, the system will not modify any BMC network during BIOS phase.<br>Options available: Unspecified, Disable, Enable. Default setting is <b>Enable</b> .            |
| IPv6 BMC Lan IP Address Source        | Selects to configure LAN channel parameters statically or dynamically (by BIOS or BMC).<br>Options available: Unspecified, Static, Dynamic-Obtained by BMC running DHCP. Default setting is <b>Dynamic-Obtained by BMC running DHCP</b> . |
| IPv6 BMC Lan IP Address/Prefix Length | Check if the IPv6 BMC LAN IP address matches those displayed on the screen.                                                                                                                                                               |






| Parameter      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Key Management | <p>Press [Enter] to configure advanced items.</p> <p><b>Please note that this item is configurable when Secure Boot Mode is set to Custom.</b></p> <ul style="list-style-type: none"> <li>◆ Factory Key Provision <ul style="list-style-type: none"> <li>– Allows to provision factory default Secure Boot keys when system is in Setup Mode.</li> <li>– Options available: Enabled, Disabled. Default setting is <b>Disabled</b>.</li> </ul> </li> <li>◆ Restore Factory Keys <ul style="list-style-type: none"> <li>– Installs all factory default keys. It will force the system in User Mode.</li> <li>– Options available: Yes, No.</li> </ul> </li> <li>◆ Enroll Efi Image <ul style="list-style-type: none"> <li>– Press [Enter] to enroll SHA256 hash of the binary into Authorized Signature Database (db).</li> </ul> </li> <li>◆ Secure Boot variable <ul style="list-style-type: none"> <li>– Displays the current status of the variables used for secure boot.</li> </ul> </li> <li>◆ Platform Key (PK) <ul style="list-style-type: none"> <li>– Displays the current status of the Platform Key (PK).</li> <li>– Press [Enter] to configure a new PK.</li> <li>– Options available: Update.</li> </ul> </li> <li>◆ Key Exchange Keys (KEK) <ul style="list-style-type: none"> <li>– Displays the current status of the Key Exchange Key Database (KEK).</li> <li>– Press [Enter] to configure a new KEK or load additional KEK from storage devices.</li> <li>– Options available: Update, Append.</li> </ul> </li> <li>◆ Authorized Signatures (DB) <ul style="list-style-type: none"> <li>– Displays the current status of the Authorized Signature Database.</li> <li>– Press [Enter] to configure a new DB or load additional DB from storage devices.</li> <li>– Options available: Update, Append.</li> </ul> </li> <li>◆ Forbidden Signatures (DBX) <ul style="list-style-type: none"> <li>– Displays the current status of the Forbidden Signature Database.</li> <li>– Press [Enter] to configure a new dbx or load additional dbx from storage devices.</li> <li>– Options available: Update, Append.</li> </ul> </li> <li>◆ Authorized TimeStamps (DBT) <ul style="list-style-type: none"> <li>– Displays the current status of the Authorized TimeStamps Database.</li> <li>– Press [Enter] to configure a new DBT or load additional DBT from storage devices.</li> <li>– Options available: Update, Append.</li> </ul> </li> <li>◆ OsRecovery Signatures <ul style="list-style-type: none"> <li>– Displays the current status of the OsRecovery Signature Database.</li> <li>– Press [Enter] to configure a new OsRecovery Signature or load additional OsRecovery Signature from storage devices.</li> <li>– Options available: Update, Append.</li> </ul> </li> </ul> |

## 5-8 Boot Menu

The Boot menu allows you to set the drive priority during system boot-up. BIOS setup will display an error message if the legacy drive(s) specified is not bootable.




| Parameter                   | Description                                                                                                                                         |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Boot Configuration          |                                                                                                                                                     |
| Setup Prompt Timeout        | Number of seconds to wait for setup activation key. 65535 (0xFFFF) means indefinite waiting.<br>Press the numeric keys to input the desired values. |
| Bootup NumLock State        | Enable/Disable the Bootup NumLock function.<br>Options available: On, Off. Default setting is <b>On</b> .                                           |
| Quiet Boot                  | Enable/Disable showing the logo during POST.<br>Options available: Enabled, Disabled. Default setting is <b>Enabled</b> .                           |
| Setup Flash                 | Press [Enter] to run setup flash.                                                                                                                   |
| Dump full Setup Data        | Press [Enter] to dump full setup data to file.                                                                                                      |
| Dump non-default Setup Data | Press [Enter] to dump non-default setup data to file.                                                                                               |
| Restore Setup Data          | Press [Enter] to restore setup data from file (cJson format).                                                                                       |
| Fast Boot                   | Options available: Disabled, Enabled. Default setting is <b>Disabled</b> .                                                                          |



| Parameter                          | Description                                                                                                                                                                                                                                                                                        |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FIXED BOOT ORDER Priorities        |                                                                                                                                                                                                                                                                                                    |
| Boot Option #1 / #2 / #3 / #4 / #5 | <p>Press [Enter] to configure the boot priority.<br/>By default, the server searches for boot devices in the following sequence:</p> <ol style="list-style-type: none"> <li>1. Hard drive.</li> <li>2. CD-COM/DVD drive.</li> <li>3. USB device.</li> <li>4. Network.</li> <li>5. UEFI.</li> </ol> |
| UEFI NETWORK Drive BBS Priorities  | Press [Enter] to configure the boot priority.                                                                                                                                                                                                                                                      |
| UEFI Application Boot Priorities   | Press [Enter] to configure the boot priority.                                                                                                                                                                                                                                                      |

# 5-9 Save & Exit Menu

The Save & Exit menu displays the various options to quit from the BIOS setup. Highlight any of the exit options then press <Enter>.



| Parameter                               | Description                                                                                                                                                                                                                                                                                                                        |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Save Options                            |                                                                                                                                                                                                                                                                                                                                    |
| Save Changes and Exit                   | Saves changes made and closes the BIOS setup.<br>Options available: Yes, No.                                                                                                                                                                                                                                                       |
| Discard Changes and Exit                | Discards changes made and exits the BIOS setup.<br>Options available: Yes, No.                                                                                                                                                                                                                                                     |
| Save Changes                            | Saves changes done so far to any of the setup options.<br>Options available: Yes, No.                                                                                                                                                                                                                                              |
| Default Options                         |                                                                                                                                                                                                                                                                                                                                    |
| Restore Defaults                        | Loads the default settings for all BIOS setup parameters. Setup Defaults are quite demanding in terms of resources consumption. If you are using low-speed memory chips or other kinds of low-performance components and you choose to load these settings, the system might not function properly.<br>Options available: Yes, No. |
| Boot Override                           | Press [Enter] to configure the device as the boot-up drive.                                                                                                                                                                                                                                                                        |
| Launch EFI Shell from filesystem device | Attempts to Launch EFI Shell application (Shell.efi) from one of the available file system devices.                                                                                                                                                                                                                                |

# 5-10 BIOS Recovery

The system has an embedded recovery technique. In the event that the BIOS becomes corrupt the boot block can be used to restore the BIOS to a working state. To restore your BIOS, please follow the instructions listed below:

Recovery Instruction:

- 1. Copy the XXX.rom to USB diskette.
- 2. Setting BIOS Recovery jump to enabled status.
- 3. Boot into BIOS recovery.
- 4. Run Proceed with flash update.
- 5. BIOS updated.

