

Characteristic:

Safety lock buckle, easy installation, cable output

Product picture printing is for reference only,
subject to the actual product

Technical index:

- Mounting type: Free hanging (In-Line)
- Material of core: Ferrite
- Applicable standards: GB20840-2014
- Operating temperature: -25℃ ~ +60℃
- Storage temperature: -30℃ ~ +90℃
- Frequency range: 50Hz-1KHz
- Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
- Output/Housing AC 3.5KV/1min 50Hz



Electrical parameters:The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

	SCT013-005	SCT013-010	SCT013-015	SCT013-020	SCT013-025	SCT013-030	SCT013-050	SCT013-060	SCT013-100		Specification of cable: 2 x 0.2mm² two core shielded cable Length of cable:100cm~105cm
Rated input	5A	10A	15A	20A	25A	30A	50A	60A	100A	A	TVS: Transient Voltage Suppressor (7.5V) Voltage output type The secondary is not allowed to short circuits
Rated output	1									V	
Accuracy	1									%	
Weight	50 g									g	

	5A	10A	15A	20A	25A	30A	50A	60A	100A	A	Specification of cable: 2 x 0.2mm² two core shielded cable Length of cable:100cm~105cm
Rated input	5A	10A	15A	20A	25A	30A	50A	60A	100A	A	TVS: Transient Voltage Suppressor (7.5V) Voltage output type The secondary is not allowed to short circuits
Rated output	0.333									V	
Accuracy	1									%	
Weight	50 g									g	

SCT013-000			Specification of cable: 2 x 0.2mm² two core shielded cable Length of cable:100cm~105cm
Rated input	100A	A	TVS: Transient Voltage Suppressor (7.5V) Current output type The secondary is not allowed to open circuit
Rated output	50	mA	
Turns ratio	1:2000	—	
Sampling resistance	10	Ω	
Accuracy	1	%	
Weight	50 g	g	

Dimensions(in mm±0.5) :



