

|              |                        |                          |
|--------------|------------------------|--------------------------|
| RANGE        | INLINE 4000 SERIES     |                          |
| TEMPERATURE  | AMBIENT                |                          |
| MODEL        | IN-4A15-SQ-FF-IC       | IN-4A15-SQ-SD-IC         |
| FRONT        | SQUARE/<br>FIXED FRONT | SQUARE/<br>SLIDING DOORS |
| INSTALLATION | IN-COUNTER             |                          |
| HEIGHT       | 996mm                  |                          |
| WIDTH        | 1503mm                 |                          |
| DEPTH        | 778mm                  |                          |

CORE PRODUCT TEMPERATURE

AMBIENT

## FEATURES

### High energy efficiency: 0.09 kWh per hour (average)

- Cabinet operating at ambient temperature
- Smart display with toughened safety glass encased in brushed stainless steel frame

### Fixed Front or Sliding Doors Ambient Display

-  Three tiltable, height-adjustable stainless steel shelves and base are full cabinet width to support maximum display capacity
-  50,000 hour LED lighting system at 2758 lumens per metre in cabinet top and to each shelf
- Unique shelf mounted ticket strip front and rear: 30mm

### Operational Excellence

-  Sliding doors (staff side) and fixed front or sliding doors options (customer side)
-  Constructed from stainless and mild steel for durability with toughened safety glass and double-glazed end panels
- Fan assisted air circulation to mitigate heat build-up
- Designed to be installed into joinery



Showing : Inline 4000 Series ambient 1500mm square in-counter fixed front

## OPTIONS & ACCESSORIES

Contact a [FPG Sales Representative](#) for our full range, including:

- Shelf trays: Toughened safety glass or mild steel. Colour and woodprint options available for steel shelf trays
- Angled base insert
- Branded decals
- Rear door or end glass mirror application
- Forward-facing controls
- Thermal divider panels
- Custom joinery solution



Please contact FPG to discuss your requirements for meeting country-specific standards.

### AMBIENT DATA

| MODEL            | CORE PRODUCT TEMPERATURE |
|------------------|--------------------------|
| IN-4A15-SQ-XX-IC | Ambient                  |

### ELECTRICAL DATA

| MODEL            | VOLTAGE   | PHASE  | CURRENT | E24H (kW/h) | kWh per hour (average) | IP RATING | MAINS                 |                              | LED LIGHTING |                |         |
|------------------|-----------|--------|---------|-------------|------------------------|-----------|-----------------------|------------------------------|--------------|----------------|---------|
|                  |           |        |         |             |                        |           | CONNECTION            | CONNECTION PLUG <sup>1</sup> | HOURS        | LUMENS         | COLOUR  |
| IN-4A15-SQ-XX-IC | 220-240 V | Single | 0.39 A  | 2.2         | 0.09                   | IP 20     | 3 metre, 3 core cable | 10 amp, 3 pin plug           | 50,000       | 2758 per metre | Natural |

<sup>1</sup>Please advise country to change plug specification.

### CAPACITY, ACCESS & CONSTRUCTION

| MODEL            | DISPLAY AREA       | LEVELS           | ACCESS FRONT  | ACCESS REAR   | CHASSIS CONSTRUCTION         |
|------------------|--------------------|------------------|---------------|---------------|------------------------------|
| IN-4A15-SQ-FF-IC | 2.8 m <sup>2</sup> | 3 Shelves + Base | Fixed front   | Sliding doors | Stainless 304 and mild steel |
| IN-4A15-SQ-SD-IC | 2.8 m <sup>2</sup> | 3 Shelves + Base | Sliding doors | Sliding doors | Stainless 304 and mild steel |


### DIMENSIONS

| MODEL            | H x W x D mm (Uncrated) | MASS (Uncrated) |
|------------------|-------------------------|-----------------|
| IN-4A15-SQ-XX-IC | 996 x 1503 x 778        | - kg            |


Crated weights and dimensions vary. Please contact us for information on your shipment.

#### Installation note:


Model cutout dimensions: IN-4A15-SQ-XX-IC models require 1475 x 755mm benchtop cutout (see product manual for installation guide). When installing this cabinet next to an adjacent Inline 4000 Series refrigerated cabinet, please install an Inline 4000 Series thermal divider panel (accessory) between them.




PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at [sales@fpgworld.com](mailto:sales@fpgworld.com) or visit [www.fpgworld.com](http://www.fpgworld.com) for full contact details for your region.

Worldwide  
contact  
details:

