



724-283-4681

SALES.BWIEAGLE@CATTRON.COM

PRODUCT GUIDE

CONTACT INPUT TRANSMITTERS

Click on the links to view detailed product information.



SINGLE CHANNEL / SINGLE DRY CONTACT INPUT

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	36-10100-AC	441-10100-AC	-
9-36VDC	36-10100-DC	441-10100-DC	-



THREE CHANNEL / THREE DRY CONTACT INPUTS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	-	-	461-1000-AC
9-36VDC	-	-	461-1000-DC



FOUR CHANNEL / FOUR DRY CONTACT INPUTS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	36-1400-AC	441-1400-AC	461-1400-AC
9-36VDC	36-1400-DC	441-1400-DC	461-1400-DC
3VDC Battery	36-1400-BAT	441-1400-BAT	-

Learn more about BWI Eagle solutions at bwieagle.com.



CONTACT INPUT TRANSMITTERS

Click on the links to view detailed product information.



FOUR CHANNEL INCLUDING STOP / FOUR DRY CONTACT INPUTS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	36-1200-AC	441-1200-AC	461-1200-AC
9-36VDC	36-1200-DC	441-1200-DC	461-1200-DC
3VDC Battery	36-1200-BAT	441-1200-BAT	-



EIGHT CHANNEL / EIGHT DRY CONTACT INPUTS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	36-1800-AC	441-1800-AC	461-1800-AC
9-36VDC	36-1800-DC	441-1800-DC	461-1800-DC



TWENTY CHANNEL / TWENTY DRY CONTACT INPUTS

	600 foot range 2.4 GHz	Up to 2 miles 900 MHz	Up to 10 miles 900 MHz
100-250VAC	36-12000-120VAC	441-12000-120VAC	-
9-36VDC	36-12000-DC	441-12000-DC	-

**Operating ranges may require high-gain antennas and repeaters.

Learn more about BW Eagle solutions at bwieagle.com

