


2CH Smart Switch

Model: 2CH12VSJ02CS

Model: 2CH12VSJ02CSRF



Parameters:

Input voltage: DC/AC 7~32V/microusb 5V
Max.Current:2200W/10A

Wi-Fi Standard:Wi-Fi 2.4ghz b/g/n+BLE

Working temperature: -20°C~70°C

Size: 116*38*25mm


Checklist before using the device

- Your smart phone or tablet has connected to a 2.4g WiFi with internet.
- You need to enable Bluetooth of the phone.
- You have the correct WiFi PWD.

- You smart phone or tablet must have access to APP store,Google play.
- Your router is MAC-open.

User Guide


- 1 Start with "EWelink" APP.



- 2 Register an EWlink account.
- 3 If you have EWelink account,just login.

- 4 Power up.

ON/OFF operating principle:
The connected appliances work/stop through live wire power on/off.



self-locking 1



self-locking 2



Add device flow to mobile APP

- 1 After installation,power the device,hold down the Reset button(pairing button) for 6 seconds until Network indicator(red light) blinks quickly (blinking twice and on)
- 2 Open ewelink app, click + on the upper right corner, and then click on "Add Device."
- 3 Select your WiFi, enter the WiFi password, and click "Next."

- 4 Wait for a few seconds, and when the device is found, click +.




- 5 After successful addition, click "Next"



Inching /interlock Switch

- 1、Click switch name.




- 2、Click ... , select "setting" .



- 3-1、Set inching duration:Click "inching Settings" , set inching duration.



- 3-2、Enable the interlock:Click "interlock" , set the interlock.



Remote control pairing/Clear code

Matching:

- 1 Hold RF Pairing button you want to pair for 3 seconds ,until the blue light is on.
- 2 Then long press the remote control buttons you to pair.
- 3 Loosen the remote control buttons,pairing success.

* note: Pair Other buttons,repeat steps ①~③.

Clear code:

Long press the RF pairing button you want to clear for 15 seconds until RF pairing indicator(blue light) is off loosen the RF Pairing button.

* note: the pairing/clear code method is only available with RF function switch/module reference.

TROUBLESHOOTING

Solutions for the failure of product matching and offline:

Enter the homepage of App,click the icon in the lower right corner of the interface to enter.

"Message" >hits" Guide" . "Profile" >hits" Ewelink support"



If none of the above is resolved,please open it with another phone.Personal hotspot,try to readd.