

The MP pellet Thermo firebox can satisfy every need as regards delivery of hot water, ensuring perfect warmth and comfort in the home, thanks to the high heat exchange rating of the boiler.

MP 973 TH ACS



GENERAL FEATURES

- Heating: hot water production
- Structure: coated steel with closed firebox
- Firebox: steel and Aluker®
- Boiler: high thickness steel from 3 to 5 mm, weight 150 kg
- Brazier: refractory steel
- Opening: door in cast iron, self-cleaning ceramic glass resistant to 750°C
- Handle: concealed detachable handle
- Function control: remote control with LCD display and Digital Control Panel on the one-piece firebox
- Timer-controlled thermostat with programming: 6 daily time frames
- Standard flue outlet position: left-hand side
- Power adjustment: automatic with 16 levels depending on the set temperature
- Domestic hot water: as standard feature
- Fuel: pellets
- Combustion air kit: optional

TECHNICAL DETAILS

- Energy efficiency class A+ (G → A++)
- Max operating pressure bar 1.5
- 3-bar safety discharge valve Ø 3/4"
- Heat system delivery Ø 3/4"
- Heat system return Ø 3/4"
- Tank capacity kg 65
- Weight kg 278,5
- Standard flue outlet Ø mm 10
- Model MP 973 TH ACS

