



30 Gallon – HONDA Powered Truckmount Air Compressor

FEATURES & BENEFITS

- HONDA GX160 OHV gas engine
 - Overhead valve (OHV) for increased efficiency and optimal power transfer
 - Equipped with low oil shutdown feature
 - Automatic idle control reduces engine RPM when the demand for air in the tank is met
- Oil lubricated twin cylinder pump features
 - Cast iron crankcase
 - Aluminum head and valve plate to maximize heat dissipation
 - Poly-v pulley & drive belt provides smooth operation with less vibration and longer life
 - Oil level sight glass and easily accessible oil fill
 - High efficiency aluminum flywheel provides maximum air flow
 - Sturdy metal belt guard provides optimal protection to drive system
- Isolated platform design absorbs engine & pump vibration
- Large 3/4" NPT air outlet port provided on both the right and left sides for customer choice to plumb air line
- 175 PSI max pressure for optimum tool performance
- Perfect for service truck and field service applications – permanently mount to a truck bed for easy access to compressed air when electricity is not available

POWERED by
HONDA

MODEL SPECIFICATIONS

Tank Size:	30 Gallon ASME*
Maximum Pressure:	175 PSI
SCFM @ 40 PSI:	13.2
SCFM @ 90 PSI:	11.0
Engine cc:	163 cc
Engine Type:	Honda GX160
Limited Warranty:	2 Year Pump 1 Year All Other Parts
Model Number:	DXCMH5593011
UPC Number:	0 45564 65547 1



Dimensions: 58" x 32" x 53" • Weight: 267 lbs. • Pallet Qty: 1 • Truckload Qty: 28 (53' trailer)

 ASME – American Society of Mechanical Engineers

Product style and configuration may vary.