

K	技术要求： 1. 尺寸:展开594*100mm, 折后54*100mm 2. 材质:105g铜板 3. 颜色:四色印刷 4. 工艺:手风琴11折页 5. 环保要求: 所有材料及工艺需满足欧盟WEEE和RoHS指令要求	<table><tr><th colspan="2">原材料</th><th colspan="2">PC, 松诺白色</th></tr><tr><th>测试项</th><th>测试要求</th><th>测试项</th><th>测试要求</th></tr><tr><td>☒ RoHS检测</td><td>第三方认证报告 (有效期一年)</td><td>☐ 低温存储 (-40℃)</td><td></td></tr><tr><td>☐ 球压试验 (125℃/70℃)</td><td></td><td>☐ 冷热冲击 (-40~70℃)</td><td></td></tr><tr><td>☐ 灼热丝试验 (850℃/650℃)</td><td></td><td>☐ 百格测试</td><td></td></tr><tr><td>☐ UV老化测试 (72H/48H)</td><td></td><td>☐ RCA试验 (100圈/150圈..)</td><td></td></tr><tr><td>☐ 冰醋酸测试 (3min/5min)</td><td></td><td>☐ 铅笔硬度测试 (3H/4H..)</td><td></td></tr><tr><td>☐ 盐雾试验 (24/36/48H..)</td><td></td><td>☐ 酒精耐摩擦测试</td><td></td></tr><tr><td>☐ 高温存储 (70℃)</td><td></td><td>☐ 镭雕/丝印附着力测试</td><td></td></tr><tr><td>☒</td><td></td><td>☐</td><td></td></tr></table>	原材料		PC, 松诺白色		测试项	测试要求	测试项	测试要求	☒ RoHS检测	第三方认证报告 (有效期一年)	☐ 低温存储 (-40℃)		☐ 球压试验 (125℃/70℃)		☐ 冷热冲击 (-40~70℃)		☐ 灼热丝试验 (850℃/650℃)		☐ 百格测试		☐ UV老化测试 (72H/48H)		☐ RCA试验 (100圈/150圈..)		☐ 冰醋酸测试 (3min/5min)		☐ 铅笔硬度测试 (3H/4H..)		☐ 盐雾试验 (24/36/48H..)		☐ 酒精耐摩擦测试		☐ 高温存储 (70℃)		☐ 镭雕/丝印附着力测试		☒		☐		<table><tr><th colspan="4">指定公差等级</th></tr><tr><th>尺寸</th><th>等级</th><th>A</th><th>B</th><th>C</th></tr><tr><td>0<L≤3</td><td></td><td>±0.05</td><td>±0.10</td><td>±0.15</td></tr><tr><td>3<L≤6</td><td></td><td>±0.10</td><td>±0.15</td><td>±0.20</td></tr><tr><td>6<L≤16</td><td></td><td>±0.15</td><td>±0.25</td><td>±0.35</td></tr><tr><td>16<L≤30</td><td></td><td>±0.20</td><td>±0.30</td><td>±0.45</td></tr><tr><td>30<L≤120</td><td></td><td>±0.25</td><td>±0.35</td><td>±0.50</td></tr><tr><td>120<L≤315</td><td></td><td>±0.30</td><td>±0.50</td><td>±0.80</td></tr><tr><td>0<L≤10</td><td>±1°</td><td>50<L≤120</td><td>±0.5°</td><td></td></tr><tr><td>10<L≤50</td><td>±0.3°</td><td>120<L≤400</td><td>±0.15°</td><td></td></tr></table>	指定公差等级				尺寸	等级	A	B	C	0<L≤3		±0.05	±0.10	±0.15	3<L≤6		±0.10	±0.15	±0.20	6<L≤16		±0.15	±0.25	±0.35	16<L≤30		±0.20	±0.30	±0.45	30<L≤120		±0.25	±0.35	±0.50	120<L≤315		±0.30	±0.50	±0.80	0<L≤10	±1°	50<L≤120	±0.5°		10<L≤50	±0.3°	120<L≤400	±0.15°		制图日期	黎业军 2024/08/30	审核日期	批准日期	物料编码:	单位	比例	图框
			原材料		PC, 松诺白色																																																																																															
			测试项	测试要求	测试项	测试要求																																																																																														
			☒ RoHS检测	第三方认证报告 (有效期一年)	☐ 低温存储 (-40℃)																																																																																															
☐ 球压试验 (125℃/70℃)		☐ 冷热冲击 (-40~70℃)																																																																																																		
☐ 灼热丝试验 (850℃/650℃)		☐ 百格测试																																																																																																		
☐ UV老化测试 (72H/48H)		☐ RCA试验 (100圈/150圈..)																																																																																																		
☐ 冰醋酸测试 (3min/5min)		☐ 铅笔硬度测试 (3H/4H..)																																																																																																		
☐ 盐雾试验 (24/36/48H..)		☐ 酒精耐摩擦测试																																																																																																		
☐ 高温存储 (70℃)		☐ 镭雕/丝印附着力测试																																																																																																		
☒		☐																																																																																																		
指定公差等级																																																																																																				
尺寸	等级	A	B	C																																																																																																
0<L≤3		±0.05	±0.10	±0.15																																																																																																
3<L≤6		±0.10	±0.15	±0.20																																																																																																
6<L≤16		±0.15	±0.25	±0.35																																																																																																
16<L≤30		±0.20	±0.30	±0.45																																																																																																
30<L≤120		±0.25	±0.35	±0.50																																																																																																
120<L≤315		±0.30	±0.50	±0.80																																																																																																
0<L≤10	±1°	50<L≤120	±0.5°																																																																																																	
10<L≤50	±0.3°	120<L≤400	±0.15°																																																																																																	
00.00.07.0155	MM	1:1	/																																																																																																	
	投影																																																																																																			
	视角																																																																																																			
图号	第1/1页																																																																																																			
版本	V1.5																																																																																																			
L									物料名称:	iFan04系列 快速指南																																																																																										