



MATERIAL FACT SHEET

719958 RCBO-C20/3N/30mA-A

General Data

Product Hierarchy	IAN40202
	RCCB
	E-RCBO
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000719958

FA-MDRC: RCBO

Series	MODULAR DIN RAIL COMPONENTS
Type	RCBO
Rated Current (A)	20
Rated Voltage (V)	240
Current Type	AC
Number of Poles	3+N
Instantaneous Tripping	TYPE C
Breaking Capacity at 415V (kA)	IEC/EN 61009: 4,5
Cycles with Rated Current	4000
Cycles without Rated Current	10000
Rated Current Sensibility (mA)	30
Pulsating Current Sensibility	AC AND PULSATING DC
Compliant with Standard(s)	EC/EN 61009
Compliant with Standard(s) (2)	EN 45545-2
Compliant with Standard(s) (3)	IEC 61373
Compliant with Standard(s) (4)	IEC/EN 60479-2

Product Dimensions & Weight

Width (mm)	70
Height (mm)	75,5
Depth (mm)	80
Weight (kg)	0,445

Logistic Dimensions & Gross Weight

Length (cm)	8,5
Width (cm)	7,5
Height (cm)	7,5
Gross Weight (kg)	0,481
Volume (cdm)	0,478

Stock Data

Planned Delivery Time (Days)	45
------------------------------	----

Life Cycle

Sales Start	01.09.2024
Predecessor	No Predecessor

Additional Product Information

Battery included	NO
------------------	----

Export Data

Commodity Code	85361050
Legal Control (Dual Use List)	Not Listed
Country of Origin	Romania (RO)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
RoHS Compliance	COMPLIANT

Conformity

CE	COMPLIANT
EAC	NON-COMPLIANT

Documentation & Media Data

Certificates URL Indicator	X
----------------------------	---

Product Packaging

Cardboard (g)	0
Other paper (g)	22,50
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0