

EN X-TOUCH MINI RX MIDI DATA

EN This RX MIDI data table shows what can get controlled and changed from outside (via MIDI receive) independent of the X-TOUCH editor software.

ES Esta tabla de datos RX MIDI le indica qué puede controlar y modificar desde el exterior (a través de datos MIDI recibidos) independientemente del programa editor X-TOUCH.

FR Ce tableau de données RX MIDI indique les fonctions pouvant être contrôlées et modifiées de manière externe (par réception de messages MIDI) indépendamment de l'éditeur X-TOUCH.

DE Diese RX MIDI-Datentabelle zeigt, was man unabhängig von der X-TOUCH Editorsoftware von außen (via MIDI Receive) steuern und ändern kann.

PT Esta tabela de dados RX MIDI mostra o que pode ser controlado e modificado de fora (através de MIDI receive) independentemente do software editor X-TOUCH.

Function	RX CH	RX Command	RX value
Operation Mode Select	GLOBAL CH	CC 127	0 = Standard Mode → MC mode LED off 1 = MC Mode → MC mode LED on 2-127 = ignored
Preset Layer Change	GLOBAL CH	Program Change	ONLY in Standard mode (see above): 0 = Layer A → A-button LED on 1 = Layer B → B-button LED on 2-127 = ignored
LED Ring Behavior Change	GLOBAL CH	Encoders 1-8: CC 1 – CC 8	0 = Single 1 = Pan 2 = Fan 3 = Spread 4 = Trim 5-127 = ignored
LED Ring Remote Control (Value Change)	GLOBAL CH	Encoders 1-8: CC 9 – CC 16	0 = all LEDs off 1-13 = LEDs 1 (left) – 13 (right) on 14-26 = LEDs 1 (left) – 13 (right) blinking 27 = all LEDs on 28 = all LEDs blinking 29-127 = ignored
Buttons LED Remote Control	GLOBAL CH	Upper Row 1-8: Note 0 – Note 7 Lower Row 9-16: Note 8 – Note 15 Layer A, B LEDs: Not assignable ; only 1 of 2 LEDs lights if Standard mode selected (see above "Preset Layer Change")	0 = LED off 1 = LED on 2 = LED blinking 3-127 = ignored

Specifications

Computer Connection	
USB 2.0	connector type Mini-B
Controls	
Rotary/Push controls with LED collar	8
Buttons with LED backlight	16
Fader, 60 mm	1
Presets (*user programmable)	A*, B*, MC mode
Power Supply	
Voltage	5 V
Power consumption (maximum)	1.26 W
Power source	USB powered
Dimensions/Weight	
Dimensions (H x W x D)	47.0 x 325.0 x 102.0 mm (1.9 x 12.8 x 4")
Weight	0.5 kg (1.1 lbs)