

# MPower Bank KENERGIPOD20R1



**User Manual** 



www.zebronics.com

Thank you for purchasing **ZEB-EnergiPod 20R1** power bank. Please read this user manual carefully before operation & save this user manual for future reference.

#### Note:

- Avoid the use of this product in high-temperature and high-humidity environments.
- Avoid the self-disassembling of the product or it will result in voiding the Product's warranty.
- Please charge the product with a power adapter output rated TYPE C (DC 5V/3A, DC 9V/3A, DC 12V/3A, 15V/2.3A, 20V/1.75A)
- To know more about Terms and conditions for warranty policy, please visit

https://zebronics.com/pages/warranty-policy

**Caution:** There is a risk of explosion if the product is disposed in the fire.

#### Features:

Dual Type-C and single USB-A Output
Rapid Charge
LED indicator
Mobile/Tablet Compatible
PD 3.0 Type C Input & Output Ports
Over Charge Protection
Overload Protection
Short Circuit Protection
35W(Max.) Output
Metal body

Specifications:

Battery Capacity : 20000mAh

Type-C Input : DC 5V/3A 9V/3A 12V/3A

15V/2.3A 20V/1.75A

Output 1 & 2

(TYPE C) : DC 5V/3A 9V/3A 12V/3A

15V/2.3A 20V/1.75A,

5~16V/2.2A PPS

Output 3 (USB) : DC 5.5V/4A, 5V/3A, 9V/2.22A,

12V/1.67A

(35 W max. output)

No.of Output port :1 USB-A + 2 Type C PD 3.0

Charging Time : 4 hours (Approx)

Product Dimension

 $(W \times D \times H)$  : 6.7 x 2.8 x 14.2 cm

Net Weight : 455g

Country of Origin : Made in India

### **Package Contents**

PowerBank :1U

Charging Cable :1 U QR Code Guide :1 U

#### **Product Representation:**




## Charging the Power Bank:

• Connect the Type C end of the charging cable to the power bank and the USB end to the charger or adapter with a Type C (DC 5V/3A, DC 9V/3A, DC 12V/3A, 15V/2.3A, 20V/1.75A) cable.

#### Charging your Device with the Power Bank:

• Connect the Type C/micro USB end of the charging cable to the device and the USB/Type C end to the output ports of the power bank.

Alternatively, connect directly using the included attached Type-C cable.



[Note: Simultaneous usage of the power bank output provides standard 5V DC output]

ISO 9001:2015 Certified Company www.zebronics.com