

Huawei AirPresence Key

Intelligent Wireless Sharing Assistant

Huawei AirPresence Key is an intelligent wireless sharing appliance that can be used with Huawei TEX0 video endpoints. When inserted into the computer's USB interface, the AirPresence Key enables wireless content sharing without any connection. It is a good assistant to share screen, document, and media files during your meetings.



Share



Compatible



HD



Secure



Plug-and-Play, One Key to Share

- Only requires the connection between the AirPresence key and the PC's USB interface.
- One key to share the contents with adaptive resolution.



Multi-terminal Login, Both Windows and MAC Compatible

- Single endpoint supports simultaneous log in of multiple AirPresence keys*.
- Compatible with dual systems: Windows and MAC.



Real Presence, Vivid and Clear

- Delivers 1080p high-definition images, smooth and vivid.
- Ability to send audio files while sharing images.



Professional technologies, Secure and Reliable

- 2.4 GHz/5 GHz dual-band Wi-Fi, more stable connection.
- Data is encrypted over HTTPS, ensuring secure transmission.



Huawei AirPresence Key

Technical Specifications

Compatibility	
Endpoints	Designed for use with Huawei TEX0 HD videoconferencing endpoints
Operating Systems	Windows: Windows7/8/8.1/10, 32 and 64 bits MAC: OSX 10.10/10.11/10.12 (Sierra)
Video Resolution	
PC Screen	640 × 480, 800 × 600, 1024 × 640, 1024 × 768, 1152 × 864, 1280 × 600, 1280 × 720, 1280 × 768, 1280 × 800, 1280 × 960, 1280 × 1024, 1360 × 768, 1366 × 768, 1400 × 1050, 1440 × 900, 1600 × 900, 1600 × 1200, 1680 × 1050, 1920 × 1080, 1920 × 1200, 2304 × 1440, 2560 × 1600, 2880 × 1800
Endpoint	1080p 60/50/30/25/24fps, 720p 60/50fps
Local Screen	Windows: 720p 30fps/1080p 25fps MAC: 720p 30fps/1080p 15fps
Optional Mode	Clear mode(default) : Up to 1080p 25fps Smooth mode: Up to 720p 30fps
Audio Features	
Local Audio**	With TE10: 16K dual-channel lossless audio playback With TE20: 48K dual-channel lossless audio playback
Shared Audio**	Share audio can be played at remote sites
Security and Reliability	
Connect Distance	≤20m
Share Delay	≤180ms
Data Security	HTTPS Encryption
Wireless	
Protocols***	<ul style="list-style-type: none">• 802.11 a/b/g/n/ac• 2.4GHz and 5GHz(default)
Mode	<ul style="list-style-type: none">• Client
Authentication	OPEN, SHAERD, WPS, WPA-PSK, and WPA2-PSK
Maintenance	
Log	Supports software log and device log collection
Upgrade	Automatic upgrade while connected with TEX0
Ports	
USB Port	1 x USB 2.0 device type A port, high-speed (HS) mode enabled, compatible with USB3.0 HUB
Physical Specifications	
Dimensions (H x W x D)	Product dimensions: 162mm x 59.6mm x 18.5mm Package dimensions: 199mm x 94.5mm x 28mm
Weight	Net weight: 75g Gross weight: 160g
Electricity Supply Requirements	Working voltage: 5V DC Maximum power consumption: 2W
Environmental requirements	Working temperature: 0℃ to 40℃ Storage temperature: -40℃ to +70℃ Relative humidity(Working state): 10% to 80% Relative humidity(Non-working state): 0% to 95%
Certification	CE (RoHS, REACH) , FCC, RCM, VCCI, IC, and Radio Type Approval Certification(CMIIT)

*: Only one AirPresence Key can be connected to a single TE30/40/50/60 at the same time

**:: TE30/40/50/60 only support content sharing

***: TE30/40/50/60 only support 2.4G Wi-Fi