


Designed to offer an exceptional user experience with superior performance and cutting-edge features for next-level productivity



Performance for any workplace

- Up to 13th Gen Intel® Core™ i7 processors (15W)
- Up to Intel® Iris® Xe graphics
- Supports PCIe Gen4 x4 M.2 SSD
-


Built for efficiency

- Ultra-capable Wi-Fi 6E wireless network and 1G wired network

Simplified IT management

- Always up to date operating system
- Centralized cloud management via Google Admin Console
- Secure by design with multilayered defense
- Supports Zero-Touch-Enrollment

Over view:



Accessories list:



- Power Cord
- AC Adapter (80cm)
- Quick Start Guide & Warranty Card
- VESA Mount Kit (Optional)
- Keyboard & Mouse for Chrome OS (Optional)

Feature table:

Power	Security	Reliability	Power
PD input	Kensington lock	24/7 Durability Test	AC Power loss

Model		ASUS Chromebox 5a (Core-i)	ASUS Chromebox 5a(Celeron)
OS		ChromeOS / Chrome Enterprise	
CPU		Intel® Core™ i7-1355U Processor Intel® Core™ i5-1335U Processor Intel® Core™ i3-1315U Processor (TDP 15W)	Intel® Celeron® Processor 7305 (TDP 15W)
Chipset		Integrated	
Graphics		Intel® Iris® Xe Graphics (i7/i5) Intel® UHD Graphics (i3)	Intel® UHD Graphics
Memory		2 x SO-DIMM DDR4 3200 memory 8GB~ 32GB	1 x SO-DIMM DDR4 3200 memory 4~16GB
Storage		1 x M.2 2280 PCIe Gen4x4 NVMe SSD (128G/256G/512G)	
Wireless Network		Intel® Wi-Fi 6E AX211, 2x2, and Bluetooth® 5.3* (* Bluetooth version depends on OS support)	
LAN		1G Ethernet, 10/100/1000 Mbps	
	Front I/O	Front I/O 1 x USB 3.2 Gen2 Type A / 3 x USB 3.2 Gen1 Type A / 1 x Audio Jack (Mic / Headphone Jack) / 1 x Micro SD card slot	
	Side I/O	1 x Kensington Lock / 1 x Recovery Button	
	Rear I/O	2 x USB 3.2 Gen1 Type-A / 1 x USB 3.2 Gen2 Type-C (supports DP1.4/PD in) 2 x HDMI / 1 x DisplayPort 1.4 / 1 x RJ45 LAN Port / 1 x DC-in	
Power Supply		90W Power Adapter	65W Power Adapter
Physical	Dimension	166.5 x 165.8 x 45.9 mm (1.27L)	
	Weight	0.8kg	
Temperature	Operating	0°C~50°C	
	Storage	-40°C~85°C	
Humidity		0%~95% Relative Humidity	
Acoustic	Idle mode	<25 dBA	
	Full loading	<45 dBA * Test results will vary slightly depending on the HDD/SSD SKU selected by customer	
Certificates		BSMI/CB/CE/FCC/UL/Energy Star/C-Tick/WiFi/RF/VCCI	