

Hisense

70
PINT

DEHUMIDIFIER BUILT-IN PUMP

up to 1,000 sq. ft. coverage

Model: DH70KP1WG



- Built-in Pump, quick-connect hose included
- 3 Modes - Auto, Continuous, Manual
- 2 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38 deg F)



Low noise airflow system

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on "Low".



Energy Efficient

Energy Star means its more energy efficient and helps reduce your utility bill.



Filter Indicator

Washable filter helps to reduce bacteria, odors and particles



Warranty

2 Years Parts & Labor

Built-in Pump - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH70KP1WG Energy Star 70-Pint 2-Speed Dehumidifier has a built-in pump that can quietly discharge water out a basement window or into a sink using the included quick-connect hose. This is a reliable and eco-friendly dehumidifier which can operate at temperatures as low as 38 degrees Fahrenheit. Three operating modes (manual set, continuous and auto dry) and the very low sound level make this a versatile choice. During dehumidification, water accumulates in the internal water tank or is continuously pumped out using the included quick-connect. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

TECHNICAL SPECIFICATIONS

Performance

Hisense-Model	DH70KPIWG
Dehumidification (Pints/24 hrs)	70 (DOE Test Procedure)
Heating Capacity	N/A
Coverage	up to 1,000 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	46 - 48 dB(A)

Electrical

Voltage / Freq / Amps	115V/60Hz / 6.8 A
-----------------------	-------------------

Control Features

Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer-Clock	Yes
Fan Speeds	2 speeds (Lo, Hi, Auto)
Pump Mode	Yes

General Features

Auto Bucket Shutoff	Yes
Bucket Capacity	13.7 pints
Bucket Shutoff Capacity	11.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	16 feet (head)

Accessories

Quick Connect Hose	Yes, included (9mm dia)
--------------------	-------------------------

Approvals

Safety	UL
Energy	Energy Star / CEC
Parcel Shippable	Yes

Shipping

Unit Dimension WxDxH (mm)	387 X 300 X 628
Carton Dimension WxDXH (mm)	435 X 335 X 667
Net Weight /Gross Weight (Kg)	21.3/23.0
Unit Dimension WxDxH (inch)	15.3 X 11.8 X 24.7
Carton Dimension WxDXH (inch)	17.1 X 13.3 X 26.3
Net Weight /Gross Weight (lbs)	46.8/50.7
Loading(40HQ)	746

Loading (53')	624 (floor loaded)
Warranty/UPC	
Parts & Labor	2 years
UPC	857603006294



Control Panel



Quick Connect Hose

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2017 Hisense USA, All rights reserved

Hisense USA Corporation
7310 McGinnis Ferry Road, Suwanee, GA, 30024
1-877-465-3566
www.hisense-usa.com

