

접 수 번 호 : 25-045218-01-1
(Receipt No.)



안전확인신고 증명서

Confirmation Letter of Declaration

신 고 번 호 (Application No.) : ZU10454-25001A
신 고 회 사 명 (Applicant) : SuZhou MEAN WELL Technology Co., Ltd.
주 소 (Address) : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China
제 품 명 (Product) : 컴퓨터용 전원공급장치(Switching Power Supply)
기 본 모 델 명 (Basic Model) : XDR-75E-48
파 생 모 델 명 (Series Model) : See the attachment 2
정격/안전기준상의 모델구분 (Rating) : Input: 100-240 Vac, 1.4 A, 50/60 Hz
(Output: 48 Vdc, 1.6 A; Vo Adj.: 48-55 Vdc, Max 76.8 W)
안 전 기 준 (Standard) : KC62368-1(2021-08)

본 확인신고는 제 조 국 명 : 중국
제조업자 명 : SuZhou MEAN WELL Technology Co., Ltd
제조공장의 주소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China
다수 공장의 명 : “이면기재” 의 제품에만 해당함

「전기용품 및 생활용품 안전관리법 시행규칙」 제28조제1항, 같은 조 제3항, 제29조제2항 또는 제34조제2항에 따라 안전확인신고 증명서를 발급합니다.

We issue this Confirmation Letter of Declaration of the Safety Confirmation for the above appliance in accordance with the Article 28(1), 28(3), 29(2) or 34(2) of the Enforcement Rule of the Electrical Appliances and Consumer Products Safety Control Act.

2025 년 08 월 06 일
Year month day

한국산업기술시험원
KOREA TESTING LABORATORY



※ 이 신고증명서는 「전기용품 및 생활용품 안전관리법」에 따른 제품의 안전성 확인에 한정된 것이며, 그 밖의 다른 법률이 적용되는 제품의 경우에는 해당 법률에 따라 추가로 인증·허가 등을 받아야 합니다.

첨부서류	1. 전기용품의 안전관리부품 및 재질목록(List of Critical Components)(전기용품에 한정한다)
	2. 기본모델·파생모델의 내용(Description of the basic and series model)
	3. 안전확인신고 내용의 변경 현황(Revisions Status)

안전인증 및 자율안전확인을 받은 자의 유의사항

Notification for recipient (license holder) of Safety Certification and Confirmation Letter of Declaration

1. 본 인증서 또는 신고증명서는 기재된 제조공장에서 생산된 제품으로서 적용된 안전기준에 적합한 경우에 한하여 유효합니다. (This certificate or confirmation letter of declaration is valid only when the product meets the applied safety standard(s) and is manufactured from the manufacturing factory that appears on this certificate.)
2. 안전인증 또는 안전확인 마크는 본래의 의미와 다르게 사용자가 오해를 일으킬 수 있는 방법으로 광고, 카탈로그 등에 사용하면 인증정지 또는 취소의 사유가 됩니다. (Termination or cancellation of the certification may occur if the actual meaning of this safety certification mark(KC-mark) or Confirmation Letter of Declaration mark(KC-mark) is misled to the public by false advertisement on a overstated catalog of the product.)
3. 다음과 같은 사유가 발생할 경우에는 사유가 발생한 날로부터 15일 이내에 안전인증기관에 안전인증 또는 안전확인 변경 신청을 하여 안전인증서 또는 안전확인신고 증명서를 재교부 받아야 합니다. (In case of the following events, this safety certificate or Confirmation Letter of Declaration shall be reapplied within 15 days from the events and reissued for revision.)
 - 1) 제조업자, 수입업자, 주소 등 인증서 기재내용의 변경 (Revision in contents of the certificate such as factory name, importer, factory address, etc)
 - 2) 파생모델의 추가, 변경 또는 삭제 (Adds, changes, or removals of derivative(minor series) model)
 - 3) 안전관리부품의 변경 또는 추가 (Adds or changes in critical components list)
 - 4) 인증서 또는 신고증명서의 분실 또는 훼손 (Losses or damages to this certificate or confirmation letter of declaration)
4. 안전인증 또는 안전확인을 받은 자는 다음 사항을 이행하여야 합니다. (The recipient (license holder) of safety certification (KC-mark) or confirmation letter of declaration shall comply with the followings.)
 - 1) 안전인증표시 등 인증요건의 유지 관리 (Maintaining and managing the marking of safety certification and other certification requirements)
 - ※ 안전인증을 받기 이전 또는 정지, 취소된 이후 생산된 제품에 안전 표시를 하면 법에 의거 처벌을 받게 됨 (It will be punished by the Act if the certification mark is used before the issue(or after suspension or cancellation) of the certification)
 - 2) 자체검사의 실시 및 그 기록관리 (Self Product Verification and record keeping)
 - ※ 안전인증을 받은 자는 제품검사를 철저히 실시하여 제품의 품질이 안전기준에 미달되지 않도록 유의 (Recipients (license holder) of the safety certification (KC-mark) shall conduct products inspection strictly for products to comply with the safety standard.)
5. 안전인증을 받은 자는 전기용품 및 생활용품 안전관리법 제7조 1항 및 동법 시행령 제9조에 의거 2년에 1회 정기검사를 받아야 합니다. (Recipients (license holder) of the safety certification (KC-mark) shall receive routine(regular) factory inspection once every two years according to the Electrical Appliances and Consumer products Safety Control Act article 7(1) and article 9 of Enforcement decree of the same Act.)

(연락처: 인증융합센터, Tel 055-791-3400, 3401)
(Contact point: Certification Evaluation Center Tel: +82 55 791 3400, 3401)

다수 공장의 현황
(The status of Multiple Factories)

No	현황	
1	다수 공장의 명 (Name)	Yongden Technology Corporation
	주소 (Address)	345 MacArthur HighWay, Tabang, Guiguinto, Bulacan 3015, Philippines
	제조국명 (Origin)	필리핀
2	다수 공장의 명 (Name)	MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED
	주소 (Address)	9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA, Bengaluru (Bangalore) Urban, Karnataka, 560058, India
	제조국명 (Origin)	인도
3	다수 공장의 명 (Name)	MEAN WELL (Guangzhou) Electronics Co.,Ltd.
	주소 (Address)	No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China
	제조국명 (Origin)	중국
4	다수 공장의 명 (Name)	MEAN WELL ENTERPRISES CO., LTD.
	주소 (Address)	No. 28 Wuquan 3rd Road, Wugu District, New Taipei City 248, Taiwan (R.O.C.)
	제조국명 (Origin)	대만

☐ 첨부 1 : 전기용품의 안전관리부품 및 재질목록
List of Critical Components

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Printed Wiring Board	Interchangeable	Interchangeable	Min. V-1, Rated 130 °C	UL
(Alternate)	Shunde junda	JD-D	min. 130 °C, min. V-0	UL
(Alternate)	Shunde Junda Electronic Co Ltd	JD-D1	Min. V-1, Rated 130 °C	UL
(Alternate)	HONG SHIEN ENTERPRISE CO LTD	03V-0	Min. V-1, Rated 130 °C	UL
(Alternate)	HSU TZU ELECTRONIC CO LTD	4V0	Min. V-1, Rated 130 °C	UL
(Alternate)	GUANGDONG CHAOHUA TECHNOLOGY CO LTD	C-109	Min. V-1, Rated 130 °C	UL
(Alternate)	GUANGDONG CHAOHUA TECHNOLOGY CO LTD	C-104	Min. V-1, Rated 130 °C	UL
(Alternate)	LOMBER CIRCUITS (HUIZHOU) LTD	FRV03A	Min. V-1, Rated 130 °C	UL
(Alternate)	LOMBER CIRCUITS (HUIZHOU) LTD	FRV03	Min. V-1, Rated 130 °C	UL
(Alternate)	Kunshan Wanyuantong	SWZ-1, SWZ-2	Min. V-1, Rated 130 °C	UL
(Alternate)	Suzhou Wutong Electronics Co Ltd	GS-3	Min. V-1, Rated 130 °C	UL
(Alternate)	Suzhou Wutong Electronics Co Ltd	GS-1	Min. V-1, Rated 130 °C	UL
(Alternate)	CHANGZHOU HAIHONG ELECTRONICS CO LTD	HDCEM1	Min. V-1, Rated 130 °C	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	CHANGZHOU HAIHONG ELECTRONICS CO LTD	CCE-V0	Min. V-1, Rated 130 °C	UL
(Alternate)	CHANGZHOU HAIHONG ELECTRONICS CO LTD	HH	Min. V-1, Rated 130 °C	UL
Input and output Terminal Block (TB1, TB2)	SWITCHLAB INC	MH140-635M8	35A, 600V, 115 °C, Cu, 8-18 SOL/STR, FW=2, min 9lb-in	UL
(Alternate)	DEGSON TECHNOLOGY CO., LTD.	DG637-6.35	30A ,600V, 120 °C, Cu, 28-10 AWG, Sol/Str, FW=2, 5.0- 7.0 lb-in.	UL
(Alternate)	Dinkle Enterprise Co., Ltd.	EPK635VN	35A, 600V, 105 °C Cu,8-18, SOL/STR, FW=2, min 4.4lb-in	UL
(Alternate)	SWITCHLAB INC	MPX332H-635	25A, 600V, 110 °C, Cu, 24-10 AWG, Str, FW=2	UL
(Alternate)	SWITCHLAB INC	MPX410H-635	25A, 600V, 115 °C, Cu, 24-10 AWG, SOL/STR, FW=2	UL
DC OK Terminal (CN101)	DEGSON TECHNOLOGY CO., LTD.	DG212R	12A, 300V, 120 °C Cu,28-14, Str/Sol,FW=2	UL
(Alternate)	DINKLE ENTERPRISE CO LTD	0138-51	12A, 300V, 130 °C Cu,28-16, FW=2	UL
Fuse (FS1)	Conquer Electronics Co., Ltd.	MST	T3.15 A, 250 Vac	VDE
(Alternate)	HOLLYLAND	5ET	T3.15 A, 250 Vac	TUV
(Alternate)	SUZHOU WALTER ELECTRONIC CO LTD	2010	T3.15 A, 250 Vac	VDE
(Alternate)	XIAMEN SET ELECTRONICS CO LTD	SPT478	T3.15 A, 250 Vac	UL
(Alternate)	SUZHOU WALTER ELECTRONIC CO LTD	FSC/FSC(P)	F3.15 AH, 250 Vac	VDE
(Alternate)	Conquer Electronics Co., Ltd.	UBM / UBM-A	F3.15 AH, 250 Vac	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Xiamen Set Electronics Co.,Ltd	SCF520P	F3.15 AH, 250 Vac	TUV
(Alternate)	Conquer Electronics Co., Ltd.	UDA-A	F3.15 AH, 250 Vac	VDE
Relay (RY1)	Xiamen Hongfa Electroacoustic Co.,Ltd.	HFD23/012-1ZS	Rated 1 A, 30 Vdc	TUV
(Alternate)	Xiamen Hongfa Electroacoustic Co.,Ltd.	HFD4	Rated 1 A, 30 Vdc	TUV
(Alternate)	Sanyou Corporation Limited	SYS-S-112L	Rated 1 A, 30 Vdc	UL TUV
X Capacitor (C1, C2) (Optional)	Joey Electronics (Dong Guan) Co., Ltd.	MPX-X1	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	VDE
(Alternate)	Joey Electronics (Dong Guan) Co., Ltd.	MPX-X2	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	VDE
(Alternate)	Kemet Electronics Italia Srl	R.46	Max. 0.68 uF min. 250 Vac. Min.125 °C Class X2.	UL
(Alternate)	TDK (Zhuhai FTZ) Co., Ltd.	B3292#	Max. 0.68 uF min. 250 Vac. Min.105 °C Class X1 or X2.	ENEC
(Alternate)	TDK (Zhuhai FTZ) Co., Ltd.	B3292#C/D/T/S/H/J3 series	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1 or X2.	ENEC
(Alternate)	Liow Gu Electronics Industry Co., Ltd	GS-L	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	HUA JUNG COMPONENTS CO LTD	MKX1	Max. 0.68 uF min. 250 Vac. Min.100 °C Class X1	UL
(Alternate)	XIAMEN FARATRONIC CO LTD	MKP65	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	KEMET ELECTRONICS ITALIA SRL	F872	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	UL
(Alternate)	CHIEFCON ELECTRONICS CO LTD	CKX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1 or X2.	UL
(Alternate)	Ultra Tech Xiphi Enterprise Co. Ltd.	HQX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Hua Jung Components Co Ltd	MKP	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Carli Electronics, Co., Ltd.	MPX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Yangzhou Nissei Electronics Co Ltd	MP1	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
Y-Capacitors (C3, C24) (max. 3300 pF for C3, max. 680 pF for C24) (Optional)	TDK Corporation	CS	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	TDK Corporation	CD	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AC	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AH	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AS	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	HM, HJ	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AB	min. 250 V, min. 125 °C, class Y1 or Y2	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Huiwan	AR	min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	VISHAY Electronic GmbH	VY1	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Murata Mfg. Co., Ltd.	KX	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Bridge Capacitor (C31, C32) (Optional)	TDK Corporation	CS	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	TDK Corporation	CD	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AC	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AH	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AS	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	HM, HJ	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AB	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	Huiwan	AR	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	VISHAY Electronic GmbH	VY1	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Murata Mfg. Co., Ltd.	KX	Max.3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Photo Coupler (U2, U3) 3)	VISHAY SEMICONDUCTOR GMBH	TCLT1008	Reinforced insulation	VDE
(Alternate)	Everlight Electronics Co., Ltd.	EL817(SMD type)	Reinforced insulation	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT817C(V)(SL)(T)-HG	Reinforced insulation	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Lite-on Technology Corp	LTV-1008	Reinforced insulation	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT1018(V)(T)-W	Reinforced insulation	VDE
(Alternate)	Lite-on Technology Corp	LTV-817S	Reinforced insulation	VDE
Varistors (ZNR1) (Optional)	Centra Science	CNR14D471K	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Joyin Co., Ltd.	JVT14S471K JVT14N471K	300 Vac, 385 Vdc, 125 °C	UL
(Alternate)	Joyin Co., Ltd.	JVZ14N471K	300 Vac, 385 Vdc, 105 °C	UL
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-M	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-D	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-V	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Guangdong Huiwan Electronics, Technology Co., Ltd.	V-471K-14D(E)H	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K	300 Vac, 385 Vdc, 85 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-2	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-3	300 Vac, 385 Vdc, 125 °C	VDE
Transformer (T1)	MEAN WELL Enterprise Co., Ltd.	TF5994 for XDR-75E -12 TF5995 for XDR-75E -24 TF5996 for XDR-75E -36 TF5997 for XDR- 75E-48	Class B	Tested with appliance

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Line Choke (LF1) (Optional)	MEAN WELL Enterprises Co., Ltd.	LF5021	min. 130 °C.	Tested with appliance
Bleeder Resistor (R1, R2)	TZAI YUAN Enterprise Co.,Ltd.	SMD*****	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	WALSIN TECHNOLOGY CORP	WF Series	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	Ever Ohms Technology Co Ltd	HR Series	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	FENGHUA	RS-06 Series	Each Max. 330K ohms min. 1/4 W	Nemko
(Alternate)	FENGHUA	RVS	Each Max. 330K ohms min. 1/4 W	Nemko
(Alternate)	Uniroyal Electronics Global Co Ltd	HV06	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	Viking Tech Corporation Kaoshiung Branch	HVR05, HVR0A, HVR12 series	Each Max. 330K ohms min. 1/4 W	UL

☐ 유의사항 (Attention) :

1. 안전관리부품은 전기적인 안전에 직접적인 영향을 주는 부품으로서 안전인증기관이 정기공장검사 시 확인 관리 하는 사항입니다. 따라서 상기목록에 기재된 사항을 변경하거나 또는 복수등재를 원하시는 경우는 안전인증기관에 인증변경신청을 하여야 합니다.

As the "Critical components" are parts in directly related with safety, these components shall be checked during a factory inspection by the certification body. In case of applying multiple listing or changing the items above, the certification revision shall be applied.

2. 인증변경신청 없이 임의로 변경하는 경우는, 전기용품 및 생활용품 안전관리법 시행규칙 제 21 조제 1 항 또는 제 38 조제 1 항 규정에 의한 안전인증 취소 혹은 안전확인신고 효력상실 사유가 됨을 유의하시기 바랍니다.

The Safety Certification will be cancelled under the Article 21(1), 38(1) of the Enforcement Rule of the Electrical appliances and Consumer Products Safety Control Act if the contents of the Certification is altered without our authorization.

□ 첨부 2 : 기본모델 · 파생모델의 내용
Description of the basic and series model

파생모델명 Derivative model	기본모델과의 차이점 Differences between the basic and derivative model(s)
XDR-75E-48PI	It is identical to basic model except for model designation.
XDR-75E-48LA	It is identical to basic model except for model designation.
XDR-75E-48KC	It is identical to basic model except for model designation.
XDR-75E-48PIKC	It is identical to basic model except for model designation.
XDR-75E-48LAKC	It is identical to basic model except for model designation.
XDR-75E-12	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-12PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-12LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-12KC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-12PIKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-12LAKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A; Vo Adj.: 12-15Vdc, Max 75.6W)
XDR-75E-24	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)
XDR-75E-24PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)
XDR-75E-24LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)
XDR-75E-24KC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)
XDR-75E-24PIKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)
XDR-75E-24LAKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A; Vo Adj.: 24-29Vdc, Max 76.8W)

파생모델명 Derivative model	기본모델과의 차이점 Differences between the basic and derivative model(s)
XDR-75E-36	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
XDR-75E-36PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
XDR-75E-36LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
XDR-75E-36KC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
XDR-75E-36PIKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
XDR-75E-36LAKC	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A; Vo Adj.: 36-42Vdc, Max 75.6W)
제품특기사항 및 시험조건 Remarks & Test conditions	
1. MoU NCB Review Report based on: (25-019489-02-2) - CB Certificate Ref. No.: JPTUV-170731 (TÜV Rheinland Japan Ltd.) - CB Test Report No.: CN256CB1 001 (TÜV Rheinland (Shanghai) Co., Ltd) 2. Product Description: - Measured Power Consumption: 82.4 W - Insulation Class: Class I - Protection against Ingress of water: IPX0 IP20 - Mass of Equipment: Approx. 0.38 kg - Operation ambient (°C): 50°C for full load or 70°C for 75% load	

제품특기사항 및 시험조건
Remarks & Test conditions

* Factory(ies)

(1). MEAN WELL (GUANGZHOU) Electronics Co., Ltd.

- No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China

(2). MEAN WELL Enterprises Co.,Ltd

- No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan (R.O.C.)

(3). Yongden Technology Corporation

- 345 MacArthur HighWay, Tabang, Guiguinto, Bulacan 3015, Philippines

(4). MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED

- 9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA, Bengaluru (Bangalore)
Urban, Karnataka, 560058, India

□ 본 제품의 검토내용에 관하여 문의하실 사항이 있으시면 아래 연락처로 문의하시기 바랍니다.

검토담당자 / 연락처 : 인증사업본부 인증융합센터 장 재용 / 055-791-3305

□ *If you have any question on product review, please contact the person below :*

Job holder: Certification Business Division, Certification Convergence Center, J.Y.Jang / +82 55 791 3305

FP511-05-00

☐ 첨부 3 : 안전확인신고 내용의 변경 현황
Revisions Status

변경발급 내용 Contents of Certificate Revisions
1 st Rev.) Revision as below (25-045218-01-1 : 2025.08.06.) - Modification of rating of basic model (typo error) - Addition of derivative models - Modification of rating of derivative models - Addition of alternate components: Printed Wiring Board, Relay (RY1), Varistor (ZNR1) - Modification of rating of Relay (RY1) - PCB photo changed - Label changed - Product description update: IP20 and comment added.

FP511-06-00

접 수 번 호 : 25-019489-02-1
(Receipt No.)



안전확인신고 증명서

Confirmation Letter of Declaration

신 고 번 호 : ZU10454-25001
(Application No.)

신 고 회 사 명 : SuZhou MEAN WELL Technology Co., Ltd.
(Applicant)

주 소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China
(Address)

제 품 명 : 컴퓨터용 전원공급장치(Switching Power Supply)
(Product)

기 본 모 델 명 : XDR-75E-48
(Basic Model)

파 생 모 델 명 : See the attachment 2
(Series Model)

정격/안전기준상의 모델구분 : Input: 100-240 Vac, 1.4 A, 50/60 Hz (Output: 48 Vdc, 1.6 A)
(Rating)

안 전 기 준 : KC62368-1(2021-08)
(Standard)

본 확인신고는 제 조 국 명 : 중국
제조업자 명 : SuZhou MEAN WELL Technology Co., Ltd
제조공장의 주소 : No.269, ChangPing Road, Huangdai Town, Xiangcheng District, Suzhou, China
다수 공장의 명 : “이면기재” 의 제품에만 해당함

「전기용품 및 생활용품 안전관리법 시행규칙」 제28조제1항, 같은 조 제3항, 제29조제2항 또는 제34조제2항에 따라 안전확인신고 증명서를 발급합니다.

We issue this Confirmation Letter of Declaration of the Safety Confirmation for the above appliance in accordance with the Article 28(1), 28(3), 29(2) or 34(2) of the Enforcement Rule of the Electrical Appliances and Consumer Products Safety Control Act.

2025 년 05 월 15 일
Year month day

한국산업기술시험원
KOREA TESTING LABORATORY



※ 이 신고증명서는 「전기용품 및 생활용품 안전관리법」에 따른 제품의 안전성 확인에 한정된 것이며, 그 밖의 다른 법률이 적용되는 제품의 경우에는 해당 법률에 따라 추가로 인증·허가 등을 받아야 합니다.

첨부서류

1. 전기용품의 안전관리부품 및 재질목록(List of Critical Components)(전기용품에 한정한다)
2. 기본모델·파생모델의 내용(Description of the basic and series model)
3. 안전확인신고 내용의 변경 현황(Revisions Status)

안전인증 및 자율안전확인을 받은 자의 유의사항

Notification for recipient (license holder) of Safety Certification and Confirmation Letter of Declaration

1. 본 인증서 또는 신고증명서는 기재된 제조공장에서 생산된 제품으로서 적용된 안전기준에 적합한 경우에 한하여 유효합니다. (This certificate or confirmation letter of declaration is valid only when the product meets the applied safety standard(s) and is manufactured from the manufacturing factory that appears on this certificate.)
2. 안전인증 또는 안전확인 마크는 본래의 의미와 다르게 사용자가 오해를 일으킬 수 있는 방법으로 광고, 카탈로그 등에 사용하면 인증정지 또는 취소의 사유가 됩니다. (Termination or cancellation of the certification may occur if the actual meaning of this safety certification mark(KC-mark) or Confirmation Letter of Declaration mark(KC-mark) is misled to the public by false advertisement on a overstated catalog of the product.)
3. 다음과 같은 사유가 발생할 경우에는 사유가 발생한 날로부터 15일 이내에 안전인증기관에 안전인증 또는 안전확인 변경 신청을 하여 안전인증서 또는 안전확인신고 증명서를 재교부 받아야 합니다. (In case of the following events, this safety certificate or Confirmation Letter of Declaration shall be reapplied within 15 days from the events and reissued for revision.)
 - 1) 제조업자, 수입업자, 주소 등 인증서 기재내용의 변경 (Revision in contents of the certificate such as factory name, importer, factory address, etc)
 - 2) 파생모델의 추가, 변경 또는 삭제 (Adds, changes, or removals of derivative(minor series) model)
 - 3) 안전관리부품의 변경 또는 추가 (Adds or changes in critical components list)
 - 4) 인증서 또는 신고증명서의 분실 또는 훼손 (Losses or damages to this certificate or confirmation letter of declaration)
4. 안전인증 또는 안전확인을 받은 자는 다음 사항을 이행하여야 합니다. (The recipient (license holder) of safety certification (KC-mark) or confirmation letter of declaration shall comply with the followings.)
 - 1) 안전인증표시 등 인증요건의 유지 관리 (Maintaining and managing the marking of safety certification and other certification requirements)
 - ※ 안전인증을 받기 이전 또는 정지, 취소된 이후 생산된 제품에 안전 표시를 하면 법에 의거 처벌을 받게 됨 (It will be punished by the Act if the certification mark is used before the issue(or after suspension or cancellation) of the certification)
 - 2) 자체검사의 실시 및 그 기록관리 (Self Product Verification and record keeping)
 - ※ 안전인증을 받은 자는 제품검사를 철저히 실시하여 제품의 품질이 안전기준에 미달되지 않도록 유의 (Recipients (license holder) of the safety certification (KC-mark) shall conduct products inspection strictly for products to comply with the safety standard.)
5. 안전인증을 받은 자는 전기용품 및 생활용품 안전관리법 제7조 1항 및 동법 시행령 제9조에 의거 2년에 1회 정기검사를 받아야 합니다. (Recipients (license holder) of the safety certification (KC-mark) shall receive routine(regular) factory inspection once every two years according to the Electrical Appliances and Consumer products Safety Control Act article 7(1) and article 9 of Enforcement decree of the same Act.)

(연락처: 인증융합센터, Tel 055-791-3400, 3401)
(Contact point: Certification Evaluation Center Tel: +82 55 791 3400, 3401)

다수 공장의 현황
(The status of Multiple Factories)

No	현황	
1	다수 공장의 명 (Name)	Yongden Technology Corporation
	주소 (Address)	345 MacArthur HighWay, Tabang, Guiguinto, Bulacan 3015, Philippines
	제조국명 (Origin)	필리핀
2	다수 공장의 명 (Name)	MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED
	주소 (Address)	9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA, Bengaluru (Bangalore) Urban, Karnataka, 560058, India
	제조국명 (Origin)	인도
3	다수 공장의 명 (Name)	MEAN WELL (Guangzhou) Electronics Co.,Ltd.
	주소 (Address)	No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China
	제조국명 (Origin)	중국
4	다수 공장의 명 (Name)	MEAN WELL ENTERPRISES CO., LTD.
	주소 (Address)	No. 28 Wuquan 3rd Road, Wugu District, New Taipei City 248, Taiwan (R.O.C.)
	제조국명 (Origin)	대만

□ 첨부 1 : 전기용품의 안전관리부품 및 재질목록
List of Critical Components

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Printed Wiring Board	Interchangeable	Interchangeable	Min. V-1, Rated 130 °C	UL
Input and output Terminal Block (TB1, TB2)	SWITCHLAB INC	MH140-635M8	35A, 600V, 115 °C, Cu, 8-18 SOL/STR, FW=2, min 9lb-in	UL
(Alternate)	DEGSON TECHNOLOGY CO., LTD.	DG637-6.35	30A, 600V, 120 °C, Cu, 28-10 AWG, Sol/Str, FW=2, 5.0-7.0 lb-in.	UL
(Alternate)	Dinkle Enterprise Co., Ltd.	EPK635VN	35A, 600V, 105 °C Cu,8-18, SOL/STR, FW=2, min 4.4lb-in	UL
(Alternate)	SWITCHLAB INC	MPX332H-635	25A, 600V, 110 °C, Cu, 24-10 AWG, Str, FW=2	UL
(Alternate)	SWITCHLAB INC	MPX410H-635	25A, 600V, 115 °C, Cu, 24-10 AWG, SOL/STR, FW=2	UL
DC OK Terminal (CN101)	DEGSON TECHNOLOGY CO., LTD.	DG212R	12A, 300V, 120 °C Cu,28-14, Str/Sol,FW=2	UL
(Alternate)	DINKLE ENTERPRISE CO LTD	0138-51	12A, 300V, 130 °C Cu,28-16, FW=2	UL
Fuse (FS1)	Conquer Electronics Co., Ltd.	MST	T3.15 A, 250 Vac	VDE
(Alternate)	HOLLYLAND	5ET	T3.15 A, 250 Vac	TUV
(Alternate)	SUZHOU WALTER ELECTRONIC CO LTD	2010	T3.15 A, 250 Vac	VDE
(Alternate)	XIAMEN SET ELECTRONICS CO LTD	SPT478	T3.15 A, 250 Vac	UL
(Alternate)	SUZHOU WALTER ELECTRONIC CO LTD	FSC/FSC(P)	F3.15 AH, 250 Vac	VDE
(Alternate)	Conquer Electronics Co., Ltd.	UBM / UBM-A	F3.15 AH, 250 Vac	VDE
(Alternate)	Xiamen Set Electronics Co.,Ltd	SCF520P	F3.15 AH, 250 Vac	TUV

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Conquer Electronics Co., Ltd.	UDA-A	F3.15 AH, 250 Vac	VDE
Relay (RY1)	Xiamen Hongfa Electroacoustic Co.,Ltd.	HFD23/012-1ZS	Rated 1 A, 125 Vac	TUV
(Alternate)	Sanyou Corporation Limited	SYS-S-112L	Rated 1 A, 125 Vac	UL
X Capacitor (C1, C2) (Optional)	Joey Electronics (Dong Guan) Co., Ltd.	MPX-X1	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	VDE
(Alternate)	Joey Electronics (Dong Guan) Co., Ltd.	MPX-X2	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	VDE
(Alternate)	Kemet Electronics Italia Srl	R.46	Max. 0.68 uF min. 250 Vac. Min.125 °C Class X2.	UL
(Alternate)	TDK (Zhuhai FTZ) Co., Ltd.	B3292#	Max. 0.68 uF min. 250 Vac. Min.105 °C Class X1 or X2.	ENEC
(Alternate)	TDK (Zhuhai FTZ) Co., Ltd.	B3292#C/D/T/S/H/J3 series	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1 or X2.	ENEC
(Alternate)	Liow Gu Electronics Industry Co., Ltd	GS-L	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	HUA JUNG COMPONENTS CO LTD	MKX1	Max. 0.68 uF min. 250 Vac. Min.100 °C Class X1	UL
(Alternate)	XIAMEN FARATRONIC CO LTD	MKP65	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	UL
(Alternate)	KEMET ELECTRONICS ITALIA SRL	F872	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1	UL
(Alternate)	CHIEFCON ELECTRONICS CO LTD	CKX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X1 or X2.	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Ultra Tech Xiphi Enterprise Co. Ltd.	HQX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Hua Jung Components Co Ltd	MKP	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Carli Electronics, Co., Ltd.	MPX	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
(Alternate)	Yangzhou Nissei Electronics Co Ltd	MP1	Max. 0.68 uF min. 250 Vac. Min.110 °C Class X2.	UL
Y-Capacitors (C3, C24) (max. 3300 pF for C3, max. 680 pF for C24) (Optional)	TDK Corporation	CS	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	TDK Corporation	CD	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AC	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AH	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AS	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	HM, HJ	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AB	min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	Huiwan	AR	min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	VISHAY Electronic GmbH	VY1	min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Murata Mfg. Co., Ltd.	KX	min. 250 V, min. 125 °C, class Y1 or Y2	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
Bridge Capacitor (C31, C32) (Optional)	TDK Corporation	CS	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	TDK Corporation	CD	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AC	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AH	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Walsin Technology Corp.	AS	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	HM, HJ	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Huiwan	AB	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	Huiwan	AR	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	UL
(Alternate)	VISHAY Electronic GmbH	VY1	Max. 3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
(Alternate)	Murata Mfg. Co., Ltd.	KX	Max.3300 pF, min. 250 V, min. 125 °C, class Y1 or Y2	VDE
Photo Coupler (U2, U3) 3)	VISHAY SEMICONDUCTOR GMBH	TCLT1008	Reinforced insulation	VDE
(Alternate)	Everlight Electronics Co., Ltd.	EL817(SMD type)	Reinforced insulation	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT817C(V)(SL)(T)-HG	Reinforced insulation	UL
(Alternate)	Lite-on Technology Corp	LTV-1008	Reinforced insulation	VDE
(Alternate)	Ct Microelectronics Far East Ltd	CT1018(V)(T)-W	Reinforced insulation	VDE
(Alternate)	Lite-on Technology Corp	LTV-817S	Reinforced insulation	VDE
Varistors (ZNR1) (Optional)	Centra Science	CNR14D471K	300 Vac, 385 Vdc, 105 °C	VDE

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	Joyin Co., Ltd.	JVT14S471K JVT14N471K	300 Vac, 385 Vdc, 125 °C	UL
(Alternate)	Joyin Co., Ltd.	JVZ14N471K	300 Vac, 385 Vdc, 105 °C	UL
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-M	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-D	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Thinking Electronic Industrial Co., Ltd.	TVR14471-V	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Guangdong Huiwan Electronics, Technology Co., Ltd.	V-471K-14D(E)H	300 Vac, 385 Vdc, 125 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-2	300 Vac, 385 Vdc, 105 °C	VDE
(Alternate)	Xiamen Wanming Electronics Co., Ltd.	WMR14D471K-3	300 Vac, 385 Vdc, 125 °C	VDE
Transformer (T1)	MEAN WELL Enterprise Co., Ltd.	TF5994 for XDR-75E -12 TF5995 for XDR-75E -24 TF5996 for XDR-75E -36 TF5997 for XDR- 75E-48	Class B	Tested with appliance
Line Choke (LF1) (Optional)	MEAN WELL Enterprises Co., Ltd.	LF5021	min. 130 °C.	Tested with appliance
Bleeder Resistor (R1, R2)	TZAI YUAN Enterprise Co.,Ltd.	SMD*****	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	WALSIN TECHNOLOGY CORP	WF Series	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	Ever Ohms Technology Co Ltd	HR Series	Each Max. 330K ohms min. 1/4 W	UL

부품명(회로기호) Component(Part no.)	제조사(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 Rating or Characteristics	인증마크 Tested by
(Alternate)	FENGHUA	RS-06 Series	Each Max. 330K ohms min. 1/4 W	Nemko
(Alternate)	FENGHUA	RVS	Each Max. 330K ohms min. 1/4 W	Nemko
(Alternate)	Uniroyal Electronics Global Co Ltd	HV06	Each Max. 330K ohms min. 1/4 W	UL
(Alternate)	Viking Tech Corporation Kaoshiung Branch	HVR05, HVR0A, HVR12 series	Each Max. 330K ohms min. 1/4 W	UL

☐ 유의사항 (Attention) :

1. 안전관리부품은 전기적인 안전에 직접적인 영향을 주는 부품으로서 안전인증기관이 정기공장검사 시 확인 관리 하는 사항입니다. 따라서 상기목록에 기재된 사항을 변경하거나 또는 복수등재를 원하시는 경우는 안전인증기관에 인증변경신청을 하여야 합니다.

As the "Critical components" are parts in directly related with safety, these components shall be checked during a factory inspection by the certification body. In case of applying multiple listing or changing the items above, the certification revision shall be applied.

2. 인증변경신청 없이 임의로 변경하는 경우는, 전기용품 및 생활용품 안전관리법 시행규칙 제 21 조제 1 항 또는 제 38 조제 1 항 규정에 의한 안전인증 취소 혹은 안전확인신고 효력상실 사유가 됨을 유의하시기 바랍니다.

The Safety Certification will be cancelled under the Article 21(1), 38(1) of the Enforcement Rule of the Electrical appliances and Consumer Products Safety Control Act if the contents of the Certification is altered without our authorization.

FP511-04-01

□ 첨부 2 : 기본모델 · 파생모델의 내용
Description of the basic and series model

파생모델명 Derivative model	기본모델과의 차이점 Differences between the basic and derivative model(s)
XDR-75E-48PI	It is identical to basic model except for model designation.
XDR-75E-48LA	It is identical to basic model except for model designation.
XDR-75E-12	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A)
XDR-75E-12PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A)
XDR-75E-12LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 12 Vdc, 6.3 A)
XDR-75E-24	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A)
XDR-75E-24PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A)
XDR-75E-24LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 24 Vdc, 3.2 A)
XDR-75E-36	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A)
XDR-75E-36PI	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A)
XDR-75E-36LA	It is identical to basic model except for model designation, output rating, turns of secondary windings for Transformer (T1). (Output: 36 Vdc, 2.1 A)

제품특기사항 및 시험조건
Remarks & Test conditions

1. MoU NCB Review Report based on: (25-019489-02-2)

- CB Certificate Ref. No.: JPTUV-170731 (TÜV Rheinland Japan Ltd.)
- CB Test Report No.: CN256CB1 001 (TÜV Rheinland (Shanghai) Co., Ltd)

2. Product Description:

- Measured Power Consumption: 82.4 W
- Insulation Class: Class I
- Protection against Ingress of water: IPX0
- Mass of Equipment: Approx. 0.38 kg

* Factory(ies)

(1). MEAN WELL (GUANGZHOU) Electronics Co., Ltd.

- No.11 Jingu South Road, Huadu District, Guangzhou 510890, Guangdong, China

(2). MEAN WELL Enterprises Co.,Ltd

- No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan (R.O.C.)

(3). Yongden Technology Corporation

- 345 MacArthur Highway, Tabang, Guiguinto, Bulacan 3015, Philippines

(4). MEAN WELL INDIA ELECTRONICS PRIVATE LIMITED

- 9C, Peenya industrial area, Chokkasandra, 2ND PHASE, PEENYA, Bengaluru (Bangalore) Urban, Karnataka, 560058, India

☐ 본 제품의 검토내용에 관하여 문의하실 사항이 있으시면 아래 연락처로 문의하시기 바랍니다.

검토담당자 / 연락처 : 인증사업본부 인증융합센터 장 재용 / 055-791-3305

☐ If you have any question on product review, please contact the person below :

Job holder: Certification Business Division, Certification Convergence Center, J.Y.Jang / +82 55 791 3305

FP511-05-00

☐ 첨부 3 : 안전확인신고 내용의 변경 현황
Revisions Status

변경발급 내용 Contents of Certificate Revisions
Not applicable

FP511-06-00

☐ 첨부 : 제품사진
Photographs



