



ULTRA RT4

CS RT4

ULTRA RT5/6

Downlight LED Retrofits

ULTRA LED™ RT4 (120V, Dimmable)

Retrofit for standard four inch insulated ceiling, airtight and non-IC Incandescent downlights housings

Nominal Wattage	Incand. Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens	LPW	CCT (K)	CRI	Notes
9	50	3.18	Med. Adaptor	70459	LED/RT4/600/827/FL80	2	50,000	80°	600	67	2700	82	W ★ _{2,4,5}
				70643	LED/RT4/600/830/FL80	2	50,000	80°	600	67	3000	85	W ★ _{2,4,5}
				73835	LED/RT4/600/840	2	50,000	80°	600	67	4000	82	W ★ _{2,4,5}
				73836	LED/RT4/600/850	2	50,000	80°	600	67	5000	82	W ★ _{2,4,5}

ULTRA LED RT4 Gimbal (30° Tilt, 120V, Dimmable)

Retrofit for standard four inch insulated ceiling, airtight and non-IC Incandescent downlights housings

Nominal Wattage	Incand. Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens	LPW	CCT (K)	CRI	Notes
9	50	3.18	Med. Adaptor	70387	LED/RT4/G/600/827	4	50,000	80°	600	67	2700	82	★ _{2,4,5}
9	50	3.16	Med. Adaptor	70395	LED/RT4/G/600/830	4	50,000	80°	600	67	3000	85	★ _{2,4,5}

Contractor LED RT4 (120V, Dimmable)

Retrofit for standard four inch insulated ceiling, airtight and non-IC Incandescent downlights housings

Nominal Wattage	Incand. Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens	LPW	CCT (K)	CRI	Notes
8	50	3.15	Med. Adaptor	70520	LED/RT4/550/827	4	11,000	80°	550	69	2700	82	W _{2,4,5}
				70521	LED/RT4/550/830	4	11,000	80°	550	69	3000	82	W _{2,4,5}
8	50	3.57	Med. Adaptor	74181	LED/RT4/550/840	4	11,000	80°	550	69	4000	82	W _{2,4,5}
				74182	LED/RT4/550/850	4	11,000	80°	550	69	5000	82	W _{2,4,5}

ULTRA LED RT5/6 HO (120-277V, Dimmable)

Retrofit for standard five or six inch downlights housings with compact fluorescent pin-base lamps

Nominal Wattage	CFL Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Rated Life L ₇₀ (hrs)	Beam Angle	Initial Lumens	LPW	CCT (K)	CRI	Notes
8	13	3.46	Conduit Adaptor	75228	LED/RT5/6/HO/700/827	2	50,000	80°	700	88	2700	>80	W ★ _{2,4,6,10}
				75229	LED/RT5/6/HO/700/830	2	50,000	80°	700	88	3000	>80	W ★ _{2,4,6,10}
				75230	LED/RT5/6/HO/700/835	2	50,000	80°	700	88	3500	>80	W ★ _{2,4,6,10}
				75231	LED/RT5/6/HO/700/840	2	50,000	80°	700	88	4000	>80	W ★ _{2,4,6,10}
13	18	3.46	Conduit Adaptor	75137	LED/RT5/6HO/900/827	2	50,000	80°	900	69	2700	>80	W ★ _{2,4,6,10}
				75138	LED/RT5/6HO/900/830	2	50,000	80°	900	69	3000	>80	W ★ _{2,4,6,10}
				75140	LED/RT5/6HO/900/835	2	50,000	80°	900	69	3500	>80	W ★ _{2,4,6,10}
				75139	LED/RT5/6HO/900/840	2	50,000	80°	900	69	4000	>80	W ★ _{2,4,6,10}
17	26/32	4.31	Conduit Adaptor	72528	LED/RT5/6/1500/HO/830	4	50,000	80°	1500	88	3000	>80	W ★ _{2,4,6,10}
				72529	LED/RT5/6/1500/HO/835	4	50,000	80°	1500	88	3500	>80	W ★ _{2,4,6,10}
				72530	LED/RT5/6/1500/HO/840	4	50,000	80°	1500	88	4000	>80	W ★ _{2,4,6,10}