

DOCTOR CHARGE 130







DESCRIPTION

Multifunctional, electronic battery charger (BATTERY MANAGER) for complete maintenance of WET, GEL, AGM, MF, PbCa, EFB, Li 6V/12V/24V batteries and for support activities in interventions, including diagnostics, on vehicles carried out in workshops, body shops and dealers.

The Pulse Tronic technology guarantees optimal battery charging over 8 phases.

Features:

- Automatic charging and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge;
- COLD function for charging and maintenance of batteries at low temperatures;
- stable POWER SUPPLY for diagnostics (BSU) when changing the battery (SUPPLY) and maintain the battery health of vehicles on display in showrooms;
- Batteries maintenance through RECOVERY function, to recover sulphated or very low batteries; -and EQUALIZATION function to restore optimal functionality with periodic regeneration;
- TESTER for checking terminal voltage, starting capacity (CCA) and vehicle alternator operation;
- Start;
- Cable extension compensation function;
- LCD display;
- Protection against overcharge, short circuit and polarity reversal.

Fit with PFC device.

Complete with cable with clamps.













TECHNICAL DATA



CODE 807599



CHARGING ABSORBED POWER



EFFECTIVE CHARGING CURRENT 140 / 70 A



MIN.RATED REFERENCE CAPAC. 20 Ah



DIMENSIONS (LxWxH) 20 x 26 x 34 cm



SINGLEPHASE MAINS VOLTAGE 1PH 230 V



STARTING ABSORBED POWER 2 kW



RATED CHAR.CUR.EN60335-2-29 120 / 60 A



MAX.RATED REFERENCE CAPAC. 1200 Ah



WEIGHT



MAINS FREQUENCY 50 / 60 Hz



CHARGING VOLTAGE 12 / 24 V



START CUR.1V/C EN60335-2-29 180 A



ADJUSTMENT POSITIONS

ON REQUEST ACCESSORIES

CLAMPS PATCH CORD 6M 180A (AND) 802945

CLAMPS PATCH CORD 10M 180A (And) 802946



TROLLEY - DIAGNOSTIC 803077



HOLDING BRACKET KIT 803086

DOWNLOAD





CATALOG IMAGE





www.telwin.com DOCTOR CHARGE 130 - PAG. 4/4