



ENTRUST



Sigma DS3 Direct-to-Card Printer With 375 Input and 375 Output Multi-Hopper

HIGHLIGHTS

The next generation of instant ID issuance

Entrust Sigma ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue full-color single- or dual-sided ID cards. This model's input and output hopper capabilities add flexible batch printing capabilities.

- **Simple:** From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Sigma was the most user-friendly ID card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will help protect your cards and your customers' data during each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve

KEY FEATURES & BENEFITS

The world's most advanced instant card solution

- **Multi-Hopper:** Pre-load multiple types of cards for different ID types and expand batch printing throughput (three 125-card input hoppers and three 125-card output hoppers)
- **Intuitive Printer Dashboard:** See printer status, order supplies, check cleaning status, update firmware, or contact help, all from your mobile device
- **Seamless Self-Service:** Access how-to videos and other resources by simply scanning a QR code on the LCD display
- **Variable LED Light Ring:** Incorporate brand colors or other customization into your ambient environment
- **Pre-Loaded Ribbon Cassettes:** Switch ribbons faster and easier

Learn more about the Sigma DS3 Direct-to-Card ID Printer at entrust.com



➤ Sigma DS3 Direct-to-Card Printer With 375 Input and 375 Output Multi-Hopper

Unmatched security

- Optional locks
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Security features protect from tampering and counterfeiting:
 - UV printing
 - Luster printing

Flexibility and scalability built for the future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-prem or driver deployment
- Expand your ID program as your needs change by adding multi-hopper, smart card capabilities, WiFi connectivity, and more
- Print anytime, anywhere with your mobile device (iOS, Android, Windows)



Learn more about the Sigma DS3 Direct-to-Card ID Printer at entrust.com

Sigma DS3 Direct-to-Card Printer With 375 Input and 375 Output Multi-Hopper

TECHNICAL SPECIFICATIONS

Standard Features & Supplies

Print technology	Dye sublimation
Print capabilities	Single- or dual-sided
Print resolution	300 dots per inch (dpi) (300 X 600, 300 X 1200)
Print, lamination, and tactile speed	Single-sided color ribbon (YMCKT): Up to 250 cards per hour (cph) Double-sided color ribbon (YMCKT-KT): Up to 180 cards per hour (cph) Single-sided monochrome ribbon (black HQ): Up to 1,100 cards per hour (cph)
Card capacity	Input hopper: 375 cards Output hopper: 375 cards Reject hopper: 10 card
Card sizes	Thickness: 0.010 in to 0.040 in (0.25mm - 1.016mm) Dimension: ID-1, CR-79, CR-80
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing
Physical dimensions	L 23 in x W 13.4 in x H 16.2 in (58.4 cm x 34 cm x 41.1 cm)
Weight	30 lbs (13.62 kg); varies with options
Connectivity	USB and Ethernet
Warranty	36 months



Learn more about the Sigma DS3 Direct-to-Card ID Printer at entrust.com



Sigma DS3 Direct-to-Card Printer With 375 Input and 375 Output Multi-Hopper

TECHNICAL SPECIFICATIONS

Optional Features & Supplies

Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option	
WiFi	WiFi types: 802.11g/n Authentication modes: None, WPA2 Personal Dual-band 2.4GHz and 5GHz	
Smart card encoding	Single wire or loosely coupled: • Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) • Contactless smart card encoding: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE® DESFire EV1/EV2, HID Prox, iClass, iClass SE, iClass Seos, Felica	
Color ribbons*	YMCKT	250/500 images
	ymcKT	650 images
	YMCKT-KT	350 images
	KT	1,000 images
	KTT	750 images
	YMCKF-KT	300 images
	YMCKL-KT	300 images
	ST-KT	500 images
	GT-KT	500 images
	YMCK & YMCK-KK	500 images
Monochrome ribbons	Black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic: 2,500 images	

* Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte



Learn more at
entrust.com



ENTRUST

Entrust, Sigma, and the hexagon logo are trademarks, registered trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer.
© 2024 Entrust Corporation. All rights reserved. DS24Q4-sigma-ds3-375-card-multi-hopper-ds

Global Headquarters
1187 Park Place, Minneapolis, MN 55379
U.S. Toll-Free Phone: 888 690 2424
International Phone: +1 952 933 1223