


LED Floodlight

- 10/20/30/50W Genuine replacement for Halogen Floodlights
- 70/100/150/200W Genuine replacement for Metal Halide Floodlights
- Marine Grade Aluminium body
- Fully encapsulated IP65 TUV certified driver
- PIR Over-ride function
- Average 8M detection range for PIR Floods
- Separately tested IP65 PIR



10W $\Rightarrow$  Energy Saving 91%	20W $\Rightarrow$  Energy Saving 88%	30W $\Rightarrow$  Energy Saving 88%	50W $\Rightarrow$  Energy Saving 88%		
70W $\Rightarrow$  MH Energy Saving 30%	100W $\Rightarrow$  MH Energy Saving 33%	150W $\Rightarrow$  MH Energy Saving 40%	200W $\Rightarrow$  MH Energy Saving 50%		
Quality Assured Product Warranty ¹ 5 Year	Colour Rendering Index ¹ 80	Lumens Maintenance Ratio ² L80 B10	Water & Dust Protected IP65	Impact Rating IK8	Operating Hours 50,000

Technical Specification	
Construction	Die Cast LM6 Marine Grade Aluminium body, Stainless Steel screws and fixings
Driver	BELL
LED Chip	Phillips
Input Voltage	240V
Power Factor	> 0.9
Operating Temp	-20°C - +25°C (Outdoor use only)
Standard	CE & UKCA





5 Year Silver Warranty								
Code	W	Description	Lm	Temp	Lm/W	Weight	Windage	WxHxD (mm)
10980	10	LED Floodlight	1200	4000K	120	0.3Kg	0.009M ²	112x134x31
10981	20	LED Floodlight	2400	4000K	120	0.4Kg	0.010M ²	120x142x33
10982	30	LED Floodlight	3600	4000K	120	0.5Kg	0.014M ²	136x158x34
10983	50	LED Floodlight	6000	4000K	120	0.8Kg	0.022M ²	172x200x44
10984	70	LED Floodlight	8400	4000K	120	1.1Kg	0.043M ²	229x259x48
10990	100	LED Floodlight	12000	4000K	120	3.1Kg	0.062M ²	276x318x60
10991	150	LED Floodlight	18000	4000K	120	3.8Kg	0.080M ²	300x357x60
10992	200	LED Floodlight	24000	4000K	120	5.0Kg	0.112M ²	355x410x60
10985	10	PIR LED Floodlight	1200	4000K	120	0.4Kg	0.009M ²	112x176x68
10986	20	PIR LED Floodlight	2400	4000K	120	0.5Kg	0.010M ²	120x185x68
10987	30	PIR LED Floodlight	3600	4000K	120	0.6Kg	0.014M ²	137x200x72
10988	50	PIR LED Floodlight	6000	4000K	120	1.0Kg	0.022M ²	172x239x72
10989	70	PIR LED Floodlight	8400	4000K	120	1.2Kg	0.043M ²	229x300x72
10995	50	Asymmetric LED Floodlight	6000	4000K	120	0.8Kg	0.044M ²	194x231x48
10996	70	Asymmetric LED Floodlight	8400	4000K	120	1.1Kg	0.074M ²	235x315x60
10977	100	Asymmetric LED Floodlight	11000	4000K	110	3.2Kg	0.062M ²	277x315x60
10978	150	Asymmetric LED Floodlight	16500	4000K	110	3.8Kg	0.080M ²	302x351x60
10979	200	Asymmetric LED Floodlight	22000	4000K	110	5.0Kg	0.112M ²	352x408x60