

1. Before your start


Which mode do you need? Please refer to the table to choose a proper mode.

Scenarios	Operating Modes
Local connection to the Flexit Nordic-/EcoNordic-product if no network is available	Access Point Mode (Default Mode)
Connect the Flexit Nordic-/EcoNordic-product to a wireless network if no wired (Ethernet) connection is possible	Client Mode

2. Configure the Access Point

2.1. ACCESS POINT MODE (DEFAULT)


Local connection to your Flexit Nordic-/EcoNordic-product if no network exist.



1. Connect the access point according to Step A to D in the diagram.
2. Power on the access point, wait until the Power (⏻) and Wireless (📶) LEDs are lit and stable, and use the default SSID and Password printed on the label of the access point to join its Wi-Fi network.
3. Connect to the Flexit Nordic-/EcoNordic-product using the Flexit Go App on your mobile device

2.2. CLIENT MODE

Connects your Flexit Nordic-/EcoNordic-product to a wireless network.




1. Connect the access point according to Step A to D in the diagram.
2. Power on the access point, wait until the Power (⏻) and Wireless (📶) LEDs are lit and stable.
3. Use standard and the password on the label under the access point to connect to the Wi-Fi network to your mobile device/PC.
4. Launch a web browser and enter 192.168.0.254. Then log in using admin (all lowercase) for both username and password.
5. Click Quick Setup and click Next.
6. Change Login Password if you want and then click Next.
7. Select Client mode and click Next. Follow the step-by-step instructions to complete the configuration.
8. Now your Flexit Nordic-/EcoNordic-product is connected to internet.

2.3. POWER ON VIA POE INJECTOR

Power the device with the included passive PoE injector when the access point is located far from a power outlet.



Note: The passive PoE injector supports a cable length up to 30 meters, but the value may vary due to the environment.



3. Technical data

3.1. DIMENSIONS

Overall dimensions (h x w x d): 36 x 181 x 125 mm
Weight: ± 0,20 kg

3.2. AMBIENT CONDITIONS

Operating Temperature Range: 0 to 40 °C
Shipping & Storage Temperature Range:
-40 to 70°C
Relative Humidity: 10 - 90%, non-
condensing

3.3. ELECTRICAL SPECIFICATION

Mains Power Source: 9 V DC
Maximum power consumption: 0,6 A

3.4. WIRELESS CONNECTION SPECIFICATIONS

Communication frequency: 2,4 GHz
Communication standards: IEEE 802.11n,
IEEE 802.11g,
IEEE 802.11b

*Our products are subject to continuous development and we
therefore reserve the right to make changes.
We also disclaim liability for any printing errors that may occur.*



Flexit AS, Televeien 15, N-1870 Ørje
www.flexit.no