



# SmartBright LED Panel RC048 G3

RC048B LED42S/865 100-277 W62L62 LA

Power supply unit, White

The SmartBright LED Panel is the most economical LED solution that provides reliable and qualified lighting in work areas within a long lifetime, creating a brighter and healthier office environment.

### Warnings and Safety

- For indoor use only
- The luminaire must not be used or stored in a corrosive environment where hazardous materials such as sulfur, chlorine, thalates, etc. are present

### Product data

General Information	
Light source replaceable	No
Driver included	Yes
Light Technical	
Luminous Flux	4,260 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	125 lm/W
Color rendering index (CRI)	≥80
Operating and Electrical	
Input Voltage	100 to 277 V
Line Frequency	50 or 60 Hz
Inrush current	10.24 A

Inrush time	0.027 ms
Power Consumption	34 W
Power Factor (Fraction)	0.9
Connection	Connection unit 2-pole
Cable	-
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum

SmartBright LED Panel RC048 G3

Housing Color	White
Overall height	34 mm
Ingress protection code	IP20/40 [Finger-protected;Wire-protected]
Net Weight (Piece)	1.450 kg

Approval and Application

Ambient temperature range	-10 to +35 °C
---------------------------	---------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L70B50	50,000 hour(s)
---------------------------	----------------

Product Data	
Order product name	RC048B LED42S/865 100-277 W62L62 LA
Full product name	RC048B LED42S/865 100-277 W62L62 LA
Full product code	872016951370999
Order code	911401857885
Material Nr. (12NC)	911401857885
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169513709
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169513785

