



Your **definitive** source
for quality pre-owned
equipment.

Artisan Technology Group

(217) 352-9330 | sales@artisanng.com | artisanng.com

Full-service, independent repair center

with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment

along with credit for buybacks and trade-ins.

Custom engineering

so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Instek GPD-3303S* at our website: ***Click HERE***

MULTIPLE OUTPUT PROGRAMMABLE LINEAR D.C. POWER SUPPLY



GPD-3303S/3303D




The GPD-3303S / GPD-3303D series inherits the superior technology and high quality, which GW Instek has established through its long history of power supply design and manufacturing. The GPD-3303S / GPD-3303D series provides 195W output power, three isolated output channels, high resolution output (GPD-3303S), digital control panel, 4 sets of setup memory, USB remote control, smart cooling fan control, high reliability, and compact size. The GPD-3303S / GPD-3303D establish a new benchmark for economic programmable linear D.C. power supply market segment. The most remarkable feature of this series product with minimum 1mV / 1mA resolution of GPD-3303S, which right fits into the applications needing accurate control of power source.GPD-3303D, another member of the family, is considered a digitally-upgraded version of GPS-3303. Besides the same power output features and the common specifications of GPS-3303, that GPD-3303S / GPD-3303D has a bigger display for Voltage and Current readings, a digital panel, and a USB port, which lifts up the product to a programmable device at a little additional cost.

FEATURES


- * Three Independent Output : (30V/3A x 2),(2.5V/3.3V/5V)/3A x 1 (Fixed)
- * 4 LED Display Sets : 3 Digits After Decimal Point
- * Minimum Resolution : 1mV/1mA(GPD-3303S),100mV/10mA(GPD-3303D)
- * Digital Panel Control (Rotary Encoder Switch, Rubber Key With Indicator)
- * User-Friendly Operation, Coarse/Fine Volume Control
- * 4 Sets Save/Recall
- * Key-Lock
- * Warning Buzzer
- * Output ON/OFF
- * Tracking Series and Parallel Mode
- * Smart Cooling Fan Achieving Low Noise
- * Compact Design

SPECIFICATIONS			
		GPD-3303S	GPD-3303D
OUTPUT			
Voltage		0~30.0V x 2 , 2.5V/3.3V/5.0V x 1	
Current		0~3.0A x 2 , 3.0A (Fixed)	
CONSTANT VOLTAGE OPERATION			
Regulation		Line regulation $\leq 0.01\%+3mV$ Load regulation $\leq 0.01\%+3mV$ (rating current $\leq 3A$) $\leq 0.02\%+5mV$ (rating current $>3A$)	
Ripple & Noise		$\leq 1mVrms$ (5Hz~1MHz)	
Recovery Time		$\leq 100 \mu s$ (50%Load change, Minimum load 0.5A)	
Temp.Coefficient		$\leq 300ppm / ^\circ C$	
Output Range		0 to rating voltage continuously adjustable	
CONSTANT CURRENT OPERATION			
Regulation		Line regulation $\leq 0.2\%+3mA$ Load regulation $\leq 0.2\%+3mA$	
Ripple Current		$\leq 3mA$ rms	
Output Range		0 to rating current continuously adjustable	
TRACKING OPERATION			
Regulation of PAR.		Line regulation $\leq 0.01\%+3mV$ Load regulation $\leq 0.01\%+3mV$ (rating current $\leq 3A$) $\leq 0.02\%+5mV$ (rating current $>3A$)	
Regulation of SER.		Line regulation $\leq 0.01\%+5mV$ Load regulation $\leq 300mV$ Tracking error $\leq 0.5\%\pm 10mV$ (10 ~ 30V no load) $\leq 0.5\%\pm 30mV$ (0 ~ 9.99V no load) with load added $\leq 300mV$ with load added $\leq 300mV$	
Tracking error		$\leq 0.5\% + 10mV$	$\leq 0.5\% + 50mV$
METER			
Display		Voltage : 4 3/4 digits 0.4" LED Display Current : 3 3/4 digits 0.4" LED Display	Voltage : 2 3/4 digits 0.4" LED Display Current : 2 3/4 digits 0.4" LED Display
Resolution		Voltage : 1mV Current : 1mA	Voltage : 100mV Current : 10mA
Program accuracy(25 \pm 5 $^\circ$ C)		Voltage : $\pm(0.03\%$ of RDG +10 digits) Current : $\pm(0.3\%$ of RDG +10 digits)	Voltage : $\pm(0.5\%$ of RDG +2 digits) Current : $\pm(0.5\%$ of RDG +2 digits)
Readback accuracy(25 \pm 5 $^\circ$ C)		Voltage : $\pm(0.03\%$ of RDG +10 digits) Current : $\pm(0.3\%$ of RDG +10 digits)	Voltage : $\pm(0.5\%$ of RDG +2 digits) Current : $\pm(0.5\%$ of RDG +2 digits)
CH3 SPECIFICATIONS			
Output Voltage		(2.5V/3.3V/5V) $\pm 8\%$	
Output Current		3A	
Regulation(25 \pm 5 $^\circ$ C)		Line regulation $\leq 5mV$ Load regulation $\leq 15mV$	
Repple & Noise		$\leq 2mVrms$	
KEY LOCK			
Yes			
MEMERY SAVE/RECALL			
4 sets			
POWER SOURCE			
AC100V/120V/220V/230V $\pm 10\%$, 50/60Hz			
DIMENSION & WEIGHT			
210(W) x 130 (H) x 265(D) mm ; Approx. 7kg			



GPD-3303S

Rear Panel



ORDERING INFORMATION

- GPD-3303S** Multiple Output High Resolution Programmable Linear D.C. Power Supply
GPD-3303D Multiple Output Programmable Linear D.C. Power Supply

- ACCESSORIES :
User Manual x1
Power cord x1
Test lead GTL-104 x 2, GTL-105 x 1
European Test Lead GTL-203 x 1 , GTL-204 x 2

Optional Accessories

- GTL-246** USB Cable

MULTIPLE OUTPUT PROGRAMMABLE LINEAR D.C. POWER SUPPLY



GPD-3303S/3303D




The GPD-3303S / GPD-3303D series inherits the superior technology and high quality, which GW Instek has established through its long history of power supply design and manufacturing. The GPD-3303S / GPD-3303D series provides 195W output power, three isolated output channels, high resolution output (GPD-3303S), digital control panel, 4 sets of setup memory, USB remote control, smart cooling fan control, high reliability, and compact size. The GPD-3303S / GPD-3303D establish a new benchmark for economic programmable linear D.C. power supply market segment. The most remarkable feature of this series product with minimum 1mV / 1mA resolution of GPD-3303S, which right fits into the applications needing accurate control of power source.GPD-3303D, another member of the family, is considered a digitally-upgraded version of GPS-3303. Besides the same power output features and the common specifications of GPS-3303, that GPD-3303S / GPD-3303D has a bigger display for Voltage and Current readings, a digital panel, and a USB port, which lifts up the product to a programmable device at a little additional cost.

FEATURES

- * Three Independent Output : (30V/3A x 2),(2.5V/3.3V/5V)/3A x 1 (Fixed)
- * 4 LED Display Sets : 3 Digits After Decimal Point
- * Minimum Resolution : 1mV/1mA(GPD-3303S),100mV/10mA(GPD-3303D)
- * Digital Panel Control (Rotary Encoder Switch, Rubber Key With Indicator)
- * User-Friendly Operation, Coarse/Fine Volume Control
- * 4 Sets Save/Recall
- * Key-Lock
- * Warning Buzzer
- * Output ON/OFF
- * Tracking Series and Parallel Mode
- * Smart Cooling Fan Achieving Low Noise
- * Compact Design

SPECIFICATIONS			
		GPD-3303S	GPD-3303D
OUTPUT			
Voltage		0~30.0V x 2 , 2.5V/3.3V/5.0V x 1	
Current		0~3.0A x 2 , 3.0A (Fixed)	
CONSTANT VOLTAGE OPERATION			
Regulation		Line regulation ≤ 0.01%+3mV Load regulation ≤ 0.01%+3mV(rating current≤ 3A) ≤ 0.02%+5mV(rating current >3A)	
Ripple & Noise		≤ 1mVrms (5Hz~1MHz)	
Recovery Time		≤100 μ S (50%Load change, Minimum load 0.5A)	
Temp.Coefficient		≤300ppm / °C	
Output Range		0 to rating voltage continuously adjustable	
CONSTANT CURRENT OPERATION			
Regulation		Line regulation≤ 0.2%+3mA Load regulation≤ 0.2%+3mA	
Ripple Current		≤3mA rms	
Output Range		0 to rating current continuously adjustable	
TRACKING OPERATION			
Regulation of PAR.		Line regulation ≤ 0.01%+3mV Load regulation≤ 0.01%+3mV (rating current≤ 3A) ≤ 0.02%+5mV (rating current >3A)	
Regulation of SER.		Line regulation ≤ 0.01%+5mV Load regulation≤ 300mV Tracking error ≤ 0.5%±10mV (10 ~ 30V no load) with load added ≤ 300mV ≤ 0.5%±30mV (0 ~ 9.99V no load) with load added ≤ 300mV)	
Tracking error		≤ 0.5% + 10mV	≤ 0.5% + 50mV
METER			
Display		Voltage : 4 3/4 digits 0.4" LED Display Current : 3 3/4 digits 0.4" LED Display	Voltage : 2 3/4 digits 0.4" LED Display Current : 2 3/4 digits 0.4" LED Display
Resolution		Voltage : 1mV Current : 1mA	Voltage : 100mV Current : 10mA
Program accuracy(25±5℃)		Voltage : ±(0.03% of RDG +10 digits) Current : ±(0.3% of RDG +10 digits)	Voltage : ±(0.5% of RDG +2 digits) Current : ±(0.5% of RDG +2 digits)
Readback accuracy(25±5℃)		Voltage : ±(0.03% of RDG +10 digits) Current : ±(0.3% of RDG +10 digits)	Voltage : ±(0.5% of RDG +2 digits) Current : ±(0.5% of RDG +2 digits)
CH3 SPECIFICATIONS			
Output Voltage		(2.5V/3.3V/5V)±8%	
Output Current		3A	
Regulation(25±5℃)		Line regulation ≤5mV Load regulation ≤15mV	
Repple & Noise		≤2mVrms	
KEY LOCK			
Yes			
MEMERY SAVE/RECALL			
4 sets			
POWER SOURCE			
AC100V/120V/220V/230V±10%, 50/60Hz			
DIMENSION & WEIGHT			
210(W) x 130 (H) x 265(D) mm ; Approx. 7kg			



GPD-3303S

Rear Panel



ORDERING INFORMATION

- GPD-3303S** Multiple Output High Resolution Programmable Linear D.C. Power Supply
GPD-3303D Multiple Output Programmable Linear D.C. Power Supply

- ACCESSORIES :
User Manual x1
Power cord x1
Test lead GTL-104 x 2, GTL-105 x 1
European Test Lead GTL-203 x 1 , GTL-204 x 2

Optional Accessories

- GTL-246** USB Cable

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at [artisan^{tg}.com](https://www.artisantg.com) for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisan^{tg}.com | [artisan^{tg}.com](https://www.artisantg.com)

