

# 1 Arm Cam Kit 9"

Single View 3 Channel 9" HD Monitor, 1 Arm Camera with Clamp Kit  
**JB-1A9D**

## Monitor

This 9" TFT LCD Digital 3-Channel Single View Color Monitor is capable of connecting and viewing up to 3 cameras. The Single View Color Monitor comes with built-in speakers and distance grid lines.



- Single View, can connect up to 3 Analog FHD cameras
- Built-in speakers for audio
- Adjustable distance grid lines for backing up reference
- Switch between mirror/normal image for any camera attached

Monitors Specs	
Screen Type	9" TFT LCD
Camera Input	3 Channel
Dot Resolution	1024 X 600 (RGB)
Aspect Ratio	16 x 9
Contrast	800
Spot Distance	0.1506 (H) x 0.1432 (V) mm
Refresh Frequency	50Hz(P) 60Hz(N)
Color Display	RGB Stripe
Brightness	400cd/m2
Field of View	L:85 R:85 U:85 D:85
Video Impedance	1VP-P 75Ω
Video System	PAL/NTSC
Frame Rate	25/30 fps
Mirror Function	Normal/Mirror (Left and right mirroring, up and down mirroring, individually)
Screen Mode	Single View
Trigger Mode	3-way hardwired trigger
Language	OSD 9 languages
Video Input	AHD/1080P, AHD/720P, CVBS
Operating Voltage	Rated: 24V, range: 9V~32V
Operating Current	≤ 200mA/24V (without camera)
Operating Temperature/Humidity	-20°C ~ +70°C / 45%~75%
Storage Temperature	-30°C ~ +85°C
Vibration Rating	3G
Dimensions/Weight	7.25" (H) x 9" (L) x 1.25" (D) / 400g



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233  
800.764.1028 RVS.Sales@safefleet.net  
[www.rearviewsafety.com](http://www.rearviewsafety.com)



SAFE FLEET  
Driving Safety Forward™

# Arm Camera with Clamp

Keep it simple with the truck Arm Camera. The CA-ARMG1H is designed to fit this onto the arm bracket of your truck, no drilling to attach the camera is necessary! This camera is equipped with a wide 120° viewing angle, a 2.8mm lens and 10 infra-red lights for excellent night vision. Completely waterproof with a IP68 rating, this camera also has a 10G vibration rating. This camera comes with two different clamp sizes. The larger clamp set has a maximum diameter of 4" and minimum diameter of 3". The smaller clamp set has a maximum diameter of 1.25" and a minimum diameter of 1"



## CONVENIENT INSTALLATION

Easily fits onto the arm bracket of various trucks

## SIMPLE INSTALL

No drilling necessary to mount the camera.

## 120° VIEWING ANGLE

With an ultra-wide viewing angle, and 2.8mm lens the side camera will provide a complete view from sides of your vehicle to ensure complete safety with no blind spots

## NIGHT VISION

10 infra-red lights support excellent night vision

## COMMERCIAL GRADE

Completely waterproof camera with IP68 rating

Camera Specs	
<b>Model</b>	CA-ARMG1H
<b>Sensor</b>	2MP pixel , 1/2.8" CMOS sensor
<b>Maximum frame rate</b>	PAL:25fps/s NTSC:30fps/s
<b>Min Illumination</b>	1920 (H) × 1080 (V)
<b>Electronic Shutter</b>	Auto:PAL 1/50s(NTSC 1/60s)~1/100,000s
<b>Backlight Compensation</b>	Auto
<b>Signal to Noise ratio</b>	Better than 39dB
<b>Audio output</b>	Optional
<b>IR Distance</b>	5M
<b>Focus</b>	2.8MM M12,fix aperture F2.0, HFOV 120°
<b>Waterproof grade</b>	IP69
<b>Material</b>	Metal & Plastic
<b>Installation Placement</b>	Side of the Vehicle - Side Mirror Bracket
<b>Operating Temperature</b>	-30°C ~ +70°C
<b>Working Relative Humidity</b>	20% - 80%
<b>Powered by</b>	DC 12V ±10%
<b>Weight</b>	400g

