




OCR-B/ MRZ & PDF417 READER



 1D	 2D	 POSTAL	 CMOS
 OCR	 RS-232	 USB	 Laser Aimer

❖ **Read OCR-B/ MRZ From Passport, ID Card**

Equipped with Megapixel 1280*800 high-resolution CMOS image sensor, this enables the IDE302 with great performance (quick and accurate) to read the long MRZ (machine readable zone) in passport and 3 lines MRZ in ID card, driver's license.

❖ **Read Big Size PDF417 From ID Card**

Thanks to its 1280*800 high resolution sensor, the IDE302 is readable those big size and high-density PDF417 code from ID card / driver' license, e.g: IDs of El Salvador, Costa Rica, Colombia, Paraguay, Vietnam, Nicaragua, Panamá, Egypt, South Africa...



Performance	Image Sensor	1280 * 800 CMOS	
	Illumination	White LED	
	Aiming	650nm Laser diode	
	Symbologies	OCR-B/ MRZ	Machine readable passports (MRP) : 2 lines of 44 characters (Readable distance: 15cm-30cm) Travel documents: 3 lines of 30 characters (Readable distance: 14cm-30cm) The best read distance is around 20cm.
		2D QR PDF417	PDF417in ID documents (Readable distance: 10cm-20cm), QR Code, Data Matrix, AZTEC, CSC, Maxicode, Micro QR, Micro PDF417, GM ,Code One, etc.
		1D	EAN-13, EAN-8, UPC-A, UPC-E, Code128, Code 39, Codabar, UCC/EAN 128, RSS, ITF, ITF-14, ITF6, Standard25, Matrix 25, COOP 25, Industrial 25, Plessey, MSI Plessey, Code 11,Code 93, Code 49, Code 16K, etc.
	Resolution	≥3mil (differ from different type bar codes)	
	Typical Depth of Field	EAN-13	70-499mm (13mil)
		Code 39	90-264mm (5mil)
		PDF417	70-225mm (6.7mil)
		Data Matrix	65-214mm (10mil)
		QR Code	40-294mm (15mil)
	Scan Mode	Sense mode, Trigger mode	
	Scan Angle	Roll: 360°, Pitch: ±61°, Skew:±61°	
	Field of View	Horizontal 43°, Vertical 29°	
	Min. Symbol Contrast	25%	
Mechanical/ Electric	Interface	RS-232, USB	
	Dimensions	180mm×80mm×90mm	
	Weight	194g	
	Notification	Beep, LED indicator	
	Operating Power	5VDC±5%, 280mA, it must reach 900mA to active the scanner, so please make sure y our system provide 900mA above current.	
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)	
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)	
	Humidity	5% to 95% (non-condensing)	
Accessories	Cable	USB	USB virtual Com, not support USB-HID
		RS-232	Standard DB9 RS232 interface
	Power Adapter	DC5V adapter to power the IDE302 for RS-232 interface.	



Tel: +86 755-23762089

Website: www.rtscan.net Email: info@rtscan.net

410, Building 10, Cloud valley Phase II, Pingshan 1st Rd, 518055, Xi'Li, Nanshan District, Shenzhen, China

Copyright RTscan Technology Limited all rights reserved. IDEPASS and RTscan are registered trademark of RTscan Technology Limited. All other trademarks are the property of their respective owners. In a continuing effort to improve our products, RTscan Technology Limited reserves the right to change specifications and features without prior notice.