

PPL Product and price list 2021

Price adjustment from 01.06.2021 + 5 %



# What can we do for you?

### CLAGE GmbH

Pirolweg 4 21337 Lüneburg Germany

Phone: +49(0)41318901-888

export@clage.de www.clage.com

### Product and price list 2021

This list contains gross price values for specialist retailers excluding applicable VAT. Valid from 1 January 2021 until a new price list is published. Due to rising raw material and logistics costs we are forced to charge a surcharge of +5% on orders from 01.06.2021. The price adjustment applies to the entire product range and must be added to the quoted prices.

This price list supersedes any previous price lists, which become invalid upon its publication. The information provided here is subject to change due to technical modifications to products. Errors and omissions excepted. Deliveries are subject to our sales and delivery terms.

All prices are provided on an ex works basis in normal packaging. We minimise the packaging material we use in an effort to protect the environment. Therefore please make your orders in the specified packaging units: UPP = unit per pallet/number of items per layer for mixed pallets, PU = packaging unit.

CLAGE GmbH is certified under:

DIN EN ISO 9001:2015 Quality management
DIN EN ISO 14001:2015 Environmental management

Hygiene certificate for the production of instant water heaters

CLAGE has been climate neutral according to Scope 1 and 2 since 2021 through continuous energy saving, use of renewable energies and  $\mathrm{CO}_2$  compensation through a certified climate protection project.

### Table of contents




E-mini instant water heaters	Storage water heaters	
Series M, electronic.  Series M, hydraulic  Sets  Accessories  Hand dryer	.5 Storage water heaters 10 to 15 litres	
E-compact instant water heaters	Boiling water heaters	
Series C, undersink	10 Accessories	
E-comfort instant water heaters	Water systems Same	
Series D	F / F	3
Taps စု	Apartment transfer stations	
aps for washbasins	18 19 20	3
Smart Control	> At a glance	4
Remote controls, Home Server, Accessories	> General Terms and Conditions of Sale and Delive	<b>ery</b> . 4

# E-mini instant water heaters, electronic

Matching taps > Price list from page 16 onwards







EUR EAN excl. number 4010436... VAT \* Type Power rating

### **MCX**

Electronically controlled E-mini instant water heater, unvented design, with effective and easymaintenance heating system IES®, for convenient hot water supply to one tap, replaceable heating cartridge, sensor button and three colour LEDs for setting the maximum outlet temperature to three levels: 35 °C, 38 °C and 45 °C, removable panel for access to the hood screw, suitable for reheating pre-warmed water (e.g. solar collector), neatly integrated wall bracket for easy push-on installation, supplied complete with aerator and connection kit with T-piece % inch and pressure hose % inch × 50 cm for easy installation with standard washroom taps, IP 25.

Dimensions (h  $\times$  w  $\times$  d): 13.5  $\times$  18.6  $\times$  8.7 cm

MCX3	3.5 kW 220 - 240 V, 1 ~, with plug	1500-15003	15003 9	244.00
MCX4	4.4 kW 220 - 240 V, 1 ~, perm. connection, 19 A	4 1500-15004	150046	249.00
MCX 6	5.7 kW 220 - 240 V, 1 ~, perm. connection, 25 A	A 1500-15006	150060	260.00
MCX7	6.5 kW 400 V, 2 ~, perm. connection, 16 A	1500-15007	15007 7	260.00

Retail box: 18.6 × 23.3 × 13.2 cm / 1.78 kg









### MCX Blue with tap EWT

Electronically controlled E-mini instant water heater MCX combined with an innovative single-lever mixer tap for energy efficient hand-washing, intuitive operation with perfect water temperature at the mixing position of the control lever, saves water because of intelligent flow technology and very short water supply lines, meets the highest requirements for drinking water hygiene by separating water lines from the tap body as well as nickel and lead-free materials, especially easy installation and maintenance thanks to EASY FIX mounting system with pull-up drain stopper, IP 25.

Dimensions without tap (h × w × d):  $13.5 \times 18.6 \times 8.7$  cm

MCX Blue	3.5 kW	220 - 240 V, 1 ~, with plug	1500-15133	151333	390.00
Retail box: 10 × 24 × 60 cm / 3.9 kg				UPP = 3	30/6, PU = 7



Electronically controlled E-mini instant water heater combined with a touch-free sensor tap for energy efficient and hygienic hot water supply at a washbasin. An infrared touch-free sensor at the tap automatically turns the instant water heater on. Temperature adjustment up to 42 °C using the side lever at the tap, colour LED ring indicates temperature in continuous colours from blue - white - red, with optional hygiene flush (automatic flush every 12 or 24 hours), connecting hose % inch × 50 cm, IP 25. The tap requires a separate power socket (230 V/16 A) for the additional electrical connection of the instant water heater. Dimensions without tap (h  $\times$  w  $\times$  d): 13.5  $\times$  18.6  $\times$  8.7 cm

MBX 3 Lumino 3.5 kW	220 – 240 V, 1 ~, with plug	1500-15113	15113 5	835.00
MBX 7 Lumino 6.5 kW	400 V, 2 ~, perm. connection, 16 A	1500-15117	15117 3	849.00
Retail box: 10 × 25 × 54.5 cm / 3.5 kg			30/6, PU = 7	

### \* Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

### E-mini instant water heaters, hydraulic

Matching taps > Price list from page 16 onwards

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT *



Energy efficiency class (Scale: A+ to F)

### **MBH**

Hydraulically controlled E-mini instant water heater, unvented design, with effective heating system  ${\sf IES}^{\tiny{\textcircled{0}}}, \text{ with safety temperature limiter, for supply to one tap (preferably at washbasin), removable panel}$ for access to the hood screw, replaceable heating cartridge, neatly integrated wall bracket for easy push-on installation, supplied complete with aerator and connection kit with T-piece % inch and pressure hose % inch × 50 cm for easy retrofitting on existing conventional fittings, power cable, IP 25. Dimensions (h  $\times$  w  $\times$  d): 13.5  $\times$  18.6  $\times$  8.7 cm

MBH 3	3.5 kW	230 V, 1 ~, with plug	1500-16003	160038	181.00
MBH 4	4.4 kW	230 V, 1 ~, perm. connection, 19 A	1500-16004	160045	181.00
MBH 6	5.7 kW	230 V, 1 ~, perm. connection, 25 A	1500-16006	16006 9	193.00
MBH 7	6.5 kW	400 V, 2 ~, perm. connection, 16 A	1500-16007	160076	193.00
Retail box: 18.6 × 23.3 × 13.2 cm / 1.8 kg PE = 100/20, PU = 10					



Energy efficiency class A


Hydraulically controlled E-mini instant water heater, vented design, with effective, easy-maintenance heating system IES®, for supply to one tap (preferably at washbasin) in connection with an open-outlet tap, removable panel for access to the hood screw, replaceable heating cartridge, neatly integrated wall bracket for easy push-on installation, aerator and power cable included, IP 25. Dimensions (h  $\times$  w  $\times$  d): 13.5  $\times$  18.6  $\times$  8.7 cm

M 3	3.5 kW	230 V, 1 ~, with plug	1500-17003	17003 7	123.00
M 4	4.4 kW	230 V, 1 ~, perm. connection, 19 A	1500-17004	17004 4	126.00
M 6	5.7 kW	230 V, 1 ~, perm. connection, 25 A	1500-17006	17006 8	142.00
M 7	6.5 kW	400 V, 2 ~, perm. connection, 16 A	1500-17007	17007 5	142.00

Retail box: 18.6 × 23.3 × 13.2 cm / 1.74 kg

PF = 100/20 PU = 10





### M-O

Hydraulically controlled E-mini instant water heater as an oversink unit, vented design, with effective, easy-maintenance heating system IES®, for supply to one tap in connection with special tap SMB or SME, removable panel for access to the hood screw, replaceable heating cartridge, two different wall brackets for easy push-on installation, aerator and power cable included, IP 25. Dimensions (h × w × d): 13.5 × 18.6 × 8.7 cm

M 3-O	$3.5  \text{kW}$ $230  \text{V}$ , $1 \sim$ , with plug	1500-17113	17113 3	126.00
M 4-O	4.4 kW 230 V, 1 ~, perm. connection, 19 A	1500-17114	171140	126.00
M 6-O	5.7 kW 230 V, 1 ~, perm. connection, 25 A	1500-17116	17116 4	142.00
M7-O	6.5 kW 400 V, 2 ~, perm. connection, 16 A	1500-17117	17117 1	142.00

Retail box: 18.6 × 23.3 × 13.2 cm / 1.76 kg UPP = 100/20 PU = 10

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

# E-mini instant water heater sets with matching taps

Type Power rating FAN EAN excl.
Type Power rating number 4010436... VAT \*\*



### M/END

Hydraulically controlled E-mini instant water heater M 3 set with open-outlet tap (single-lever mixer tap) for undersink installation. Single-lever washbasin tap with EASY FIX mounting system and pull-up drain stopper, outlet  $10.5\,\mathrm{cm}$ .

M3/END	3.5 kW 230 V, 1 ~, with plug	1500-17243	17243 7	189.00
Retail box: 18.6	5 × 23.3 × 21.1 cm / 3.9 kg PE = 100/		0/20, PU = 9	



### M/SNM

Hydraulically controlled E-mini instant water heater M 3 set with open-outlet tap (two-handle mixer tap) for undersink installation.

M3/SNM	3.5 kW	230 V, 1 ~, with plug	1500-17203	17203 1	142.00
Retail box: 18.6 ×	23.3 × 21.1 c	m / 2.74 ka		PE = 100	/20. PU = 12



### M/SMB

Hydraulically controlled E-mini instant water heater M as an oversink unit combined with a mixer tap for wall connection ½ inch, outlet 16 cm.

M3/SMB	3.5 kW	230 V, 1 ~, with plug	1500-17103	17103 4	142.00
M4/SMB	4.4 kW	230 V, 1 ~, perm. connection, 19 A	1500-17104	17104 1	187.00
M7/SMB	6.5 kW	400 V, 2 ~, perm. connection, 16 A	1500-17107	17107 2	203.00

Retail box: 18.6 × 23.3 × 21.1 cm / 2.9 kg PE = 100/20, PU = 12



### MBX Shower

Electronically controlled E-mini instant water heater as an oversink unit combined with shower mixer tap for  $\frac{1}{2}$  inch wall connection, pipe extensions 60 cm, shower fitting with chrome shower head and limescale prevention insert including wall rail.

MBX 4 Shower	4.4 kW	220 - 240 V, 1 ~, perm. connection, 19 A	1500-15314	15314 6	310.00
MBX 6 Shower	5.7 kW	220 - 240 V, 1 ~, perm. connection, 25 A	1500-15316	153160	321.00
MBX 7 Shower	6.5 kW	400 V, 2 ~, perm. connection, 16 A	1500-15317	153177	323.00
Retail box: 24 × 65 × 11.5 cm / 3.5 kg UPP = 50/5, PU = 6				50/5, PU = 6	



<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Accessories for E-mini instant water heaters

	Туре	Power rating	Part number	EAN 401043	EUR excl. 36 VAT *
	<b>FVS</b> Flexible co	nnecting hose ¾ inch cap nut × ¾ inch o	cap nut, 50 cm long		
	FVS	25×31cm/0.11kg	89620	896203	8.00 PU = 10
	T-piece	siece % inch cap nut × % inch angle valve	10 mm		
- 1	T-piece	nece /8 inch cap hat ^ /8 inch angle valve	89610	89610 4	13.00
_		11 × 17.5 cm / 0.09 kg	0,010		PU = 10

# Hand dryer

Туре	Power rating	Part number	EAN 4010436	EUR excl. VAT



### νыт

Hand dryer with electronic infrared sensor for touch-free, fully automatic activation. Integrated mounting plate and anti-theft protection thanks to cover plate, with plug, IP 23. Dimensions ( $h \times w \times d$ ):  $30.4 \times 26.8 \times 18.2$  cm

THT 1.0 kW 220 – 240 V, 1 ~, with plug 7000-70300 70300 6 **287.00** 

Retail box: 21.5 × 32.5 × 35 cm / 3.9 kg

6 < Product and price list PPL 2021 (information subject to change) > 7

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# E-compact instant water heaters, undersink

Matching taps > Price list from page 16 onwards

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT *



### CFX-U

Electronically controlled E-compact instant water heater as undersink unit with wireless remote control for energy efficient hot water supply to one or two taps such as one kitchen sink or two washbasins. Temperature adjustment  $20\,^{\circ}\text{C}$  to  $60\,^{\circ}\text{C}$  using bidirectional wireless remote control. Effective heating system IES®, unvented design, suitable for reheating pre-warmed water (e.g. solar collector). Supplied complete with connection kit including T-piece  $\frac{3}{2}$  inch and pressure hose  $\frac{3}{2}$  inch  $\times$  50 cm for easy installation with conventional tap. With power cable, external water connectors  $\frac{3}{2}$  inch for unvented or vented installation, IP 24.

Dimensions (h × w × d): 29.4 × 17.7 × 10.8 cm

CFX-U	11/13.5 kW	380 – 415 V, 3 ~, perm. connection	2400-26313	26313 5	333.00
Retail hox: 39	× 23 5 × 14 5 cm / 3 0 k		PF = 8	0/10 PU = 8	



### Matching taps:





Energy efficiency class (Scale: A+ to F)

### CEX-U

Electronically controlled E-compact instant water heater as undersink unit for energy efficient hot water supply to one or two taps such as one kitchen sink or two washbasins. Temperature adjustment 20 °C to 60 °C using push-button controls with LCD indicator, two programmable preset buttons. Effective heating system IES®, unvented design, suitable for reheating pre-warmed water (e.g. solar collector). Supplied complete with connection kit including T-piece ¾ inch and pressure hose ¾ inch × 50 cm for easy installation with conventional tap. With power cable, external water connectors ¾ inch for unvented or vented installation. IP 24.

Dimensions (h  $\times$  w  $\times$  d): 29.4  $\times$  17.7  $\times$  10.8 cm

CEX-U	11/13.5 kW	380-415 V, 3 ~, perm. connection	2400-26213	26213 8 <b>281.00</b>
CEX 7-U	6.9 kW	380 - 415 V, 3 ~, perm. connection	2400-26224	26224 4 <b>281.00</b>
Retail hox: 39 × 23 5 × 14 5 cm / 3.1 kg				UPP = 80/10 PU = 8





### CEX 9-U

Electronically controlled E-compact instant water heater as undersink unit for energy efficient hot water supply to one or two taps such as one kitchen sink or two washbasins (in countries with suitable power supply). Temperature adjustment  $20\,^{\circ}\text{C}$  to  $55\,^{\circ}\text{C}$  using push-button controls with LCD indicator, two programmable preset buttons. Effective heating system IES®, unvented design, suitable for reheating pre-warmed water (e.g. solar collector). External water connectors ½ inch for unvented or vented installation, IP 24. Dimensions (h × w × d):  $29.4 \times 17.7 \times 10.8 \, \text{cm}$ 

CEX 9-U					
	6.6/8.8 kW	220 - 240 V, 1 ~, perm. connection	2400-26249	26249 7	281.00
(Export)					

Retail box: 40 × 23.8 × 14.7 cm / 2.8 kg UPP = 80/10, PU = 8

# E-compact instant water heaters, undersink

Matching taps > Price list from page 16 onwards

Туре	Power rating	Part number	EAN 4010436	excl. VAT *
 CDX-U				
Electrical and		and a superior and a superior to the first burners.		



Energy efficiency class (Scale: A+ to F)

Electronically controlled E-compact instant water heater as undersink unit for hot water supply to one or two taps such as one kitchen sink or two washbasins. Internally adjustable outlet temperature  $\leq 50\,^{\circ}$ C, effective heating system IES®, unvented design. Supplied complete with connection kit including T-piece % inch and pressure hose % inch  $\times$  50 cm for easy installation with conventional tap. With power cable, external water connectors % inch for unvented or vented installation, IP 24. Dimensions (h  $\times$  w  $\times$  d): 29.4  $\times$  17.7  $\times$  10.8 cm

CDX 11-U	11kW 380-415V, 3~, perm. connection	2400-26113	26113 1	253.00
CDX7-U	6.9 kW 380 - 415 V, 3 ~, perm. connection	2400-26107	261070	253.00

Retail box: 39 × 23.5 × 14.5 cm / 3.1 kg UPP = 80/10, PU = 8

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# E-compact instant water heaters, oversink

Matching taps > Price list from page 16 onwards







#### EUR EAN excl. number 4010436... VAT \* Type Power rating

### CEX/CSO

Electronically controlled E-compact instant water heater in a set with open-outlet single-lever oversink tap for energy efficient hot water supply to a sink. Temperature adjustment 20 °C to 60 °C using push-button controls with LCD indicator, two programmable preset buttons. Effective IES® bare-wire heating system, with power cable. Single-lever oversink fitting for installation on ½ inch wall connection with 16 cm swivel spout, IP 25.

Dimensions (h  $\times$  w  $\times$  d): 29.4  $\times$  17.7  $\times$  10.8 cm

CEX / CSO	11/13.5 kW	380-415V,3 ~, perm. connection	2400-26390	263906	415.00
D-+-!l b 20 41	245 / 5541				DII 40

Retail box: 28 × 41 × 24.5 cm / 5.54 kg



# Energy efficiency class A


### CEX

Electronically controlled E-compact instant water heater for energy efficient hot water supply to suitable taps such as kitchen sinks or washbasins. Temperature adjustment 20 °C to 60 °C using pushbutton controls with LCD indicator, two programmable preset buttons. Effective heating system IES®, unvented design, suitable for reheating pre-warmed water (e.g. solar collector). With power cable, external water connectors ½ inch for unvented or vented installation, IP 25.

Dimensions (h × w × d): 29.4 × 17.7 × 10.8 cm

|--|

Retail box: 39 × 23.5 × 14.5 cm / 2.9 kg





### Energy efficiency class

### CEX9

Electronically controlled E-compact instant water heater for energy efficient hot water supply to suitable taps such as kitchen sinks or washbasins (in countries with suitable power supply). Temperature adjustment 20 °C to 55 °C using push-button controls with LCD indicator, two programmable preset buttons. Effective heating system IES®, unvented design, suitable for reheating pre-warmed water (e.g. solar collector). External water connectors ½ inch for unvented or vented installation, IP 25. Dimensions (h × w × d): 29.4 × 17.7 × 10.8 cm

6.6/8.8kW 220 - 240 V, 1 ~, perm. connection 2400-26239 26239 8 **281.00** (Export)

Retail box: 40 × 23.8 × 14.7 cm / 2.8 kg

PE = 80/10, PU = 8



Electronically controlled E-compact instant water heater CEX9 combined in a set with shower head for as optimal solution for the supply of a single shower.

<b>CEX 9 Plus</b> 6,6/8,8 kW 220 – 240 V, 1 ~, perm. connection 2400-26270 26270 1
--

# Accessories for E-compact instant water heaters



### Type **FVS**

Tiexible confidenting	11036 /8 IIICII Cap	nut ~ /8 men cap nut,	30 cm long

Retail box: 2 × 25 × 31 cm / 0.11 kg



EAN

number

4010436..

896203

EUR

excl.

VAT \*

8.00



### T-piece

Special T-piece % inch cap nut × % inch angle valve, 10 mm			
T-piece	89610	89610 4	13.00
Retail box: 2 × 11 × 17.5 cm / 0.09 kg			PU = 10



### LAB

Load shedding module with pre-installed cables, contactor and load shedding relay, for joint connection of an 11 kW instant water heater and an electromechanical cooker at a cooker terminal outlet box, if no separate outlet is available for the instant water heater, IP 55.

Dimensions (h  $\times$  w  $\times$  d): 18  $\times$  13  $\times$  8 cm

	AB 82260 82260 8	167.00
--	------------------	--------

Retail box: 16 × 20.5 × 30 cm / 2.28 kg

10 < Product and price list PPL 2021 (information subject to change) Product and price list PPL 2021 (information subject to change) > 11

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

# E-comfort instant water heaters

Matching taps > Price list from page 16 onwards

				EUR
Type	Dower rating	Part	EAN 4010436	excl. VAT *
туре	Power rating	number	4010430	VAI







### **DSX Touch**

High-tech E-comfort instant water heater, the top-of-the-range model with integrated Wi-Fi and Bluetooth function for control via smartphone or tablet using the "Smart Control" app, colour touch display (TOUCHTRONIC®) with real-glass cover, fully electronically controlled for always comfortable and precise hot water temperatures between 20°C and 60°C thanks to TWIN TEMPERATURE Control TTC® and SERVOTRONIC® dynamic flow rate control valve, adjustable filling programmes, user profiles, energy efficiency monitor, operating and service information, unvented design, flow-optimised heating system IES®, double safety system, suitable for water-saving taps thanks to particularly low initial flow of 1.5 l/minute, suitable for reheating pre-warmed water (e.g. solar collector). With FX3 Bluetooth remote control for easy temperature setting of the instant water heater from a distance of up to ten metres, with electronic safety system with air bubble detection, temperature and vent shut-off as well as water-stop function, Multiple Power System MPS® for setting the maximum power rating at the time of installation, variable electrical connection options, spacious connection area for surface-mounted and recessed installation ½ inch, IP 25.

Dimensions (h  $\times$  w  $\times$  d): 46.8  $\times$  23.9  $\times$  9.6 cm

DSX Touch	18/21/24/27* kW	3200-36600	26600.2	710.00
D3X Touch	380-415V 3 ~ perm connection	3200-30000	30000 3	719.00

Retail box: 53.5 × 29 × 16.4 cm / 6 kg
\* Only approved for rated voltage 400 V

6.4 cm / 6 kg UPP = 36/9, PU = 5







### DFX Next (expected to be available from the 4rd quarter)

High-tech E-comfort instant water heater, with integrated Wi-Fi and Bluetooth function for control via smartphone or tablet using the "Smart Control" app or the supplied FX Next remote control, fully electronically controlled, precise hot water temperatures between 20 °C and 60 °C thanks to TWIN TEMPERATURE Control TTC® and SERVOTRONIC® dynamic flow control valve, adjustable filling programmes, user profiles, energy efficiency monitor, operating and service information, unvented design, flow-optimised heating system IES®, double safety system, suitable for water-saving taps thanks to particularly low initial flow of 1.5 l/minute, suitable for reheating pre-warmed water (e.g. solar collector). With FX Next Bluetooth remote control with high-contrast e-paper display, real-glass cover and sensor keys for convenient temperature setting of the instant water heater over a distance of up to ten metres, with electronic safety system with air bubble detection, temperature and vent shut-off as well as water stop function, Multiple Power System MPS® for setting the maximum power rating at the time of installation, variable electrical connection options, spacious connection area for surface-mounted and recessed installation ½ inch, IP 25.

Dimensions (h × w × d): 46.8 × 23.9 × 9.6 cm

DFX Next	18/21/24/27*kW	3200-36500	36500 6	600 00	
DFX Next	380-415 V. 3~, perm, connection	3200-30300	303000	099.00	

Retail box: 53.5 × 29.2 × 16.5 cm

# E-comfort instant water heaters

Type

Matching taps > Price list from page 16 onwards

	DEX Next
	E-comfort instant water heater, high-contrast e-paper display with real-glass cover and sensor keys,
	programmable user profiles, operating and service information, electronically controlled for always pre
	cise hot water temperatures adjustable between 20 °C and 60 °C up to the limit, TWIN TEMPERATURE
	Control TTC®, unvented design, flow-optimised heating system IES®, double safety system, suitable
	for water-saving taps thanks to particuluarly low initial flow of 1.5 l/minute, suitable for reheating
(38)	pre-warmed water (e.g. solar collector), with electronic safety system with air bubble detection,
000	Multiple Power System MPS® for setting the maximum power rating at the time of installation, variable

Power rating

Energy efficiency class A

Dimensions (h × w × d): 46.8 × 23.9 × 9.6 cm

18/21/24/27\* WW

installation ½ inch, IP 25.

DEX Next	18/21/24/27* kW 380 - 415 V, 3 ~, perm. connection	3200-36400	36400 9	513.00
DEX 12 Next	8.8/11.5 kW 220–240 V, 3 ~, perm. connection	3200-36421	36421 4	513.00

electrical connection options (DEX Next), spacious connection area for surface-mounted and recessed

Part

number

Retail box: 53.3 × 29 × 16.4 cm / 4.7 kg
\* Only approved for rated voltage 400 V

UPP = 36/9, PU = 6

EUR


excl.

YAT <sup>\*</sup>

EAN

4010436.





#### **DCX Next**

E-comfort instant water heater, electronically controlled for consistent hot water temperatures, single-button control with five different colour LEDs to set one of five possible outlet temperatures:  $35\,^{\circ}$ C,  $38\,^{\circ}$ C,  $42\,^{\circ}$ C,  $48\,^{\circ}$ C and  $55\,^{\circ}$ C, flow-optimised heating system IES®, double safety system, particularly low switch-on water volume from 1.5 l/min thanks to innovative water flow technology, Multiple Power System MPS® for setting the maximum power rating at the time of installation, variable electrical connection options, spacious connection area for surface-mounted and recessed installation ½ inch, IP 25. Dimensions (h × w × d):  $46.8 \times 23.9 \times 9.6\,$ cm

DCX Next	18/21/24/27* kW 380 – 415 V, 3 ~, perm. connection	3200-36300	36300 2	385.00
DCX 13 Next	11/13.5 kW 380 - 415 V, 3 ~, perm. connection	3200-36313	36313 2	385.00


Retail box: 53.5 × 29.2 × 16.5 cm / 4.94 kg

\* Only approved for rated voltage 400 V

PE = 36/9, VPE = 6



UPP = 36/9 PU = 6



### **DLX Next**

E-comfort instant water heater, electronically controlled for stable hot water temperatures, single-button control with three different colour LEDs to set one of three possible outlet temperatures:  $35\,^{\circ}\text{C}$ ,  $45\,^{\circ}\text{C}$  and  $55\,^{\circ}\text{C}$ , flow-optimised heating system IES®, double safety system, particularly low switch-on water volume from  $1.5\,\text{l/min}$  thanks to innovative water flow technology, variable electrical connection options, spacious connection area for surface-mounted and recessed installation ½ inch, IP 25. Dimensions (h × w × d):  $46.8 \times 23.9 \times 9.6\,\text{cm}$ 

DLX 24 Next	24kW	380-415V,3 ~, perm. connection, $35A$	3200-36224	36224 1	322.00
DLX 21 Next	21kW	380 – 415 V, 3 ~, perm. connection, 30 A	3200-36221	362210	322.00
DLX 18 Next	18kW	380 – 415 V, 3 ~, perm. connection, 26 A	3200-36218	362180	322.00

Retail box: 53.5 × 29.2 × 16.5 cm / 4.7 kg PE = 36/9, VPE = 6

 $^{st}$  Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

<sup>\*</sup> Only approved for rated voltage 400 V

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

### E-comfort instant water heaters

Matching taps > Price list from page 16 onwards

Part EAN excl.
Type Power rating number 4010436... VAT \*\*



### **DBX Next**

Basic instant water heater, electronically controlled, internally adjustable outlet temperature 50 °C, flow-optimised heating system IES®, double safety system, particularly low switch-on water volume from 1.5 l/min thanks to innovative water flow technology, variable electrical connection options, spacious connection area for surface-mounted and recessed installation ½ inch, IP 25. Dimensions (h × w × d):  $46.8 \times 23.9 \times 9.6$  cm


Retail hov: 53 5 x 29 2 x 1			· / / / / / / / / / / / / / / / / / / /			86/9 V/PF = 6
	DBX 24 Next	24kW	380 - 415 V, 3 ~, perm. connection, 35 A	3200-36124	361244	289.00
	DBX 21 Next	21kW	380 – 415 V, 3 ~, perm. connection, 30 A	3200-36121	36121 3	289.00
	DBX 18 Next	18kW	380 – 415 V, 3 ~, perm. connection, 26 A	3200-36118	36118 3	289.00



### **DSX Touch Twin**

Two fully electronically controlled E-comfort instant water heaters with special frame and pipe connection kit for in-wall installation and wireless remote control to accommodate increased hot water demand (e.g. for a spa shower), IP 25. Dimensions (h  $\times$  w  $\times$  d): 81.6  $\times$  60.3  $\times$  14 cm

DSX Touch Twin	3200-36130	36130 5	1.789.00
Retail box: 60 × 85 × 24.5 cm / 24.51 kg			VPE = 1



# Accessories for E-comfort instant water heaters






### RDX 3 Universi

Universal mounting frame for DSX Touch, DFX Next, DEX Next, DCX Next, DLX Next and DBX Next with electrical wiring and brass extension for special installations, e.g. electrical connection at any point behind the unit

RDX 3	3200-36100	361008	52.00
Retail box: 9 × 25 × 46 cm / 1 kg			PU = 6



NEW



### **UDX**

Pipe extension kit for undersink installation with protruding water connectors G % inch above (mounting frame RDX or RDX 3 required)

UDX	3200-34110	34110 9	42.00
Retail box: 7.5 × 16 × 28.5 cm / 0.58 kg			PU = 10



### VDX

Pipe extension kit for offset mounting or exchanged water connectors when replacing gas water heaters (mounting frame RDX or RDX 3 required)

3			
VDX	3200-34120	341208	42.00
Retail hox: 7.5 × 1.6 × 28.5 cm / 0.58 kg			PU = 10

14 < Product and price list PPL 2021 (information subject to change) > 15

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

 $<sup>^{*}</sup>$  Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Taps for washbasins 🛫



EUR EAN excl. 4010436.. Power rating VAT ' Type number



### **EWT**

Single-lever washbasin tap, open-outlet, directly delivers warm water at the ideal usage temperature when lever is in a central position, nickel and lead-free water lines, EASY FIX mounting system and pull-up drain stopper, outlet 11.2 cm, not suitable for storage water heaters.

EWT	1100-04420	044208	203.00
Retail hox: 9 × 21 5 × 40 cm / 2 23 kg			PU = 10





Single-lever washbasin tap, open-outlet, with EASY FIX mounting system and pull-up drain stopper,

END	1100-04410	044109	142.00
Retail box: 7 × 16 × 51.5 cm / 1.8 kg			PU = 10



### SNM

Two-handle washbasin tap, open-outlet, with swivel spout 16 cm

SNM	1100-04200	04200 6	72.00
D-t-11 b 0 16 21 / 1 21			DII 10

Suitable for: Series M





Open-outlet two-handle mixer tap, open-outlet, with swivel spout 15.5 cm for undersink installation with three flexible connecting hoses ¾ inch

SNT	4100-02100	02100 1	69.00
Retail box: 37 × 23.5 × 6 cm / 1.28 kg			PU = 10





Single-lever washbasin tap, closed-outlet, nickel and lead-free water lines, EASY FIX mounting system and pull-up drain stopper, outlet 11.2 cm.

EWT-C	1100-04421	044215	203.00
Potail boy: 9 x 21 5 x 40 cm / 2 2 kg			DII - 10

Suitable for: Series M Series C Series D Storage water heaters > Only for unvented installation!

# Sensor taps for washbasins

### Type **AEB**

Electronically controlled sensor tap, open-outlet, with optional hygiene flush (6 V battery operation). Side lever for temperature adjustment. Ideally suited for E-mini instant water heaters.

AEB	1100-04250	04250 1	522.00
Retail box: 7.5 × 23.5 × 38 cm / 2 kg			PU = 10

number

EUR

VAT \*

4010436...

Suitable for: Series M Series C Series D Storage water heaters



Power rating

### AEN

Electronically controlled sensor tap, open-outlet, with optional hygiene flush (230 V power supply adapter). Side lever for temperature adjustment. Ideally suited for E-mini instant water heaters.

AEN	1100-04255	04255 6	543.00
Retail box: 7.5 × 23.5 × 38 cm / 2.04 kg			PU = 10



Electronically controlled sensor tap, **closed-outlet**, with optional hygiene flush (6 V battery operation). Side lever for temperature adjustment.

AEB-C	1100-04260	04260 0	522.00
Retail box: 7.5 × 23.5 × 38 cm / 2 kg			PU = 10

AEN-C





Electronically controlled sensor tap, closed-outlet, with optional hygiene flush (230 V power supply adapter). Side lever for temperature adjustment.

AEN-C	1100-04265	04265 5	543.00
Retail box: 7.5 × 23.5 × 38 cm / 2 kg			PU = 10

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

Suitable for: Series M Series C Series D Storage water pages > Only for unvented installation!

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Wall-mounted taps for sinks 党





				EUR
		Part	EAN	excl.
уре	Power rating	number	4010436	VAT

### CSO

Single-lever oversink tap, open-outlet, for installation on ½ inch wall connection with swivel spout 16 cm.

. J			
CSO	1100-04165	041658	212.00
Retail box: 13 × 28 × 17 cm / 2.12 kg			PU = 10



Single-lever oversink mixer tap, **open-outlet**, with swivel spout for oversink installation with ½ inch water connector. For E-mini instant water heater M-O, not suitable for storage water heaters.

SME	Length 16 cm	1100-04150	041504	86.00
Retail box	x: 8.5 × 15 × 21 cm / 0.9 kg			PU = 10



Oversink mixer tap, open-outlet, with swivel spout and thread connection for oversink installation with ½ inch water connector. For E-mini instant water heater M-O, not suitable for storage water heaters.

SMB/LS	Length 16 cm	1100-04100 04100 9	69.00
Retail box: 6.4	× 11.5 × 21 cm / 0.7 kg		PU = 10

### LS

Swivel spout with thread connection for wall fixtures SMB and SME, with thread M 22 at the outlet

LS 12	Length 12 cm	0010-0052	005209	24.00
LS 20	Length 20 cm	0010-0054	00054 9	22.00
LS 30	Length 30 cm	0010-0055	005506	26.00
Retail box LS	512: 3 × 25 × 11 cm / 0.09 kg 520: 3 × 33 × 11 cm / 0.11 kg 530: 3 × 43 × 11 cm / 0.14 kg			PU = 10



Single-lever wall-mounted mixer tap, open-outlet, for oversink installation ½ inch with swivel spout

SSO	Length 16 cm	4100-01250	012504	212.00
Retail box: 1	13 × 28 × 17 cm / 2.12 kg			PU = 10



Two-handle washbasin mixer tap, open-outlet, with swivel spout and combination valve for oversink installation ½ inch

SNO	Length 16 cm	4100-0110	401100	109.00
Retail box: 8.	5 × 17.5 × 32.5 cm / 1.39 kg			PU = 10

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Taps for kitchen sinks



Dimensions (h  $\times$  w  $\times$  d): 37.5  $\times$  12  $\times$  25 cm

		Туре	Power rating	number	4010436	VAT
		EKE				
		Sensor tap	o for the kitchen sink with latera	I operating lever and <b>closed-outlet</b> co	onstruction for pr	ressure
( )	NEW	resistant v	vater heaters, continuous tempe	erature regulation via side control leve	er, activatable hy	gienic
_		rinse (auto	omatic rinse every 12 or 24 hou	rs), adjustable water run-on time, out	let 21 cm.	

Battery box BBW (6 V) or plug-in power supply unit SNG (220 –  $240 \, \text{V}$ ) must be ordered separately.

1100-04235 042358 **611.00** 

EUR



### EAK

Single-lever tap, open-outlet, with side lever and swivel spout 20 cm, with flexible connecting hoses.

EKA	1100-04430	04430 /	213.00
Retail box: 7 × 33.5 × 59.5 cm / 2.3 kg			PU = 10





### **EKM**

Single-lever tap, **open-outlet**, with swivel spout 21 cm, with flexible connecting hoses.

EKM	1100-04220	04220 4 139.00
Retail box: 7 × 34 × 65 cm / 1.7 kg		PU = 10





Single-lever tap, open-outlet, with pull-out rinse sprayer, outlet 20 cm, with flexible connecting hoses.

EKA	1100-04230	042303	203.00
Retail box: 7 × 33.5 × 59.5 cm / 2.3 kg			PU = 10



 $<sup>^{*}</sup>$  Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Taps for shower applications |



		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT



### CXH

Shower head for instant water heaters 4 to 13 kW, chrome, 3 jet modes, limescale prevention insert

СХН	Approx. 3 – 6 l/min	0300-0086	008606	24.00
Retail box: 1	0.5 × 24 × 5 cm / 0.32 kg			PU = 10





### CXK

Overhead shower for instant water heaters, chrome, with ball joint and anti-limescale insert, Ø 250 mm.

СХК	4 – 8 I/min	0300-00880	008804	36.00
Retail box: 2	25.5 × 25.5 × 6.5 cm / 0.67 kg			PU = 10

### Matching accessories





# Accessories for taps

6	3	
0		l



Type

Waterproof battery box including battery 6 V lithium CRP 2. Cable length approx. 10 cm, ∅ 6 cm for

BBW	89516	89516 9	37.00
			PU = 1





Plug-in power supply 220 – 240 V / 6 V for contactless taps

Power rating

SNG	89484	89484 1	50.00

PU = 1

EUR

VAT \*

4010436...

number




### CXKA

Shower arm 40 cm, including mounting plate  $1\!\!/\!\!2$  "

CXKA	0300-00890	008903	42.00
Retail box: 7 × 7 × 43 cm / 0.36 kg			PU = 10





Aerator insert for tap adapter M 22/24 at the tap

CSP3	≤ 21/ min, for mini instant water heater	0010-00421	004219	8.00
CSP 6	≤ 3.51/ min, for instant water heaters 5 – 13 kW	0010-00461	004615	8.00
Patail hov: 2 x 10 4 x 20 3 cm / 0.03 kg				PII = 10



### Aerators for male threads

Aerator with chrome tap adapter M 24a (suitable for taps with female threads at the outlet)

CSP 3a	≤ 21/ min, for mini instant water heater	0010-0043	00430 1	12.00
CSP 6a	$\leq$ 3.51/ min, for instant water heaters 5 – 13 kW	0010-0047	00470 7	12.00
Retail box: 2 ×	10.4 × 20.3 cm / 0.03 kg			PU = 10



### Aerators for female threads

Aerator with chrome tap adapter M 22i (suitable for taps with male threads at the outlet)

CSP 3i	≤ 21/ min, for mini instant water heater	0010-0042	00420 2	12.00
CSP 6i	≤ 3.51/min, for instant water heaters 5 – 13 kW	0010-0046	004608	12.00
Retail box: 2 ×	10.4 × 20.3 cm / 0.03 kg			PU = 10



### CSS

Aerator for vented storage water heaters

CSS	For tap adapter M22/24	0010-00504	00504 9	8.00
CSSi	With chrome tap adapter M22i	89125	89125 3	12.00
Retail box: 2	× 10.4 × 20.3 cm / 0.05 kg			PU = 10



### Aerator set

Set consisting of green mounting wrench for aerator, one CSP 3a aerator and one additional CSP 3 aerator insert.

Aerator set	≤ 2 l/min, for mini instant water heaters	9100-92150	929505	15.00
Retail box: 2.5	× 11 × 5 cm / 0.06 a			PU = 12

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Smart Control



EUR
Part EAN excl.
Type Power rating number 4010436... VAT \*\*



### FX3

Additional remote control for a convenient temperature adjustment of DSX Touch or DEX Next instant water heaters at interior distances of up to ten metres. Secure Bluetooth® wireless transmission, infinitely variable temperature selection via two buttons, two preset buttons and LCD indicator, with magnetic wall bracket, batteries included, IP 20.

Dimensions (h × w × d):  $5.8 \times 12.5 \times 1.9$  cm

FX 3 Wireless remote control (only for units manufactured from 2019)

Retail box: 14.5 × 21.5 × 6 cm / 0.3 kg

PU = 10



### FXS3

FX 3 wireless remote control plus Bluetooth® wireless adapter in a set for installation in the DEX Next instant water heater. In addition to user controls directly at the unit, the remote control allows a convenient temperature adjustment of the instant water heater at interior distances of up to ten metres. Secure Bluetooth® wireless transmission, infinitely variable temperature selection via two buttons, two preset buttons and LCD indicator, with magnetic wall bracket, batteries included, IP 20. Dimensions (h × w × d):  $5.8 \times 12.5 \times 1.9 \, \text{cm}$ 

FXS3	Wireless remote control (only for units manufactured from 2019)	3200-34020	34020 1	95.00
Retail hov: 14	15 x 21 5 x 6 cm / 0 3 kg			PII = 10



### FXE<sub>3</sub>

Bluetooth® wireless adapter for installation in the instant water heater for connecting the DEX Next instant water heater to the smartphone/tablet or CLAGE remote control. This extension is required if the units are not yet equipped with an FX 3 wireless remote control.

FXE3	Only for units manufactured from 2019	3200-34022	340225	60.00
Retail box: 3 ×	14.5 × 10 cm / 0.04 kg			PU = 10

\* Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Smart Control

_	Part	EAN	excl
Туре	number	4010436	VAT



### FX

Wireless remote control for instant water heater MCX, CEX / CEX-U, DSX, DSX Twin and DEX, with wireless adapter for installation in the instant water heater. In addition to user controls directly at the unit, the remote control allows a convenient temperature adjustment of the instant water heater at interior distances of up to ten metres. Secure, bidirectional wireless transfer, two-button temperature selection plus two preset buttons and LCD indicator, with magnetic wall bracket, batteries included, IP 20

Dimensions (h  $\times$  w  $\times$  d): 6  $\times$  12.5  $\times$  2 cm

FX	Wireless remote control (only for units manufactured from 2017)	2400-26090	26090 5	95.00
Retail box: 1	7 14.5 × 21.5 × 6 cm / 0.3 kg			PU = 10



### HSX

Home server for convenient temperature control of special CLAGE instant water heaters using a smartphone or tablet. Integrated server with WiFi, network connection and wireless adapter as interface between control app and instant water heaters. The server software provides all services required for the app to control the outlet water temperature of the E-instant water heaters and display the usage data. The "Smart Control" app is available for free from the app stores (usable with tablets and smartphones from iOS 9 or Android OS 4.4). With plug.

Dimensions (h × w × d):  $13.7 \times 14.2 \times 3.8$  cm

HSX	3200-34030	34030 0	522.00
Retail box: 4.5 × 32 × 19.5 cm / 0.65 kg			PU = 10



### HSX 2

Additional server for extending the wireless network

HSX 2	3200-34032	34032 4	388.00
Retail box: 4.5 × 32 × 19.5 cm / 0.65 kg			PU = 10



### HS-K KNX® Gateway

Bidirectional gateway for connecting a CLAGE home server to the  $KNX^{\circledast}$  bus system of the building automation system.

HS-K KNX® Gateway	3200-34034	34034 8	844.00
Retail box: 6 × 10 × 11 cm / 0.22 kg			PU = 10



# Small storage water heaters 5 litres

Matching taps > Price list from page 16 onwards

**EUR** 



Energy efficiency class

Туре	Power rating	number	4010436	VAT
		Part	EAN	excl.

### S5-O

Open-outlet (vented) small storage water heater as oversink unit with internal polypropylene tank (5 litre capacity), recyclable insulation, temperature control approx. 35 °C to 85 °C with energy-saver range, optional temperature limitation and automatic frost protection, operating display, brass water connectors, resettable safety temperature limiter, water connector ½ inch, IP 24. Dimensions (h  $\times$  w  $\times$  d): 37.6  $\times$  25.6  $\times$  22.8 cm

S 5-O	2.0 kW 230 V, 1 ~, with plug	4100-41052	41052 2	95.00

UPP = 40/8, PU = 5 Retail box: 44 × 30 × 27 cm / 3.7 kg

Energy efficiency class A

### S 5-U

Open-outlet (vented) small storage water heater as undersink unit with internal polypropylene tank (5 litre capacity), recyclable insulation, temperature control approx. 35 °C to 85 °C with energy-saver range, optional temperature limitation and automatic frost protection, operating display, brass water connectors, resettable safety temperature limiter, water connector 3/8 inch, IP 24. Dimensions (h × w × d): 37.6 × 25.6 × 22.8 cm

Retail box: 44 × 30 × 27 cm / 3.7 kg

UPP = 40/8. PU = 5





Energy efficiency class A

### S5-U/SNT

Open-outlet (vented) small storage water heater as undersink unit with internal polypropylene tank (5 litre capacity), with matching two-handlemixer tap, temperature selection on the left, water volume selection on the right, recyclable insulation, temperature control approx. 35 °C to 85 °C with energy-saver range, optional temperature limitation and automatic frost protection, operating display, brass water connectors, resettable safety temperature limiter, water connector % inch, IP 24. Dimensions (h × w × d): 37.6 × 25.6 × 22.8 cm

S 5-U / SNT	2.0 kW	230 V, 1 $\sim$ , with plug	4100-42055	42055 2	142.00


Retail box: 46 × 35 × 32 cm / 5 kg UPP = 25/5, PU = 2

### Storage water heaters, 10 to 15 litres

Matching taps > Price list from page 16 onwards

#### EUR EAN excl. number 4010436... VAT \* Type Power rating






### S10-O

Small storage water heater as oversink unit with unvented internal copper tank (10 litre capacity). Suitable for both open-outlet and - in connection with a safety assembly - for closed-outlet installation (also with two taps). Electromechanical temperature control, temperature selection between 5 °C and 80 °C with three detent positions at 35 °C (ECO), 55 °C and 80 °C (MAX), highly effective thermal insulation, with automatic frost protection, operating display, resettable safety temperature limiter, water connector ½ inch, IP 24. Dimensions (h × w × d): 45.2 × 30.0 × 28.5 cm

S 10-O	2.2 kW	230 V, 1 $\sim$ , with plug	4100-41103	41103 1	294.00
Retail box: 47 ×	31 × 31.5 cm /	7.1 kg		UPP = 2	25/5, PU = 2





### S10-U

Small storage water heater as undersink unit with unvented internal copper tank (10 litre capacity). Suitable for both open-outlet and - in connection with a safety assembly - for closed-outlet installation (also with two taps). Electromechanical temperature control, temperature selection between 5 °C and 80 °C with three detent positions at 35 °C (ECO), 55 °C and 80 °C (MAX), highly effective thermal insulation, with automatic frost protection, operating display, resettable safety temperature limiter, water connector % inch, IP 24. Dimensions (h × w × d): 45.2 × 30.0 × 28.5 cm

S 10-U	2.2 kW	230 V, 1 ~, with plug	4100-42103	421030	294.00

Retail box: 47 × 31 × 31.5 cm / 7.1 kg

UPP = 25/5, PU = 2





### S15-O

Small storage water heater as oversink unit with unvented internal copper tank (15 litre capacity). Suitable for both open-outlet and - in connection with a safety assembly - for closed-outlet installation (also with two taps). Electromechanical temperature control, temperature selection between 5 °C and 80°C with three detent positions at 35°C (ECO), 55°C and 80°C (MAX), highly effective thermal insulation, with automatic frost protection, operating display, resettable safety temperature limiter, water connector ½ inch, IP 24. Dimensions (h × w × d): 45.2 × 30.0 × 28.5 cm

S15-O	$2.2\text{kW}$ $230\text{V}$ , $1\sim$ , with plug	4100-41153	41153 6	366.00
Retail box: 47 ×	× 31 × 31.5 cm / 7.7 kg		UPP = 1	25/5, PU = 2





S15-U Small storage water heater as undersink unit with unvented internal copper tank (15 litre capacity). Suitable for both open-outlet and - in connection with a safety assembly - for closed-outlet installation (also with two taps). Electromechanical temperature control, temperature selection between 5 °C and 80 °C with three detent positions at 35 °C (ECO), 55 °C and 80 °C (MAX), highly effective thermal insulation, with automatic frost protection, operating display, resettable safety temperature limiter, water connector % inch, IP 24. Dimensions (h × w × d): 45.2 × 30.0 × 28.5 cm

S 15-U	2.2 kW 230 V, 1 ~, with plug	4100-42153	42153 5	366.00
D : :!! 47	24 24 5 7 7 7 1		LIDD	DE /E DII O

Retail box: 47 × 31 × 31.5 cm / 7.7 kg

\* Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

UPP = 25/5 PU = 2

Product and price list PPL 2021 (information subject to change) > 25

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

### Wall-mounted storage water heaters, 50 to 100 litres

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT *



norgy officionsy class

C	$\mathbf{a}$
•	 .,

Hot water storage heater (50 litre capacity) with unvented internal enamel-coated steel tank, temperature selection between 8 °C and 70 °C with thermometer to display the actual temperature, operating display, thermostat with overheating protection, highly effective PU hard foam insulation, magnesium protection anode, water connector ½ inch, IP 25D.

Dimensions (h × w × d): 61.3 × 49.3 × 49.9 cm

\$50 2 kW 220 - 240 V, 1 ~, with plug 4100-43850 43850 2 **368.00**Retail box: 67 × 54.4 × 54.5 cm / 21 kg

UPP = 16/4, PU = 1




Energy efficiency class

### S 80


Hot water storage heater (80 litre capacity) with unvented internal enamel-coated steel tank, temperature selection between 8 °C and 70 °C with thermometer to display the actual temperature, operating display, thermostat with overheating protection, highly effective PU hard foam insulation, magnesium protection anode, water connector ½ inch, IP 25D.

Dimensions (h  $\times$  w  $\times$  d): 84.1  $\times$  49.3  $\times$  49.9 cm

**S80** 2 kW 220 – 240 V, 1 ~, with plug 4100-43880 43880 9 **375.00** 



### S 100



Dimensions (h  $\times$  w  $\times$  d): 99.3  $\times$  49.3  $\times$  49.9 cm

\$100	2 kW	$220-240\mathrm{V},1$ ~, with plug	4100-43900	43900 4	409.00
Datail have 106 v E /	C ~ C / C	am / 21 E lea	·	LIDD -	0/4 DII = 1

### \* Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# Wall-mounted storage water heaters, 50 to 120 litres



Energy efficiency class
(Scale: A+ to F)

### SX 50

Type

Hot water storage heater (50 litre capacity) with unvented internal steel container with titanium enamel coating and magnesium protection anode, temperature selection between 40 °C, 60 °C or 85 °C, electronic temperature control with heat content indicator and fast heating function, temperature limitation to 40 °C or 60 °C possible, highly effective insulation, premium stainless steel heating elements with inspection flange and drain nozzle, universal connection for single-circuit and economical dual-circuit operation, water connector  $\frac{1}{2}$  inch, IP 24D.

number

EUR excl.

VAT \*

4010436...

Dimensions (h × w × d): 61.3 × 53.0 × 51.6 cm

Power rating

	,			
	0.75 / 4.5 kW			
SX 50	220 - 240 V / 380 - 415 V, switchable	4100-43050	43050 6	522.00
	perm. connection			
Dotail hov: 69	2 x 60 x 60 cm / 25 0 kg		LIDD -	12// DII = 1



Energy efficiency class (Scale: A+ to F)

### SX 80

Hot water storage heater (80 litre capacity) with unvented internal steel container with titanium enamel coating and magnesium protection anode, temperature selection between 40 °C, 60 °C or 85 °C, electronic temperature control with heat content indicator and fast heating function, temperature limitation to 40 °C or 60 °C possible, highly effective insulation, premium stainless steel heating elements with inspection flange and drain nozzle, universal connection for single-circuit and economical dual-circuit operation, water connector  $\frac{1}{2}$  inch, IP 24D.

Dimensions (h  $\times$  w  $\times$  d): 84.1  $\times$  53.0  $\times$  51.6 cm

	1/6kW			
SX 80	220 - 240 V / 380 - 415 V, switchable,	4100-43080	43080 3	551.00
	perm. connection			
Retail box: 90	× 60 × 60 cm / 33.2 kg		UPP =	8/4, PU = 1





### SX 100

Hot water storage heater (100 litre capacity) with unvented internal steel container with titanium enamel coating and magnesium protection anode, temperature selection between 40 °C, 60 °C or 85 °C, electronic temperature control with heat content indicator and fast heating function, temperature limitation to 40 °C or 60 °C possible, highly effective insulation, premium stainless steel heating elements with inspection flange and drain nozzle, universal connection for single-circuit and economical dual-circuit operation, water connector ½ inch, IP 24D.

Dimensions (h × w × d): 99.3 × 53.0 × 51.6 cm

	1/6kW			
SX 100	220 - 240 V / 380 - 415 V, switchable	4100-43100	431008	587.00
	perm. connection			
Retail hov: 106	5 × 60 × 60 cm / 37 4 kg		I IPP =	8/4 PII = 1





### SX 120

Hot water storage heater (120 litre capacity) with unvented internal steel container with titanium enamel coating and magnesium protection anode, temperature selection between  $40\,^{\circ}$ C,  $60\,^{\circ}$ C or  $85\,^{\circ}$ C, electronic temperature control with heat content indicator and fast heating function, temperature limitation to  $40\,^{\circ}$ C or  $60\,^{\circ}$ C possible, highly effective insulation, premium stainless steel heating elements with inspection flange and drain nozzle, universal connection for single-circuit and economical dual-circuit operation, water connector  $\frac{1}{2}$  inch, IP 24D.

Dimensions (h × w × d): 115.3 × 53.0 × 51.6 cm

Retail box: 123 × 60 × 60 cm / 42.4 kg

	1/6kW			
SX 120	220 - 240 V / 380 - 415 V, switchable	4100-43120	43120 6	707.00
	perm. connection			

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

UPP = 4/4 PU = 1

# Accessories for storage water heaters

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT *



### SGU

Undersink safety assembly with non-return valve, pressure reducer and flexible connecting hoses. Complete with drain tundish for undersink installation with closed-outlet hot water storage heaters

SGU	4100-0013	400134	207.00
Retail box: 10.5 × 12 × 17.5 cm / 1.44 kg			PU = 10



### **SGUT**

Set of 1-pieces for second tap			
SGUT	4100-0014	40014 1	40.00
Retail box: 3 × 10.5 × 18.5 cm / 0.3 kg			PU = 10



Oversink safety assembly (6 bar), complete with drain tundish for installation with closed-outlet hot water storage heaters.

SG	4100-0011	400110	109.00
Retail box: 10.5 × 12 × 17.5 cm / 1.11 kg			PU = 10



### SGM

Oversink safety assembly (6 bar) with pressure reducing valve up to 10 bar, complete with drain tundish for installation with closed-outlet hot water storage heaters.

SGM	4100-0012	40012 7	155.00
Retail box: 10.5 × 12 × 17.5 cm / 1.28 kg			PU = 10

# Boiling water heaters



				LUK
		Part	EAN	excl.
Type	Power rating	number	4010436	VAT



### K 5

Boiling water heater for 0.2 to 5 litres of hot water, plastic tank with heating, temperature selection between 37 °C and 99 °C, continuous boil level with automated intervals, control light, water level indicator, integrated tap, overflow drain integrated in the swivel spout, IP 21.

Dimensions (h  $\times$  w  $\times$  d): 27  $\times$  29  $\times$  20 cm

K5	2.0 kW	220 - 240 V,  1 ~~, with plug	4100-41002	410027	250.00
K 5	5 litres		4100-41002	41002 /	256.00

Retail box: 36.5 × 35 × 24 cm / 3.7 kg UPP = 40/10, PU = 5



### Zip Hydroboil® Plus 3

Electronic boiling water heater for automatic supply of boiling water. The unit provides 100 cups of hot water/h for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, push-lever valve for convenient dispensing, premium insulation, electronic temperature control, LCD for operation and function indicators, optional energy-saver function, white painted steel housing, IP 20. Dimensions (h  $\times$  w  $\times$  d): 43.1  $\times$  28.9  $\times$  18 cm

HB Plus 3	1.4 kW 3 litres	220 - 240 V, 1 ~, with plug	4100-44603	44603 3 1	1,046.00
Retail box: 55 × 3	88 × 30 cm / 8 kg			UPP :	= 8. PU = 8



### Zip Hydroboil® Plus 5

Electronic boiling water heater for automatic supply of boiling water. The unit provides 110 cups of hot water/h for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, push-lever valve for convenient dispensing, premium insulation, electronic temperature control, LCD for operation and function indicators, optional energy-saver function, white painted steel housing, IP 20. Dimensions (h × w × d): 46.5 × 31.8 × 19.8 cm

HB Plus 5	2.2 kW	220 – 240 V, 1 ~, with plug	4100-44605	44605 7 <b>1,133.0</b> 0
11511050	5 litres		1100 11000	11000 / 1,100.00

Retail box: 57 × 40 × 30 cm / 10 kg



### Zip Hydroboil® Plus 7

Electronic boiling water heater for automatic supply of boiling water. The unit provides 110 cups of hot water/h for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, push-lever valve for convenient dispensing, premium insulation, electronic temperature control, LCD for operation and function indicators, optional energy-saver function, white painted steel housing, IP 20. Dimensions (h  $\times$  w  $\times$  d): 57.8  $\times$  31.8  $\times$  19.8 cm

HB Plus 7	2.2 kW 220 – 240 V, 1 ~, with plug 7.5 litres	4100-44607	44607 1 <b>1,173.00</b>
-----------	---	------------	-------------------------

Retail box: 69 × 40 × 30 cm / 10 kg UPP = 8 PU = 8

\* Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

# Boiling water heaters

| Part | EAN | excl. | Type | Power rating | Power



### Zip Hydroboil® 15

Electric boiling water heater as oversink unit for automatic supply of boiling water. The unit provides hot water for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, convenient dispensing valve, premium insulation, electronic temperature control, white painted steel housing, IP 20.

Dimensions (h  $\times$  w  $\times$  d): 60  $\times$  39  $\times$  29.9 cm

HB15 2.8 kW 220 - 240 V, 1 ~, perm. connection 4100-44615 44615 6 2,203.00

Retail box: 73 × 45 × 30 cm / 15.8 kg UPP = 4, PU



### Zip Hydroboil® 25

Electric boiling water heater as oversink unit for automatic supply of boiling water. The unit provides hot water for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, convenient dispensing valve, premium insulation, electronic temperature control, white painted steel housing, IP 20.

Dimensions (h  $\times$  w  $\times$  d): 78  $\times$  39  $\times$  29.9 cm

HB 25 2.8 kW 220 - 240 V, 1 ~, perm. connection 4100-44625 44625 5 2,534.00

Retail box: 90 × 44 × 40 cm / 18.6 kg UPP = 2, PU = 2



### Zip Hydroboil® 40

Electric boiling water heater as oversink unit for automatic supply of boiling water. The unit provides hot water for preparing tea, coffee or other hot drinks. Two-chamber system with stainless steel tanks, no steam emission, convenient dispensing valve, premium insulation, electronic temperature control, white painted steel housing, IP 20.

Dimensions (h  $\times$  w  $\times$  d): 84  $\times$  51.5  $\times$  28.4 cm

HB 40	$5.6\text{kW}$ $2\times220-240\text{V}, 2\sim$ , perm. connection 40 litres	4100-44640	44640 8 <b>2,693.00</b>	
-------	---	------------	-------------------------	--

Retail box: 96 × 57 × 40 cm / 25 kg UPP = 2, PU = 2

# Accessories for boiling water heaters





### KAT 2

Stainless steel drip tray with drainage connection, 32.5 × 17.5 cm

	, ,	9	*				
KAT 2				4100-	44081	440819	76.00
Retail box: 4 × 2	25 × 41 cm / 0.61 kg						PU = 10

EUR



### KAS<sub>1</sub>

Tundish for undersink installation, ¾ inch

KAS1	4100-44085	44085 7	70.00
Retail box: 10 × 10 × 26 cm / 0.1 kg			PU = 10



### KAS 2

Wall-mounted tundish, ¾ inch

KAS 2	4100-44086	44086 4	70.00
Retail box: 7.5 × 10.5 × 27 cm / 0.04 kg			PU = 10





### KA AZ und KA A

Connection kit for one or two additional side dispensing valves

KA AZ	For KA 15 / KA 25 and HB 15 / HB 25	84426	84426 6	61.00
KA A	For KA 40 and HB 40	84427	84427 3	86.00
Retail box: 3 ×	· 18 × 40 cm / 0.67 kg			PU = 10



### KA Z

Additional dispensing valve

KA Z	For KA and HB 15/25/40	84321	84321 4	58.00
D-4-11 b 2	x 10 x 10 cm / 0.61 kg	·		DII - 10



### Claris Ultra filter systems for water softening

Unique three-level ion exchanger cartridge for reliable softening, pH-stabilisation and filtering of drinking water. Improves the taste of the water and reduces maintenance. In order to reach the appropriate water hardness, a small amount of the active carbon-filtered water bypasses the water softening stage. Uses ion exchanger resins with pH value and active carbon from coconut shells with especially high capacity. The filter cartridges are hygienic and easy to replace.

Filter head must be ordered separately.

ULTRA 500	Capacity at 10 KH: 4,200 litres	84500	84500 3	184.00
<b>ULTRA 1000</b>	Capacity at 10 KH: 8,500 litres	84501	845010	260.00
ULTRA 2000	Capacity at 10 KH: 20,000 litres	84502	84502 7	419.00
Dimensions (H × Ø)	ULTRA 500: 42.5 × 9.5 cm / Retail box: 12 × 13 × 46 cm / 2.05 kg ULTRA 1000: 36 × 13.6 cm / Retail box: 14 × 14.5 × 40 cm / 3.25 kg ULTRA 2000: 47.5 × 17.5 cm / Retail box: 18.5 × 19 × 52 cm / 6.4 kg			PU = 10 PU = 10 PU = 4

 $<sup>^{\</sup>ast}$  Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

				EUR
		Part	EAN	excl.
Гуре	Power rating	number	4010436	VAT





### Zip HydroTap® G4 BCS

Electronic water system for undersink installation for immediate supply of filtered boiling, chilled or sparkling drinking water (carbonation max.  $5\,\mathrm{g}$  CO $_2$  per litre, which produces a medium fizz). Touch control panel for programming and service settings, leakage protection system, white steel housing. Pressure reducer must be installed, IP 20.

Dimensions (h × w × d):  $33.5 \times 34.8 \times 46.6$  cm (BCS 100/75),  $33.5 \times 45.4 \times 47$  cm (BCS 160/175)

### Tap, carbon dioxide cylinder and pressure reducer must be ordered separately.

BCS 100/75	2.2 kW 220 – 240 V, 1~, with plug 100 cups/h Boiling water	4100-44579	44579 1 <b>3,617.00</b>
	75 glasses/h cooled water 2.3 kW 220 – 240 V, 1~, with plug		
BCS 160/175	160 cups/h Boiling water	4100-44580	44580 7 <b>4,604.00</b>
	175 glasses/h cooled water		
	5): 53.5 × 38 × 56.5 cm / 35,0 kg 75): 54 × 44 × 67 cm / 41.0 kg		PU = 1

### Compatible taps:



### Zip Classic BCS

Electric dispensing tap for Zip HydroTap $^{\circ}$  BCS with operating buttons on top, function display, holding function for easy filling of canisters, fixed 12 cm spout, 21 cm tall, drill hole with 35 mm diameter required.

Classic BCS	Polished chrome	4100-44500	44500 5	488.00
Classic BCS	<ul><li>Brushed chrome</li></ul>	4100-44501	44501 2	636.00
Classic BCS	<ul><li>Matt black</li></ul>	4100-44502	44502 9	636.00
Retail box: 10 × 54,	5 × 36,5 cm / 2,0 kg			PU = 1



### Zip Arc BCS

Electric dispensing tap for Zip Hydro $Tap^{\otimes}$  BCS with operating button on the side, 16 cm fixed spout, 35.3 cm tall, drill hole with 35 mm diameter required.

Arc BCS	Polished chrome	4100-44503	44503 6	488.00
Arc BCS	Brushed chrome	4100-44504	445043	636.00
Arc BCS	Matt black	4100-44505	44505 0	636.00
Retail box: 10 × 5	4,5 × 36,5 cm / 2,2 kg			PU = 1



### **Zip Touch-Free BCS**

Sensor tap for touchless tapping of boiling, chilled still or sparkling water. Function for convenient quantity filling, fixed spout 12 cm, height 21 cm,  $\emptyset$  35 mm hole drilling required.

Touch-Free BCS ( ) Polished chrome	4100-44540 44540 1	976.00
Retail box: 10 × 55 × 35 cm / 1,9 kg		PU = 1



### Zip Celsius Arc AIO "AII-In-One"

All-round tap for boiling, cooled and carbonated water from the Zip HydroTap® undersink unit as well as additional normal tap water from the central or decentralised supply (regulated by the side-mounted lever). 22.5 cm swivel spout, 44.5 cm tall, drill hole with 50 mm diameter required.

Celsius Arc AIO ( Polished chrome	4100-44524	44524 1 <b>1,973.00</b>
Celsius Arc AIO Brushed chrome	4100-44525	44525 8 <b>2,138.00</b>
Celsius Arc AlO Matt black	4100-44526	44526 5 <b>2,138.00</b>
Retail box: 10 × 54,5 × 36,5 cm / 5,1 kg		PU = 1

### \* Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT *



Water systems

### Zip HydroTap® G4 BC

Electronic water system for undersink installation for immediately supply of filtered, boiling (100 cups/h) and chilled water (75 glasses/h). Touch control panel for programming and service settings, leakage protection system, premium insulation, white steel housing, IP 20. Dimensions ( $h \times w \times d$ ): 33.5 × 29 × 46 cm

### Tap must be ordered separately.

BC 100/75	2.1 kW	220 - 240 V, with plug	4100-44577	44577 7	3,221.00
Detail how E2 E v 20	v E 4 E am				DLL - 1

### Compatible taps:



### Zip Classic BC

Electric dispensing tap for Zip Hydro $\mathrm{Tap}^{\otimes}$  BC with operating buttons on top, function display, hold function for easy filling of canisters,  $12\,\mathrm{cm}$  fixed spout,  $21\,\mathrm{cm}$  tall, drill hole with  $35\,\mathrm{mm}$  diameter required.

Classic BC	Polished chrome	4100-44506	44506 7	488.00
Classic BC	Brushed chrome	4100-44507	44507 4	636.00
Classic BC	<ul><li>Matt black</li></ul>	4100-44508	44508 1	636.00
Datail bass 10 v E 4	E v 24 E am / 2 Oka			DII - 1



### Zip Arc BC

Electric dispensing tap for Zip Hydro $Tap^{\otimes}$  BC with side-mounted operating button, 16 cm fixed spout, 35.3 cm tall, drill hole with 35 mm diameter required.

Arc BC         Brushed chrome         4100-44510         44510           Arc BC         Matt black         4100-44511         44511	
<b>Arc BC</b> Brushed chrome 4100-44510 44510	636.00
1 1	
Arc BC         Polished chrome         4100-44509         44509	488.00



### NEW

### Zip Touch-Free BC

Sensor tap for touchless tapping of boiling or chilled still water. Function for convenient quantity filling, fixed spout 12cm, height 21cm,  $\emptyset$  35 mm hole drilling required.

Touch-Free BC  Polished chrome	4100-44541 44541 8	976.00
Retail box: 10 × 55 × 35 cm / 1 9 kg		PIJ = 1

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.



EAN 4010436.. EUR

VAT \*

				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT



### Zip HydroTap® G4 CS

Electronic water system for undersink installation for supply of filtered, chilled drinking water (175 glasses/h), sparkling drinking water if desired (carbonation max.  $5\,\mathrm{g}$  CO $_2$  per litre, which produces a medium fizz). Touch control panel for programming and service settings, leakage protection system, white steel housing. Pressure reducer must be installed, IP 20.

Dimensions (h  $\times$  w  $\times$  d): 33.5  $\times$  34  $\times$  47.6 cm

Tap, carbon dioxide cylinder and pressure reducer must be ordered separately.

CS 175	0.45 kW	220 - 240 V, with plug	4100-44582	44582 1	2,970.00
Retail box: 53.5 × 38	3 × 56.5 cm				PU = 1

France Service Control of the Contro

### Zip HydroTap® G4 B

Type

Electronic boiling water heater for undersink installation for immediately supply of boiling water (160 cups/h). With Touch control panel for programming and service settings, leakage protection system, high-quality thermal insulation, white steel housing, IP 20.

Part

number

Dimensions (h  $\times$  w  $\times$  d): 33.5  $\times$  28  $\times$  31.3 cm

Power rating

### Tap must be ordered separately.

B 160	1.9 kW	220 – 240 V, with plug	4100-44578	44578 4	1,655.00
Retail box: 53.5 × 3	37.5 × 56.5 cm				PU = 1

### Compatible taps:



### Zip Classic CS

Electric dispensing tap for Zip Hydro $Tap^{\otimes}$  CS with operating buttons on top, function display, hold function for easy filling of canisters, fixed 12 cm spout, 21 cm tall, drill hole with 35 mm diameter required.

Classic CS	Polished chrome	4100-44518	445180	488.00
Classic CS	Brushed chrome	4100-44519	44519 7	636.00
Classic CS	Matt black	4100-44520	44520 3	636.00
Datail how 10 v E 1	E v 24 E am / 1 0 kg			DII - 1



### 7in Arc CS

Electric dispensing tap for Zip HydroTap $^{\otimes}$  CS with side-mounted operating button, 16 cm fixed spout, 35.3 cm tall, drill hole with 35 mm diameter required.

Arc CS	Polished chrome	4100-44521	445210	488.00
Arc CS	Brushed chrome	4100-44522	44522 7	636.00
Arc CS	Matt black	4100-44523	44523 4	636.00
Retail box: 10 ×	54,5 × 36,5 cm / 2,1 kg			PU = 1



### Zip Touch-Free CS

Sensor tap for touchless tapping of chilled still or sparkling water. Function for convenient quantity filling, fixed spout  $12 \, \text{cm}$ , height  $21 \, \text{cm}$ ,  $\emptyset \, 35 \, \text{mm}$  hole drilling required.

Touch-Free CS ( Polished chrome	4100-44544	44544 9	976.00
Retail box: 10 × 55 × 35 cm / 1,6 kg			PU = 1

### \* Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

### Compatible taps:



### Zip Classic B

Electric dispensing tap for Zip HydroTap $^{\circ}$  B with operating buttons on top, function display, hold function for easy filling of canisters, fixed 12 cm spout, 21 cm tall, drill hole with 35 mm diameter required.

Classic B	Polished chrome	4100-44512	445128	488.00
Classic B	Brushed chrome	4100-44513	44513 5	636.00
Classic B	<ul><li>Matt black</li></ul>	4100-44514	44514 2	636.00
Retail box: 10 × 5	54,5 × 36,5 cm / 2,0 kg			PU = 1



### Zip Arc B

Electric dispensing tap for Zip HydroTap® B with side-mounted operating button, 16 cm fixed spout, 35.3 cm tall, drill hole with 35 mm diameter required.

Arc B	Polished chrome	4100-44515	44515 9	488.00
Arc B	Brushed chrome	4100-44516	44516 6	636.00
Arc B	Matt black	4100-44517	44517 3	636.00
Potail boy: 10 x	545 x 365 cm / 2 2 kg			DII - 1



### EM

Sensor tap for touchless tapping of boiling water. Function for convenient quantity filling, fixed spout  $12 \, \text{cm}$ , height  $21 \, \text{cm}$ ,  $\emptyset \, 35 \, \text{mm}$  hole drilling required.

Touch-Free B	Polished chrome	4100-44542	445425	976.00
Retail hox: 10 × 55 ×	35 cm / 1 9 kg			PIJ = 1

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

Zip Touch-Free B

# Accessories for water systems

#### EUR EAN excl. VAT \* number 4010436.. Power rating Type



### **Zip Classic AlO "All-In-One"** (As long as stocks last)

All-use tap for boiling, chilled and sparkling drinking water from the Zip HydroTap® undersink unit and also normal tap water from a centralised or decentralised supply (can be controlled using the side lever). Eliminates the need for an additional tap for normal tap water.

Classic AIO	Polished chrome	4100-44112	441120	1,013.00
Retail box: 10 × 27	× 49 cm / 3 62 kg			PU = 1

Retail box: 10 × 27 × 49 cm / 3.62 kg

Optional extension for raising the Zip Classic electronic dispensing tap by 13.5 cm.

KXV 10	Polished chrome	4100-44165	44165 6 <b>83.00</b>
KXV 20	<ul><li>Brushed chrome</li></ul>	4100-44166	44166 3 <b>133.00</b>
KXV 40	Matt black	4100-44167	44167 0 <b>133.00</b>

Retail box: 5 × 25 × 27 cm / 0.5 kg



### **KXTV**

The optional stainless steel font with drainage connection and chrome extension allows for flexible installation of the Zip Classic electronic dispensing tap at any location away from the sink. Drill hole with 108 mm diameter required.

KXTV 10	Polished chrome	4100-44565	44565 4	212.00
KXTV 20	Brushed chrome	4100-44566	44566 1	454.00
KXTV 40	Matt black	4100-44567	445678	454.00

Retail box: 11 × 22 × 42 cm / KXTV 10, 20 und 30: 1.5 kg / KXTV 40: 1.6 kg



The optional stainless steel font with drainage connection allows flexible installation of the Zip Arc electronic dispensing tap at any location away from the sink. Drill hole with 140 mm diameter required.

KXTV 50	O Polished chrome	4100-44560	44560 9	148.00
KXTV 60	Brushed chrome	4100-44561	445616	253.00
KXTV 70	Matt black	4100-44562	445623	253.00

Retail box: 11.2 × 42 × 22 cm / 1.1 kg

PIJ = 1

PU = 10

# Accessories for water systems

				EUR
		Part	EAN	excl.
Type	Power rating	number	4010436	VAT



### Claris Ultra filter systems for water softening

Unique three-level ion exchanger cartridge for reliable softening, pH-stabilisation and filtering of drinking water. Improves the taste of the water and reduces maintenance. In order to reach the appropriate water hardness, a small amount of the active carbon-filtered water bypasses the water softening stage. Uses ion exchanger resins with pH value and active carbon from coconut shells with especially high capacity. The filter cartridges are hygienic and easy to replace.

### Filter head must be ordered separately.

ULTRA 500	Capacity at 10 KH: 4,200 litres	84500	84500 3	184.00
<b>ULTRA 1000</b>	Capacity at 10 KH: 8,500 litres	84501	845010	260.00
ULTRA 2000	Capacity at 10 KH: 20,000 litres	84502	84502 7	419.00
Dimensions (h × Ø) ULTF	RA 500: 42.5 × 9.5 cm / Retail box: 12 × 13 × 46 cm / 2.0 RA 1000: 36 × 13.6 cm / Retail box: 14 × 14.5 × 40 cm / 3 RA 2000: 47.5 × 17.5 cm / Retail box: 18.5 × 19 × 52 cm /	3.25 kg		PU = 10 PU = 10 PU = 4



### Filter head

For installation of the Claris Ultra filters in all Zip units.

Filter head universal	84519	84519 5	105.00
Retail box: 22.5 × 13 × 18.5 cm / 0.84 kg			PU = 10



### KXF

Sub-micron particle filter cartridge (installed by the factory) filters particles >0.2 µm and additionally improves the taste of the water. Capacity approx. 6,000 litres depending on local factors. Dimensions (h  $\times$  Ø) KXF1 and KXF2: 25  $\times$  8.5 cm, KXF1.1: 21  $\times$  8 cm, KXF2.1: 23  $\times$  8 cm

KXF1	For Zip HydroTap® MINIBOIL	891289	91289 7	153.00
KXF 2	For all Zip HydroTap® G4 models	891290	912903	153.00
KXF 1.1	For Zip HydroTap® MINIBOIL 1)	893701	93701 2	153.00
KXF 2.1	For all Zip HydroTap® G4 models <sup>1)</sup>	893702	93702 9	153.00

KXF 1 / KXF 2: Retail box: 35 × 18 × 10 cm / 0.6 kg KXF 1.1 / KXF 2.2: Retail box: 34 × 18 × 8.5 cm / 0.5 kg 1) from serial number 20170118\*\*\*



### COF

CO<sub>2</sub> cylinder filled, content 425 grams, for soda club connecting thread

COF	Provides about 80 litres CO <sub>2</sub> water	9910-90005	90005 5	30.00
Retail box: 37 × 5.	.5 × 5.5 cm / 1.9 kg			PU = 10
*	C			

\* Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

# Accessories for water systems





### **DMBCS**

Pressure reducer with standard  ${\rm CO_2}$  connecting thread (½ inch)

DMBCS	4100-44120	441205	96.00
Retail box: 18.5 × 13 × 22.5 cm / 1 kg			PU = 10



### **KXB**

Plastic installation kit for G4 BCS 160/175, allows for easier installation of ventilation in the base cabinet. Dimensions ( $h \times w \times d$ ):  $4 \times 49.5 \times 50$  cm

KXB	893450	93450 9	81.00
Retail box: 8 × 55 × 52 cm / 1.9 kg			PU = 10



### KXB-C

Plastic installation kit for G4 CS 175 and G4 C 175, allows for easier installation of ventilation in the base cabinet. Dimensions ( $h \times w \times d$ ):  $4 \times 49.5 \times 50$  cm

KXB-C	893541	935414	84.00
Retail box: 8 × 55 × 52 cm / 1.9 kg			PU = 10



### **VBZ**

Usage counter, developed especially for checking Claris Ultra filters, used to measure and display the remaining filter capacity until it is time to replace the filter, with % inch thread.

. ,	<u> </u>	
VBZ	84509	84509 6 <b>137.00</b>
Retail box: 5 × 22 5 × 15.5 cm / 1.9 kg		PU = 10



### DTK

The digital temperature controller for Zip devices is used to keep the temperature in the cupboard under  $35\,^{\circ}\text{C}$  when normal ventilation is not sufficient. The digital controller operates independently of the undersink unit and will require a separate  $230\,\text{V}$  socket.

DTK	893159	93159 1	516.00
Retail box: 11.5 × 22 × 42 cm / 1.34 kg			PU = 1

# Apartment transfer stations



				EUR
		Part	EAN	excl.
Туре	Power rating	number	4010436	VAT



Note: Illustration similar, varies depending on the equipment

### WS-Hybrid

Apartment transfer stations for supplying an apartment with an integrated heating circuit and plate-type heat exchangers for hygienic hot drinking water supply. The copper-soldered plate-type heat exchanger with 30 plates ensures constant hot water thanks to its long thermal length. With plastic pipe clamps for noise and heat insulation, DVGW-certified PM controller with priority switching and utility-model-protected sealing technology, ventilation, multi-function valve underparts for modular assembly system, dirt collector for cold water 0.5 mm, dirt collector HZ-VL primary 0.5 mm, TW panel, zone valve insert with panel adjustment without pass change and connecting thread M30 × 1.5 for optional drive, zone valve DG, installation length 68 mm: kvs value 0.67, preset to 0.43, no. 7. Preparation for subsequent connection to service water circulation, AGFW sensor, drain valves and equipotential bonding. Plastic fitted piece for WMZ 110 ×  $\frac{3}{4}$  inch AG and sensor connection (AGFW) M10 × 1. The stations are designed so that the following heat exchangers can be installed on the same base plate B = 555 mm: copper/nickel-soldered and bolted plate-type heat exchangers with up to 40 plates.

Also for WS-Hybrid: with E-instant water heater with 400 V to achieve increased hot water temperature, with remote control option. Including heat exchanger insulation, panel 10 l/min, differential pressure control in secondary heating circuit, kvs value 3.5, preset to 100 mbar, adjustable 50–300 mbar. TTV, temperature maintenance module, adjustable 0–45 °C, preset to 28 °C, for maintaining the heat of the heat exchanger. Drainage kit for flushing/emptying the systems, with  $\frac{1}{4}$  inch hose connection. Dimensions WS-Hybrid (h × w × d):  $60 \times 55.5 \times 18$  cm

WS-Hybrid 13 kW	11 / 13,5 kW	F400 F4400	F4400 7	2 2 2 2 2 2
	380-415 V, 3~, perm. connection	5100-51100	51100 /	2,207.00
WS-Hybrid 21 kW	21kW	E100 E11E0	E11E0 2	2 429 00
	380-415 V, 3~, perm. connection	5100-51150	31130 2	2,428.00
D-t-:1104(F10	/10 11-			DII 1



Note: Illustration similar, varies depending on the equipment

### WS-B1000-20

Apartment transfer station for supplying an apartment with an integrated heating circuit and plate-type heat exchangers for hygienic hot drinking water supply. The copper-soldered plate-type heat exchanger with 20 plates ensures constant hot water thanks to its long thermal length. With plastic pipe clamps for noise and heat insulation, DVGW-certified PM controller with priority switching and utility-model-protected sealing technology, ventilation, multi-function valve underparts for modular assembly system, dirt collector for cold water 0.5 mm, dirt collector HZ-VL primary 0.5 mm, TW panel, zone valve insert with panel adjustment without pass change and connecting thread M30 × 1.5 for optional drive, zone valve DG, installation length 68 mm: kvs value 0.67, preset to 0.43, no. 7. Preparation for subsequent connection to service water circulation, AGFW sensor, drain valves and equipotential bonding. Plastic fitted piece for WMZ 110 ×  $\frac{1}{2}$  inch AG and sensor connection (AGFW) M10 × 1. The station is designed so that the following heat exchangers can be installed on the same base plate B = 555 mm: copper/nickel-soldered and bolted plate-type heat exchangers with up to 40 plates. Dimensions (h × w × d): 60 × 55.5 × 15 cm

WS	S-B1000-20	5100-51105	51105 2	896.00
Dot	ail boy: 04 x 65 x 18 cm / 13 0 kg			DII - 1

### Note:


Additional accessories are required to install the station. Please request these accessories from us.

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

# At a glance

### E-mini instant water heaters



Туре	Part number	EAN	Euro*	UPP	PU	Page
Series M						
MCX 3	1500-15003	401043615003 9	244.00	100/20	10	4
MCX 4	1500-15004	401043615004 6	249.00	100/20	10	4
MCX 6	1500-15006	4010436150060	260.00	100/20	10	4
MCX7	1500-15007	401043615007 7	260.00	100/20	10	4
MCX Blue	1500-15133	401043615133 3	390.00	30/60	7	4
MBX 3 Lumino	1500-15113	401043615113 5	835.00	30/60	7	4
MBX 7 Lumino	1500-15117	401043615117 3	849.00	30/60	7	4
MBH 3	1500-16003	4010436160038	181.00	100/20	10	5
MBH 4	1500-16004	401043616004 5	181.00	100/20	10	5
MBH 6	1500-16006	401043616006 9	193.00	100/20	10	5
MBH 7	1500-16007	401043616007 6	193.00	100/20	10	5
M 3	1500-17003	401043617003 7	123.00	100/20	10	5
M 4	1500-17004	401043617004 4	126.00	100/20	10	5
M 6	1500-17006	401043617006 8	142.00	100/20	10	5
M 7	1500-17007	401043617007 5	142.00	100/20	10	5
M 3-O	1500-17113	401043617113 3	126.00	100/20	10	5
M4-O	1500-17114	401043617114 0	126.00	100/20	10	5
M 6-O	1500-17116	401043617116 4	142.00	100/20	10	5
M7-O	1500-17117	401043617117 1	142.00	100/20	10	5
Sets						
M3/END	1500-17243	401043617243 7	189.00	100/20	9	6
M3/SNM	1500-17203	401043617203 1	142.00	100/20	12	6
M3/SMB	1500-17103	401043617103 4	142.00	100/20	12	6
M4/SMB	1500-17104	401043617104 1	187.00	100/20	12	6
M7/SMB	1500-17107	401043617107 2	203.00	100/20	12	6
MBX 4 Shower	1500-15314	401043615314 6	310.00	50/5	6	6
MBX 6 Shower	1500-15316	401043615316 0	321.00	50/5	6	6
MBX 7 Shower	1500-15317	401043615317 7	323.00	50/5	6	6
Accessories						
FVS	89620	4010436896203	8.00		10	7
T-piece	89610	4010436896104	13.00		10	7
Hand dryer						
WHT	7000-70300	401043670300 6	287.00		6	7



Туре	Part number	EAN	Euro*	UPP	PU	Page
Series C						
CFX-U	2400-26313	401043626313 5	333.00	80/10	8	8
CEX-U	2400-26213	4010436262138	281.00	80/10	8	8
CEX 7-U	2400-26224	401043626224 4	281.00	80/10	8	8
CEX 9-U (Export)	2400-26249	401043626249 7	281.00	80/10	8	8
CDX 11-U	2400-26113	401043626113 1	253.00	80/10	8	9
CDX7-U	2400-26107	401043626107 0	253.00	80/10	8	9
CEX/CSO	2400-26390	401043626390 6	415.00		10	10
CEX	2400-26233	401043626233 6	281.00	80/10	8	10
CEX 9 (Export)	2400-26239	4010436262398	281.00	80/10	8	10
CEX 9 Plus	2400-26270	401043626270 1	290.00			10
Accessories						
FVS	89620	4010436896203	8.00		10	11
T-piece	89610	401043689610 4	13.00		10	11
LAB	82260	401043682260 8	167.00	-	10	11

### E-comfort instant water heaters



			$\hookrightarrow$	I	<u> </u>	$\overline{}$
Туре	Part number	EAN	Euro*	UPP	PU	Page
Series D						
DSX Touch	3200-36600	401043636600 3	719.00	36/9	5	12
DFX Next	3200-36500	401043636500 6	699.00	36/9	5	12
DEX Next	3200-36400	401043636400 9	513.00	36/9	6	12
DEX 12 Next	3200-36412	401043636412 4	513.00	36/9	6	12
DCX Next	3200-36300	401043636300 2	385.00	36/9	6	13
DCX 13 Next	3200-36313	401043636313 2	385.00	36/9	6	13
DLX 18 Next	3200-36218	401043636218 0	322.00	36/9	6	13
DLX 21 Next	3200-36221	4010436362210	322.00	36/9	6	13
DLX 24 Next	3200-36224	401043636224 1	322.00	36/9	6	13
DBX 18 Next	3200-36118	401043634118 3	289.00	36/9	6	14
DBX 21 Next	3200-36121	4010436361213	289.00	36/9	6	14
DBX 24 Next	3200-36124	401043636124 4	289.00	36/9	6	14
DSX Touch Twin	3200-36130	401043636130 5	1,789.00		1	14
Accessories						
RDX**	3200-34100	401043634100 0	52.00		6	15
RDX 3	3200-36100	4010436361008	52.00		6	15
UDX	3200-34110	401043634110 9	42.00		10	15
VDX	3200-34120	4010436341208	42.00		10	15

PU = Packaging unit UPP = Units per pallet / quantity per layer for mixed pallet

### \* Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

# At a glance

### Taps **Type** Suitable for Part number EAN Euro\* UPP PU Page Taps for washbasins EWT 1100-04420 4010436044208 **203.00** 10 **16** END 10 **16** 1100-04410 401043604410 9 **142.00** SNM 1100-04200 4010436042006 **72.00** 10 **16** 4100-02100 4010436021001 69.00 10 **16**

EWT-C	1100-04421	4010436044215	203.00	10	16
Sensor tap	ps for washbasins				
AEB	1100-04250	401043604250 1	522.00	10	17
AEN	1100-04255	401043604255 6	543.00	10	17
AEB-C	1100-04260	401043604260 0	522.00	10	17
AEN-C	1100-04265	401043604265 5	543.00	10	17
Wall-mou	nted taps for sinks				
	<b>f</b> h				

Wall-mounte	d taps fo	r sinks				
cso	H	1100-04165	4010436041658	212.00	10	18
SME	Ô	1100-04150	401043604150 4	86.00	10	18
SMB/LS	Ü	1100-04100	401043604100 9	69.00	10	18
LS 12	Ö	0010-0052	401043600520 9	24.00	10	18
LS 20		0010-0054	401043600054 9	22.00	10	18
LS 30	Ü	0010-0055	401043600550 6	26.00	10	18
SSO		4100-01250	401043601250 4	212.00	10	18
SNO		4100-0110	401043640110 0	109.00	10	18
Taps for kitch	hen sinks	•				
EKE	Ħ	1100-04235	401043604235 8	611.00	1	19
EAK		1100-04430	401043604430 7	213.00	10	19
EKM		1100-04220	401043604220 4	139.00	10	19
EKA		1100-04230	401043604230 3	203.00	10	19
Taps for show	ver appli	cations				
СХН		0300-0086	401043600860 6	24.00	10	20
СХК		0300-00880	401043600880 4	36.00	10	20
Accessories						
BBW		89516	401043689516 9	37.00	1	21
SNG		89484	401043689484 1	50.00	1	21
CXKA		0300-00890	401043600890 3	42.00	10	21

CALL	<u> </u>	4010430000000	24.00	10	
СХК	0300-00880	401043600880 4	36.00	10	20
Accessories					
BBW	89516	401043689516 9	37.00	1	21
SNG	89484	401043689484 1	50.00	1	21
CXKA	0300-00890	401043600890 3	42.00	10	21
CSP3	0010-00421	401043600421 9	8.00	10	21
CSP 6	0010-00461	4010436004615	8.00	10	21
CSP 3a	0010-0043	401043600430 1	12.00	10	21
CSP 6a	0010-0047	4010436004707	12.00	10	21
CSP 3i	0010-0042	401043600420 2	12.00	10	21

0010-0046 4010436004608 **12.00** 

0010-00504 4010436005049 8.00

9100-92150 4010436929505 **15.00** 

4010436891253 **12.00** 

### Smart Control

уре	Part number	EAN	Euro* UPP	PU	Page
X 3	3200-34021	4010436340218	74.00	10	22
XS 3	3200-34020	401043634020 1	95.00	10	22
XE 3	3200-34022	4010436340225	60.00	10	22
X	2400-26090	4010436260905	95.00	10	22
ISX	3200-34030	4010436340300	522.00	10	23
ISX 2	3200-34032	401043634032 4	388.00	10	23
HS-K KNX®	3200-34034	401043634034 8	844.00	10	23

### Storage water heaters

Туре	Part number	EAN	Euro*	UPP	PU	Page
Small storage wat	ter heaters and w	all-mounted storage	water he	aters		
\$5-0	4100-41052	401043641052 2	95.00	40/8	5	24
S 5-U	4100-42052	401043642052 1	94.00	40/8	5	24
S 5-U / SNT	4100-42055	401043642055 2	142.00	25/5	2	24
S 10-O	4100-41103	401043641103 1	294.00	25/5	2	25
S 10-U	4100-42103	401043642103 0	294.00	25/5	2	25
\$15-0	4100-41153	401043641153 6	366.00	25/5	2	25
S 15-U	4100-42153	401043642153 5	366.00	25/5	2	25
\$50	4100-43850	401043643850 2	368.00	16/4	1	26
S 80	4100-43880	401043643880 9	375.00	12/4	1	26
S 100	4100-43900	401043643900 4	409.00	8/4	1	26
SX 50	4100-43050	401043643050 6	522.00	8/4	1	27
SX 80	4100-43080	401043643080 3	551.00	8/4	1	27
SX 100	4100-43100	401043643100 8	587.00	8/4	1	27
SX 120	4100-43120	401043643120 6	707.00	4/4	1	27
Accessories						
SGU	4100-0013	401043640013 4	207.00		10	28
SGUT	4100-0014	401043640014 1	40.00		10	28
SG	4100-0011	401043640011 0	109.00		10	28
SGM	4100-0012	401043640012 7	155.00		10	28

\*\* As long as stocks last

89125

CSP 6i

CSS

CSSi

Aerator

10 21

10 **21** 

10 **21** 

12 **21** 

<sup>\*</sup> Price adjustment from 01.06.2021: +5 % surcharge must be added to the quoted prices.

### At a glance

### **Boiling water heaters**



Туре	Part number	EAN	Euro*	UPP	PU	Page
Zip Hydroboil						
K5	4100-41002	401043641002 7	258.00	40/10	5	29
HB Plus 3	4100-44603	401043644603 3	1,046.00	8	1	29
HB Plus 5	4100-44605	401043644605 7	1,133.00	8	1	29
HB Plus 7	4100-44607	401043644607 1	1,173.00	8	1	29
HB 15	4100-44615	401043644615 6	2,203.00	4	1	30
HB 25	4100-44625	401043644625 5	2,534.00	2	1	30
HB 40	4100-44640	4010436446408	2,693.00	2	1	30
Accessories						
KAT 1	4100-44080	401043644080 2	70,-		10	31
KAT 2	4100-44081	401043644081 9	76,-		10	31
KAS 1	4100-44085	401043644085 7	70,-		10	31
KAS 2	4100-44086	401043644086 4	70,-		10	31
KA AZ	84426	401043684426 6	61,-		10	31
KA A	84427	401043684427 3	86,-		10	31
KA Z	84321	401043684321 4	58,-		10	31
ULTRA 500	84500	401043684500 3	184,-		10	31
ULTRA 1000	84501	401043684501 0	260,-		10	31
ULTRA 2000	84502	4010436845027	419,-		4	31

### Water systems



Туре	Part number	EAN	Euro*	UPP	PU	Page
Zip HydroTap G4						
BCS 100/75	4100-44579	401043644579 1	3,617.00		1	32
BCS 160/175	4100-44580	401043644580 7	4,604.00		1	32
BC 100/75	4100-44577	401043644577 7	3,221.00		1	33
CS 175	4100-44582	401043644582 1	2,970.00		1	34
B 160	4100-44578	401043644578 4	1,655.00		1	35
Taps						
Classic BCS	4100-44500	401043644500 5	488.00		1	32
Classic BCS	4100-44501	401043644501 2	636.00		1	32
Classic BCS	4100-44502	401043644502 9	636.00		1	32
Arc BCS	4100-44503	401043644503 6	488.00		1	32
Arc BCS	4100-44504	401043644504 3	636.00		1	32
Arc BCS	4100-44505	401043644505 0	636.00		1	32
Touch-Free BCS	4100-44540	401043644540 1	976.00		1	32
Celsius Arc AIO	4100-44524	401043644524 1	1,973.00		1	32
Celsius Arc AIO	4100-44525	401043644525 8	2,138.00		1	32
Celsius Arc AIO	4100-44526	401043644526 5	2,138.00		1	32
Classic BC	4100-44506	401043644506 7	488.00		1	33
Classic BC	4100-44507	401043644507 4	636.00		1	33
Classic BC	4100-44508	401043644508 1	636.00		1	33
Arc BC	4100-44509	401043644509 8	488.00		1	33
Arc BC	4100-44510	401043644510 4	636.00		1	33
Arc BC	4100-44511	401043644511 1	636.00		1	33
Touch-Free BC	4100-44541	4010436445418	976.00		1	33
Classic CS	4100-44518	401043644518 0	488.00		1	34
Classic CS	4100-44519	401043644519 7	636.00		1	34

Туре	Part number	EAN	Euro*	UPP	PU	Page
Classic CS	4100-44520	401043644520 3	636.00		1	34
Arc CS	4100-44521	401043644521 0	488.00		1	34
Arc CS	4100-44522	401043644522 7	636.00		1	34
Arc CS	4100-44523	401043644523 4	636.00		1	34
Touch-Free CS	4100-44544	401043644544 9	976.00		1	34
Classic B	4100-44512	4010436445128	488.00		1	35
Classic B	4100-44513	401043644513 5	636.00		1	35
Classic B	4100-44514	401043644514 2	636.00		1	35
Arc B	4100-44515	401043644515 9	488.00		1	35
Arc B	4100-44516	401043644516 6	636.00		1	35
Arc B	4100-44517	401043644517 3	636.00		1	35
Touch-Free B	4100-44542	401043644542 5	976.00		1	35
Accessories						
Classic AIO**	4100-44112	401043644112 0	1,013.00		1	36
KXV10	4100-44165	401043644165 6	83.00		10	36
KXV 20	4100-44166	401043644166 3	133.00		10	32
KXV40	4100-44167	401043644167 0	133.00		10	36
KXTV 10	4100-44565	401043644565 4	212.00		10	36
KXTV 20	4100-44566	401043644566 1	454.00		10	36
KXTV 40	4100-44567	4010436445678	454.00		10	36
KXTV 50	4100-44560	401043644560 9	148.00		1	36
KXTV 60	4100-44561	401043644561 6	253.00		1	36
KXTV 70	4100-44562	4010436445623	253.00		1	36
ULTRA 500	84500	401043684500 3	184.00		10	37
ULTRA 1000	84501	4010436845010	260.00		10	37
ULTRA 2000	84502	4010436845027	419.00		4	37
Filter head universal	84519	401043684519 5	105.00		10	37
KXF1	891289	4010436912897	153.00		10	37
KXF 2	891290	401043691290 3	153.00		10	37
KXF 1.1	893701	401043693701 2	153.00		5	37
KXF 2.1	893702	401043693702 9	153.00		5	37
COF	9910-90005	401043690005 5	30.00		10	37
DMSP	4100-44125	401043644125 0	96.00		10	38
DMBCS	4100-44120	401043644120 5	96.00		10	38
KXB	893450	401043693450 9	81.00		10	38
KXB-C	893541	401043693541 4	84.00		10	38
VBZ	84509	401043684509 6	137.00		10	38
DTK	893159	4010436931591	516.00		1	38
			*:	* As long	as stoo	cks last

### Apartment transfer stations



Туре	Part number	EAN	Euro* UPP	PU	Page
WS-Hybrid 13 kW	5100-51100	401043651100 7	2,207.00	1	39
WS-Hybrid 21 kW	5100-51150	401043651150 2	2,428.00	1	39
WS-B1000-20	5100-51105	401043651105 2	896	1	39

<sup>\*</sup> Price adjustment from 01.06.2021: +5% surcharge must be added to the quoted prices.

### General Terms and Conditions of Sale and Delivery

Last updated: May 2021

#### I. General

- 1. These terms and conditions of sale and delivery (hereinafte "GCSD") shall apply exclusively to all our business relations with our customers. Our GCSD shall only apply if the customer is an entrepreneur (§ 14 BGB), a legal entity under public law or a special fund under public law. We do not accept the customer's own terms and conditions if different or contrary to our terms and conditions. These terms and conditions shall apply even if we execute delivery to the customer without reservation in the knowledge of the customer's terms and conditions that are different or contrary to our terms and conditions.
- 2. Individual agreements made with the customer in individual cases shall in any case take precedence over these GCSD. The content of such agreements shall be governed by a contract in writing or text form.
- 3. All quotations issued by us are subject to change and without obligation. This shall also apply if we have provided the customer with catalogs, technical documentation (e.g. drawings, plans, calculations, references to DIN standards). other product descriptions or documents - also in electronic form. A contractual relationship shall only come into force when it has been acknowledged by us in writing or the goods are delivered. If an order addressed to us is sent by e-mail and that e-mail is confirmed as received such confirmation shall not constitute acknowledgment of the order.
- 4. Legally relevant declarations and notifications by the customer with regard to the contract (e.g. setting of deadlines, notification of defects, rescission or reduction) shall be made in writing or text form (e.g. letter, e-mail, fax). Legal formal requirements and further proof, in particular in the case of doubts about the legitimacy of the person making the declaration, shall remain unaffected.
- 5. We reserve the copyright to catalogs, technical documen tation (e.g. drawings, plans, calculations, references to DIN standards), other product descriptions or documents. If an order is not placed, the drawings and other documents enclosed with the offers and prepared by us shall be returned immediately upon request.

- 1. Unless agreed otherwise, our prices are quoted ex works/ warehouse including standard packaging and in Euros. Any customs duties, fees, taxes and other public charges shall be borne by the customer. The statutory value-added tax is not included in our prices; it will be shown separately in the invoice at the statutory rate on the day of invoicing.
- 2. The prices quoted in order acknowledgments apply exclusively to the dimensions and versions specified therein We shall be entitled to charge correspondingly higher prices for divergences from the original order, any changes in version or additional performances ordered by the customer and implemented.
- 3. Our prices are quoted exclusive of value-added tax at the statutory rate. It is itemized separately in the invoice at the statutory rate in force on the invoice date.

### III. Payments

- 1. Payments shall be effected in accordance with the agreed terms of payment. Payments shall be deemed to have been effected on the date on which the sum is at our disposal (obligation to be performed at the creditor's habitual place of residence) and shall be set off against the oldest debt due. They shall be set off against costs, interest and the principal outstanding, in that order.
- 2. Invoices shall be payable within thirty (30) days of the invoice date, unless otherwise agreed.
- 3. If payments are in arrears, we shall be entitled to charge interest on the defaulted sum at the statutory rate. The right to claim further damages due to delayed performance is reserved.
- 4. The customer shall only be entitled to set off payments against counterclaims which have been legally established by a court of law, which are undisputed or which have been accepted by us at least in text form. Moreover, the customer may only withhold payments if the counterclaim is based on the same contractual relationship.

### IV. Delivery / shipment

- 1. Our quoted time for delivery shall not start until the customer has correctly fulfilled its obligations in a timely manner. The right to plead non-performance of the contract
- 2. If we are unable to meet binding delivery deadlines for reasons for which we are not responsible (non-availability of the service), we shall inform the customer without delay and at the same time notify the customer of the expected new

- delivery deadline. If the service is also not available within the new delivery period, we shall be entitled to withdraw from the contract in whole or in part; we shall immediately refund any consideration already made by the customer.
- 3. Delivery takes place ex warehouse. If the goods are dispatched at the customer's request the risk of accidental loss or deterioration of the goods shall pass to the customer upon dispatch to the customer by the stipulated delivery date and at the latest upon leaving the factory or warehouse. This shall apply irrespective of whether the goods are shipped from the place of performance or who bears the shipping costs. If dispatch is delayed by actions or declarations by the customer, the risk shall pass to the customer as from the date on which the goods are ready for shipment.
- If the customer is in default of acceptance or culpably violates other duties to cooperate, we shall be entitled to demand compensation for the loss thereby suffered, including any extra expense incurred. The right to assert other claims or rights is reserved.

#### V. Reservation of proprietary rights

- We reserve ownership of the goods until receipt of all payments arising from the business relationship with the customer
- 2 In case of breach of contract by the customer and particularly if payments are in arrears, we shall be entitled to rescind the contract and reclaim the goods after setting an appropriate period of grace. After taking back the purchased goods we shall be entitled to dispose of the goods and the proceeds from such disposal shall be set off against our claims against the customer
- The customer shall inform us immediately in writing or in text form in the event of seizure or other third party intervention. In the event of seizures or other interventions by third parties, the customer shall notify us immediately in writing or in text form. If, after conclusion of the contract, it becomes apparent (e.g. by filing for insolvency proceedings) that our claim to the purchase price is jeopardized by the customer's inability to pay, we shall be entitled to refuse performance in accordance with the statutory provisions and - if necessary after setting a deadline - to withdraw from the contract (§ 321 BGB). In the case of contracts for the manufacture of unjustifiable items (custom-made products), we may declare withdrawal immediately; the legal regulations on the dispensability of setting a deadline shall remain unaffected.
- 4. The customer is entitled to resell the goods in the ordinary course of business. However, the customer herewith assigns its future claims (including value-added tax at the rate in force) arising from resale against third party to us according to the invoice value of the goods. The customer shall remain entitled to collect the claims but, if the customer fails to meet its payment obligations, gets into arrears of payment or if an application for commencement of composition or insolvency proceedings is made, the customer shall give us the name of its customer and the third party and the invoice details of the goods sold.
- 5. Processing or conversion of the goods by the customer shall always be undertaken on behalf of us. If the goods are processed or mixed with other objects we shall acquire joint ownership of the new thing in proportion of the value of the
- The customer shall also assign to us as security for the claims against him the claims arising against a third party from combination of the goods with a property. We accept

- Any warranty rights and rights of recourse on the customer's part shall be dependent upon the customer's having duly fulfilled his obligations of examination and notification of defects in accordance with Section 377 of the German Commercial Code.
- The usual minor technical deviations in design or workmanship (e.g. quality, colour, size) of the goods shall not constitute a defect, insofar as they do not significantly impair either the serviceability or the value of the goods, and shall not confer any warranty rights.
- If at the time of passing of risk the goods are defective we may choose whether to provide subsequent performance by remedying the defect (rectification) or by delivering a defect-free item (replacement). We are entitled to make the subsequent performance owed dependent on the customer paying the purchase price due. The customer shall be entitled to retain an appropriate part of the purchase price in relation to the defect.

- 4. In the event of subsequent performance, we shall bear all expenses necessary for the purpose of remedying the defect in accordance with the statutory provisions, unless such expenses are increased by the fact that the goods have been taken to a place other than the place of performance.
- The warranty shall not include such defects or damage attributable to incorrect handling, use or installation of the goods by the customer or other third parties. In addition, warranty claims shall be excluded in the case of goods on which work has been undertaken by third parties without our consent.
- 6. Liability cannot be accepted for any damage or losses due to the build-up of scale or chemical or electrochemical action, or to the use of supplementary, replacement or accessory parts and fittings which have not been specially adapted to our goods; this also applies to damage or losses due to noncompliance with the installation and operating instructions.
- 7. If the customer has received goods and satisfies warranty claims, based on its own customer's warranty right, arising from a defect in the goods that was present at the time of passing of risk, the customer shall be entitled to demand compensation only for the foreseeable expenses typically necessary for that purpose
- 8. The statutory warranty periods shall apply. A one-year period of limitation shall apply in the case of commercial. craft and industrial enterprises or activities of a similar or comparable nature (e.g. freelance or professional work).

- 1. We shall be liable as provided by law in the event of intent or gross negligence on our part or that of our vicarious agents and likewise in the case of culpable breach of essential contractual obligations.
- Our liability for culpable injury to life, limb or health and our liability in accordance with the German Product Liability Act shall be unaffected.
- . In the event of negligently caused property damage or pecuniary loss we shall be liable only if an essential contractual obligation has been breached. The amount shall be limited to the losses foreseeable and typical at the time of the conclusion of the contract.

### VIII. Taking back and disposal

- 1. Consumers may dispose of goods produced by us that come under the German Act on the Marketing, Taking Back and Environmentally Sound Disposal of Electrical and Electronic Equipment (ElektroG) by taking them to a municipal collection point. This is a free service
- 2. Customers reselling our goods for payment or without payment to external third parties carrying on a commercial, craft or industrial enterprise or other similar or comparable activities shall give us an undertaking that they will meet the cost of correct disposal in accordance with the abovementioned Act.
- . Our claims for the meeting of costs and any consequential claims shall become due as soon as we are notified by the customer or a third party (e.g. authority) of the disposal costs actually incurred.

### IX. Jurisdiction and applicable law / GDPR

- Unless otherwise agreed, the place of performance and exclusive place of jurisdiction for all disputes arising from this contract shall be at our headquarters (Lüneburg).
- 2. The laws of the Federal Republic of Germany shall always apply. The UN Convention on the International Sale of Goods (CISG) is herewith explicitly excluded.
- 3. We are, in principle, unwilling and not obliged to participate in any dispute resolution procedure at a consumer
- 4. CLAGE and its vicarious agents are entitled to collect, use, transfer, store or otherwise process customer information that may be assigned to specific individuals ('personal data') for the purposes of the performance of contractually agreed services, quality and risk management and/or invoicing. CLAGE processes personal data exclusively in accordance with applicable law, especially in consideration of the GDPR and the Federal Data Protection Act, and refers to its data protection statement as per Article 13
- 5. If any of the provisions prove or become partly or complete ly invalid, this shall not affect the validity of the remainder

CLAGE GmbH · 21337 Lüneburg / Germany Registered at Lüneburg District Court, HRB 1159 Managing Directors: Jörg A. Gerdes, Joachim D. Gerdes VAT number: DE 116084519



CLAGE GmbH Pirolweg 4 21337 Lüneburg Germany

Phone: +49(0)41318901-888

export@clage.de www.clage.com

Retailer's stamp