



# Specifications

**Payload** 

Waste Management (waste, recyclables)

## **Dimensions**

Length	53' (14.6m)
Width	102" (2.6m)
Overall Height	162" (4.1m)
Volume	3,905 ft <sup>3</sup> (144.6 yd³)
Weight	14,006 kg (30,877.9 lbs)

## Running Gear

Axles/Suspensions	Primary/Lifts: SAF CBX 25/30 Steers: Titan ParaMAX 25,000 lbs
ABS	6S4M
Brake Type	Drum
Tires	Goodyear & Continental
Landing Gear	Holland Mark 5

Body	
Side Panels	Aluminum Patented THINWALL® Horizontal Hollow-Core Extruded Panels
Flooring	Keith® Walking Floor Unit
Mud flaps	Black Rubber with Titan Logo
Lights	LED - Truck Lite
Rear Door	Side Swing Door in Door, Air Operated
Bumper	None - Bottom of lightbar is less than 22" from ground - bumper not required



# TITAN 53' 7 Axle THINWALL® Walking Floor (S.P.I.F.#7)

# THINWALL Original

# TAILOR YOUR TITAN

# to suit your personal preference and application



Front Access Door



24" Catwalk



Front Roadside Ladder



All Aluminum Chassis



**Top Cross Tubes** 



Back Ladder Centre of Rear Door



Tow Shackles



Flip Down Step



Top Rail Overlay



Triple Ridge 18, Slat Floor with 2' Wear Strips at Rear

## **IOB PROFILE**

- Maximize your profit with larger load capacity, fuel efficiency and minimal downtime Effective performance and customer satisfaction require rapid on and off-loading with reliability
- · Long-term return-on-investment means low maintenance costs plus maximum residual value

### **KEY FEATURES**

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside AND outside for end-to-end strength.
- KEITH® WALKING FLOOR® Steel coupler assembly with bolt in kingpin Aluminum frame/floor assembly Offset top rail Single top cross tube

#### **HEAD OFFICE**

1129 Hwy #3, R.R. #3, Delhi, Ontario, Canada N4B 2W6 Tel: 519-688-4826 • Fax: 519-688-6453 • e-mail: info@titantrailers.com

