

Model P4010ACSCOAQ-WF Compatibility Guide

The following Kidde models can be interconnected to P4010ACSCOAQ-WF / 21030843 using the standard AC wiring interconnect:

120V AC/DC Smoke Alarms



i12060-A, i12060
(21006931 9V Alkaline,
21006376 9V Carbon Zinc)
120V AC/DC Spring load,
Hush, w/Alkaline Batt.
(repl 1276A)



i5000
(21007582)
120V AC/DC Slide load
w/Alkaline Batt. 10yr.
Warranty



i4618-A, i4618
(21007583 9V Alkaline,
21007581 9V Carbon Zinc)
120V AC/DC Slide load w/
Alkaline Batt., 6 pk. (repl
46182)



RF-SM-AC
(1279-9999)
120V AC/DC RF
Wireless Interconnect
3pc PDQ



i12040
(21006378)
120V AC/DC Rear load,
front pull tab, Hush
(repl 1275)



i12080
(21006379)
120V AC/DC with Light,
Hush (repl 1285)



P12040
(21006371)
Photoelectric 120V AC/
DC, Hush (formerly
PE120)



PI2010
(21007915-N)
120V AC/DC, Photo/
Ion Dual Sensor,
Wire-in, Hush

Combination CO/Smoke Alarms



KN-COSM-IBA (21006377-N)
AC/DC Wire-In Intelligent Ion
Smoke/CO Alarm, Front Load
Battery, Voice (900-0114A)



KN-COPE-IC (21007624)
AC/DC Wire-In Photoelectric
Smoke/CO Alarm - Voice
Warning (900-0123)

Model P4010ACSCOAQ-WF Compatibility Guide

Ten-Year Sealed Lithium Battery Alarms



i12010SCO (21010408-N)

120V AC/DC Intelligent Ion
Smoke/CO Alarm, Ten-Year
Sealed Battery, Voice



i12010S (21010407-A)

120V AC/DC Ion Smoke
Alarm, Ten-Year Sealed
Battery Backup



P4010ACSCO (21027536)

120V AC/DC Intelligent Photo
Smoke/CO Alarm, Ten-Year
Sealed Battery, Voice



P4010ACS (21027537)

120V AC/DC Photo Smoke
Alarm, Ten Year Sealed Battery
Backup, Voice



**P4010ACLEDS-2
(21026872) ***

120V AC/DC Smoke/Strobe
Alarm, Ten-Year Sealed
Battery, Sync, Voice



**P4010ACLEDSCO-2
(21028057) ***

120V AC/DC Smoke/CO/
Strobe Alarm, Ten-Year
Sealed Battery, Sync, Voice



**P4010ACSCO-W
(21027323)**

120V AC/DC Wireless
Combo CO/Smoke,
Photo, Ten-Year



**P4010LACS-W
(21027326)**

120V AC/DC Wireless
Smoke w/Light,
Photo, Ten-Year



**P4010ACS-W
(21027320)**

120V AC/DC
Wireless Smoke,
Photo, Ten-Year

Auxiliary Devices



HD135F

135° Heat Detector -
120V AC w/9V backup



SL177i (SLED177i) *

Hearing Impaired LED 177cd
Light - Interconnectable