

Good

Better

Best

Click on products
to learn more

		Metalux RBG	Corelite Bryx	Corelite Hugo	Corelite RZL	Metalux WSL	Corelite Jaylum
APPLICABILITY¹	Education	★★★	★★★	★★★	★★	★★	★★★
	Office	★	★	★★	★	★★★	★★★
	Healthcare	★★	★★	★★	★★	★★	★★
	Retail	★★★	★★★	★★★	★★	★★★	★
FEATURES / PERFORMANCE	Construction	Extruded Aluminum	Steel / Extruded Aluminum	Extruded Aluminum	Cold Rolled Steel	Steel/Extruded Aluminum	Cold Rolled Steel
	Lengths	4', 8', 12', Cont.	4', 8', Cont.	4', 8', 12', Cont.	4', 8', 12', Cont.	4', 8', Cont.	4', 8', Cont.
	lm/W (Max)	145	138	145	135	133	157
	Lumens (Max)	8000 (2000 lms/ft)	9840 (2460 lm/ft)	8000 (2000 lms/ft)	8800 (2200 lms/ft)	8000 (2000 lms/ft)	8000 (2000 lms/ft)
	Up/Down % Options	2	20	2	2	3	5
	CIE Type	Direct, Semi-Direct	Direct/Indirect	Direct, Semi-Direct	Direct, Semi-Direct	Direct, Semi-Direct	Direct/Indirect
	Life (@60K)	L85	L86	L85	L85	L93	L93
	Shielding	Frost - Smooth, Drop Lens, Baffle	Frost - Smooth	Frost - Smooth, Drop Lens, Baffle	Frost -Linear Prismatic, Baffle	WaveStream - Acrylic	Frost - Smooth
	Mounting Type	Surface, Suspended, Recessed	Surface, Suspended, Recessed	Surface, Suspended	Surface, Suspended	Surface, Suspended	Suspended, Wall, Sconce
	Driver Location	Integral	Integral	Integral	Integral	Integral	Integral
	Emergency	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
	CRI	80+ / 90	80+	80+ / 90	80+ / 90	80+ / 90	80+ / 90
	Sensor Location	Integrated, Side Mount	Integrated	Integrated, Side Mount	Integrated	Integrated, Fixture or Hub	Integrated
INTEGRATED CONTROLS	DLC	Premium	Premium	Premium	Premium	Premium	Premium
	VividTune™	No	No	No	No	No	Tunable White
	Stand Alone Daylight / Occupancy				✓	✓	
	WaveLinx	✓	✓	✓	✓	✓	✓
	Enlighted	✓		✓	✓	✓	✓

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable

		Corelite Iridium i3	Corelite Continua CTA	Corelite Continua SQ4	Corelite Iridium i2 WaveStream	Corelite Divide	Corelite Vaulta
APPLICABILITY¹	Education	★★★	★★★	★★	★★	★★	★★
	Office	★★	★★	★★★	★★★	★★★	★★★
	Healthcare	★★	★★	★	★★	★★	★★
	Retail	★	★★	★★	★★	★★	★
FEATURES / PERFORMANCE	Construction	Cold Rolled Steel	Extruded Aluminum	Extruded Aluminum	Cold Rolled Steel	Extruded Aluminum	Extruded Aluminum
	Lengths	4', 8', Cont.	4', 8', 12', Cont.	4', 6', 8', 12', Cont.	4', 8', Cont.	4', 8', Cont.	4',6', 8', 12' Cont.
	lm/W (Max)	158	147	135	114	140	127
	Lumens (Max)	8000 (2000 lms/ft)	6000 (1500 lms/ft)	10,800 lm (2,700 lms/ft)	7200 (1800 lms/ft)	6000 (1500 lms/ft)	1250 (1500 lms/ft)
	Up/Down % Options	5	4+	20+	3	2	28+
	CIE Type	Direct/Indirect	Direct, Direct/Indirect	Direct, Direct/Indirect	Direct, Direct/Indirect	Direct, Direct/Indirect	Direct, Direct/Indirect
	Life (@60K)	L93	L84	L84	L81	L87	L85
	Shielding	Frost - Smooth	Frost - Continuous Roll Lens	Frost - Continuous Roll Lens	Frost - Smooth	Frost - Smooth	Discrete Optics, Black or White Baffles
	Mounting Type	Suspended	Suspended, Wall	Surface, Suspended, Recessed	Suspended	Surface, Suspended, Recessed	Surface, Suspended
	Driver Location	Integral	Integral	Integral	Integral	Integral	Integral
	Emergency	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
	CRI	80+ / 90	80+ / 90	80+ / 90	80+ / 90	90+	80+ / 90
	Sensor Location	Integrated	Integrated, Side Mount	Integrated, Endcap/Side Mount	Integrated	Integrated	Integrated
INTEGRATED CONTROLS	DLC	None	Premium	Premium	In-process	In-process	In-process
	VividTune™	Tunable White	No	Premium	Standard	Premium	In-process
	Stand Alone Daylight / Occupancy	✓			✓		
	WaveLinx	✓	✓	✓	✓	✓	✓
	Enlighted	✓	✓	✓	✓	✓	✓




Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable

Architectural LED

Linear Ambient

Best

Click on products
to learn more



		Corelite S02	NeoRay Cirque	NeoRay Omni	NeoRay Define	NeoRay Converge	NeoRay Covera
APPLICABILITY ¹	Education	★★	★★	★★	★★★	★★★	★★★
	Office	★★	★★★	★★★	★★★	★★★	★★★
	Healthcare	★★	★★	★★	★★★	★	★
	Retail	★★	★	★	★★	★★	★★
FEATURES / PERFORMANCE	Construction	Extruded Aluminum	Extruded Aluminum	Extruded Aluminum	Extruded Aluminum	Extruded Aluminum	Metal cast
	Lengths	4',6', 8', 12' Cont.	4',6', 8', 12' Cont.	4',6', 8', 12' Cont.	2' - 12', Cont.	4', 8', Cont.	2', 4'
	lm/W (Max)	127	164	121	164	119	157
	Lumens (Max)	11920 (2980 lms/ft)	1500 (2475 lms/ft)	1500 (2475 lms/ft)	9900 (2475 lms/ft)	6700 (1700 lms/ft)	8000 (2000 lms/ft)
	Up/Down % Options	28+	28+	28+	∞	3	2
	CIE Type	Direct, Direct/Indirect	Direct, Direct/Indirect, Indirect	Direct, Direct/Indirect, Indirect	Direct, Direct/Indirect, Indirect	Direct, Direct/Indirect	Direct/Indirect
	Life (@60K)	L85	L90	L85	L85	L93	L93
	Shielding	Discrete Optics, Black or White Baffles	Discrete Optics, Black or White Baffles	Discrete Optics, Black or White Baffle	Diffuse, Drop, 1in Regress, 3inRegress,Asymmetric,Batwing, Graze, Wash, Corridor	WaveStream - Frost, Smooth	WaveStream- Frost, Smooth
	Mounting Type	Surface	Surface, Suspended, Recessed	Surface, Suspended	Suspended, Surface, Wall, Recessed, Perimeter	Suspended	Suspended
	Driver Location	Integral	Integral	Integral	Integral	Remote w/ Luxwire	Integral
	Emergency	Integrated	Integrated	Integrated	Integrated	Remote	Integrated
	CRI	90+	80+ / 90	80+ / 90	80+ / 90	80+ / 90	80+ / 90
	Sensor Location	Integrated	Integrated	Integrated	Integrated	Tile Mount	Integrated
INTEGRATED CONTROLS	DLC	In-process	In-process	In-Process	Premium	None	None
	VividTune™	No	No	No	Tunable White	No	No
	Stand Alone Daylight / Occupancy				✓	✓	✓
INTEGRATED CONTROLS	WaveLinx	✓	✓	✓	✓	✓	✓
	Enlighted	✓	✓	✓	✓	✓	✓

Notes: 1. ★★★ = high applicability, ★★ = medium applicability, ★ = low applicability, blank = non-applicable