

60cm Series 9 Contemporary Warming Drawer

Series 9 | Contemporary



Serve meals hot and directly from a pre-heated plate thanks to our panel-ready, warming drawer.

- Integrates with surrounding cabinetry for a seamless look
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	290 mm
Width	596 mm
Depth	567 mm

FEATURES & BENEFITS

Complementary Design

Our Warming Drawer comes with the option of a stylish black glass panel or elegant grey glass panel, for seamless pairing with our Minimal or Contemporary style ovens.

Multi-Function Flexibility

Choose from six tailored functions including Rapid Proof for proofing dough, Dehydrate for drying foods such as meat, fruit and herbs and Slow Cook, ideal for finishing of seared meats, casseroles, stews and braises.

Precise Control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking. You can even rest meat after a traditional roast in the oven and proof dough for bread making and pizza.

Added Convenience

Handle-free, push-to-open with intuitive touch controls, our warming drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Easy To Clean

Cleaning and care of the warming drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Safe And Sound

With automatic switch-off and delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

Sized To Suit

With enough room to gently heat 16 place settings, 20 cappuccino cups or 42 espresso cups, our tall warming drawer is an ideal kitchen companion.

SPECIFICATIONS

Accessories (included)

Wire shelf	1
------------	---

Capacity

Accessory rack maximum allowable weight	19kg
Cappuccino cups	20
Espresso cups	42
Maximum allowable weight	25 kg
Place settings	16
Usable depth	408 mm
Usable height	237 mm
Usable width	535 mm

Cleaning

Easy clean smooth-glass base	•
------------------------------	---

Controls

Audio feedback	•
Automatic pre-set temperatures	•

Automatic timers	30', 45', 1h, 2h, 4h, 6h	Supply frequency	50 Hz	↓	User Guide Warming Drawer DEU
Delayed start	•	Supply voltage	220 V	↓	User Guide Warming Drawer DUT
Electronic capacitive touch controls	•			↓	User Guide Warming Drawer
On/Off indicator	•			↓	User Guide Warming Drawer FIN
Pre-set heating functions	•			↓	User Guide Warming Drawer FR
Push-to-open drawer	•			↓	User Guide Warming Drawer HEB
Standby mode	•			↓	User Guide Warming Drawer ITA
				↓	User Guide Warming Drawer NOR
				↓	User Guide Warming Drawer SWE
Functions		Product dimensions			
Cups	•	Adjustable front door panel to align with surrounding cabinetry	•		
Dehydrate	•	Depth	567 mm		
Number of functions	6	Height	290 mm		
Plates	•	Width	596 mm		
Rapid proof	•				
Slow cook	•				
Warm	•				
Performance		Safety			
Heated glass base and fan	•	Automatic turn off after 12 hours	•		
Low temperature cooking	•	Full extension slides	•		
Temperature levels	6				
Temperature range	35°C-85°C				
Power requirements		SKU	84229		
Amperage	10 A	The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020			
Power cord length	1800 mm	Other product downloads available at fisherpaykel.com			
Power outlet	3-prong grounding-type	↓	2D-DWG Warming Drawer		
		↓	2D-DXF Warming Drawer		
		↓	Declaration of Conformity		
		↓	User Guide Warming Drawer DA		

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 08000886605 W [www.fisherpaykel.com](#)