

PL 68EN

CEILING SPEAKER WITH FIRE DOME



Description

PL 68EN is a ceiling speaker featuring a flameproof steel back can, designed for recess installation into ceilings or panels. It is especially suitable for broadcasting alarm messages thanks to the highly intelligible sound reproduction and its resistance to high temperatures reached during fires. The terminal connection blocks, for input and output flameproof cables, are made of ceramic material. A thermal fuse protects the integrity of the line in case of heat affecting the speaker. Ground screw available (if needed). Cables inside speaker made using flameproof leads.

Features

- > 6" fullrange transducer.
- \rightarrow Power selectable (100 V): 6 W 3 W 1.5 W.
- > 94 dB sensitivity.
- > Colour white RAL 9003.
- > Steel frame, grille and back can.
- > In/out ceramic terminal block.
- > Thermal fuse protection.

Part Number

13133082 PL 68EN

100 V

White - RAL 9003 EAN 8024530011857







PL 68EN

CEILING SPEAKER WITH FIRE DOME

Line Art 2D





TECHNICAL SPECIFICATIONS

Acoustical specifications Frequency Response (-10dB) 230 Hz ÷ 20000 Hz

 Max SPL @ 1m
 102 dB

 Max SPL @ 4m
 90 dB

 Coverage angle
 126°

 System Sensitivity
 94 dB

 System Sensitivity 1W @ 4m
 82 dB

Power sectionAmplificationFull RangePower Handling6 W

Power Handling 6 W
Peak Power Handling 24 W PEAK
Protections Thermal fuse

Recommended Amplifiers DXT 3000, DXT 4000, DXT 7000

Transducers Fullrange 1 x 6.0"

Input/Output section Input connectors Ceramic screw terminals

Output connectors Ceramic screw terminals
Constant Voltage Transformer 100 V

Constant Voltage Transformer

Power selection 1

Power selection 2

Power selection 3

Safety agency

100 V

6 W - 1667 ohm

3 W - 3333 ohm

1.5 W - 6667 ohm

CE compliant

Standard complianceSafety agencyCE compliantEN54-24 certifiedYes

CPR number 1488-CPR-0486/W

Physical specificationsCabinet/Case MaterialMetalHardwareSteel back cover

Grille Steel

Color White - RAL 9003

Size Height 91 mm / 3.58 inches

Recessed Depth 90 mm / 3.54 inches
Diameter 220 mm / 8.66 inches
Cut out diameter 200 mm / 7.87 inches
Weight 1.12 kg / 2.47 lbs

Technical Specifications Page 2 of 2