



25683B

20000mAh 20W 1C2A Powerbank



Specifications

- * Input: USB-C : 5V3A 9V2.22A 12V1.67A 20W Max
- * Output:
- USB-C : 5V3A 9V2.22A 12V1.67A 20W Max
- USB-A 1: 10V2.25A 5V3A 9V2A 12V1.5A 22.5W Max
- USB-A 2: 10V2.25A 5V3A 9V2A 12V1.5A 22.5W Max
- Dual/Three-port Output: 5V 3A, 15W Max
- * Battery capacity: 20,000mAh (2*10000mAh)
- * Battery energy: 74Wh (20,000mAh * 3.7V)
- * Rated capacity: 12,500mAh (TYP 5V3A)
- * Battery Type: Lithium Polymer Battery (Brand: Ampress/Yiwei)
- * Support Protocols:
- Input: USB-C: PD3.0/PD2.0/FCP/AFC/BC1.2/5V Adaptive
- Output: USB-C: PD3.0/PD2.0/PPS/QC3.0/QC2.0/FCP/AFC/APPLE 5V2.4A/BC1.2/5V
- USB-A: SCP/QC3.0/QC2.0/FCP/AFC/APPLE 5V2.4A/BC1.2/5V
- * Working environment temperature: -10°C to 35°C (no condensation or ice)
- * Storage environment temperature: -10°C to 55°C (no condensation or ice)
- * Full charge time: approximately 6 hours (using a PD20W charger)
- * Full battery storage time: Estimated 6 years
- * Cable: AC cable, 3A, 0.5 meters
- * USB-C pins: 16PIN, USB-A pins: 4PIN
- * Battery Life Cycle Count: Standard: 300 cycles with at least 80% remaining capacity
- * Product net weight: 426±10 g
- * Discharge Output Capacity

Selling points



MORE FOR YOU