


Surface Mount Grid System

CeilingMAX®

Room Planning

ESTABLISHING ALIGNMENT

To ensure professional looking results, the room layout should be balanced with equal size border panels used on opposite sides of the room, as shown below.



■ = Border Panels

Formula:

- Measure room in one direction
- Round down to closest even number of feet
- Subtract those numbers
- Add 24" (48" for 4' direction using 2'x4' panels)
- Divide by 2 to get border tile size

Example

$$\begin{array}{r}
 17'6'' \\
 \underline{16'} \\
 1'6'' \\
 1'6'' - 16' = 18'' \\
 \underline{18'' + 24'' = 42''} \\
 42'' \div 2 = 21''
 \end{array}$$

Your Project

Establish your string (or dryline) at this measurement. Repeat these same steps for the other direction. **Note:** If your border tile size ends up being 0" or 24" adjust the layout so your border tiles are less than 24-inches. Otherwise, the Cross-Tees will be too short.

Tools you will need



String or Chalk Line



Drill with Phillips Tip



Tape Measure



Tin Snips



Quantity of 1" Drywall Screws

Surface Mount Grid System

CeilingMAX®

Here are some examples of the amount of CeilingMAX 100 square foot kits and ceiling tiles needed based on some room dimensions.

Room Size:	# Cases 2'x2'	# Cases 2'x4'	# 100 s.f. Kits
6'x6'	1	1	1
8'x8'	1	1	1
8'x10'	2	1	1
10'x10'	3	2	2
10'x15'	4	2	2
10'x12'	3	2	2
12'x18'	5	3	3
14'x16'	5	3	3
16'x20'	7	4	4