

CMM-30

Marine Source Unit with Full-Color LCD

OWNER'S MANGAL MANUEL D'UTILISATION MANUAL DEL PROPIETARIO BEDIENUNGSANLEITUNG MANUALE DEL PROPRIETARIO






































FCC COMPLIANCE STATEMENT

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must not accept any interference received, including interference that may cause undesired operation. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a perticular installation. If this equipment does cause harmful interference to radio or television reception, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase separation between the equipment and the receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.


SAFETY CONSIDERATIONS

- Only use this product in vehicles with 12 volt, negative-ground electrical systems. This product is not certified or approved for use in aircraft.
- Mount this product securely to prevent damage or injury in severe conditions.
- Do not replace the power wire fuse with one of a different value.
 Never bypass the fuse.
- Listen to your audio system at levels appropriate for operating conditions and hearing safety.

INSTALLATION CONSIDERATIONS

- Installation requires appropriate tools and safety equipment.
 Professional installation is recommended.
- This product is water-resistant. Do not submerge or subject to highpressure water spray.
- Before installation, turn off the audio system and disconnect the battery system from the audio system.
- Install in a dry, well-ventilated location that does not interfere with your factory-installed systems. If a dry environment is not available, a location that is not exposed to heavy splashing may be used.
- Before cutting or drilling, check for potential obstacles behind mounting surfaces.
- Carefully route all system wiring away moving parts and sharp edges, secure with cable ties or wire clamps and use grommets and loom where appropriate to protect from sharp edges.

GENERAL CONTROL FUNCTIONS



Control		Function	
SOURCE	Source/ Power	Short press to turn ON; Long press to turn OFF When on, short press to display the Source: Select menu	
0	Volume/ Select	Rotate to adjust volume Rotate/press for navigation and making selections	
SETTONGS	Settings	Short press to access Tone, Balance & EQ settings Long press to access Settings: Main Menu	
BACKWENZ	Back/ Memu	Short press to go back one step or access source specific menus.	
**	Favorites	Short press to access stored presets Long press to store a frequency as a preset (up to 18)	
►n	Mute/ Pause	 Short press to mute/unmute audio (AM/FM/Srss/XM/WB/AcxQ or pause/resume the current selection (USB/Bluetooth) 	
▶ ►	Forward	Short press to: • Manually adjust tuner forwards (AM/FM/SmusXM/WE) • Select the next track (USB/Bluetooth) Long press to: • Seek to the next channel (AM/FM/WE) • Initiate Rapid Channel Browsing forward (SelusXM) • Fast-forward (USB/Bluetooth)	
144	Backward	Short press to: • Manually adjust tuner beckwards (AM/FM/SirusXM/WB) • Restart track/select the previous track (USB/Bluetooth) Lung press to: • Seek to the previous channel (AM/FM/WB) • Initiate Rapid Channel Browsing backward (SiriusXM) • Fast-rewind (USB/Bluetooth)	

SYSTEM MENU SETTINGS		
SETTONGS	Long press to access the Settings: Main Menu	
0	Rotate to navigate Press to make selections	
Setting	Function	
Audio Zone Satup	Configures each set of audio zone outputs	
Aux Input Sensitivity	Configures AUX input sensitivity: 2V or 1V RMS (default)	
Diagnostic	Displays hardware and software version into	
Display	Configures display and brightness settings	
Scrolling test	Enables continuous scralling of available RDS/track text info	
Tuner Region	Configures AMFM tuner range/scale for a specific region	

	FAVORITES MENU SETTINGS	
FAVORETES	Short press to access settings/stored presets Long press to store a frequency as a preset (up to 18)	
0	Rotate to navigate Press to make selections	
Setting	Function	
Edit	Select to Move or Delete stored presets	

	TONE, BALANCE & EQ MENU SETTINGS		
SETTINGS	Short press to access settings		
0	Rotate to navigate Press to make selections		
Setting	Function	Note	
Treble	Trobile level control from -10 to +10		
Mid	Mid level control from -10 to +10	EQ must be set to Off	
Bass	Bass level control from -10 to +10		
Balance	Balance control from full left J-10) to full right (+10)		
EO	5-band equalizer control from -10 to +10 per band		

	AUDIO ZONE	MENU SETTINGS
O SETTINGS	Long press to access settings	
0	Rotate to navigate Press to make selections	
Zone	Function	Setting 1
		Variable (default)
	Level Control Mode	Absolute
		Sub (Zone 4 only)
		Off
tt: Zone 1	HP Xaver	Off
22: Zone 2		80 Hz
23: Zone 3 24: Zone 4		100 Hz
za: zane v		120 Hz
	Rename Zone	Bow, Bridge, Calom, Cockpit, Galley, Helm, Statemoom 1, Statemoom 2, Tower, Transom
		Factory Default
	Volume Limit	Max Volume Limit

	BLUETOOTH MENU SETTINGS		
Short press to access settings			
0	Rotate to navigate Press to make selections		
Setting	Function		
Now Playing	Return to the Now Playing Screen		
Connect Paired Device	Display all paired devices for connection		
Pair New Device	Initiates Pairing Mode (current connected devices will be disconnected		
Set Primary Device	Assign priority to a paired device for automatic connection		
Delete a Paired Device	Select from paired devices for removal		
Delete All Paired devices	Removes all pained devices from memory		

USB MENU SETTINGS		
≜ EACK/MENU	Short press to access settings	
0	Rotate to navigate Press to make selections	
Setting	Function	
Now Playing	Return to the Now Playing Screen	
Random	Random playback of all tracks	
Repeat	Repeats playback of the current track or all tracks	
Play All	Plays all tracks within all folders	
Folder list	Displays list of folders/trucks	

IMPORTANT

- Properly secure the connected device before driving to prevent damage from dropping or sudden acceleration/braking.
- Control, functionality and display may vary depending on the model and version of iPhone® connected.
- When connected via USB port, make sure to unpair or disable the Bluetooth connection to avoid possible playback conflicts.
- If you experience abnormal performance during operation, disconnect the iPhone® and check its condition, Restart your iPhone® if performance does not improve.
- "Made for iPhone" means that an electronic accessory has been designed to connect specifically to an iPhone® and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with an iPhone® may affect wireless performance.
- iPhone® and all related marks and logos are trademarks of Apple Inc., registered in the U.S. and other countries.

SIRIUSXM® SATELLITE RADIO

Only SiriusXM® brings you more of what you love to listen to, all in one place. Get over 140 channels, including commercial-free music plus the best sports, news, talk, comedy and entertainment. Welcome to the world of satellite radio. A SiriusXM Vehicle Tuner and Subscription are required. For more information, visit www.airiusxm.com. (SiriusXM service is only available in the continental US and Canada.)

Activating Your SiriusXM Subscription
After installing your SiriusXM Connect
tuner and antenna, power on your
CMM-30 and select SiriusXM mode.
You should be able to hear the
SiriusXM preview channel on Channel
1. If you cannot hear the preview
channel, please check the installation
instructions to make sure your SiriusXM
Connect tuner is properly installed.

After you can hear the preview channel, tune to Channel II to find the Radio ID of your tuner, In addition, the Radio ID is located on the bottom of the SiriusXM Connect Vehicle Tuner and its packaging. You will need this number to activate your subscription. Write the number down for reference.

Note: the SiriusXM Radio ID does not include the letters I, O, S or F.

In the USA, you can activate online or by calling SiriusXM Listener care:

- Visit www.siriusxm.com/activatienow
- Call SiriusXM Listener Care at 1-866-635-2349

For Canadian Subscriptions, please contact:

- Visit www.siriusxm.ca/activate
- Call SiriusXM Customer Care at 1-888-539-7474

As part of the activation process, the SiriusXM satellites will send an activation message to your tuner. When your radio detects that the tuner has received the activation message, your radio will display: "Subscription Updated". Once subscribed, you can tune to channels in your subscription plan.

Note: The activation process usually takes 10 to 15 minutes, but may take up to an hour. Your radio will need to be powered on and receiving the SiriusXM signal to receive the activation message.

Parental Controls

Some SiriusXM channels contain mature content. When the Parental Controls feature is enabled, channels with mature content are restricted and will require a 4-digit lock code to access.

Enabling Parental Controls

- Press BACK/MENU to access the SiriusXM: Main Menu.
- Turn VOL/SEL to Parental Controls and press to enter.
- Press VOL/SEL to select Lock Mature Channels. After, you must enter a 4-digit lock code to lock mature content channels. (Parental Control default passcode: 0000)
- Use VOL/SEL to enter the 4-digit lock code and select Save when finished.

Changing the Lock Code

- Press BACK/MENU to access the SiriusXM: Main Menu.
- Turn VOL/SEL to Parental Controls and press to enter.
- Turn VOL/SEL to Edit Lock Code and press enter.
- Use VOL/SEL to enter the current 4-digit lock code and select Enter when finished.
- Use VOL/SEL to enter the new lock code and select Enter to confirm.
 Make sure to save your 4-digit lock code for future reference.

SIRIUSXM MAIN MENU

This allows access to the SiriusXM operational menu options. Refer to the table below for available settings and functionality.

- Press BACK/MENU to access the Strius XM: Main Menu.
- Turn VOL/SEL to highlight one of the menu settings listed in the table below and press to enter.
- 3. Use VOL/SEL to make selections.

Setting	Function
Now Playing	Return to the Now Playing Screen
Browse By Channel	View list of available SiriusXM channels
Browse By Category	View list of available SiriusXM channels by category
Direct Tune	Allows entry for direct channel selection
My Account	View your SinusXM account status, Radio iD and Reset SinusXM command
Parental Controls	Settings for access to Lock and Unlock Mature SiriusXM channels

Album Art

Album art can be displayed for most of the SiriusXM music channels. When album art is not available, the Channel Default Logo image or the SiriusXM Default Logo image will be displayed.

Resetting SiriusXM Settings

A reset will restore all presets and settings, including parental controls, back to their factory defaults.

- Press BACK/MENU to access the Sirius XM: Main Menu.
- Turn VOL/SEL to My Account and press to enter.
- Turn VOL/SEL to Reset SiriusXM Tuner and press to enter.
- 4. Use VOL/SEL to select Confirm.

Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. All rights reserved.

SIRIUSXM TROUBLESHOOTING

Advisory messages may appear on the display when a SiriusXM-Connect. Vehicle Tuner is connected to the CMM-30. Refer to the table below for an explanation and suggested corrective actions.

Advisory Message	Description	
Check Antenna	The radio has detected a fault with the SmusXM antenna. The antenna cable may be either disconnected or damaged. • Verify that the antenna cable is connected to the SmusXM Connect Vehicle Tune. • Inspect the antenna cable for damage and kinks. Replace the antenna if the cable is stamaged. • SirlusXM products are available at your local audio retailer or online at your shop streams com.	
Check Tuner	The radio is having difficulty communicating with the SchaXM Connect Vehicle Tuner. The tuner may be disconnected or damaged. • Verify that the SiriusXM Connect Vehicle Tuner cable is securely connected to the radio.	
No Signal	The SniusXM Connect Vehicle Tuner is having difficulty receiving the SniusXM satellite signal. • Verify that your vehicle/vessel is nutritions with a clear view of the sky. • Verify that the SniusXM priterina is mount on the exterior. • Move the SniusXM antenna away from any obstructions. • Inspect the enterest cable for damage and kinks. • Consult the SniusXM Connect Vehicle tuner installation manual for more information on antenna installation, Replace the antenna if the cable is damaged. SniusXM products are evaluable at your local audio netaller or online at avenualists.	
Subscription Updated	The radio has detected a change in your ShinXM subscription status. Free VOL/5EL to clear the message. In the U.S.A., sist www.shinsam.com or call 1-866-635-2349 if you have questions about your subscription. In Carada, visit yews.shinsam.ca or call 1-886-539-7474 if you have questions about your subscription.	
Channel Unsvalishle	The channel that you have requested is not a valid SiriusXM channel or the chan you were fistening to it no longer available. You may also see this message brief when first connecting a new SiriusXM Comment Vehicle sures. Visit www.siriusem.com for more information about the SiriusXM channel lineup.	
Channel Unsubscribed	The channel that you have requested is not included in your SiriuxXM subscriptic package of the channel that you were listening to is no longer included in your SiriuxXM subscription package. In the U.S.A., visit www.siriusam.com or call 1-866-635-2349 if you have questions about your subscription package or would sike to subscribe to this channel, in Canada, visit www.siriusam.com or call 1-877-436-W27.	
Channel Locked	The channel that you have requested is Locked by the radio Parental Control fea- ture. See Parental Controls, page 12 for more information on the Parental Control feature and how to access locked channels.	

SPECIFICATIONS

Electrical	
Operating Voltage	16/AV DC (IDV - 1AV)
Operating Temp Range	-8"Fto +140"F120"Cto +40"C)
Current Draw / Fine Value	15-A (mag./ 53 mA (standing)./ 15-A
NMEA 2000* LEN	1 (Mera-Cicenector)
Compatible MFOs	Sineud, Lowrance, Garrier. Someof Sendorselly varies by MFC manufactures.
Remote Turn-On Output	500 mA
Display	3 to 1971 CCD hashill / 360 x 840
Tuner .	
FM Sanso	USA: 87.9 MHz to 107.9 MHz (0.2 MHz step) 8136: 87.50 MHz to 108.00 MHz (0.01 MHz step) AUS: 87.50 MHz to 108.00 MHz (0.10 MHz step) O DHEB: 87.50 MHz to 108.00 MHz (0.05 MHz step)
AM Tuner	S/SA: S/30 kHz, no. 17 10 kHz (10 kHz neng) EUR: S/31 kHz to 16/17 kHz (9 kHz neng) AUS: S/31 kHz no. 16/31 kHz (9 kHz neng) C/11HER: S/31 kHz no. 16/31 kHz (9 kHz neng)
NOW Wortherband	175A 162-900 MHz - 162 500 MHz (0.001 MHz rings)
Emortes	18 persets across all brends
lluetooth*	
Profile / Spec	S07 AZDP, AVRCP
Connection Range	Up is 25 h / 11 m.
JSB	
Immilion / Charging Output	ISB20HighSpeed721 A
Supported Audio Formats	MP), WMA, FLAC, WW
File Limits	Fridden: 205 Files in a virgle fride: 2,000 Until Files 8,779
Apple Compatibility	Phone SE Coal personation) or bayonal (Sunctionally contingent upon coreguithin ICIS release)
reamp Audio Outputs/Inputs	
Output Charmets	First stereo pairs of BCA plugs (J.W RMS)
Output Configuration	Variable, Absolves, Off (all earnes) or Sub (Zoros 4 only)
Audlay Input Chamels	One steems puix of RCA plugs (VV / 2V RMS liquit Sensitivity)
Amplified Audio Outputs	
Rated RMS Flower @ 14,4V	25W x 4 B 4 G
Audio Control Options	
Turing	Trobbs, Mid. Blass, Balance or Schard equality (all correct
High Fass Cossover	CHE, 60 Ho., 100 Ho & 120 Ho (All sortes)
Dimensions	
SHEWARKS	534 m. s 330 m. s 230 in. DM mm s Winnes Di mmi
Mounting Hale W x H	3.66 in: x 3.09 in: (94 mm x 79 mm)

AUXILIARY CONTROL OPTIONS

Two connection types are included for adding control capabilities from auxiliary locations. Refer to the supplied Owner's Manual of each controller/type (sold separately) for specific user and installation instructions.

REMOTE Connection

Permits direct connection of wired controllers (sold separately) using accessory controller cables and splitters (sold separately). Connect up to three controllers to a single source unit, at up to 75 ft (23m) away (cumulative cable length). Each wired remote connects directly using controller cables and 2-way splitters (sold separately). Refer to the supplied Owner's Manual for specific user and installation instructions.



CMR-20 Wired Remote Controller with LCD Display Full-function, water-resistant

Full-function, water-resistant (IP67 rated) controller



CMR-10 Wired Remote Controller Auxiliary, water-resistant (IP67 rated) controller

NMEA 2000* Connection

NMEA 2000*, Micro-C connector interfaces directly with NMEA 2000* networks using applicable NMEA 2000* cables and connectors (sold separately).



NMEA 2000* MFD Control

Achieve control capabilities from compatible multi-function displays (MFD), NMEA 2000** functionality requires compatible NMEA 2000** entertainment protocols (PGN) and may require a software upgrade of connected MFD devices. Refer to your MFD's manufacturer for device compatibility info.

