


Inlet/Outlet Plug



Inlet and outlet plugs are installed into the grout tubes of the coupler in order to keep dirt, water and concrete slurry out of the coupler during the concrete pour, transportation and installation.

FEATURES

Designed to fit inside schedule 40 PVC pipe

Easy to install and remove

SPECIFICATIONS

Color: Blue
Material: Polyethylene

Table 1/1

Catalog Number	Type	Height (H)	Diameter 1 (Ø1)	Diameter 2 (Ø2)
LK502	Outlet	1/2"	0.64"	0.55"
LK501	Inlet	0.63"	0.85"	3/4"

ADDITIONAL PRODUCT DETAILS

Prior to installation, please read and understand the detailed instructions and safety notices provided in the nVent LENTON Interlok Instruction Manual.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE