

ENGLISH

Diagram References

- 1 Appearance
1. Tamper Switch 2. Mode Switch
3. Power Switch 4. Indicator
- Alarm: Microwave Triggered: PIR Triggered:
- Masked: Fault:
- 2 Enrollment
- 3 Installation
- I. Check signal strength.
- II. Install the device.
- C Ceiling mounting
- W Wall mounting
- G Mounting with the general mounting plate.
- L Mounting with L-mounting plate.

4 Anti-Masking Alarm

User Manual

Scan the QR code for more information and operation help.

Specification

Detection Range	Wall Mount: 10m Ceiling Mount: 5m
Auto Sensitivity	Yes
Pet Immunity	Wall Mount: 12Kg Ceiling Mount: None
Microwave Frequency	24GHz (24.15 to 24.25GHz)
Tamper Protection	Front, Rear
LED Indicators	Green(PIR), Red(Microwave), Green+Orange(Mask), Blue(Alarm)
Operation Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Storage Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Operation Humidity	10% to 90%
Mounting Height	2 to 3.5m
Dimension (WxHxD)	29.2 mm x 134.4 mm x 39.5 mm
Weight	120g
Transmission Frequency	868 MHz
RF range	1.6 km (free space)
Battery Type	CR123A × 2 (included)
Standard Battery Life	5 Years
Low Battery Voltage	2.45 V
Current	Max. current: 24mA Quiescent current: 25uA
Bracket	L-shaped adapter included

Note: when the low voltage message appears there will be at least 30 days of use.

UD26896B-A

1

2

3

4

User Manual

