

varioPRINT 140 series

BUILT FOR BUSINESS: CLASS LEADING PRODUCTION PRINTER – SUPERB UPTIME AND OUTSTANDING IMAGE QUALITY

The varioPRINT 140 series offers unparalleled reliability, impressive quality, green credentials and excellent output speeds, setting a new standard for monochrome production printing.



- Consistently high-quality prints thanks to DirectPress technology
- Speeds of up to 143 images per minute
- Maximum output volume of 800,000 images per month
- Peerless reliability means the printer requires minimal maintenance
- EnergyLogic delivers truly sustainable printing with zero ozone emissions
- HeatXchange technology further reduces energy consumption
- Embedded PRISMAsync controller offers intuitive operation and simplified scheduling
- Seamless workflow integration for smooth end-to-end production
- Range of inline accessories and DFD support for online finishing
- Superb registration, with excellent line-sharpness and halftone uniformity

Canon

TECHNICAL SPECIFICATIONS

varioPRINT 140 series

TECHNOLOGY

Description	Black & white printer / scanner / copier		
Imaging technology	DirectPress®		
Toner	Mono-component toner		
Engine resolution	600 x 2400 dpi		
Features	Toner Transfer Fusing (TTF) technology, HeatXchange technology, On-the-fly toner and paper refill; Automatic duplexing (up to 300 gsm), Active registration		
Options	Operator attention light with adjustable warn-ahead functions, CCD interface		
Print speed (simplex and duplex)	A4 duplex	A3 duplex	SRA3 duplex
varioPRINT 140	143 ipm	75 ipm	70 ipm
varioPRINT 130	133 ipm	69 ipm	65 ipm
varioPRINT 115	117 ipm	61 ipm	58 ipm

SEGMENT

Recommended average print volume (A4)	varioPRINT 140: 200,000-800,000 varioPRINT 130: 150,000-650,000 varioPRINT 115: 80,000-500,000		
Duty cycle	varioPRINT 115 up to 1,800,000 images per month varioPRINT 130 up to 2,100,000 images per month varioPRINT 140 up to 2,300,000 images per month		

GENERAL

User operation	Integrated 15" full colour touchscreen operator panel; Full engine / controller integration with one point of control PRISMAsync controller Remote Control: iOS/Android application Remote monitoring: on desktop via Remote User Interface Remote Meter Reading: secure and easy transmission of meter readings Remote Diagnostics: for maximum printer uptime Remote Software Upgrade: always the latest software and functionality available		
Warm-up time	150-270 seconds, depending on amount of toner in cleaner		
First copy time	Simplex: 3.9 seconds		
First print time	Simplex and ripped: 5.1 seconds		
Registration tolerance	Maximum +/- 0.5 mm (A4 images)		
Dimensions main engine (WxDxH)	1130 x 765 x 1040 mm (excluding user interface) 1130 x 765 x 1430 mm (including user interface)		
Weight main engine	263 kg (with Scanner / Automatic document feeder)		
Certificates	EPA Energy Star® / TEC compliance, RoHS, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, REACH		
Product Safety & Environment	EPA/TEC compliance, RoHS compliance, Cetecom / CE Class A, FCC Class A, UL / TÜV / CE, VCCI, ErP, China RoHS, CRDH FDA (USA), WEEE, Green Procurement Standards, EAC, KC, RCM, International Energy Star		
Other compliances	Section 508, EPEAT SILVER, De-inkability certificate		
Operating system	Windows 10		
Processor	3.1 GHz		
Memory	4 GB		
Hard disk	500 GB		
Interface	10/100/1000 Base-T		
Page Description Language	APPE (Adobe® PDF Print Engine); Adobe® PostScript® 3TM/ streaming PostScript®; PPML/GA Level 1; PPML versions 1.5, 2.1 and 2.2 PDF 1.7; PCL 6; XPS; IPDS(options); Xerox® PPP support		
Fonts	136 Type1 fonts for roman languages Use of PostScript fonts via Settings Editor		
Protocols	TCP/IP (LPR/LPD, socket), SMB static/auto IP (via DHCP), SNMP v1-v3 (printer MIB, private MIB), Job monitoring MIB, IPP		
Printer drivers	PS3 UPD - Windows Server 2003(R2) / Vista/Windows Server 2008 /Windows 7/ Windows Server 2008 R2/ Windows 8/Windows server 2012/Windows 8.1/Windows 2012 R2/Windows 10/ Windows Server 2016 PS3 PPD - legacy Windows and MAC/Linux-CUPS/other PS3 - Macintosh (Mac OS 10.6/10.7/10.8/10.9/10.10/ 10.11/ 10.12/ 10.13) PCL6 UPD - Windows Server 2003(R2)/Vista/Windows Server 2008 /Windows 7/ Windows Server 2008 R2/ Windows 8/Windows server 2012/Windows 8.1/Windows 2012 R2/Windows 10/ Windows Server 2016 PCL6 GPD - legacy Windows and MAC/Linux-CUPS/other MicroSoft XPS UPD - Microsoft Windows Client Vista/Windows Server 2008 /Windows 7/ Windows Server 2008 R2/ Windows 8/Windows server 2012/Windows 8.1/Windows 2012 R2/Windows 10/ Windows Server 2016 SAP Device Type (SAP R/3 4.6 and higher)		

Security

Features

Optional licenses

ENVIRONMENTAL

Sound power level

Ozone emissions

Power requirement

Power consumption

Optimum temperature & Relative humidity

Room ventilation

INTERNAL PAPER MODULE

Paper trays

Paper size and weight

Paper feed technology

EXTERNAL PAPER MODULE-D1

Description

First module

Maximum paper capacity

Paper size and weight

Paper feed technology

Dimensions (WxDxH)

Weight unit

Power requirement

Features

PRINTING

Job management

Print resolution

Maximum printable area

Screen frequency

Grey levels

Features

Common Criteria EAL 2+, E-shredding, HTTPs, Firewall, PIN for Doc Box, User authentication to SDS, Removable hard disk, IPv6, software protection license (integrity checker), user authentication per user role: key operator, system administrator and service representative

Schedule (8 hours ahead), DocBox for advanced job editing, One queue and job management for copying and printing, Spool-while-rip-while-print-while-clean-up, Multi-job processing, Multitasking (print / copy / scan), JDF connector compatible, Remote Meter Reading, Remote Diagnostics, Remote Software Upgrade and remote control

DocBox, Schedule, Colour Scan to file/e-mail, E-shredding, Multiple queues, Streaming printing, Accounting
DPLink (integration in customer Xerox infrastructure), KDKlink (integration in customer Kodak infrastructure), PRISMAlytics Dashboard
Font sets: Korean, Japanese, Simplified Chinese, Traditional Chinese

Ready mode: max 33dB

Print mode: max 64dB

None (engine)

1-Phase, 200 - 240 V; 50/60 Hz

Ready mode: 270W

Low power mode: 150W

Sleep mode: 4.3W (excl. controller)

Operation (duplex): vP115: 1.9 kW

vP130: 2.0 kW

vP140: 2.2 kW

17° C - 30° C / 20% - 80%

50 m³ or >2AC/hr at room size > 50 m³

2 x 1500 sheets (80 gsm)

2 x 500 sheets (80 gsm)

50 - 300 gsm

A4, B5 and A5 (bulk trays 1+2)

140 x 182 mm - up to 320 x 432 mm (tray 3)

140 x 182 mm - up to 320 x 488 mm (tray 4)

Friction feed, Paper Logic from all trays

Optional external paper input module with single or dual paper trays

2 x 1700 sheets (80 gsm, all sizes)

2 x 600 sheets (80 gsm, all sizes)

Dual configuration: max. up to 3400 sheets (80 gsm, A4)

2 x 600 sheets (80 gsm, all sizes)

8,000 sheets (A4 80 gsm) / 4,600 sheets (all sizes)

50 - 300 gsm

203 x 203 mm - 320 x 488 mm (all trays)

Suction feed, Air separation, Paper Logic from all trays

987 x 743 x 1056 mm

203 kg

90-264 V, 40-67 Hz, 200 W

Automatic paper size detection, Tray-empty detection, On-the-fly paper loading, Paper-level indication, Tab sheet processing, Custom paper size support, Optional dual paper trays

DocBox, Queue and History, Waiting Room

Adobe PostScript 3: 1200 x 1200 dpi, 600 x 2400 dpi

PCL: 600 x 600 dpi

Adobe PostScript 3: 3 mm from side, maximum 308 x 484 mm

PCL: 6 mm

PCL: maximum 106 lpi

Adobe PostScript 3: maximum 200 lpi

Adobe PostScript 3: 200

PCL: 125

RIP at rated engine speed, Pre-RIP, Print-while-rip-while-spool (Streaming), Mixplex, Hotfolder & multiple queue support

TECHNICAL SPECIFICATIONS

varioPRINT 140 series

COPYING

Copy resolution	600 x 1200 dpi
Exposure control	Auto / Manual (9-step scale), Text, Text / Photo, Photo
Zoom	25 - 400%; automatic
Screen frequency	200 lpi
Grey levels	200
Features	Automatic quality optimization for text / photo

SCANNING

Resolution	75, 100, 150, 200, 300 (default), 600 dpi
Colour scanning	Optional License
Destination	Scan-to-Email, Scan-to-DocBox, Scan-to-FTP, Scan-to-USB, scan to PDF (DocBox), scan to SMB
File format	PDF (single-page and multiple-page), TIFF, JPEG / sRGB (colour scanning)
Features	Thumbnail preview (DocBox), Scan profiles, Status overview, Grey level scanning Scan-once-print-many, Scan-while-warming up, Scan-while-print, Subset-scanning, RGB color scanning, Scan to File mixed sizes, Multi-tasking user interface, Double sheet detection

DUPLEX COLOUR IMAGE READER-N1

Capacity	200 sheets (80 gsm)
Maximum resolution	600 x 600 dpi
Maximum scan speed (Duplex)	A4, Black & white/colour, 300 x 300 dpi: up to 139 ipm/136 ipm A4, Black & white, 600 x 600 dpi: up to 139 ipm A4, Colour, 600 x 600 dpi: up to 36 ipm
Auto detectable original size	A3, A4, A4R, A5, A5R, Free sizes (W x L): Min. 140 mm x 128 mm, Max. 432 mm x 305 mm
Paper weight	1-sided: 38 - 220 gsm 2-sided: 38 - 220 gsm

DOCUMENT INSERTION UNIT-N1

Number of Trays	2-bin
Tray Capacity	200 sheet / bin
Paper Weight	52 - 300 gsm
Paper Size	A3, A4, A4R, A5, A5R, SRA3, 13"x19", Free size (182 x 182 mm to 330.2 x 487.7 mm)
Power Source / Consumption	230V 10A
Dimensions	336 mm (746 mm including Tray) x 793 mm x 1407 mm
Weight	Approx 61 kg

HIGH CAPACITY STACKER-H1

Stack Tray Capacity	Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each
Top Tray Capacity	Top Tray: 200 sheets
Acceptable Paper Weight	50 - 300 gsm
Acceptable Paper Size	Max defined for main engine. Custom sizes between min. 140 x 182mm up to 320 x 488mm, mixed sizes, tabs and folded sheets 230V 10A (2nd Stacker can get power from 1st Stacker)
Optionals	DFD interface kits for 860 mm and 1002 mm
Dimension	899 x 745 x 1040 mm
Weight	Approx 210 kg

PAPER FOLDING UNIT-J1

Basic Information	Z Fold, C Fold, Zigzag Fold, Double Parallel
Acceptable Paper Weight	50 - 105 gsm Double parallel: 50 - 90 gsm
Acceptable Paper Size	A4R Z-fold: A3, B4
Power Source	From Finisher-W1 or Booklet Finisher-W1
Dimension	336 x 793 x 1190 mm
Weight	Approx 71 kg

STAPLE FINISHER-W1 PRO

Basic Information	Staple and stacking finisher
Number of Trays	2
Upper Tray (A) Capacity	A4/A4R/A5R 1,000 sheets, A3 1,000 sheets, SRA3/13"x19" 1,000 sheets
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Staple Capacity:	A4: 100 sheets, A3/A4R: 50 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	130 kg

BOOKLET FINISHER-W1 PRO

Basic Information	Same functionality as Finisher W1 and additional saddle stitching and V-folding functionality Up to 100 pages booklet available (2 - 25 sheets) Stack capacity up to 5000 sheets and up to 100 sheets stapled
Number of Trays	2
Upper Tray (A) Capacity	1,000 sheets A4/A4R/A5R, 1,000 sheets A3, 1,000 sheets SRA3/13"x19"
Lower Tray (B) Capacity	A4 4,000 sheets, A4R 2,000 sheets, A3 1,500 sheets, SRA3 1,000 sheets
Stapled stacking capacity	A4 200 sets or max 3,000 sheet
Stapling Position	Corner, Double
Acceptable Paper Weight	50 - 300 gsm
Booklet stitch paper size	A3, A4R, SRA3, 13"x19", Free size 210 x 279.4 mm to 330.2 x 487.7 mm
V-Folding	Up to 5 sheets
Power Source	230V x 10A
Dimension	800 x 792 x 1239 mm
Weight	Approx 180 kg

BOOKLET TRIMMER-F1

One Edge Trimming	Fore-edge
Trim Width	2 - 28 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	Booklet finisher W1
Dimension	2,095 mm (including joint, conveyer and output tray: 162 mm) x 790 mm x 1,040 mm
Weight	Approx 152 kg

TWO-KNIFE BOOKLET TRIMMER-A1

Basic Information	Top and Bottom Edge trim
Trim Width	2 - 15 mm
Trim Thickness	Up to 50 sheets (includes Cover, by half fold)
Acceptable Paper Weight	50 - 300 gsm
Output Tray Capacity	30 booklets
Power Source	230V x 10A
Dimension	536 x 770 x 1040 mm
Weight	Approx 145 kg

Canon

TECHNICAL SPECIFICATIONS

varioPRINT 140 series

PUNCH UNIT BT1 / BU1

Basic information

Requires either the Booklet Finisher W1 or Staple Finisher W1

Punch Hole type

BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (Swe)

Acceptable Punch Paper Weight

52 - 300 gsm

Acceptable Punch Paper Size

2 holes: A3, A4, A4R, Free size (182 x 182 to 297 x 432.0 mm)
4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm)

Weight:

Approx 7.7 kg

MULTIFUNCTIONAL PRO PUNCHER-B1

Basic information

External In-line Punch Unit

Acceptable Paper Weight

75 - 300 gsm (Plain paper), 118 - 300 gsm (Coated paper),
157 - 300 gsm (Crease/ Plain & Coated paper)

Acceptable Paper Size

Punch: A4, A4R, SRA4, A3, SRA3
Crease: A4R, A3, SRA3, 13 x 19

Punch tools

Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Rectangle), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole,
Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Loose Leaf 3-Hole, Crease

Power source

230V x 2A

Dimensions

445 mm x 795 mm x 1040 mm

Weight

Approx 102 kg

DFD ADAPTER-A1

Basic information

Enables DFD connectivity directly beside the engine

Acceptable Paper Weight

Same as engine

Acceptable Paper Size

Same as engine

Optionals

DFD Interface kit for 1002 mm. Standard DFD height is 860 mm.

Power source

230 V x 10 A

Dimensions

300 mm x 745 mm x 1040 mm

Weight

Approx 60 kg

FINISHER BRIDGE-A1

Basic information

Offers connectivity of Finisher-W1 and Booklet Finisher-W1 with 3rd party DFD finishing equipment. Always in combination with DFD Adapter-A1

Acceptable Paper Weight

Same as engine

Acceptable Paper Size

Same as engine

Power source

Power and control from DFD Adapter-A1

Dimensions

600 mm x 745 mm x 150 mm

Weight

Approx 30 kg

OUTPUT TRAY

Basic information

Basic tray face-up / face-down stacking

Paper Size

All available size on marking engine

Paper Weight

50 to 300 gsm

Output Capacity

250 sheets at simplex printing/100 sheets at duplex printing

Dimensions

360 mm x 547 mm x 256 mm

Weight

Approx. 4.2 kg

3RD PARTY FINISHER

Basic information

The varioPRINT 140 series can be configured also with 3rd party finishing. Please find here a list of listed and approved finishers
Plockmatic Pro 50 and Pro 35 Booklet makers
BLM300 Booklet maker
GBC eWire Pro
SDD Press Trim
SDD Square Fold module

