

100SE580ED12C


Allen-Bradley 100SE Safety Contactor 355kW 3Pole 100 to 250VAC and VDC Elec Coil 1NO 1NC Contact Aux



SAFETY CONTACTORS



Allen-Bradley



Component type	Power contactor, AC switching
Range	100SE
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 100S-E safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

ELECTRICAL

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
ELECTRICAL	Rated operation current Ie at AC-3, 400 V	580 A
	Rated operation power at AC-3, 400 V	355 kW
ELECTRICAL	Rated operation current Ie at AC-1, 400 V	800 A
	Max. rated operation voltage Ue AC	1000 V
ELECTRICAL	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	100-250 V
ELECTRICAL	Rated control supply voltage Us at DC	100-250 V
	Number of auxiliary contacts as normally open contact	1
ELECTRICAL	Number of auxiliary contacts as normally closed contact	2
	Rated operation current Ie at AC-3, 690 V	500 A
ELECTRICAL	Rated operation power at AC-3, 690 V	500 kW
	Rated operation current Ie at AC-3, 1000 V	250 A
ELECTRICAL	Rated operation power at AC-3, 1000 V	355 kW
	Rated control supply voltage Us at AC 60HZ	100-250 V
ELECTRICAL	Power consumption, AC coil pickup	880 VA
	Power consumption, AC coil hold-in	12 VA
ELECTRICAL	Power consumption, DC coil pickup	898 W
	Power consumption, DC coil hold-in	5 W
ELECTRICAL	Type of electrical connection of main circuit	Bolt connection
	IP rating	IP00
CONSTRUCTION	Mounting method	Screw mounting
DIMENSIONS	Height	273 mm

100SE580ED12C

Allen-Bradley 100SE Safety Contactor 355kW 3Pole 100 to 250VAC and VDC Elec Coil 1NO 1NC Contact Aux



SAFETY CONTACTORS



Allen-Bradley

DIMENSIONS

Width	210 mm
Depth	242 mm
Weight	15 kg