

APC Back UPS, 900VA/480W, Floor/Wall Mount 120V, 9x NEMA 5-15R outlets, USB Type A Port, User Replaceable Battery

BVN900M1-CA

Ov	er	VI	e	W
----	----	----	---	---

Lead time Usually in Stock

Main

wain	
Main Input Voltage	120 V
Rated power in W	480 W
Rated power in VA	900 VA
Output connection type	6 NEMA 5-15R 3 NEMA 5-15R surge

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery charger power	10000 W rated
Battery power in VAH	100 VAh runtime
Extended runtime	0
Replacement battery	APCRBCV212 ☐

General

Provided equipment	user manual
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	5.47 in (13.9 cm)
Width	4.13 in (10.5 cm)
Depth	12.87 in (32.7 cm)
Net weight	8.38 lb(US) (3.8 kg)
Mounting preference	No preference
Mounting mode	Not rack-mountable

Two post mountable	0	
USB compatible	No	
Innut		

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	88143 V

Output

Maximum configurable power in W	480 W
Output frequency	50/60 Hz +/- 1 Hz unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	900 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	California Energy Commission (CEC) cTUVus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$75000

Equipment protection policy Lifetime: \$75000

Environmental

Ambient air temperature for operation	32104 °F (040 °C)
Relative humidity	090 %
Operating altitude	06666 ft
Ambient air temperature for storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	010000 ft (0.003048.00 m)

Communications & Management

Alarm when on battery: distinctive low battery alarm: overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate 490 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.70 in (22.1 cm)
Package 1 Width	15.35 in (39 cm)
Package 1 Length	6.18 in (15.7 cm)
Package 1 Weight	9.99 lb(US) (4.53 kg)

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	

3 years repair or replace (excluding battery) and 1 year for battery

Recommended replacement(s)

Warranty