

introctave range; Latch: The arpegglator will still arpegglated even when you lift your fingers; Gate+, Gate -: Set the length of each note has been arpeggiated; Tap: Tap the key to adjust the tempo of arpeggiator (Display area show the B

Smart Chord Mode:

Chord Types: Phens the notes on the keybed (Triad, 7th, 9th, Random) to select, the keyber of Lorici, the keyber of Lorici, and the select weather it's a majoriminor closed.

Smart Smart Smart Smart Smart Smart Lorici Major, Minor) to select weather it's a majoriminor closed.


Scales Press the notes on the keyberd (C-81) to select the scale of chord:

To set out of the smart chord mode press the off on the right ideal flashyade, Note II Smart Scale mode was activated, Then It will just exit out of Smart Chord mode press rute Smart Scale mode was activated, Then It will just exit out of Smart Chord mode press rute Smart Scale mode was activated.


Product Dimensions 321mm(L) x 178mm (W)x 46mm(H)
Product Weight 750a



中文










0CT- 0CT+





T.	營育 [Arpeggiator] 编辑说明
	授型 (Up, Down, Incl. Excl. Random, Order, Repeat)
式,放	按住舊而Arp功能總加琴總区經的展而类型琴號或旋转旋钮来选择舊百漢奏的模 不同的演奏模式下營音会模据已设置的基于BPM(每分钟节拍数)的时间间開握
Up:	: 按下的會符会按照會高从最低点點升至最高点,不重复首尾會;
Dov	wn:按下的音符的音高从最高点降低至最低点,不重复首尾音;
Ind 次:	: 按下的音符会重复从最低点爬升至最高点再降低至最低点,首音和尾音重复两

型; Gate+, Gate-: 调整器音音符的长矩 (Length); Tap: 通过鼓击驾驶减整器的的BM, (货码管量示BM数值); Swing+, Swing-: 调整器含音符的作动; Tempo+, Tempo+, 调整器备的速率 (Rate), 长统时可加速调整;

時周周期 非下居會功能按批即即避免的 (1/4, 1/47, 1/8, 1/87, 1/16, 1/167, 1/32, 1/327) 連整目布的連帯 (Rato); 注: 版以構定下目着98/aste与暗量设置的Tempo/BPM (毎分钟节热数) 同步, 下Sync2計解准率機動を指定数件BPM同步;

五. 智能音阶/和弦模式 智能音阶模式 (Smart Scale)

例如:按住按键按C,松开C琴键再按T 大调 (C Major Scale) 音阶内的音符;

例如:按住功能按键选择导键Triad,再按下Major,此别弹奏的所有单音导键变为三音大调和弦、按下C音符弹奏的则为C大调和弦;

主:如果在智能音阶模式,则会保留智能音阶模式,如果未开启则功能键灯光熄灭 E (Triad为和弦的1.3.5音,例如Cmaj,为C大调7个音中的1.3.5,7TH为1.3.5.7

产品尺寸	321mm(L) x 178mm (W)x 46mm(H)
产品重量	750g
琴键	25键力度感应琴键
鼓垫	8个RGB背光支持力度感应和触后的打击垫
旋钳	8个可分配的360度旋转旋钮
滑条触摸	电容式触摸弯音滑条和Modulation滑条
輸出	6.35mm延音\表情踏板接口 USB-B型接口 无线连接Windows/Mac/los/Androld 无线MIDI OUT功能(需要额外的无线接收器)
电源	电池供电戏USB供电
电池型号规格	704060
电池标称电压	3.7V
电池额定容量	2000mAh
修订	20240815
连接指南	



SMK-	25 MIDI键盘中	备注				
版本	V32	比例	1:1	日期	2024-08-15	1.英文作为封面。
排版	李丽华	印刷	黑白双面印刷	尺寸	+55-150 105 ····	2.所有表格中的电池容量单位mA改为 mAh
材质	书纸80克	工艺	骑马钉	16.0	折后:150x105mm	
审核	张丽			公司	珠海笙科智能科技有限公司	