

D135

CONTACTLESS mPOS



Micro & Small Merchants



Fashion & Retail



Food & Beverage



CLASSIC



Powered by
Monitor



PCI 5
SRED



Flexible
Platform

















Pin on
Mobile



Pocket
Sized

SPECIFICATIONS

| | | |
|---|-----------------------------|---|
|  | Operating System | Monitor |
|  | Processor | Cortex M3 |
|  | Memory | Built-in 1MB FLASH + 128KB SRAM External 4MB SPI Nor Flash for Fonts, Config Files |
|  | Card Readers | Chip & PIN NFC Contactless Magnetic Stripe (optional) |
|  | Comms Configurations | Bluetooth®4.2 , Supports : Bluetooth® Low Energy 1 Type-C Optional Pogo PIN |
|  | Battery | 250mAh Optional 400mAh |
|  | Keys / Buttons | 1 Button: Power On / Power Off / Sleep / Pair to Bluetooth® COTS |
|  | Indicators | 4 RF Indicators, 1 Power Indicators (green & red) |
|  | Cable | 1 USB Cable |
|  | Audio | 1 Buzzer |
|  | Ports | 1 Type-C OTG POGO PIN (optional) |
|  | Physical | 13 x 67 x 67 mm, 63.6g (with MSR) |
|  | Environmental | -10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10%-93% Relative Humidity, Non-Condensing |
|  | Certifications | PCI PTS 5.x SRED EMV L1 & L2 EMV CL L1 Mastercard contactless L2 Visa payWave L2 DPAS L2 QUICS L2 AMEX L2 InteacFlash L2 TQM UL FCC IC RoHs |

