



UniFlood C Pro

BVP374 60LED RGBW 220V 30 DMX 150W HP

7855 lm - 150 W - -

The Philips UniFlood C Pro offers a unique rugged elegance, with a cylindrical form and flowing lines that connect the front and back housings beautifully. This is a compact architectural floodlighting design where every element has a purpose; the front section provides exceptional lighting, the back section houses all the electrical components. Between the two, the fins dissipate heat and also serve as a decorative element. Exterior-rated, the Philips UniFlood C Pro is a cost-effective, architectural LED floodlight that is designed for façade, landscape and outdoor floodlighting applications. The robust mechanical design and high-efficiency optics make it ideal for illuminating multi-storey exterior façades, bridges, landmarks and monuments. Architects and designers have the freedom to explore a wide range of concepts and designs with no limitations, thanks to a range of colours, multiple spread lenses and a DMX512/RDM control option.

Warnings and Safety

- For outdoor use only

Product data

| General information | |
|-------------------------|--|
| Lamp colour code | RGBW |
| Driver included | Yes |
| Optical cover/lens type | GC [Clear glass] |
| Control interface | Dynamic DMX/RDM |
| Connection | Flying leads/wires and 2 push-in connectors 4-pole |
| Cable | Cable 0.5 m without plug 3-pole and 2 cables 0.5 m with connector 4-pole |
| Protection class IEC | Safety class I (I) |

| CE mark | CE mark |
|--------------------------|--------------|
| Operating and electrical | |
| Input Voltage | 220 to 240 V |
| Input frequency | 50 to 60 Hz |
| Power factor (min.) | 0.9 |
| Controls and dimming | |
| Dimmable | Yes |

UniFlood C Pro

Mechanical and housing

| | |
|-----------------------------|-------------------|
| Housing material | Aluminum die-cast |
| Optical cover/lens material | Polycarbonate |
| Colour | Dark Grey |

Approval and application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial performance (IEC compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 7855 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 52 lm/W |
| Lamp colour temperature | - |
| Colour Rendering Index | N.A. |
| Initial input power | 150 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|-----------------------------------|--|
| Full product code | 872016950649799 |
| Order product name | BVP374 60LED RGBNW 220V 30 DMX 150W HP |
| EAN/UPC – product | 8720169506497 |
| Order code | 911401776673 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 2 |
| SAP material | 911401776673 |
| Net Weight (Piece) | 8.000 kg |



Dimensional drawing



BVP374 60LED RGBNW 220V 30 DMX 150W HP

