Product of xxx Packaged in xxx





55 cm catheter length 1018 inch dia. spring-wire guide





Two Lumen Catheter: 5 Fr. (1.81 mm OD) x 55 cm, Pressure Injectable, T-Port Connector, Blue FlexTip®, Contamination Guard and Placement Wire

GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr.

Dilator
Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm)
(Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
Injection Needle: Eclipse™1 22 Ga. x 1-5/8" (4 cm)
Injection Needle: Eclipse™1 25 Ga. x 1* (2.54 cm)
Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

Syringe: 10 mL Luer-Lock
Syringe: 3 mL Luer-Lock
Syringe: 3 mL Luer-Lock
SecondSite™ Adjustable Hub: Fastener
SecondSite™ Adjustable Hub: Catheter Clamp
SharpsAway® II Locking Disposal Cup
SharpsAway® Disposal Cup

Catheter Trimmer

Catheter Infilmer
Towel: 24" x 36" (61 cm x 91 cm)
Drape: 60" x 76" (152 cm x 193 cm)
Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration

Safety Scalpel: #11 Patient ID Card

Sterile Procedure Sign Patient Information Booklet

Chart Sticker

PICC Line Insertion Checklist Paper Tape Measure

Tourniquet
Gauze Pad: 2" x 2" (5 cm x 5 cm)
Gauze Pad: 4" x 4" (10 cm x 10 cm)
Dressing: Tegaderm®2 I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)
Dressing: GRIP-LOK®3 Catheter Fixation Device
Surgical Apparel: Cap

Surgical Apparel: Impervious Gown Dressing: Steri-Strip®2 1/2" x 4" (1.2 cm x 10 cm) Surgical Apparel: Mask

Surgical Apparel: Mask with Shield
Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm)
Valve: MicroCLAVE™4 Neutral Displacement Connector

HemoHopper® Fluid Recentacle

¹A trademark of Becton, Dickinson and Company.

²A registered trademark of 3M Company. ³A registered trademark of TIDI. ⁴A trademark of ICU Medical, Inc. All components are CE 2797 unless otherwise noted

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex. Fluid path components are non-pyrogenic

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.48	356	2934	4 4
Proximal (18 Ga.)	0.51	356	3317	

* Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.




















Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL069900 R02 (2024-02)







(01)XXXXXXXXXXXXXXX (10)Lot Number













