



W4-CH12

Order No.: 1000020

PRODUCTINFOS

Transport case with integrated charging function,

for UHF PLL microphone desk stand transmitter CS-W4T/5.

- For simultaneously charging rech. batteries of up to 12 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 5 hours
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge
- Supplied with 24 x NiMH rech. battery AA size (2,000 mAh)
- Butterfly locks and recessed drop handles
- Stackable
- Matching transport case cover W4-CH12/COVER is available at option and can be ordered separately

Supplied w/o cover and devices.

Manufacturer information:

JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.

41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS**W4-CH12**

Description	transport case with charging function
Colour	black
Suitable for	12 x CS-W4T/5
Power supply	~ 100-240 V/50-60Hz/VA
Admiss. ambient temp.	0-40 °C
Dimensions	542 x 240 x 463 mm
Weight	11 kg
Packing unit	1
Packaging dimensions (W x H x L)	0.55 x 0.25 x 0.49 m
Gross weight	12.08 kg
Net weight	10.85 kg

W4-CH12

EAN code	4007754274523
----------	---------------

W4-CH12

Net weight

10.85 kg