

GM RSE A/V Harness 2007-Up

INTERFACE FEATURES

- Retains the A/V-IN jack (if applicable)
- Provides A/V output to the factory installed rear seat overhead entertainment system *
- Designed for models that have a DVD player built into the factory radio

* Only applicable for models with a second row RSE

INTERFACE COMPONENTS

- AXRSEH-GL29 harness

APPLICATIONS

BUICK

Enclave	2008-Up
Cadillac	
Escalade	2007-2011
Escalade ESV	2007-2011
Escalade EXT	2007-2011
SRX	2007-2009

CHEVROLET

Avalanche Δ	2007-2013
Equinox	2007-2009
Silverado 2500/3500 Δ	2014
Silverado (new body) Δ	2007-2013
Suburban Δ	2007-2014
Tahoe Δ	2007-2014
Traverse	2009-Up

GMC

Acadia	2007-2016
Acadia Limited	2017
Sierra 2500/3500 Δ	2014
Sierra (new body) Δ	2007-2013
Yukon/Yukon XL Δ	2007-2014

HUMMER

H2	2008-2009
----	-----------

PONTIAC

Torrent	2007-2009
---------	-----------

SATURN

Outlook	2007-2010
---------	-----------

SUZUKI

XL-7	2007-2009
------	-----------

Δ For 2012-Up models with NAV use the AXRSEH-G2.

TOOLS REQUIRED

- Wire cutter • Crimping tool
- Connectors (example: butt-connectors, bell caps, etc.)

CONNECTIONS TO BE MADE

- Connect the **Black** wire with a ring terminal to the chassis of the aftermarket radio.
- From the RCA jacks labeled "FROM REAR A/V INPUT" to the A/V input of the aftermarket radio:
 - Connect the **Yellow** RCA jack to the video in.
 - Connect the **Red** and **White** RCA jacks to the audio in.
- From the RCA jacks labeled "TO OVERHEAD SCREEN" to the A/V output of the aftermarket radio:
 - Connect the **Yellow** RCA jack to the video out.
 - Connect the **Red** and **White** RCA jacks to the audio out.

INSTALLATION

- Connect to the AXRSEH-GL29 harness to the wiring harness in the vehicle located at the radio location.

GM Arnés A/V RSE 2007 y Mas

CARACTERÍSTICAS DE LA INTERFAZ

- Retiene el conector A/V-IN (si aplica)
- Proporciona salida A/V al sistema de entretenimiento instalado en el asiento trasero de fábrica *
- Diseñado para los modelos que tienen un reproductor de DVD integrado en la radio de fábrica

* Sólo aplicable a modelos con una segunda fila RSE

COMPONENTES DE LA INTERFAZ

- Arnés AXRSEH-GL29

APLICACIONES

BUICK

Enclave	2008-Up
Cadillac	
Escalade	2007-2011
Escalade ESV	2007-2011
Escalade EXT	2007-2011
SRX	2007-2009

CHEVROLET

Avalanche Δ	2007-2013
Equinox	2007-2009
Silverado 2500/3500 Δ	2014
Silverado (nueva carrocería) Δ	2007-2013
Suburban Δ	2007-2014
Tahoe Δ	2007-2014
Traverse	2009-Up

GMC

Acadia	2007-2016
Acadia Limited	2017
Sierra 2500/3500 Δ	2014
Sierra (nueva carrocería) Δ	2007-2013
Yukon/Yukon XL Δ	2007-2014

HUMMER

H2	2008-2009
----	-----------

PONTIAC

Torrent	2007-2009
---------	-----------

SATURN

Outlook	2007-2010
---------	-----------

SUZUKI

XL-7	2007-2009
------	-----------

Δ Para los modelos 2012 y mas con NAV utilice el AXRSEH-G2.

HERRAMIENTAS REQUERIDAS

- Cortacables • Ponchadora
- Conectores (ejemplo: conectores de extremo, de campana, etc.)

CONEXIONES

- Conecte el cable **negro** con una terminal de aro al chasis del radio de mercado secundario.
- Desde los conectores RCA etiquetados "DE LA ENTRADA TRASERA A/V" a la entrada A/V de la radio de mercado secundario:
 - Conecte el conector RCA **amarillo** al entrada de video.
 - Conecte el conectores RCA **rojo** y **blanco** al entrada de audio.
- Desde los conectores RCA etiquetados "A LA PANTALLA DE TECHO" a la salida A/V de la radio de mercado secundario:
 - Conecte el conector RCA **amarillo** al salida de video.
 - Conecte el conectores RCA **rojo** y **blanco** al salida de audio.

INSTALACIÓN

- Conectar al arnés AXRSEH-GL29 al arnés de cables del vehículo situado en la ubicación de la radio.